

# Vishay Sfernice

## **Knob Potentiometer**




The P16 is a revolutionary concept in panel mounted potentiometers. This unique design consists of a knob driving and incorporating a cermet potentiometer. Only the mounting hardware and terminals are situated on the back side of the panel reducing to a minimum the required clearance.

#### **FEATURES**




- Test according to CECC 41000 or IEC 60393-1
- P16 Version for professional and industrial applications (cermet) 1 W at 40 °C
- COMPLIANT
- PA16 Version for professional audio applications (conductive plastic) 0.5 W at 40 °C
- Compact (integrated)
- High dielectric strength: 2500 V<sub>RMS</sub>
- Fully sealed and panel sealed
- Metallic or plastic knob options
- · Custom knob on request
- Compliant to RoHS Directive 2002/95/EC



# Knob Potentiometer



| ELECTRICAL SPECIFICATIONS                       |  |  |  |  |  |
|---|--|--|--|--|--|
|   | P16  | PA16   |  |  |  |
| Resistive Element                               | Cermet Conductive plastic  |  |  |  |  |
| Electrical Travel                               | 270° ± 10°   | 270° ± 10°   |  |  |  |
| Power Rating Chart                              | 0.50 & PA16 LIN. TAPER PA16 LOG. TAPER NO 0 20 40 60   | 80 100 120 140<br>MPERATURE IN °C                              |  |  |  |
| Circuit Diagram                                 | $ \begin{array}{c} \stackrel{a}{\circ} \longrightarrow & \stackrel{c}{\circ} \\ \stackrel{(1)}{\circ} \longrightarrow & \stackrel{(3)}{\circ} \\ \stackrel{(2)}{\circ} \longrightarrow & \stackrel{(3)}{\circ} \end{array} $ |  |  |  |  |
| Taper   | 0 20 40 % CLOCK  | A L L 60 80 100 WISE SHAFT ROTATION                            |  |  |  |
| Resistance Range Linear Taper Logarithmic Taper | 22 $\Omega$ to 10 M $\Omega$<br>100 $\Omega$ to 2.2 M $\Omega$   | 1 k $\Omega$ to 1 M $\Omega$<br>470 $\Omega$ to 500 k $\Omega$ |  |  |  |
| Standard Series E3                              | 1 - 2.2 - 4.7 and on request 1 - 2 - 5   | 1 - 2.2 - 4.7  |  |  |  |
| Tolerance Standard On Request                   | ± 20 %<br>± 10 %   | ± 20 %<br>± 10 % (1 kΩ to 100 kΩ)                              |  |  |  |
| Power Rating Logarithmic                        | 1 W at + 40 °C<br>0.5 W at + 40 °C   | 0.5 W at + 40 °C<br>0.25 W at + 40 °C                          |  |  |  |
| Temperature Coefficient (Typical)               | ± 150 ppm/°C   | ± 500 ppm/°C   |  |  |  |
| Dielectric Strength (RMS)                       | 2500 V   | 2500 V   |  |  |  |
| Limiting Element Voltage (Linear Law)           | 350 V  | 350 V  |  |  |  |
| Contact Resistance Variation                    | 3 % Rn or 3 Ω  | 2 % Rn or 3 $\Omega$   |  |  |  |
| End Resistance (Typical)                        | 1Ω   | 1 Ω  |  |  |  |
| Insulation Resistance (500 V <sub>DC</sub> )    | $10^6\mathrm{M}\Omega$   | 10 <sup>6</sup> MΩ   |  |  |  |



#### **Knob Potentiometer**

| Vishay Sfernice | Visha | v Sfe | rnice |
|-----------------|-------|-------|-------|
|-----------------|-------|-------|-------|

| MECHANICAL SPECIFICATIONS              |                 |  |  |  |  |
|--|-----------------|--|--|--|--|
| Mechanical Travel                      | 300° ± 5°       |  |  |  |  |
| Operating Torque                       | 2 Ncm typical   |  |  |  |  |
| End Stop Torque                        | 25 Ncm maximum  |  |  |  |  |
| Max. Tightening Torque of Mounting Nut | 250 Ncm maximum |  |  |  |  |
| Unit Weight                            | 4.5 g typical   |  |  |  |  |

| ENVIRONMENTAL SPECIFICATIONS |                                   |                  |  |  |  |
|------------------------------|-----------------------------------|------------------|--|--|--|
|                              | Metallic Knob                     | Plastic Knob     |  |  |  |
| Temperature Range            | - 40 °C to 125 °C                 | - 40 °C to 85 °C |  |  |  |
| Climatic Category            | 40/100/56                         | 40/85/56         |  |  |  |
| Sealing                      | Sealed container and panel sealed |                  |  |  |  |
| Protection Grades            | IP67                              |                  |  |  |  |

#### **MARKING**

- Ohmic value code, tolerance code and taper
- Manufacturing date code

#### **PACKAGING**

• Carton box of 20 pieces

#### **CONTROL KNOB**

Black metallic knob (NM).

Black plastic knob (NP).

For white and blue color see ordering information.

Other dimensions, shapes, colors of control knobs are manufactured on request - please consult Vishay.

Other reference marks (shapes, colors) and legends can be printed on plastic knob on request - please consult Vishay.

| P16 S   | P16 STANDARD RESISTANCE ELEMENT DATA  |   |   |  |  |  |  |  |  |
|---|---|---|---|--|--|--|--|--|--|
| STAN-   | LI  | NEAR TAPI   | ER  | ı  | LOG TAPER  | 3  |  |  |  |
| DARD<br>RESIS-<br>TANCE<br>VALUES   | MAX.<br>POWER<br>AT<br>40 °C  | MAX.<br>VOLTAGE   | MAX.<br>CUR.<br>THROUG<br>H WIPER   | MAX.<br>POWER<br>AT<br>40 °C                                       | MAX.<br>VOLTAGE  | MAX.<br>CUR.<br>THROUG<br>H WIPER  |  |  |  |
| Ω   | W   | ٧   | mA  | W  | V  | mA   |  |  |  |
| 22<br>47<br>100<br>220<br>470<br>1K<br>2.2K<br>4.7K<br>10K<br>22K<br>47K<br>100K<br>220K<br>470K<br>1M<br>2.2M<br>4.7M<br>10M | 1<br>1<br>1<br>1<br>1<br>1<br>1<br>1<br>1<br>1<br>1<br>0.56<br>0.26<br>0.12<br>0.05<br>0.02 | 4.69<br>6.85<br>10<br>14.8<br>21.7<br>31.6<br>46.9<br>68.5<br>100<br>148<br>217<br>316<br>350<br>350<br>350<br>350<br>350 | 213<br>146<br>100<br>67.4<br>46.1<br>31.6<br>21.3<br>14.6<br>10<br>6.74<br>4.61<br>3.16<br>1.59<br>0.75<br>0.35<br>0.16<br>0.07 | 0.5<br>0.5<br>0.5<br>0.5<br>0.5<br>0.5<br>0.5<br>0.5<br>0.5<br>0.5 | 7.1<br>10.5<br>15.3<br>22.4<br>33.2<br>48.5<br>70.7<br>105<br>153<br>224<br>332<br>350<br>350<br>350 | 71<br>48<br>32.6<br>22.4<br>15.1<br>10.3<br>7.07<br>4.77<br>3.26<br>2.24<br>1.51<br>0.74<br>0.35<br>0.16 |  |  |  |

| PA16 STANDARD RESISTANCE ELEMENT DATA  |   |  |  |  |  |  |  |  |
|--|---|--|--|--|--|--|--|--|
| STAN-  | L   | INEAR TAP  | PER  | LOG TAPER  |  |  |  |  |
| DARD MAX POWE AT VALUES 40 °C  |   | MAX.<br>VOLTAGE  | MAX. CUR.<br>THROUGH<br>WIPER  | MAX.<br>POWER<br>AT<br>70 °C                                 | MAX.<br>VOLTAGE  | MAX. CUR.<br>THROUGH<br>WIPER                            |  |  |
| Ω  | W   | ٧  | mA   | W  | ٧  | mA   |  |  |
| 470<br>1K<br>2.2K<br>4.7K<br>10K<br>22K<br>47K<br>100K<br>220K<br>470K<br>1M | 0.5<br>0.5<br>0.5<br>0.5<br>0.5<br>0.5<br>0.5<br>0.5<br>0.5<br>0.26 | 22.4<br>33.2<br>48.5<br>79.7<br>105<br>153<br>224<br>332<br>350<br>350 | 22.4<br>15.1<br>10.3<br>7.07<br>4.77<br>3.26<br>2.24<br>1.51<br>0.74<br>0.35 | 0.25<br>0.25<br>0.25<br>0.25<br>0.25<br>0.25<br>0.25<br>0.25 | 10.8<br>15.8<br>23.5<br>34.3<br>50.0<br>74<br>108<br>158<br>235<br>343 | 23.1<br>16<br>11<br>7<br>5.0<br>3.4<br>2.3<br>1.6<br>1.1 |  |  |


Document Number: 51036 Revision: 07-Apr-11

# Vishay Sfernice

## **Knob Potentiometer**



| PERFORMANCE                                       |   |   |   |   |  |  |  |
|---|---|---|---|---|--|--|--|
| TESTS   | CONDITIONS  | TYPICAL VALUES AND DRIFTS                           |   |   |  |  |  |
|   | CONDITIONS  | ∆ <i>R</i> <sub>T</sub> / <i>R</i> <sub>T</sub> (%) | ∆R <sub>1-2</sub> /R <sub>1-2</sub> (%) | OTHER   |  |  |  |
| Electrical Endurance                              | 1000 h at rated power<br>90'/30' cycle at + 40 °C         |   |   | Insulation resistance: > $10^4  \text{M}\Omega$<br>Contact res. variation: < $2  \%$ Rn |  |  |  |
| Damp Heat, Steady State                           | 56 days<br>40 °C, 93 % HR                                 | ± 2 %   | ± 1 %                                   | Insulation resistance: > $10^4 \mathrm{M}\Omega$  |  |  |  |
| Mechanical Endurance                              | 50 000 cycles   | ± 5 %   | -                                       | Contact res. variation: < 2 % Rn  |  |  |  |
| Shock   | 50 g's at 11 ms<br>3 successive shocks<br>in 3 directions | ± 0.2 %   | ± 0.5 %                                 | -   |  |  |  |
| 10 Hz to 55 Hz<br>0.75 mm or 10 g's<br>during 6 h |   | ± 0.2 %   | -                                       | $\Delta V_{1-2}/\Delta V_{1-3} \le \pm \ 0.5 \%$  |  |  |  |



| PART NUMBER DESCRIPTION (for information only) |       |               |           |       |         |           |         |                   |
|--|-------|---------------|-----------|-------|---------|-----------|---------|-------------------|
| P16  | NP    | <b>22 k</b> Ω | 20 %      | Α     |         | во        |         | e3                |
| MODEL  | STYLE | VALUE         | TOLERANCE | TAPER | SPECIAL | PACKAGING | SPECIAL | LEAD<br>(Pb)-FREE |



## **Legal Disclaimer Notice**

Vishay

## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

# **Material Category Policy**

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.

Revision: 02-Oct-12 Document Number: 91000

## **ПОСТАВКА** ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

многоканальный

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

# Данный компонент на территории Российской Федерации Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

### http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г. Москва, ул. Щербаковская д. 3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru moschip.ru\_6 moschip.ru 4 moschip.ru 9