TRE25 SERIES
25W SWITCHING ADAPTER

Features



* Miniature Size
* Universal Input: 90~264Vac
* EMI Meets EN55022 Class B and CISPR/FCC Class B
* Continuous Short Circuit Protection
* Over Voltage Protection
* Meet CoC V5 Tier 2 & DoE Level VI (Output Cable Length ≦ 1800mm) (TRE25050: Output Cable Length ≦ 1220mm)
* No Load Power Consumption<75mW

Ordering information

TRE25XXX -	X	XX	G	XX
Model No.	AC Plug Type	DC Plug Type	UL 1571 WITH OVP	DC Cable Length and Type
	A: USA 2 Pin			01: 720mm
	E: Europe 2 Pin			02: 1220mm
	U: British 3 Pin			03: 1800mm
				11: 720mm with Ferrite Core
				12: 1220mm with Ferrite Core
				13: 1800mm with Ferrite Core
				* 20AWG / UL1571 or Equivalent
				* 16AWG / UL1571 for Vo:5V or Equivalent

MODEL	OUTPUT VOLTAGE	OUTPUT CURRENT	RIPPLE & NOISE NOTE 1	VOLTAGE ACCURACY NOTE 2	LINE REGULATION NOTE 3	LOAD REGULATION NOTE 4	AVG.ERAGE EFF. min.
TRE25050	5V	4A	50mVp-p	±2%	±1%	±6%	83.7%
TRE25120	12V	2.1A	1%	±2%	±1%	±5%	87.0%
TRE25150	15V	1.67A	1%	±2%	±1%	±3%	87.0%
TRE25180	18V	1.4A	1%	±2%	±1%	±2%	87.0%
TRE25240	24V	1.05A	1%	±2%	±1%	±2%	87.0%

Specifications are subject to change without notice.

Specifications

INPUT SPECIFICATIONS:

Voltage ..... 90~264Vac
Frequency ..... 47 to 63Hz
Input Current ..... 0.7A max.
Inrush Current ..... 60A max. @240Vac
Conducted EMI ..... CISPR/FCC Class B
Leakage Current ..... 0.25mA max.

OUTPUT SPECIFICATIONS:

Holdup Time ..... 10ms typ. @115Vac
Short Circuit Protection ..... Continuous(Auto Recovery)
Over Voltage Protection ..... IC Component to Clamp
Temperature Coefficient ..... ±0.05%/℃

GENERAL SPECIFICATIONS:

Isolation ..... Input to output = 3,000VAC
Operating Temperature ..... -20~60℃(see derating curve)
Storage Temperature ..... -20~85℃
Humidity ..... 93% RH max. Non condensing
Cooling ..... Natural Convection
Switching Frequency ..... 65KHz typ.
MTBF ..... MIL-HDBK-217F, GB, 25℃/115VAC ..... 300K hrs min.
Altitude 2000m
Life time ..... Ambient 40degC 75% Load ..... >3years
Dimensions 2.795x1.906x1.299Inches (71.00x48.4x33.00mm)
Weight ..... 140g(0.31 Pounds)

TRE25 Series Derating Curve



SAFETY AND EMC:

Emission and Immunity ..... EN55022 Class B, FCC Part 15 Class B
EN61000-6-3, EN61000-3-2, EN61000-3-3
EN55024, EN61204-3, EN61000-6-1
Safety ..... Class II, IEC60950-1, EN60950-1, UL60950-1

NOTE:

1. Add a 0.1uF ceramic capacitor and a 10uF E.L. capacitor to output for ripple & noise measuring @20MHz BW.
2. Voltage setpoint at 60% full load.
3. Line regulation measured from 100Vac to 240Vac, full load.
4. Load regulation measured from 60% to 100% full load and from 60% to 20% load (60% +/- 40% full load).

Mechanical Specification

All Dimensions are in inches[mm]
Tolerance:Inches:X.XXX±0.02
Millimeters:X.XX±0.5

FIG.E



FIG.A



FIG.U



Typical at 25°C, nominal line and 75% load, unless otherwise Specified

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9