


T90 Series, 30A PCB Relay

- 30A, 1 Form A (NO); 20A, 1 Form C (CO)
- Available as open frame or sealed construction
- Meets UL 508 and 873 Spacing - 3.18 through air, 6.36 over surface
- UL class F insulation system standard

Typical applications
HVAC, Appliances, Industrial Controls



Approvals

UL E22575; CSA LR15734
Technical data of approved types on request

Contact Data

Contact arrangement	1 form A (NO), 1 form B (NC), 1 form C (CO)
Rated voltage	277VAC
Max. switching voltage	277VAC
Rated current	30A
Limiting continuous current	30A
Limiting making current	30A
Limiting breaking current	30A
Contact material	AgCdO
Min. recommended contact load	1A, 5VDC or 12VAC
Initial contact resistance	75 mΩ at 1A at 5VDC or 12VAC
Frequency of operation, with load	360hr
Operate/release time max., including bounce	15/15ms

Contact ratings

Type	Load	Cycles
------	------	--------

Typical

AgCdO, open style relay		
NO	30A, 240VAC, general purpose	100x10 ³
NO	20A, 240VAC, resistive heater	100x10 ³
CO	20A/10A, 240VAC, general purpose	100x10 ³
CO	20A/10A, 28VDC, resistive	100x10 ³

UL 508/873

AgCdO		
NO	30A, 240VAC, general purpose	100x10 ³
NC	15A, 240VAC, general purpose	100x10 ³
CO	20A/10A, 240VAC, general purpose	100x10 ³
NO	20A, 240VAC, resistive	100x10 ³
NC	15A, 240VAC, resistive	100x10 ³
CO	20A/10A, 240VAC, resistive	100x10 ³
NO	80LRA/30FLA, 240VAC	30x10 ³
NC	30LRA/10FLA, 240VAC	30x10 ³
CO	53.6LRA/20FLA / 20LRA/6.7FLA, 240VAC	100x10 ³
NO	98LRA/22FLA, 120VAC	100x10 ³
NO	2HP, 240VAC	1x10 ³
NC	1/2HP, 240VAC	1x10 ³
NO	1HP, 120VAC	1x10 ³
NC	1/4HP, 120VAC	1x10 ³
NO	6A, 277VAC, ballast	100x10 ³
NC	3A, 277VAC, ballast	6x10 ³
NO	TV5, 240VAC, tungsten	6x10 ³
NC	TV3, 240VAC, tungsten	6x10 ³
NO	20A, 28VDC, resistive	100x10 ³
NC	10A, 28VDC, resistive	100x10 ³

All ratings at 25°C (unless otherwise noted) with relay properly vented. Remove vent nib from enclosed relays after soldering and cleaning for optimum life.

Mechanical endurance	10x10 ⁶ ops.
----------------------	-------------------------

Coil Data


Coil voltage range	5 to 110VDC
Max. coil power	1.0W
Max. coil temperature	155°C
Coil insulation system according UL	Class F

Coil versions, DC coil

Coil code	Rated voltage VDC	Operate voltage VDC	Release voltage VDC	Coil resistance Ω±10%	Rated coil power wW
5	5	3.75	0.5	27	900
6	6	4.5	0.6	40	900
9	9	6.75	0.9	97	900
12	12	9	1.2	155	900
18	18	13.5	1.8	380	900
24	24	18	2.4	660	900
48	48	36	4.8	2560	900
110	110	82.5	11	13450	900

All figures are given for coil without preenergization, at ambient temperature +23°C.

Ambient temperature vs. coil voltage – 1W coil



Data graphed above are average values and should be verified in application. Tests were conducted within a 2' (.6m) cube (still air); at nominal coil power @ 25°C; with normally open contact loaded; and with 4' (1.22m) long, #10AWG load wires. P.C. board relays were mounted to a 30A, single side P.C. board. Coil rise test conducted with a 30A PC board to maintain 20°C max. rise at 30°C. The relay connections and wiring must be designed with an adequate cross section to ensure proper current flow and heat dissipation. After cleaning process knock-off nib should be removed for optimum life of wash-tight relays.

T90 Series, 30A PCB Relay (Continued)

Insulation Data

Initial dielectric strength	
between open contacts	1500V _{rms}
between contact and coil	1500V _{rms}
Initial insulation resistance	
between insulated elements	1x10 ⁹ Ω
Clearance/creepage	
between contact and coil	3.17mm

Other Data

Material compliance: EU RoHS/ELV, China RoHS, REACH, Halogen content refer to the Product Compliance Support Center at www.te.com/customersupport/rohssupportcenter

Ambient temperature
DC coil -55°C to 85°C ¹⁾

Category of environmental protection
IEC 61810 RT0 - open, RTII - flux proof

Other Data (continued)

Vibration resistance (functional)	1.65mm max excursions, 10-55 Hz
Shock resistance (functional)	10g for 11msec
Shock resistance (destructive)	100g
Terminal type	pcb-tht
Weight	20g open relay 26g wash-tight relay


Resistance to soldering heat THT
IEC 60068-2-20 250°C

Packaging/unit tray/50 pcs., box/500 pcs.


1) Operating ambient temperature must consider "Must Operate Voltage Change Over Temperature," Contact Temperature Rise, Coil Temperature Rise (If coil is not allowed to cool) and Maximum Coil Temperature. Specification ambient considers 20A load with coil cooled to ambient.

Dimensions

T90N




T90S




Terminal assignment

Bottom view on pins



PCB layout

Bottom view on pins




Only necessary terminals are present on single throw models and terminal code 4 models. Consequently, some holes will be unnecessary for those models.

Accessory

Optional plastic dust cover is a snap-on unit, open on the PC board side of the relay. The cover, when ordered with the relay, is shipped separately. It is designed to be snapped into place by the customer after the relay has been assembled to the PC board.

Product Code	Description	Part Number
35C620A	Black dust cover, for use on T90N relay	4-1393209-2

35C620A



T90 Series, 30A PCB Relay (Continued)
Product code structure

Typical product code

T90 S 5 D 1 2 -24
Type
T90 Power PCB relay T90

Enclosure
N Open, no enclosure (snap-on dust cover available as an option)

S Wash-tight, sealed plastic case with knock off nib for ventilation

Contact arrangement
1 1 form A (1 NO)

2 1 form B (1 NC)

5 1 form C (1 CO)

Coil Input
D DC voltage

Mounting and termination
1 PCB terminals

4 PCB terminals, no common terminal between coil terminals (see pcb layout/terminal assignment drawing)

Note: Terminal code 4 recommended for UL 873 applications. Consult factory for use of terminal code 1 for UL 873 applications.

Contact material
2 AgCdO

Coil voltage

Coil code: please refer to coil versions table

Product Code	Enclosure	Contacts	Terminals	Contact Material	Coil	Part Number			
T90N1D12-5	open, no cover	1 form A, 1 NO	pcb	AgCdO	5 VDC	7-1393208-4			
T90N1D12-9					9 VDC	7-1393208-5			
T90N1D12-12					12 VDC	6-1393208-5			
T90N1D12-18					18 VDC	6-1393208-8			
T90N1D12-24					24 VDC	7-1393208-0			
T90N1D12-48					48 VDC	7-1393208-3			
T90N1D12-110					110 VDC	6-1393208-4			
T90N1D42-12			pcb, no extra COM		12 VDC	7-1393208-7			
T90N1D42-24					24 VDC	7-1393208-9			
T90N5D12-5			1 form C, 1 CO		pcb		5 VDC	9-1393208-5	
T90N5D12-12							12 VDC	8-1393208-6	
T90N5D12-18							18 VDC	9-1393208-0	
T90N5D12-24							24 VDC	9-1393208-3	
T90N5D12-48							48 VDC	9-1393208-4	
T90N5D12-110	110 VDC	8-1393208-5							
T90N5D42-12				pcb, no extra COM				12VDC	9-1393208-9
T90N5D42-24			24 VDC		1393209-2				
T90S1D12-5			wash tight	1 form A, 1 NO	pcb			5 VDC	1-1393209-8
T90S1D12-6								6 VDC	1-1393209-9
T90S1D12-9								9 VDC	2-1393209-0
T90S1D12-12								12 VDC	1-1393209-2
T90S1D12-18								18 VDC	1-1393209-3
T90S1D12-24	24 VDC	1-1393209-6							
T90S1D42-12							pcb, no extra COM		12 VDC
T90S1D42-24			24 VDC	2-1393209-5					
T90S1D42-48			48 VDC	2-1393209-6					
T90S5D12-5			1 form C, 1 CO	pcb		5 VDC	3-1393209-4		
T90S5D12-12						12 VDC	2-1393209-8		
T90S5D12-18						18 VDC	3-1393209-0		
T90S5D12-24						24 VDC	3-1393209-1		
T90S5D12-48	48 VDC	3-1393209-3							
T90S5D42-12	pcb, no extra COM	12 VDC				1423094-1			
T90S5D42-18		18 VDC				3-1393209-8			
T90S5D42-24				24 VDC	4-1393209-0				

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9