



ACA-4HSRPP-2458

Data Sheet



4" Antenna with Hinged SMA Reverse Polarity Plug for 2.4/5 GHz

Disclaimer

While the information provided in this document is believed to be accurate, it is under development and ACKme Networks reserves the right to make changes without further notice to the product described herein to improve reliability, function, or design, and makes no guarantee or warranty concerning the accuracy of said information, nor shall it be responsible for any loss or damage of whatever nature resulting from the use of, or reliance upon, such information. ACKme Networks makes no warranties of any kind, whether express, implied or arising by custom or course of trade or performance, and specifically disclaims the implied warranties of title, non-infringement, merchantability, or fitness for a particular purpose.

No part of this document may be copied, reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photographic, or otherwise, or used as the basis for manufacture or sale of any items without the prior written consent of ACKme Networks.

Trademarks

ACKme Networks and the ACKme Networks logo are trademarks of ACKme Networks. Other trademarks in this document belong to their respective owners.

Copyright © 2014 ACKme Networks.

All rights reserved.

Document Number: ACA-4HSRPP-2458-1xx

Release Date: April 12, 2014

Contact

Web: <http://ack.me/contact>

About this Data Sheet

This document provides information about the ACA-4HSRPP-2458 dual-band 2.4/5 GHz antenna.

1 Description

The ACA-4SSRPP-2458 is a 2.4/5 GHz antenna approximately 4" in length ideally suited for Wi-Fi communications.

The antenna is hinged with an SMA Reverse Polarity Plug (RPP) connector and stands 108.0mm tall (including SMA) with a top diameter of 7.80mm and base diameter of 9.30mm.


The antenna is ideal for Wi-Fi applications in the 2400-2500 MHz and 5200-5800 MHz bands of operation.

2 Specifications

Table 1. ACA-SSRPP-2458 Specifications

Parameter	Value	Tolerance	Unit
Frequency Band	2400 – 2500 5200 – 5800		MHz
Total Height (including SMA connector)	108.0	± 0.50	mm
Height (excluding SMA connector)	87.0	± 0.25	mm
Diameter (top/base)	7.80/9.30	± 0.25	mm
Connector	Hinged SMA RPP		
Antenna Cover Material	Polyurethane		
Antenna Base Material (flammability rating)	Polycarbonate (UL 94V-0)		
Color	Black		


3 Mechanical



4 Radiation Pattern


4.1 E-Plane: 2.4 GHz

Parameter	Value	Unit
Pattern Field	E-Plane	
Frequency	2450	MHz
Average Gain	-3.6	dB
Maximum Gain @ 291 degrees	1.0	dB
Minimum Gain @ 0 degrees	-27.7	dB




4.2 H-Plane: 2.4 GHz

Parameter	Value	Unit
Pattern Field	H-Plane	
Frequency	2450	MHz
Average Gain	0.3	dB
Maximum Gain @ 112 degrees	1.0	dB
Minimum Gain @ 212 degrees	-0.3	dB




4.3 E-Plane: 5 GHz

Parameter	Value	Unit
Pattern Field	E-Plane	
Frequency	5800	MHz
Average Gain	-2.9	dB
Maximum Gain @ 283 degrees	4.5	dB
Minimum Gain @ 223 degrees	-17.5	dB




4.4 H-Plane: 5 GHz


Parameter	Value	Unit
Pattern Field	H-Plane	
Frequency	5800	MHz
Average Gain	3.74	dB
Maximum Gain @ 53 degrees	4.5	dB
Minimum Gain @ 282 degrees	2.6	dB



4.5 S11 Plot




4.6 VSWR Plot



Appendix A – SMA Connector Types

To keep everyone guessing, the industry offers four different types of SMA connectors each depicted in the figure below.

The ACA-4HSRPP-2458 comes with a Hinged SMA Reverse Polarity Plug connector with a female center pin as depicted by the large arrow underneath the following picture (the hinge is **NOT** shown).



The SMA connector on the ACA-4HSRPP-2458 antenna looks like this.

ACKme reserves the right to make changes without further notice to any products or data herein to improve reliability, function, or design. Information furnished by ACKme is believed to be accurate and reliable. However, ACKme does not assume any liability arising out of the application or use of this information, nor the application or use of any product described herein, neither does it convey any license under its patent rights nor the rights of others.

ACKme Networks

US Headquarters:	Australian Office:
2 North Santa Cruz Ave	Level 21, Tower 2
Suite #207	201 Sussex St
Los Gatos CA 95030	Sydney NSW 2000

© 2014 ACKme Networks. All rights reserved.

ACA-4HSRPP-2458-100R • Data Sheet
April 12, 2014

Contact Information

Phone: +1 (408) 402 5708
www: <http://ack.me/contact>



Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9