

Non-Contacting Hall Effect Single Turn Position Sensor



6120 Series

Features:

- 7/8" diameter
- Non-contacting
- Hall Effect
- Single turn
- Multiple styles available
- Custom models available



Description:

The BI Technologies line of single-turn non-contacting hall-effect position sensors is 7/8" in diameter. Custom models are available. The hall-effect technology used makes this set of position sensors ideal for harsh environments where shock levels, vibration and temperature.

Applications:

- Industrial grade joystick
- HVAC controls

Model Styles Available

| | |
|-----------|--|
| 6121 | 1/8" Shaft, 1/4" Bushing |
| 6126 | 1/8" Shaft, 3/8" Bushing |
| 6127 | 1/4" Shaft, 3/8" Bushing |
| 612x-XXXX | Custom models are available; Contact Customer Service for special features |

Ordering Information



General Note
 TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | BI Technologies
 Circulo de la Amistad #102 PIMSA IV Mexicali B.C. Mexico C.P 21210
 Ph: +1 714 447 2345
www.ttelectronics.com/bi-technologies

Non-Contacting Hall Effect Single Turn Position Sensor



6120 Series

Electrical Specifications¹

| | |
|---|--|
| Output voltage | 0.25 Vdc to 4.75 Vdc typical (see Feature Codes table) |
| Output overvoltage limits | 10 Vdc to -0.3 Vdc; output may be shorted to ground or supply without damage |
| Output current | ±8 mA max. |
| Output load | 1 kΩ min., 10 kΩ typical |
| Input voltage | 4.5 to 5.5 Vdc |
| Supply voltage absolute limits | 20 Vdc max., -10 Vdc min. |
| Independent linearity ² | ±0.5% (0.25% available) |
| Hysteresis | 0.2% max. |
| Resolution | 0.088° for 360° travel, 0.011° for 45° travel |
| Supply current | 7.5 mA typical, 11 mA max. |
| Dielectric strength | 750 V rms |
| Insulation resistance | 1,000 megΩ min. |
| Electrostatic discharge (ESD) | Passes 2 kV human body model and 15 kV air discharge |
| Bulk current injection (BCI) | Passes 2-500 MHz at 200 mA |
| Actual electrical travel | 360° typical (see ordering information) |
| Temperature coefficient of output voltage | ±20 ppm/°C |

Mechanical Specifications

| | |
|--------------------------------|---|
| Total mechanical travel | 360° continuous (320° with stop feature) |
| Bearing | Bearing bronze bushing |
| Weight | 0.6 oz. typical |
| Static stop strength | 40 in. oz. |
| Panel nut tightening torque | 25 in. lb. max. |
| Supply voltage absolute limits | 20 Vdc max., -10 Vdc min. |
| Independent linearity | ±0.5% (0.25% available) |
| Hysteresis | 0.2% max. |
| Resolution | 0.088° for 360° travel, 0.011° for 45° travel |

¹ Specifications subject to change without notice.

² Linearity is measured between 1% and 99% of input voltage.

Non-Contacting Hall Effect Single Turn Position Sensor



6120 Series

Environmental Specifications

| | |
|------------------------------|---|
| Operating temperature range | -40°C to +125°C |
| Shock | Per MIL R-39023, 6 ms saw-tooth 100 G's |
| Vibration | Per MIL R-39023, 10 G's, 100 to 500 Hz |
| Moisture resistance, powered | Per MIL 202G, method 106G |
| Rotational life | 10 million shaft revolutions |
| Storage temperature range | -55°C to +125°C |

Feature Codes

| Voltage Output Codes | | Optional Feature Codes | |
|----------------------|-----------------------------------|------------------------|-------------------------------|
| V0 | ≤ 0.15 Vdc to ≥ 4.8 Vdc | ST | Stop (320°) |
| V1 | 0.2 Vdc to 4.8 Vdc | FS | Flatted Shaft (slot standard) |
| V2 | 0.25 Vdc to 4.75 Vdc | LT | Linearity Data |
| V3 | 0.5 Vdc to 4.5 Vdc | SL | Shaft Lock |
| V4 | 0.75 Vdc to 4.25 Vdc | CW | Reverse Direction |
| V5 | 1 Vdc to 4 Vdc | | |

When V0 is used the angle specified is the theoretical angle over which the output would vary if the output could actually reach 0% and 100% of Vcc.

Non-Contacting Hall Effect Single Turn Position Sensor



6120 Series

Outline Drawings



- NOTES:
1. UNIT SHIPS WITH NUT AND WASHER (NOT SHOWN).
 2. FOR SLOTTED OR FLATTED SHAFT, OUTPUT IS AT 50% IN POSITION SHOWN.
 3. DIMENSIONS: INCHES [mm].
 4. TOLERANCES: $\pm .015$ [.38] UNLESS NOTED.

General Note
TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | BI Technologies
Circulo de la Amistad #102 PIMSA IV Mexicali B.C. Mexico C.P 21210
Ph: +1 714 447 2345
www.ttelectronics.com/bi-technologies

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9