# **Dual Matched General Purpose Transistor**

# **PNP Matched Pair**

These transistors are housed in an ultra-small SOT-363 package ideally suited for portable products. They are assembled to create a pair of devices highly matched in all parameters, eliminating the need for costly trimming. Applications are Current Mirrors; Differential, Sense and Balanced Amplifiers; Mixers; Detectors and Limiters. Complementary NPN equivalent NST65011MW6T1G is available.

#### **Features**

- Current Gain Matching to 10%
- Base–Emitter Voltage Matched to ≤ 2 mV
- Drop-In Replacement for Standard Device
- NSV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb–Free, Halogen Free/BFR Free and are RoHS Compliant

#### **MAXIMUM RATINGS**

| Rating                         | Symbol         | Value | Unit |
|--------------------------------|----------------|-------|------|
| Collector – Emitter Voltage    | $V_{CEO}$      | -65   | V    |
| Collector - Base Voltage       | $V_{CBO}$      | -80   | V    |
| Emitter-Base Voltage           | $V_{EBO}$      | -5.0  | V    |
| Collector Current – Continuous | I <sub>C</sub> | -100  | mAdc |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

#### THERMAL CHARACTERISTICS

| Characteristic  | Symbol                            | Max         | Unit  |
|---|-----------------------------------|-------------|-------|
| Total Device Dissipation Per Device FR-5 Board (Note 1) T <sub>A</sub> = 25°C | P <sub>D</sub>                    | 380<br>250  | mW    |
| Derate Above 25°C   |                                   | 3.0         | mW/°C |
| Thermal Resistance,<br>Junction to Ambient                                    | $R_{	heta JA}$                    | 328         | °C/W  |
| Junction and Storage<br>Temperature Range                                     | T <sub>J</sub> , T <sub>stg</sub> | -55 to +150 | °C    |

1.  $FR-5 = 1.0 \times 0.75 \times 0.062$  in.




# ON Semiconductor®

www.onsemi.com



SOT-363 CASE 419B STYLE 1



# **MARKING DIAGRAMS**



4G = Device Code

M = Date Code

= Pb-Free Package

(Note: Microdot may be in either location)

#### ORDERING INFORMATION

| Device          | Package              | Shipping <sup>†</sup> |
|-----------------|----------------------|-----------------------|
| NST65010MW6T1G  | SOT-363<br>(Pb-Free) | 3000 /<br>Tape & Reel |
| NSVT65010MW6T1G | SOT-363<br>(Pb-Free) | 3000 /<br>Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure. BRD8011/D.

# **ELECTRICAL CHARACTERISTICS** (T<sub>A</sub> = 25°C unless otherwise noted)

| Characteristic   | Symbol                               | Min             | Тур               | Max                  | Unit     |  |
|--|--------------------------------------|-----------------|-------------------|----------------------|----------|--|
| OFF CHARACTERISTICS  |                                      |                 |                   |                      |          |  |
| Collector – Emitter Breakdown Voltage, (I <sub>C</sub> = –10 mA)   | V <sub>(BR)CEO</sub>                 | -65             | _                 | -                    | V        |  |
| Collector – Emitter Breakdown Voltage, ( $I_C = -10 \mu A$ , $V_{EB} = 0$ )  | V <sub>(BR)CES</sub>                 | -80             | _                 | -                    | V        |  |
| Collector – Base Breakdown Voltage, (I <sub>C</sub> = –10 μA)  | V <sub>(BR)CBO</sub>                 | -80             | _                 | -                    | V        |  |
| Emitter – Base Breakdown Voltage, ( $I_E = -1.0 \mu A$ )   | V <sub>(BR)EBO</sub>                 | -5.0            | _                 | -                    | V        |  |
| Collector Cutoff Current ( $V_{CB} = -30 \text{ V}$ )<br>( $V_{CB} = -30 \text{ V}$ , $T_A = 150 ^{\circ}\text{C}$ )   | I <sub>CBO</sub>                     | <u>-</u><br>-   | _<br>_            | –15<br>–5.0          | nA<br>μA |  |
| ON CHARACTERISTICS   |                                      |                 |                   |                      |          |  |
| DC Current Gain $ \begin{array}{l} (I_C = -10~\mu\text{A},~V_{CE} = -5.0~\text{V}) \\ (I_C = -2.0~\text{mA},~V_{CE} = -5.0~\text{V}) \\ (I_C = -2.0~\text{mA},~V_{CE} = -5.0~\text{V})~(\text{Note 2}) \end{array} $ | h <sub>FE</sub>                      | -<br>220<br>0.9 | 150<br>290<br>1.0 | -<br>475<br>1.1      | -        |  |
| Collector – Emitter Saturation Voltage ( $I_C = -10$ mA, $I_B = -0.5$ mA) ( $I_C = -100$ mA, $I_B = -5.0$ mA)  | V <sub>CE(sat)</sub>                 | _<br>_          | -<br>-            | -300<br>-650         | mV       |  |
| Base-Emitter Saturation Voltage ( $I_C = -10$ mA, $I_B = -0.5$ mA) ( $I_C = -100$ mA, $I_B = -5.0$ mA)   | V <sub>BE(sat)</sub>                 | -<br>-          | -700<br>-900      | _<br>_               | mV       |  |
| Base – Emitter On Voltage $ \begin{array}{l} (I_C=-2.0 \text{ mA}, V_{CE}=-5.0 \text{ V}) \\ (I_C=-10 \text{ mA}, V_{CE}=-5.0 \text{ V}) \\ (I_C=-2.0 \text{ mA}, V_{CE}=-5.0 \text{ V}) \end{array} $ (Note 3)      | $V_{BE(on)}$ $V_{BE(1)} - V_{BE(2)}$ | -600<br>-<br>-  | -<br>-<br>-1.0    | -750<br>-820<br>-2.0 | mV       |  |
| SMALL-SIGNAL CHARACTERISTICS   |                                      |                 |                   |                      |          |  |
| Current – Gain – Bandwidth Product, ( $I_C = -10 \text{ mA}$ , $V_{CE} = -5 \text{ Vdc}$ , $f = 100 \text{ MHz}$ )   | f <sub>T</sub>                       | 100             | _                 | -                    | MHz      |  |
| Output Capacitance, (V <sub>CB</sub> = -10 V, f = 1.0 MHz)   | C <sub>ob</sub>                      | ı               | _                 | 4.5                  | pF       |  |
| Noise Figure, (I <sub>C</sub> = $-0.2$ mA, V <sub>CE</sub> = $-5$ Vdc, R <sub>S</sub> = $2$ k $\Omega$ , f = 1 kHz, BW = $200$ Hz)   | NF                                   | ı               | -                 | 10                   | dB       |  |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

2.  $h_{FE(1)}/h_{FE(2)}$  is the ratio of one transistor compared to the other transistor within the same package. The smaller  $h_{FE}$  is used as numerator.

3.  $V_{BE(1)} - V_{BE(2)}$  is the absolute difference of one transistor compared to the other transistor within the same package.

# **TYPICAL CHARACTERISTICS**




Figure 1. Normalized DC Current Gain




Figure 2. "Saturation" and "On" Voltages




Figure 3. Collector Saturation Region




Figure 4. Base-Emitter Temperature Coefficient




Figure 5. Capacitances




Figure 6. Current-Gain - Bandwidth Product

# **TYPICAL CHARACTERISTICS**





Figure 7. Active Region Safe Operating Area


The safe operating area curves indicate  $I_C$ – $V_{CE}$  limits of the transistor that must be observed for reliable operation. Collector load lines for specific circuits must fall below the limits indicated by the applicable curve.

The data of Figure 7 is based upon  $T_{J(pk)} = 150$ °C;  $T_{C}$  or  $T_{A}$  is variable depending upon conditions.

#### PACKAGE DIMENSIONS

# SC-88 (SOT-363) CASE 419B-02 **ISSUE Y**






#### NOTES:

- DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
- CONTROLLING DIMENSION: MILLIMETERS.
  DIMENSIONS D AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS. MOLD FLASH, PROTRU-SIONS, OR GATE BURRS SHALL NOT EXCEED 0.20 PER END. DIMENSIONS D AND E1 AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY AND DATUM H.

- DATUMS A AND B ARE DETERMINED AT DATUM H.
  DIMENSIONS b AND c APPLY TO THE FLAT SECTION OF THE LEAD BETWEEN 0.08 AND 0.15 FROM THE TIP.
  DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION.
- ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 TOTAL IN EXCESS OF DIMENSION 6 AT MAXIMUM MATERIAL CONDI-TION. THE DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OF THE FOOT.

|     | MILLIMETERS |            |      | INCHES    |       |       |
|-----|-------------|------------|------|-----------|-------|-------|
| DIM | MIN         | NOM        | MAX  | MIN       | NOM   | MAX   |
| Α   |             |            | 1.10 |           |       | 0.043 |
| A1  | 0.00        |            | 0.10 | 0.000     |       | 0.004 |
| A2  | 0.70        | 0.90       | 1.00 | 0.027     | 0.035 | 0.039 |
| b   | 0.15        | 0.20       | 0.25 | 0.006     | 0.008 | 0.010 |
| С   | 0.08        | 0.15       | 0.22 | 0.003     | 0.006 | 0.009 |
| D   | 1.80        | 2.00       | 2.20 | 0.070     | 0.078 | 0.086 |
| E   | 2.00        | 2.10       | 2.20 | 0.078     | 0.082 | 0.086 |
| E1  | 1.15        | 1.25       | 1.35 | 0.045     | 0.049 | 0.053 |
| е   | 0.65 BSC    |            |      | 0.026 BSC |       |       |
| L   | 0.26        | 0.36       | 0.46 | 0.010     | 0.014 | 0.018 |
| L2  | 0.15 BSC    |            |      | 0.006 BSC |       |       |
| aaa | 0.15        |            |      | 0.006     |       |       |
| bbb | 0.30        |            |      | 0.012     |       |       |
| ccc | 0.10 0.004  |            |      |           |       |       |
| ddd |             | 0.10 0.004 |      |           | -     |       |

#### RECOMMENDED **SOLDERING FOOTPRINT\***



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

STYLE 1:

- PIN 1. EMITTER 2 2 BASE 2

  - COLLECTOR 1 EMITTER 1

  - COLLECTOR 2

ON Semiconductor and una are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

#### **PUBLICATION ORDERING INFORMATION**

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor P.O. Box 5163, Denver, Colorado 80217 USA **Phone**: 303–675–2175 or 800–344–3860 Toll Free USA/Canada Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free

Europe, Middle East and Africa Technical Support: Phone: 421 33 790 2910 Japan Customer Focus Center Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

# **ПОСТАВКА** ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

многоканальный

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

# Данный компонент на территории Российской Федерации Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

# http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

# Офис по работе с юридическими лицами:

105318, г. Москва, ул. Щербаковская д. 3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru moschip.ru\_6 moschip.ru 4 moschip.ru 9