

## 1794A Coax - Low Loss Serial Digital Coax



For more Information  
please call

1-800-Belden1



### Description:

16 AWG solid 0.051" bare copper conductor, gas-injected foamed high-density polyethylene insulation, Duofoil® + tinned copper braid shield (95% coverage) plus Beldfoil® with shorting fold, PVC jacket.

### Usage (Overall)

**Suitable Applications:** SMPTE 424M 3 Gb/s HD-SDI 1080p

### Physical Characteristics (Overall)

#### Conductor

AWG:

| # Coax | AWG | Stranding | Conductor Material | Dia. (in.) |
|--------|-----|-----------|--------------------|------------|
| 1      | 16  | Solid     | BC - Bare Copper   | 0.051      |

**Total Number of Conductors:** 1

#### Insulation

Insulation Material:

| Insulation Material                                 | Dia. (in.) |
|---|------------|
| Gas-injected FHDPE - Foam High Density Polyethylene | 0.225      |

#### Outer Shield

Outer Shield Material:

| Layer # | Outer Shield Trade Name      | Type  | Outer Shield Material                      | Coverage (%) |
|---------|------------------------------|-------|--|--------------|
| 1       | Duofoil®                     | Tape  | Aluminum Foil-Polyester Tape-Aluminum Foil | 100.000      |
| 2       |                              | Braid | TC - Tinned Copper                         | 95.000       |
| 3       | Beldfoil® with shorting fold | Tape  | Polyester Tape-Aluminum Foil               | 100.000      |

#### Outer Jacket

Outer Jacket Material:

| Outer Jacket Material    |
|--------------------------|
| PVC - Polyvinyl Chloride |

#### Overall Cable

**Overall Nominal Diameter:** 0.320 in.

### Mechanical Characteristics (Overall)

**Operating Temperature Range:** -30°C To +75°C

**Bulk Cable Weight:** 59 lbs/1000 ft.

**Max. Recommended Pulling Tension:** 111 lbs.

**Min. Bend Radius/Minor Axis:** 3.250 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

**NEC/(UL) Specification:** CMR

**CEC/C(UL) Specification:** CMG

**EU CE Mark:** Yes

**EU Directive 2000/53/EC (ELV):** Yes

|                                       |            |
|---------------------------------------|------------|
| EU Directive 2002/95/EC (RoHS):       | Yes        |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2004 |
| EU Directive 2002/96/EC (WEEE):       | Yes        |
| EU Directive 2003/11/EC (BFR):        | Yes        |
| CA Prop 65 (CJ for Wire & Cable):     | Yes        |
| MII Order #39 (China RoHS):           | Yes        |
| Series Type:                          | Series 7   |

### Flame Test

|                 |                       |
|-----------------|-----------------------|
| UL Flame Test:  | UL1666 Vertical Shaft |
| CSA Flame Test: | FT4                   |

### Suitability

|                       |     |
|-----------------------|-----|
| Suitability - Indoor: | Yes |
|-----------------------|-----|

### Plenum/Non-Plenum

|               |    |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

## Electrical Characteristics (Overall)

### Nom. Characteristic Impedance:

|                 |
|-----------------|
| Impedance (Ohm) |
| 75              |

### Nom. Inductance:

|                    |
|--------------------|
| Inductance (µH/ft) |
| 0.091              |

### Nom. Capacitance Conductor to Shield:

|                     |
|---------------------|
| Capacitance (pF/ft) |
| 16.100              |

### Nominal Velocity of Propagation:

|        |
|--------|
| VP (%) |
| 84.000 |

### Nominal Delay:

|               |
|---------------|
| Delay (ns/ft) |
| 1.210         |

### Nom. Conductor DC Resistance:

|                          |
|--------------------------|
| DCR @ 20°C (Ohm/1000 ft) |
| 4.000                    |

### Nominal Outer Shield DC Resistance:

|                          |
|--------------------------|
| DCR @ 20°C (Ohm/1000 ft) |
| 1.900                    |

### Nom. Attenuation:

| Freq. (MHz) | Attenuation (dB/100 ft.) |
|-------------|--------------------------|
| 1.000       | 0.170                    |
| 3.580       | 0.300                    |
| 5.000       | 0.350                    |
| 6.000       | 0.380                    |
| 7.000       | 0.400                    |
| 10.000      | 0.480                    |
| 12.000      | 0.520                    |
| 25.000      | 0.740                    |
| 55.000      | 1.080                    |
| 67.500      | 1.200                    |
| 71.500      | 1.240                    |
| 88.500      | 1.370                    |
| 100.000     | 1.460                    |

## 1794A Coax - Low Loss Serial Digital Coax

|          |        |
|----------|--------|
| 135.000  | 1.700  |
| 143.000  | 1.750  |
| 180.000  | 1.970  |
| 270.000  | 2.430  |
| 360.000  | 2.830  |
| 540.000  | 3.500  |
| 720.000  | 4.090  |
| 750.000  | 4.180  |
| 1000.000 | 4.890  |
| 1500.000 | 6.100  |
| 2000.000 | 7.200  |
| 2250.000 | 7.690  |
| 3000.000 | 9.080  |
| 4500.000 | 11.530 |

### Max. Operating Voltage - UL:

| Voltage   |
|-----------|
| 300 V RMS |

**Other Electrical Characteristic 1:** Impedance tested in accordance with ASTM D-4566 paragraph 43.2, option 2 using a 75 Ohm fixed bridge and termination. 75 +/- 3 Ohms

**Other Electrical Characteristic 2:** Return Loss tested in accordance with ASTM D-4566 paragraph 45.3, using a 75 Ohm fixed bridge and termination.

### Minimum Return Loss:

| Start Freq. (MHz) | Stop Freq. (MHz) | Min. RL (dB) |
|-------------------|------------------|--------------|
| 5                 | 1600             | 23           |
| 1600              | 4500             | 21           |

### Sweep Test

**Sweep Testing:** 100% Sweep tested 5 MHz to 4.5 GHz.

### Put Ups and Colors:

| Item #        | Putup    | Ship Weight | Color       | Notes | Item Desc                    |
|---------------|----------|-------------|-------------|-------|------------------------------|
| 1794A N3U1000 | 1,000 FT | 63.000 LB   | GREEN, MIL  | C     | #16 LDPE/GIFHDLDPPE SH FRPVC |
| 1794A 0011000 | 1,000 FT | 63.000 LB   | BROWN       | C     | #16 LDPE/GIFHDLDPPE SH FRPVC |
| 1794A 0021000 | 1,000 FT | 63.000 LB   | RED         | C     | #16 LDPE/GIFHDLDPPE SH FRPVC |
| 1794A 0031000 | 1,000 FT | 63.000 LB   | ORANGE      | C     | #16 LDPE/GIFHDLDPPE SH FRPVC |
| 1794A 0041000 | 1,000 FT | 63.000 LB   | YELLOW      | C     | #16 LDPE/GIFHDLDPPE SH FRPVC |
| 1794A 0061000 | 1,000 FT | 63.000 LB   | BLUE, LIGHT | C     | #16 LDPE/GIFHDLDPPE SH FRPVC |
| 1794A 0071000 | 1,000 FT | 63.000 LB   | VIOLET      | C     | #16 LDPE/GIFHDLDPPE SH FRPVC |
| 1794A 0081000 | 1,000 FT | 63.000 LB   | GRAY        | C     | #16 LDPE/GIFHDLDPPE SH FRPVC |
| 1794A 0091000 | 1,000 FT | 63.000 LB   | WHITE       | C     | #16 LDPE/GIFHDLDPPE SH FRPVC |
| 1794A 0101000 | 1,000 FT | 63.000 LB   | BLACK       | C     | #16 LDPE/GIFHDLDPPE SH FRPVC |

#### Notes:

C = CRATE REEL PUT-UP.

Revision Number: 1    Revision Date: 05-12-2010

© 2012 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide

## 1794A Coax - Low Loss Serial Digital Coax

for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9