

## METRIC MEASUREMENT VERSION

76104WS Multi-Conductor - 300V Foil/Spiral Shield, Continuous Flexing Data Applications Up to 6 Million Flex Life Cycles



For more Information  
please call

1-800-Belden1

**General Description:**

26 AWG stranded (7x33) tinned copper conductors, PVC insulation, Aluminum/Polyester Foil Shield, Tinned copper spiral shield, 90% coverage, oil-resistant PVC jacket.

**Physical Characteristics (Overall)****Conductor**

AWG:

| # Conductors | AWG | Stranding | Conductor Material |
|--------------|-----|-----------|--------------------|
| 4            | 26  | 7x34      | TC - Tinned Copper |

**Insulation**

Insulation Material:

| Insulation Material      | Wall Thickness (mm) |
|--------------------------|---------------------|
| PVC - Polyvinyl Chloride | 0.254               |

Insulation Color Code Chart:

| Number | Color |
|--------|-------|
| 1      | Black |
| 2      | Red   |
| 3      | White |
| 4      | Green |

**Outer Shield**

Outer Shield Material:

| Layer # | Type  | Outer Shield Material | Coverage (%) |
|---------|-------|-----------------------|--------------|
| 1       | Tape  | Aluminum/Mylar        | 100.000      |
| 2       | Serve | TC - Tinned Copper    | 90.000       |

**Outer Jacket**

Outer Jacket Material:

| Outer Jacket Material    | Nom. Wall Thickness (mm) |
|--------------------------|--------------------------|
| PVC - Polyvinyl Chloride | 1.016                    |

**Overall Cable**

Overall Nominal Diameter: 5.055 mm

**Mechanical Characteristics (Overall)**

|                                        |                  |
|----------------------------------------|------------------|
| Bulk Cable Weight:                     | 35.717 Kg/Km     |
| Max. Recommended Pulling Tension:      | 58.716 N         |
| Min. Bend Radius/Minor Axis:           | 40.640 mm        |
| Min. Bend/Installation:                | 40.640 mm        |
| Min. Bend Radius (Continuous Flexing): | 40.640 mm        |
| Flex Cycle Rating:                     | 6 Million Flexes |

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

|                                               |                                                                                                                                               |
|-----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| NEC/(UL) Specification:                       | CM                                                                                                                                            |
| CEC/(UL) Specification:                       | CMG                                                                                                                                           |
| EU Directive 2011/65/EU (ROHS II):            | Yes                                                                                                                                           |
| MII Order #39 (China RoHS):                   | Yes                                                                                                                                           |
| Customer Part Number Reference Specification: | AWM/STYLE 10002, AWM/STYLE 2661, CSA AWM I/II A/B, EU Directive 2011/65/EU(RoHS2), REACH Regulation (EC 1907/2006), California Proposition 65 |

**Flame Test**

CSA Flame Test: FT4

**Suitability**

Suitability - Burial: Yes

**Electrical Characteristics (Overall)**

Nom. Inductance:

| Inductance (µH/m) |
|-------------------|
|-------------------|



METRIC MEASUREMENT VERSION

76104WS Multi-Conductor - 300V Foil/Spiral Shield, Continuous Flexing Data Applications Up to 6 Million Flex Life Cycles

0.656

Nom. Capacitance Conductor to Conductor:

| Freq. (MHz) | Capacitance (pF/m) |
|-------------|--------------------|
| 0.001       | 91.868             |

Nom. Conductor DC Resistance:

| DCR @ 20°C (Ohm/km) |
|---------------------|
| 137.802             |

Nominal Outer Shield DC Resistance:

| DCR @ 20°C (Ohm/km) |
|---------------------|
| 21.655              |

Max. Operating Voltage - UL:

| Voltage |
|---------|
| 300V    |

Notes (Overall)

Notes: Temperature Range -10 to 105°C(static), +5 to 105°C (dynamic)

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|--------|-------|-------------|-------|-------|-----------|
|--------|-------|-------------|-------|-------|-----------|

Revision Number: 0    Revision Date: 09-27-2017

© 2017 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9