AUK Semiconductor

S1117API/S1117-xxPI

Adjustable and Fixed LDO Voltage Regulator

Descriptions

The S1117 series of positive adjustable and fixed regulators are designed to provide 1A with high efficiency. All internal circuitry is designed to operate down to 1.3V input to output differential. On-chip trimming adjusts reference voltage to 2%.

Features


- Adjustable or Fixed output
- Output Current of 1A
- Low Dropout, 1.3V maximum at 1A Output Current
- Thermal Shutdown Protection
- Fast Transient Response

Ordering Information


Type NO.	Marking	Package Code
S1117API/S1117xxPI	S1117□□PI/ S1117□□□PI	TO-220F

□□:Voltage Code (Aj : 1.25V, 15:1.5V,:18: 1.8V, 25:2.5V, 33:3.3V, 50:5.0V)
□□□:Voltage Code (285:2.85V)

Outline Dimensions (Unit : mm)



BLOCK DIAGRAM



PIN Connections
1. GND/Adj
2. Output voltage
3. Input voltage

Absolute Maximum Ratings

Ta=25°C

Characteristic	Symbol	Rating	Unit
Input voltage	V_I	16	V
Power Dissipation	P_D	2.0	W
Junction Temperature	T_J	150	°C
Storage Temperature Range	T_{stg}	-55 ~ 150	°C

Device Selection Guide (NOTE1)

Device	Output Voltage
S1117API	Adjustable
S1117-15PI	1.5V
S1117-18PI	1.8V
S1117-25PI	2.5V
S1117-285PI	2.85V
S1117-33PI	3.3V
S1117-50PI	5.0V

Note 1 : Other fixed versions are available V_O=1.5V to 5V

Electrical Characteristics

(Electrical Characteristics at T_J = 25℃ and V_I=(V_O+1.5V), I_L=10 ㎃, C_O=10 ㎌ unless otherwise specified.)

Characteristic	Symbol	Device	Test Condition		Min	Typ	Max	Unit
Output Voltage	V_O	S1117A	V_I = (V_O+1.5V),I_O = 10 ㎃		1.225	1.25	1.275	V
			V_I = (V_O+1.5V) to 7V I_O = 0 to 1000 ㎃	*	1.200		1.300	
		S1117-15	V_I = (V_O+1.5V),I_O = 10 ㎃		1.470	1.5	1.530	
			V_I = (V_O+1.5V) to 7V I_O = 0 to 1000 ㎃	*	1.440		1.560	
		S1117-18	V_I = (V_O+1.5V),I_O = 10 ㎃		1.764	1.8	1.836	
			V_I = (V_O+1.5V) to 7V I_O = 0 to 1000 ㎃	*	1.728		1.872	
		S1117-25	V_I = (V_O+1.5V),I_O = 10 ㎃		2.450	2.5	2.550	
			V_I = (V_O+1.5V) to 7V I_O = 0 to 1000 ㎃	*	2.400		2.600	
		S1117-285	V_I = (V_O+1.5V),I_O = 10 ㎃		2.793	2.85	2.907	
			V_I = (V_O+1.5V) to 7V I_O = 0 to 1000 ㎃	*	2.736		2.964	
		S1117-33	V_I = (V_O+1.5V),I_O = 10 ㎃		3.234	3.3	3.366	
			V_I = (V_O+1.5V) to 7V I_O = 0 to 1000 ㎃	*	3.168		3.432	
		S1117-50	V_I = (V_O+1.5V),I_O = 10 ㎃		4.900	5.0	5.100	
			V_I = (V_O+1.5V) to 7V I_O = 0 to 1000 ㎃	*	4.800		5.200	
Line Regulation (Note2)	$\triangle V_{O(\triangle VI)}$	All	1.5V≤ V_I-V_O≤7V I_O=10 ㎃		-	5	10	㎷
Load Regulation (Note2)	$\triangle V_{O(\triangle IL)}$	All	V_I=(V_O+1.5V) I_O=10 ㎃ ~ 1000 ㎃		-	10	30	㎷
Quiescent Current	I_{QC}	All	V_I= V_O + 1.5V V_{ADJ}=0V	*	-	7	13	㎃
Minimum Load Current	$I_{L(MIN)}$	S1117A	V_I=(V_O+1.5V), V_O=0V	*		3	7	㎃
Adjust Pin Current	I_{ADJ}	S1117A	V_I = (V_O+1.5V) to 7V I_O = 10 ㎃	*		55	90	㎂
Dropout Voltage (Note4)	V_{DROP}	All	I_O =1000 ㎃	*	-	1.2	1.3	V
Ripple Rejection (Note3)	RR	All	V_I-V_O=1.5V, I_O=1000 ㎃ V_{Ripple}=1V_{P-P} , f=120 ㎐		60	72	-	㏈
Current Limit	I_{LIMIT}	All	(V_I-V_O)=1.5V	*	1			A

The * denotes the specifications which apply over the full temperature range.

Note 2: Low duty pulse testing with Kelvin connections required.

Note 3: 120 ㎐ input ripple (C_{ADJ} for ADJ=25 ㎌)

Note 4: △ V_O = 1%

■ Typical Applications





Fig. 1 Fixed Voltage Regulator



$V_O=V_{ADJ} * (1 + R_2/R_1) + I_{ADJ}*R_2$

Fig. 2 Adjustable Voltage Regulator

Notes:

1) C_I needed if device is far from filter capacitors

2) C_O minimum value required for stability

Electrical Characteristic Curves

Fig. 3 V_{DROP} vs. I_O




Fig. 4 ΔV_O vs. T_a




Fig. 5 RR vs. Frequency




Fig. 6 Temperature Stability




Fig. 7 I_{ADJ} vs. T_a





Fig. 8 P_D vs. T_a



These AUK Corp. products are intended for usage in general electronic equipment (Office and communication equipment, measuring equipment, domestic electrification, etc.) Please make sure that you consult with us before you use these AUK products in equipm- ents which require high quality and/or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, traffic signal, combustion central, all types of safety device, etc.) AUK cannot accept liability to any damage which may occur in case these AUK products were used in the mentioned equipments without prior consultation

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9