10135267 - 1 0 X LF

SEE NOTE 2

LEAD-FREE DESIGNATION ONLY WITH APPLICABLE PLATING CODES

MODULE DESCRIPTION	LETTER DESIGNATION REPRESENTED IN DASH NUMBER										BASE MODULE
LEFT POLARIZING GUIDANCE MODULE (SEE SHEET 3)	N	J (NO KEY)	A	B	C	D	E	F	G	H	
	NO KEY NO GUIDEPIN										
RIGHT POLARIZING GUIDANCE MODULE (SEE SHEET 2)	Z	Y (NO KEY)	P	Q	R	S	T	U	V	W	
	NO KEY NO GUIDEPIN										

NO TOOLED

PRELIMINARY

spec ref	---		dr	Jeny Ren	2015/05/26	projection	MM	size A2 / scale 8:1
tolerance std ASME Y14.5M	TOLERANCES UNLESS OTHERWISE SPECIFIED		eng	Jackie Chen	2016/03/13			
			chr	-	-			ecn no -
			appr	-	-	product family AirMax VS2		rel level Preliminary
surface -	linear	0.X ±.3	Amphenol FCi	title	AIRMAX VS2 R.A. RECEPTACLE ASS'Y, 3 PAIR, 72 POS, 8 IMLA, 24MM, W/GUIDE/KEY		dwg no 10135267	rev 1
		0.XX ±.15						
		0.XXX ±.050						
	angular	0° ±°		cat. no. -		Product - Customer Drw		sheet 1 of 4

© 2016 AFCI

For information only. This is a preliminary customer document that is subject to change without notice.

RIGHT POLARIZATION WITH GUIDE









PRELIMINARY

spec ref	- - -		dr	Jeny Ren	2015/05/26	projection	MM
tolerance std ASME Y14.5M	TOLERANCES UNLESS OTHERWISE SPECIFIED		eng	Jackie Chen	2016/03/13		size A2 / scale 6:1
			chr	-	-		ecn no -
			appr	-	-	product family AirMax VS2	rel level Preliminary
surface -	linear	0.X ±.3	Amphenol FCi	title	AIRMAX VS2 R.A. RECEPTACLE	dwg no 10135267	rev 1
		0.XX ±.15			ASS'Y, 3 PAIR, 72 POS, 8 IMLA, 24MM, W/GUIDE/KEY		
		0.XXX ±.050			cat. no. -	Product - Customer Drw	sheet 2 of 4
	angular	0° ±°					

© 2016 AFCI

Creo File - REV E - 2016-02-12

For information only. This is a preliminary customer document that is subject to change without notice.

LEFT POLARIZATION WITH GUIDE









RECOMMENDED PCB LAYOUT

PRELIMINARY

spec ref	- - -		dr	Jeny Ren	2015/05/26	projection	MM	size A2 / scale 8:1
tolerance std ASME Y14.5M	TOLERANCES UNLESS OTHERWISE SPECIFIED		eng	Jackie Chen	2016/03/13			ecn no -
			chr	-	-			
			appr	-	-	product family	AIRMAX VS2	rel level Preliminary
surface -	linear	0.X ±.3	Amphenol FCi	title	AIRMAX VS2 R.A. RECEPTACLE ASS'Y, 3 PAIR, 72 POS, 8 IMLA, 24MM, W/GUIDE/KEY		dwg no 10135267	rev 1
		0.XX ±.15						
		0.XXX ±.050						
	angular	0° ±°	www.fci.com	cat. no. -		Product - Customer Drw		sheet 3 of 4

Amphenol FCi
© 2016 AFCI
Creo File - REV E - 2016-02-12
For information only. This is a preliminary customer document that is subject to change without notice.

PRODUCT NUMBER	PRESS-FIT TAIL PLATING TYPE
10135267-10*LF	TIN OVER NICKEL (LEAD FREE)



10135267 -10ALF



10135267-10PLF

(1) - CONNECTOR MATERIALS:
HOUSING: HIGH TEMP THERMOPLASTIC, NATURAL, UL94-V0
IMLA PLASTIC: HIGH TEMP THERMOPLASTIC, BLACK, UL94-V0
CONTACT: COPPER ALLOY
ORGANIZER: HIGH TEMP THERMOPLASTIC, WHITE, UL94-V0

2 - CONTACT PLATING:
SEPARABLE INTERFACE:
PERFORMANCE-BASED PLATING, QUALIFIED TO MEET THE REQUIREMENTS OF FCI PRODUCT SPECIFICATION GS-12-0956 INCLUDING TELCORDIA GR-1217-CORE (NOVEMBER 1995) CENTRAL OFFICE TEST SEQUENCE

PRESS-FIT TAILS: SEE TABLE

3 - PRODUCT SPECIFICATION: GS-12-0956

4 - APPLICATION SPECIFICATION: GS-20-0305.

(5) - PRODUCT MARKING, (PART NUMBER & LOT CODE), ON THIS SURFACE.

(6) - THE MINIMUM CENTERLINE SPACING BETWEEN ADJACENT MODULES IS 24.0 MM.

(7) - CONNECTOR OUTLINE MAY BE SCREEN PRINTED ONTO CUSTOMER PCB TO BE USED AS A GUIDE FOR MANUAL CONNECTOR PLACEMENT.

(8) - REFER TO CUSTOMER DRAWING 10104444 FOR INFORMATION ON PCB HOLE DIAMETERS AND PLATING OPTIONS

9 - LEAD FREE PRODUCT MEETS THE EUROPEAN UNION DIRECTIVES & OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008

10 - PACKAGING MEETS GS-14-920 LEAD FREE LABELING SPECIFICATION.

(11) - GROUND CONTACTS (C,F, AND I IN ODD COLUMNS AND A, D, AND G, EVEN COLUMNS) REQUIRE (∅0.500) FINISHED HOLES. SIGNAL LOCATIONS REQUIRE (∅0.400) FINISHED HOLES.

(12) - THESE OUTER VIAS (J) ARE OPTIONAL. WHILE NO CONNECTOR EONS ARE PRESSED INTO THESE HOLES WE RECCOMMEND (∅0.500) FINISHED HOLES AT THESE LOCATIONS TO PROVIDE GROUND SYMMETRY THROUGH THE PCB.

13 - A △- SYMBOL WILL BE NEXT TO ANY DIMENSION, VIEW, OR NOTE, WHICH HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION

(14) - CUSTOMER CAN FIX THE CONNECTOR WITH THREAD FORMING SCREW THROUGH THIS PTH. THE SCREW IS #2-32, THE VALID LENGTH OF SCREW IS 4.5MM PLUS THE THICKNESS OF PCB.



DETAIL A
SCALE 20:1

© 2016 AFCI

PRELIMINARY

spec ref	---		dr	Jeny Ren	2015/05/26	projection	MM	size A2 / scale 6:1
tolerance std ASME Y14.5M	TOLERANCES UNLESS OTHERWISE SPECIFIED		eng	Jackie Chen	2016/03/13			ecn no -
			chr	-	-			
			appr	-	-	product family	AirMax VS2	rel level Preliminary
surface -	linear	0.X ±.3	Amphenol FCi	title	AIRMAX VS2 R.A. RECEPTACLE ASS'Y, 3 PAIR, 72 POS, 8 IMLA, 24MM, W/GUIDE/KEY	dwg no	10135267	rev 1
		0.XX ±.15						
		0.XXX ±.050						
	angular	0° ±°	www.fci.com	cat. no. -		Product - Customer Drw		sheet 4 of 4

Creo File - REV.E - 2016-02-12
For information only. This is a preliminary customer document that is subject to change without notice.

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9