







Copyright FCI.

PRODUCT NUMBER SEE SHEET 2




spec ref				dr		Eddy Zeng	2014/04/17		projection				size		A3	scale		3:2					
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED				eng		Rainbow Zhan	2014/06/20				ecn no					-					
ASME Y14.5						chr		LI- He	2014/06/18														
						appr		Pei-Ming Zheng	2014/06/20														
												product family		PowerBlade+		rel level		Released					
surface				linear		0.X		±0.50				title		3ACP +16S + 5HP		dwg no		10106268-8004001		rev		A	
				0.XX		±0.25																	
				0.XXX		±0.10																	
ASME Y14.5		angular		0°		±2°		www.fci.com		cat. no.		Product - Customer Drw		sheet 1 of 3									



Copyright FCI.

PRODUCT NO.	ROWS															CODE	DESCRIPTION
		E1	P8	P7	P6	P5	P4	4	3	2	1	P3	P2	P1	E2		
10106268-8004001LF	D C B A		H6	H3	H3	H3	H6	E	E	E	E	H3	H3	H6		E	STD SIGNAL CONTACT
								E	E	E	E					H3	STD HIGH POWER CONTACT (3.43)
								E	E	E	E					H6	MFBL HIGH POWER CONTACT (3.43)



dr	Eddy Zeng	2014/04/17	projection	MM	size	A3	scale	3:2
eng	Rainbow Zhan	2014/06/20			ecn no	-		
chr	Li- He	2014/06/18			rel level	Released		
appr	Pei-Ming Zheng	2014/06/20	product family	PowerBlade+				
www.fci.com		cat. no.		Product - Customer Drw			sheet 2 of 3	
FCi		title			dwg no		rev	
		3ACP + 16S + 5HP			10106268-8004001		A	
		VT STB RECEPTACLE						

A

B

C

D

A

B

C

D

NOTES:

- 1) "FCI", PART NUMBER AND DATE CODE TO BE MARKED ON THIS SURFACE.
THE MARK CAN BE OMITTED IF THERE IS NOT ENOUGH SPACE ON THIS SURFACE.
- 2) MATERIALS:
-HOUSING - GLASS FILLED WITH HIGH TEMP THERMOPLASTIC, UL94V-0.
-SIGNAL CONTACT - COPPER ALLOY.
-POWER CONTACT - HIGH CONDUCTIVITY COPPER ALLOY.
- 3) PLATING SPECIFICATION REFER TO FCI 10116351
- 4) DENOTES CONNECTOR KEEP OUT ZONE.
- 5) DATUM AND BASIC DIMENIONS WERE ESTABLISHED BY CUSTOMER.
- 6) ALL HOLE DIAMETERS ARE FINISHED HOLE SIZES.
- 7) 1.15 ± 0.025MM DRILLED HOLE PLATED WITH 0.00762MM MIN Sn
OVER 0.0254-0.0762MM Cu PLATING TO ACHIEVE A 1.02 ± 0.07MM HOLE.
- 8) PRODUCT SPECIFICATION REFER TO FCI GS-12-658.
APPLICATION SPECIFICATION REFER TO FCI GS-20-141.
PRODUCT PACKAGED IN TRAYS, REFER TO FCI GS-14-1502.
- 9) THE VOID CORING IN BETWEEN POWER MODULES, SIGNAL
MODULES AND END MODULES ARE OPTIONAL AND THE SHAPE
MAY BE DIFFERENT FOR OPTIMIZE THE MOLDING PROCESS. THE
VOID CORING WILL NOT EFFECT TO PRODUCT FUNCTION.



Copyright FCI.

dr	Eddy Zeng	2014/04/17	projection	MM	size	A3	scale	1:1				
eng	Rainbow Zhan	2014/06/20			ecn no			-				
chr	Li- He	2014/06/18			rel level			Released				
appr	Pei-Ming Zheng	2014/06/20	product family		PowerBlade+							
			title			3ACP +16S + 5HP		dwg no	10106268-8004001	rev	A	
VT STB RECEPTACLE			cat. no.			Product - Customer Drw			sheet 3 of 3			
www.fci.com												

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9