

Description

Single pole, miniaturised thermal circuit breaker with trip-free mechanism and push/pull on/off manual actuation (M-type TO CBE to EN 60934). Threadneck panel mounted, temperature-compensated, with optional auxiliary contacts. Fully approved for commercial aircraft and similar requirements.

Various dummies are available without protective function, allowing connection of pre-installed wiring without loads.

US patent number: US 6,490,141 B2 (4120-G4 moulded threadneck)

Typical applications

Extra low voltage wiring systems on all types of vehicles for land, sea and air.

Ordering information

Type No.

4120 single pole, with temperature compensation

Mounting

G threadneck panel mounting

Threadneck design

1 M12x1x6.3 (aluminium)

2 7/16-32 UNx6.3 (aluminium)

Number of poles

1 1-pole, thermally protected

Hardware for threadneck

0 without hardware

1 hex nut M12x1, corrugated washer 12/15, fitted

3 hex nut M12x1 (aluminium), serrated lock washer 12.1/17.2, bulk shipped

4 hex nut 7/16-32UN (aluminium), serrated lock washer 11.3/14.9, fitted

Terminal design (main terminals)

K1 screw terminals with metric thread K14 (M4)

J1 screw terminals with inch thread J14 (8-32UNC-2B)

J2 screw terminals with inch thread J17 (8-32UNC-2B)

J3 screw terminals with inch thread J25 (6-32UNC-2B)

P1 blade terminals 6.3x0.8, DIN 46244, silver-plated

Characteristic curve

M1 thermal, 1.15 - 1.4 I_N

Terminal screws

A Phillips screw M4x6, fitted

B Phillips screw 8-32UNC-2Ax6, fitted

C Phillips screw 6-32UNC-2Ax6 (MS 51957-26)

K hex screw with Phillips head 8-32UNC-3Ax7.6, fitted

M hex screw with Phillips head 8-32UNC-3Ax7.6, bulk shipped

Z without terminal hardware

Terminal washers

0 without lock washer

1 wave washer A4, fitted

2 lock washer 4.3, fitted

4 lock washer 3.7 (MS 35338-136)

5 lock washer 4.3/9, fitted

6 lock washer 4.3/9, bulk shipped

Auxiliary contact

S0 without auxiliary contact

S1 with auxiliary contact (connector

EN 3155-016M2018) (NC)

S5 with polarized auxiliary contact (NC)

Barrier

Z without barrier

Colour of the push button

G green to EN (e. g. 2 1/2)

N black to EN (e. g. 2 1/2)

Current ratings

1...25 A

4120 - G 1 1 - 1 - K1 M1 - A 1 S0 Z N - 10 A ordering example



4120-...

Technical data

Voltage rating	AC 115 V (300 Hz to 800 Hz); DC 28 V		
Current rating range	1...25 A (0.5 A upon request)		
Auxiliary circuit	1 A, DC 28 V (0.5 A upon request)		
Typical life	20,000 operations mechanical, or 5,000 operations at 1 x I _N		
Ambient temperature	-55°C ...+125°C (-67...+257 °F)		
Insulation co-ordination (IEC 60664 and 60664A)	rated impulse withstand voltage 1.5 kV	pollution degree 3	
Dielectric strength (IEC 60664 and 60664A) operating area main to aux. circuit	test voltage AC 1,500 V AC 1,500 V		
Insulation resistance	> 100 MΩ (DC 500 V)		
Interrupting capacity I _{cn}	AC 115 V (400 Hz):	1...4 A 5...25 A	1,000 A 2,000 A
	DC 28 V:	1...25 A	6,000 A
Degree of protection (IEC 60529/DIN 40050)	operating area IP40 terminal area IP00		
Vibration (sinusoidal)	10 g (57-2000 Hz), ± 0.76 mm (5-57 Hz) to ISO 7137, EN 2350 para. 5.3.1		
Vibration	1...2.5 A: 0.04 g ² /Hz ± 1,5 dB; 7.3 g eff 3...20 A: 0.06 g ² /Hz ± 1,5 dB; 9 g eff to ISO 7137, EN 2350 para. 5.3.1		
Acceleration	17 g, to ISO 2669, EN 2350 para. 5.3.3		
Shock	50 g (11 ms), to ISO 7137, EN 2350 para. 5.3.2		
Corrosion	48 hours at 5 % salt mist to ISO 7137, EN 2350 para. 5.4.2		
Humidity	240 hours at 95 % RH, to ISO 7137, EN 2350 para. 5.4.3		
Explosion	to VG 95210, sheet 10		
Altitude	≤ 22,000 m above sea level		
Mass	approx. 20.6 g with terminal screws, without -Si approx. 24.6 g with terminal screws, with -Si		

Preferred types

Preferred types	Standard current ratings (A)								
	1	2	3	5	7.5	10	15	20	25
4120-G214-J1M1-B2S0ZN (MS3320)	x	x	x	x	x	x	x	x	x
4120-G111-K1M1-A1S0ZN (EN 2495/VG93345 T06)	x	x	x	x	x	x	x	x	x

Standard current ratings and typical volt drop values


Current rating (A)	Volt drop (mV)	Current rating (A)	Volt drop (mV)
1	1100	7.5	250
2	550	10	230
2.5	460	15	200
3	440	20	190
4	380	25	190
5	260		

Approvals (configurations)

Authority	Standard	Voltage ratings	Current ratings
UL	UL 1077	DC 50 V	0.5 A...25 A
Bw	VG 95345, part 6	AC 115 V, 400 Hz DC 28 V	1 A...25 A 1 A...25 A
Bw	EN 2495-...U / -...M	AC 115 V, 400 Hz DC 28 V	1 A...25 A 1 A...25 A
Bw	LN 29887	AC 115 V, 400 Hz DC 28 V	5 A...25 A 5 A...25 A
Bw	EN 3773-004	AC 115 V, 400 Hz DC 28 V	1 A...25 A 1 A...25 A
Dep. of the Navy	MS 3320	AC 115 V, 400 Hz DC 28 V	1 A...20 A 1 A...20 A
Airbus	EN 2995-004	AC 115 V, 400 Hz DC 28 V	1 A...25 A 1 A...25 A
Airbus	EN 2995-005	AC 115 V, 400 Hz DC 28 V	1 A...25 A 1 A...25 A


Dimensions 4120-...

4120-G214-J1M1-B2S0ZN (MS 3320)




Dimensions 4120-G1..


4120-G111-K1M1-A1S0ZN (EN2495-...M) (VG95345 T06)



4120-G11-J2M1-K5S0ZN (EN2495-...U, EN3773-004 D...)



4120-G112-J2M1-K5S1ZG - 4120-G112-J2M1-K5S5ZG (EN2995-004) (EN2995-005)



This is a metric design and millimeter dimensions take precedence (mm)
inch

Mounting holes

4120-G2...

mounting holes S0

Technical drawing of mounting plate 4120-G2 showing dimensions for mounting holes S0. The plate has a central circular hole and four corner mounting holes. Dimensions include overall width and height, hole diameters, and hole positions.

Dimensions:

- Overall width: $\varnothing 3.2^{+0.15}_{-0.126}$
- Overall height: $9.5^{+0.2}_{-0.374}$
- Central hole diameter: $\varnothing 11.5^{+0.2}_{-0.453}$
- Thickness: 1.5 - 3 mm, .059 - .118 in.
- Mounting hole diameter: $\varnothing 3.5^{+0.1}_{-0.118}$
- Mounting hole positions: min. 20, min. 25*, min. .787, min. .984*
- Mounting hole diameter: $\varnothing 12.5^{+0.2}_{-0.492}$
- Mounting hole positions: min. 30, min. 1.18
- Thickness: 1.5 - 3 mm, .059 - .118 in.

4120-G1...

mounting holes S1 or S5

Technical drawing of mounting plate 4120-G1 showing dimensions for mounting holes S1 or S5. The plate has a central circular hole and four corner mounting holes. Dimensions include overall width and height, hole diameters, and hole positions.

Dimensions:

- Overall width: $\varnothing 3.2^{+0.15}_{-0.126}$
- Overall height: $9.5^{+0.2}_{-0.374}$
- Central hole diameter: $\varnothing 12.5^{+0.2}_{-0.492}$
- Thickness: 1.5 - 3 mm, .059 - .118 in.
- Mounting hole diameter: $\varnothing 3.5^{+0.1}_{-0.138}$
- Mounting hole positions: min. 20, min. 25*, min. .787, min. .984*
- Mounting hole diameter: $\varnothing 12.5^{+0.2}_{-0.492}$
- Mounting hole positions: min. 40, min. 1.57
- Thickness: 1.5 - 3 mm, .059 - .118 in.

* min. 25 mm / .984 in. when fitted with splash cover

[illegible]

4120-G1...

mounting holes S1 or S5

Technical drawing showing the dimensions for mounting holes S1 or S5. The drawing includes two views: a top view and a side view.

Top View Dimensions:

- Outer diameter: $\varnothing 3.2^{+0.15}_{-0.006}$
- Inner diameter (hole): $\varnothing 1.26^{+0.02}_{-0.008}$
- Thickness: $1.5^{+0.2}_{-0.008}$ mm (0.059 - 0.118 in.)

Side View Dimensions:

- Outer diameter: $\varnothing 3.5^{+0.1}_{-0.004}$
- Inner diameter (hole): $\varnothing 1.38^{+0.004}_{-0.004}$
- Center-to-center distance: $\varnothing 12.5^{+0.2}_{-0.008}$
- Thickness: $1.5^{+0.2}_{-0.008}$ mm (0.059 - 0.118 in.)

Notes:

- thickness: 1.5 - 3 mm .059 - .118 in.
- * min. 25 mm / .984 in. when fitted with splash cover

mounting holes S1 or S5

Technical drawing of a mounting plate with dimensions for S1 or S5 mounting holes. The plate is rectangular with a central square area containing four circular mounting holes. The dimensions are as follows:

- Top edge: $\phi 3.5^{+0.1}_{-0.04}$ (hole diameter), $.138 \pm .004$ (hole spacing), 9.6 ± 0.1 (total width), $.378 \pm .004$ (total height).
- Left edge: $\phi 12.5^{+0.2}_{-0.08}$ (hole diameter), $.492^{+0.008}$ (hole spacing).
- Right edge: $.40$ (hole spacing), 1.57 (total width).
- Bottom edge: $.40$ (hole spacing), 1.57 (total width).
- Thickness: $1.5 - 3 \text{ mm}$ (indicated by a dimension line and text).

* min. .25 mm / .984 in. when fitted with splash cover

* min. 25 mm / .984 in. when fitted with splash cover

Internal connection diagram

with auxiliary contact
VG 95345 T06

2

with auxiliary contact
EN 2995-004

2

with polarized auxiliary contact
EN 2995-005

2

with auxiliary contact
EN 2995-004

with polarized auxiliary contact
EN 2995-005

with polarized auxiliary contact
EN 2995-005

Other terminal designs

Terminal design -J2

Terminal distances to:

- MS 14 105 (a, b)
- MS 14 153 (a, b)
- MS 22 073 (a)
- MS 22 074 (a)
- MS 25 244 (a)
- MS 25 373 (a, b)

Technical drawing of terminal design -J2. The front view shows a rectangular terminal block with a central screw terminal and two side terminals. The distance between the side terminals is labeled 'a' (18 mm/.709 in.). The distance from the center of the side terminals to the center of the top terminal is labeled 'b' (31 mm/1.22 in.). The side terminals are angled at 45°. The side view shows the terminal block with a width of 10.5 mm (.413 in.).

Terminal design -J3

Terminal distances to:

- MS 26 574 (a, b)

Technical drawing of terminal design -J3. The front view shows a rectangular terminal block with a central screw terminal and two side terminals. The distance between the side terminals is labeled 'a' (15 mm/.591 in.). The distance from the center of the side terminals to the center of the top terminal is labeled 'b' (35.5 mm/1.40 in.). The side terminals are angled at 45°. The side view shows the terminal block with a width of 8.5 mm (.335 in.).

Terminal design -P1

Technical drawing of terminal design -P1. The front view shows a rectangular terminal block with a central screw terminal and two side terminals. The distance between the side terminals is labeled '13' (.512 in.). The distance from the center of the side terminals to the center of the top terminal is labeled '36' (1.42 in.). The side view shows the terminal block with a width of 6.3 mm (.248 in.).

Terminal design -J2

Terminal distances to:

- MS 14 105 (a, b)
- MS 14 153 (a, b)
- MS 22 073 (a)
- MS 22 074 (a)
- MS 25 244 (a)
- MS 25 373 (a, b)

Technical drawing of terminal design -J2. The front view shows a rectangular terminal block with a central screw terminal and two side terminals. The distance between the side terminals is labeled 'a' (18 mm/.709 in.). The distance from the center of the side terminals to the center of the top terminal is labeled 'b' (31 mm/1.22 in.). The side terminals are angled at 45°. The side view shows the terminal block with a width of 10.5 mm (.413 in.).

Terminal design -J3

Terminal distances to:

- MS 26 574 (a, b)

Technical drawing of terminal design -J3. The front view shows a rectangular terminal block with a central screw terminal and two side terminals. The distance between the side terminals is labeled 'a' (15 mm/.591 in.). The distance from the center of the side terminals to the center of the top terminal is labeled 'b' (35.5 mm/1.40 in.). The side terminals are angled at 45°. The side view shows the terminal block with a width of 8.5 mm (.335 in.).

Terminal design -P1

Technical drawing of terminal design -P1. The front view shows a rectangular terminal block with a central screw terminal and two side terminals. The distance between the side terminals is labeled '13' (.512 in.). The distance from the center of the side terminals to the center of the top terminal is labeled '36' (1.42 in.). The side view shows the terminal block with a width of 6.3 mm (.248 in.).

Terminal design -J2

Terminal distances to:

- MS 14 105 (a, b)
- MS 14 153 (a, b)
- MS 22 073 (a)
- MS 22 074 (a)
- MS 25 244 (a)
- MS 25 373 (a, b)

Technical drawing of terminal design -J2. The front view shows a rectangular terminal block with a central screw terminal and two side terminals. The distance between the side terminals is labeled 'a' (18 mm/.709 in.). The distance from the center of the side terminals to the center of the top terminal is labeled 'b' (31 mm/1.22 in.). The side terminals are angled at 45°. The side view shows the terminal block with a width of 10.5 mm (.413 in.).

Terminal design -J3

Terminal distances to:

- MS 26 574 (a, b)

Technical drawing of terminal design -J3. The front view shows a rectangular terminal block with a central screw terminal and two side terminals. The distance between the side terminals is labeled 'a' (15 mm/.591 in.). The distance from the center of the side terminals to the center of the top terminal is labeled 'b' (35.5 mm/1.40 in.). The side terminals are angled at 45°. The side view shows the terminal block with a width of 8.5 mm (.335 in.).

Terminal design -P1

Technical drawing of terminal design -P1. The front view shows a rectangular terminal block with a central screw terminal and two side terminals. The distance between the side terminals is labeled '13' (.512 in.). The distance from the center of the side terminals to the center of the top terminal is labeled '36' (1.42 in.). The side view shows the terminal block with a width of 6.3 mm (.248 in.).

Terminal design -J3

Terminal distances to:
MS 26 574 (a, b)

The drawing shows a front view and a side view of terminal design -J3. The front view includes dimensions: a total height of 35.5 mm (1.40 inches), a base width of 15 mm (.591 inches), a base angle of 45°, and a terminal width of 8.5 mm (.335 inches). The side view shows a terminal height of 6.3 mm (.248 inches).

35.5 mm / 1.40

b

8.5

.335

45°

a

(15 mm / .591 in.)

6.3

.248

Terminal design -J3

Terminal distances to:
MS 26 574 (a, b)

Technical drawing of terminal design -J3. The front view shows a rectangular terminal with a central rectangular cutout. The overall height is dimensioned as $b = 35.5 \text{ mm} / 1.40$. The width is dimensioned as $a = 15 \text{ mm} / .591 \text{ in.}$. The terminal has two mounting holes on the sides, with a 45° angle indicated. The side view shows the terminal's profile with a width of 8.5 and a thickness of $.335$.

Terminal design -P1

Technical drawing of terminal design -P1. The front view shows a rectangular terminal with a central rectangular cutout. The overall height is dimensioned as 36 and 1.42 . The width is dimensioned as 13 and $.512$. The terminal has two mounting holes on the sides. The side view shows the terminal's profile with a width of 6.3 and a thickness of $.248$.

Terminal design -J3

Terminal distances to:
MS 26 574 (a, b)

The drawing shows a front view and a side view of terminal design -J3. The front view includes dimensions: a total height of 35.5 mm (1.40 inches), a base width of 15 mm (.591 inches), a base angle of 45°, and a terminal width of 8.5 mm (.335 inches). The side view shows a terminal width of 8.5 mm (.335 inches).

Terminal distances to:
MS 26 574 (a, b)

35.5 mm / 1.40

b

8.5

.335

45°

a

(15 mm / .591 in.)

Terminal design -P1

The drawing shows a front view and a side view of terminal design -P1. The front view includes dimensions: a total height of 36 mm (1.42 inches), a base width of 13 mm (.512 inches), and a terminal width of 6.3 mm (.248 inches). The side view shows a terminal width of 6.3 mm (.248 inches).

36

1.42

13

.512

6.3


.248

Terminal design -P1

Terminal design -P1

Terminal design -P1

Typical time/current characteristics



This is a metric design and millimeter dimensions take precedence ($\frac{\text{mm}}{\text{inch}}$)

Accessories (approved to VG 95 345, part 23)


Splash cover/hex nut assembly with O ring (IP66 and IP67)

X 200 801 08 nickel plated nut, transparent cover

X 200 801 03 matt black finish nut, black cover


X 200 801 09 matt black finish nut 7/16-32, black cover

X 200 801 12 with blackened nut and transparent cover



Actuator extension (black) to be fitted on the push button

X 200 803 01



Accessories

Identification collar to be snapped on the push button


Y 307 004 01 black

Y 307 004 02 white

Y 307 004 03 red

Y 307 004 04 green


Y 307 004 05 blue



Lock out ring to block the push button in OFF position

Y 307 005 01 red

Y 307 005 02 black



This is a metric design and millimeter dimensions take precedence ($\frac{\text{mm}}{\text{inch}}$)

All dimensions without tolerances are for reference only. In the interest of improved design, performance and cost effectiveness the right to make changes in these specifications without notice is reserved. Product markings may not be exactly as the ordering codes. Errors and omissions excepted.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9