



## Main

|                               |                                          |
|-------------------------------|------------------------------------------|
| Range of product              | OsiSense XC                              |
| Series name                   | Standard format                          |
| Product or component type     | Limit switch                             |
| Device short name             | XCMD                                     |
| Sensor design                 | Miniature                                |
| Body type                     | Fixed                                    |
| Head type                     | Rotary head                              |
| Material                      | Metal                                    |
| Body material                 | Zamak                                    |
| Head material                 | Zamak                                    |
| Fixing mode                   | By the body                              |
| Movement of operating head    | Rotary                                   |
| Type of operator              | Spring return roller lever thermoplastic |
| Type of approach              | Lateral approach 2 directions            |
| Number of poles               | 2                                        |
| Contacts type and composition | 1 NC + 1 NO                              |
| Contact operation             | Snap action                              |

## Complementary

|                                        |                                                                                                                                                                                                                                                                                                                                                                                |
|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Tracks                                 | 24/31 mm                                                                                                                                                                                                                                                                                                                                                                       |
| Switch actuation                       | By 30° cam                                                                                                                                                                                                                                                                                                                                                                     |
| Electrical connection                  | Removable cable connector                                                                                                                                                                                                                                                                                                                                                      |
| Cable length                           | 3.28 ft (1 m)                                                                                                                                                                                                                                                                                                                                                                  |
| Cable composition                      | 5 x 0.75 mm <sup>2</sup>                                                                                                                                                                                                                                                                                                                                                       |
| Wire insulation material               | PvR                                                                                                                                                                                                                                                                                                                                                                            |
| Contacts insulation form               | Zb                                                                                                                                                                                                                                                                                                                                                                             |
| Positive opening                       | With                                                                                                                                                                                                                                                                                                                                                                           |
| Positive opening minimum force         | 0.5 N                                                                                                                                                                                                                                                                                                                                                                          |
| Minimum force for tripping             | 0.1 N                                                                                                                                                                                                                                                                                                                                                                          |
| Maximum actuation speed                | 4.92 ft/s (1.5 m/s)                                                                                                                                                                                                                                                                                                                                                            |
| Contact code designation               | B300, AC-15 (U <sub>e</sub> = 240 V, I <sub>e</sub> = 1.5 A) conforming to EN/IEC 60947-5-1 appendix A<br>R300, DC-13 (U <sub>e</sub> = 250 V, I <sub>e</sub> = 0.1 A) conforming to EN/IEC 60947-5-1 appendix A                                                                                                                                                               |
| [Ui] rated insulation voltage          | 300 V degree of pollution 3 conforming to UL 508<br>400 V degree of pollution 3 conforming to IEC 60947-5-1<br>300 V degree of pollution 3 conforming to CSA C22.2 No 14                                                                                                                                                                                                       |
| Resistance across terminals            | <= 25 MOhm conforming to IEC 60255-7 category 3                                                                                                                                                                                                                                                                                                                                |
| [Uimp] rated impulse withstand voltage | 4 kV conforming to IEC 60664<br>4 kV conforming to IEC 60947-1                                                                                                                                                                                                                                                                                                                 |
| Short-circuit protection               | 6 A by gG cartridge fuse                                                                                                                                                                                                                                                                                                                                                       |
| Electrical durability                  | 5000000 cycles, DC-13, 120 V, 1 W, operating rate: <= 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13, 24 V, 3 W, operating rate: <= 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13, 48 V, 2 W, operating rate: <= 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Mechanical durability                  | 10000000 cycles                                                                                                                                                                                                                                                                                                                                                                |
| Width                                  | 1.18 in (30 mm)                                                                                                                                                                                                                                                                                                                                                                |
| Height                                 | 1.97 in (50 mm)                                                                                                                                                                                                                                                                                                                                                                |
| Depth                                  | 0.63 in (16 mm)                                                                                                                                                                                                                                                                                                                                                                |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                |                       |
|----------------|-----------------------|
| Product weight | 0.49 lb(US) (0.22 kg) |
|----------------|-----------------------|

## Environment

|                                       |                                                                                              |
|---------------------------------------|----------------------------------------------------------------------------------------------|
| shock resistance                      | 25 gn (duration = 18 ms) conforming to IEC 60068-2-27                                        |
| vibration resistance                  | 5 gn (f = 10...500 Hz) conforming to IEC 60068-2-6                                           |
| IP degree of protection               | IP68 conforming to IEC 60529<br>IP66 conforming to IEC 60529<br>IP67 conforming to IEC 60529 |
| IK degree of protection               | IK06 conforming to EN 62262                                                                  |
| overvoltage category                  | Class I conforming to NF C 20-030<br>Class I conforming to IEC 61140                         |
| ambient air temperature for operation | -13...158 °F (-25...70 °C)                                                                   |
| ambient air temperature for storage   | -40...158 °F (-40...70 °C)                                                                   |
| protective treatment                  | TC                                                                                           |
| product certifications                | CCC<br>CSA<br>UL                                                                             |
| standards                             | EN/IEC 60204-1<br>EN/IEC 60947-5-1<br>UL 508<br>CSA C22.2 No 14                              |


## Offer Sustainability

|                                                                                                                            |                                                                                                                            |
|----------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Green Premium product                                                                                                      | Green Premium product                                                                                                      |
| Compliant - since 1002 - Schneider Electric declaration of conformity                                                      | Compliant - since 1002 - Schneider Electric declaration of conformity                                                      |
| Reference not containing SVHC above the threshold                                                                          | Reference not containing SVHC above the threshold                                                                          |
| Available                                                                                                                  | Available                                                                                                                  |
| Need no specific recycling operations                                                                                      | Need no specific recycling operations                                                                                      |
| WARNING: This product can expose you to chemicals including:                                                               | WARNING: This product can expose you to chemicals including:                                                               |
| Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                | Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                |
| Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. | Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

## Dimensions




(1) 2 fixing holes Ø 4.2 mm, counterbored Ø 8 mm by 4 mm deep.

- (2) External diameter of cable 7.5 mm.

## Mounting


### Sweep of Connecting Cable



- (1) Recommended  
(2) To be avoided


## Mounting with Rotary Heads and Levers

### Type of Cam



- (1) Recommended  
(2) To be avoided


## Setting-up with Head ZCE01 and ZCE09



- (1) Tightening torque (Min : 1) (Max : 1.5)

## Wiring Diagram

### 2-pole NC + NO Snap Action




- (BK) Black  
(BK- Black White  
WH)  
(BU) Blue  
(BN) Brown  
(GN- Green Yellow


YE)

## Characteristics of Actuation

### Switch Actuation by 30° Cam



## Functionnal Diagram



(P) Positive opening point

(1) NC contact with positive opening operation

(2) Closed

(3) Open

(4) Tripping

(5) Resetting

(BK) Black

(BK- Black White  
WH)

(BU) Blue

(BN) Brown

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9