





LOC		DIST		REVISIONS				
ES	00	P	LTR	DESCRIPTION	DATE	DWN	APVD	
		K9		REV PER ECR-12-018831	30OCT2012	AY	SZ	



- 1
- OPTIONAL CENTER MODULE, WITH Ø.150 THRU HOLE OR HOLD DOWN FEATURE
- 2
- "AMP", PART NUMBER AND DATE CODE TO BE MARKED IN AREA SHOWN
PARTS UNDER 2.00 LONG MAY BE MARKED ON BOTH SIDES
- 3
- MATERIAL: HOUSING - GLASS FILLED HIGH TEMP THERMO PLASTIC, UL94 V-O
SIGNAL CONTACT - HIGH CONDUCTIVITY COPPER ALLOY
POWER CONTACT - HIGH CONDUCTIVITY COPPER ALLOY
- 4
- CONTACT PLATING: NOBLE METAL PLATING ON CONTACT FUNCTIONAL AREA
OF POWER CONTACTS AND SIGNAL CONTACTS.
- 5
- MECHANICAL CONNECTOR KEEP OUT ZONE
- 6
- DATUM AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER
- 7
- PCB - ALL HOLE DIAMETERS ARE FINISHED HOLE SIZES
- 8
- PCB - 0.0453 ±.0010 DRILLED HOLES PLATED WITH .0003 MIN Sn
OVER .001 TO .003 Cu PLATING TO ACHIEVE A .040 HOLE
- 9
- VARAIBLE DIMENSION SHOWN VIEW (SHEET 6)


THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R.GRZYBOWSKI 29APR05	TE Connectivity	NAME	
		CHK M.PERCHERKE 29APR05			
DIMENSIONS:		APVD M.PERCHERKE	PRODUCT SPEC	APPLICATION SPEC	
INCHES					
		0 PLC ±"	108-1973	114-13038	
		1 PLC ±.01			
		2 PLC ±.01	CUSTOMER DRAWING	SCALE 2:1	
		3 PLC ±.005			
		4 PLC ±.0020	SHEET 1 OF 19	REV K9	
		ANGLES ±.0020			
		FINISH #2	CUSTOMER DRAWING	SCALE 2:1	
MATERIAL		WEIGHT	SIZE A1	CAGE CODE 00779	
			DRAWING NO 6450540	RESTRICTED TO -	

LOC	DIST	REVISIONS					
ES	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-	SEE SHEET 1	-	-	-	

K9	1.350	1.300	-	-	1.200	.625	-	1.650	.450	1P + 20S + 1P	6-6450540-6
	2.550	2.500	.250	.250	1.650	1.375	-	2.85	.450	4P + 8S + 4P	6-6450540-5
	1.350	1.300	-	-	1.200	.625	-	1.650	.450	1P + 20S + 1P	6-6450540-2
	-	3.300	.200	.200	2.200	1.625	-	3.650	.450	6P + 20S + 6P	6-6450540-1
	2.950	2.900	.250	.250	2.050	1.375	-	3.250	.450	4P + 24S + 4P	6-6450540-0
	2.050	2.000	.250	.250	1.650	.925	-	2.350	.450	2P + 24S + 2P	5-6450540-9
	2.050	2.000	.250	.250	1.400	1.125	-	2.350	.450	3P + 8S + 3P	5-6450540-5
	2.500	2.450	.250	.250	1.850	1.375	-	2.800	.450	4P + 16S + 3P	5-6450540-4
	2.950	2.900	.250	.250	2.050	1.375	-	3.250	.450	4P + 24S + 4P	5-6450540-3
	1.350	1.300	-	-	1.200	.675	-	1.650	.450	1P + 16S + 1P	5-6450540-2
	1.750	1.700	.250	.250	1.350	.875	-	2.050	.450	2P + 16S + 2P	5-6450540-1
	5.950	5.900	.250	.250	3.550	2.8750	-	6.250	.450	10P + 24S + 10P	5-6450540-0
	5.150	5.100	.250	.250	3.250	2.375	-	5.450	.450	8P + 32S + 8P	4-6450540-9
	1.250	1.200	-	-	1.100	.625	-	1.550	.450	1P + 16S + 1P	4-6450540-8
	2.150	2.100	.250	.250	1.500	1.175	-	2.450	.450	3P + 8S + 3P	4-6450540-7
	1.150	1.100	-	-	1.000	.675	-	1.450	.450	1P + 8S + 1P	4-6450540-6
	-	-	-	.200	-	-	-	2.820	.450	12HDP	4-6450540-5
	-	-	.200	.200	2.600	1.625	-	3.970	.450	6HDP + 36S + 7HDP	4-6450540-4
	2.65	2.60	.250	.250	2.250	1.625	-	2.950	.450	5P + 20S + 2P	(E)4-6450540-3
	-	-	-	.200	-	-	-	2.620	.450	11HDP	(E)4-6450540-2
	-	-	.200	.200	2.600	1.625	-	3.770	.450	6P + 36S + 6P	4-6450540-1
	-	-	.200	.200	4.500	3.425	-	7.470	.450	15P + 40S + 15P	4-6450540-0
	-	-	.200	.200	-	-	-	7.470	-	15P + 40S + 15P	(D)3-6450540-9
	4.650	4.600	.250	.250	3.250	1.875	-	4.950	.450	6P + 52S + 6P	(D)2-6450540-7
	1.950	1.900	-	-	1.550	.875	-	2.250	.450	2P + 24S + 2P	(D)2-6450540-5
	2.450	2.400	.250	.250	1.800	1.125	-	2.750	.450	3P + 24S + 3P	(D)2-6450540-0
	-	1.575	-	-	1.425	.700	-	1.925	.475	1P + 24S + 1P	(E)1-6450540-8
	-	5.450			3.075	2.425	-	5.800	.425	10P + 24S + 12P	1-6450540-4
	3.250	3.200	.200	.200	2.125	1.575	-	3.550	.425	6P + 20S + 6P	1-6450540-2
	-	2.850	.250	.250	2.000	1.125	-	3.200	.450	3P + 32S + 4P	1-6450540-1
	1.950	1.900	.250	.250	1.550	.875	-	2.250	.450	2P + 24S + 2P	1-6450540-0
	-	1.400	.250	.250	1.300	.625	-	1.750	.450	1P + 24S + 1P	6450540-7
	-	2.400	.250	.250	2.050	1.375	-	2.750	.450	4P + 24S + 2P	6450540-6
	-	3.100	.250	.250	2.000	1.625	-	3.450	.450	5P + 12S + 5P	6450540-5
	-	3.400	.250	.250	2.050	1.375	-	3.750	.450	4P + 24S + 6P	6450540-4
	-	7.400	.250	.250	5.050	2.875	-	7.750	.450	10P + 84S + 10P	6450540-3
	-	4.000	.250	.250	2.650	1.675	2.225	4.350	.450	5P+24S+1M+6P	6450540-2
	-	1.575	-	-	1.425	.700	-	1.925	.475	1P + 24S + 1P	6450540-1
	D	U	T	S	R	W	M	L	K	DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.
TOLERANCES UNLESS OTHERWISE SPECIFIED:

DIMENSIONS:
INCHES



MATERIAL

0 PLC ±.1
1 PLC ±.01
2 PLC ±.005
3 PLC ±.005
4 PLC ±.0020
ANGLES ±.2°
FINISH

0 PLC ±.1
1 PLC ±.01
2 PLC ±.005
3 PLC ±.005
4 PLC ±.0020
ANGLES ±.2°
FINISH

DWN
R. GRZYBOWSKI
CHK
M. PERCHERKE
APVD
M. PERCHERKE

29APR05
29APR05

PRODUCT SPEC
108-1973
APPLICATION SPEC
114-13038
WEIGHT
-

CUSTOMER DRAWING

NAME
VERTICAL RECEPTACLE ASSEMBLY
WITH GUIDES
MULTI-BEAM XL

SIZE
A1

CAGE CODE
100779

DRAWING NO
6450540

RESTRICTED TO
-

SCALE
2:1


SHEET
2

OF
19

REV
K9

ITE Connectivity

PART NUMBER	ROWS		POWER		SIGNAL							POWER			
			P4	P3	6	5	4	3	2	1	P2	P1			
2-6450540-5	D C B A				AP	AP	AP	AP	AP	AP	AP				
					AP	AP	AP	AP	AP	AP	AP				
					AP	AP	AP	AP	AP	AP	AP				
					AP	AP	AP	AP	AP	AP	AP				
2P + 24S + 2P															




VS	STD POWER PRESSFIT CONTACT .115 LG
VP	MFBL POWER PRESSFIT CONTACT .115 LG
GS	STD POWER PRESSFIT CONTACT .135 LG
GP	MFBL POWER PRESSFIT CONTACT .135 LG
P	SIGNAL PRESSFIT CONTACT .115 LG
AP	SIGNAL PRESSFIT CONTACT .135 LG
CODE	TAIL LENGTH

4805 (3/11)

LOC	DIST	REVISIONS					
ES	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-	-	SEE SHEET 1	-	-	-






PART NUMBER	ROWS		POWER										SIGNAL																				POWER													
			P20	PI9	PI8	PI7	PI6	PI5	PI4	PI3	PI2	PI1	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	PI0	P9	P8	P7	P6	P5	P4	P3	P2	PI			
6450540-3	D C B A		GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP		
			GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	
			GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP
			GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP
10P + 84S + 10P																																														





HP	MFBL POWER PRESSFIT CONTACT .165 LG
BP	SIGNAL PRESSFIT CONTACT .165 LG
GP	MFBL POWER PRESSFIT CONTACT .135 LG
AP	SIGNAL PRESSFIT CONTACT .135 LG
CODE	TAIL LENGTH
CONTACT TABLE	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R.GRZYBOWSKI CHK M.PERCHERKE APVD M.PERCHERKE	29APR05 29APR05 -
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:	
		0 PLC ± 1 PLC ±.01 2 PLC ±.01 3 PLC ±.005 4 PLC ±.0020 ANGLES ±.2° FINISH	
MATERIAL		PRODUCT SPEC 108-1973 APPLICATION SPEC 114-13038 WEIGHT -	
CUSTOMER DRAWING		NAME VERTICAL RECEPTACLE ASSEMBLY WITH GUIDES MULTI-BEAM XL	
SCALE 2:1		SIZE A1 CAGE CODE 00779 DRAWING NO. 6450540	
SHEET 4 OF 19		RESTRICTED TO -	
REV K9		TE Connectivity	

LOC	DIST	REVISIONS					
ES	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-	-	SEE SHEET 1	-	-	-



PART NUMBER	ROWS		POWER						SIGNAL						POWER				
			P10	P9	P8	P7	P6	P5	6	5	4	3	2	1	P4	P3	P2	P1	
6450540-4	D C B A																		
4P + 24S + 6P																			


PART NUMBER	ROWS		POWER					SIGNAL			POWER					
			P10	P9	P8	P7	P6	3	2	1	P5	P4	P3	P2	P1	
6450540-5	D C B A															
5P + 12S + 5P																



GP	MFBL POWER PRESSFIT CONTACT .135 LG
AP	SIGNAL PRESSFIT CONTACT .135 LG
CODE	TAIL LENGTH
CONTACT TABLE	


THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R. GRZYBOWSKI 29APR05	NAME	
DIMENSIONS:		CHK M. PERCHERKE 29APR05	VERTICAL RECEPTACLE ASSEMBLY	
INCHES		APVD M. PERCHERKE	WITH GUIDES	
		PRODUCT SPEC	MULTI-BEAM XL	
		108-1973	SIZE	
		APPLICATION SPEC	CAGE CODE	
		114-13038	DRAWING NO	
		WEIGHT	RESTRICTED TO	
		CUSTOMER DRAWING	A100779	
		SCALE 2:1	SHEET 5 OF 19	
		REV K9		

PART NUMBER	ROWS		POWER	SIGNAL							POWER																					
			P2	6	5	4	3	2	1	P1																						
6450540-7	D C B A		GP <table><tr><td>AP</td><td>AP</td><td>AP</td><td>AP</td><td>AP</td><td>AP</td><td>AP</td></tr><tr><td>AP</td><td>AP</td><td>AP</td><td>AP</td><td>AP</td><td>AP</td><td>AP</td></tr><tr><td>AP</td><td>AP</td><td>AP</td><td>AP</td><td>AP</td><td>AP</td><td>AP</td></tr><tr><td>AP</td><td>AP</td><td>AP</td><td>AP</td><td>AP</td><td>AP</td><td>AP</td></tr></table> GP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	AP	
AP	AP	AP	AP	AP	AP	AP																										
AP	AP	AP	AP	AP	AP	AP																										
AP	AP	AP	AP	AP	AP	AP																										
AP	AP	AP	AP	AP	AP	AP																										
IP + 24S + IP																																


4805 (3/11)

LOC	DIST	REVISIONS				
		P	LYR	DESCRIPTION	DATE	OWN
ES	00	-	-	SEE SHEET 1	-	-


PART NUMBER	ROWS		POWER						SIGNAL					POWER																																																																																															
			PI2	PI1	PI0	P9	P8	P7	5	4	3	2	1	P6	P5	P4	P3	P2	P1																																																																																										
1-6450540-2	D C B A	HD	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP	GP GP GP GP GP GP



PART NUMBER	ROWS		POWER											SIGNAL						POWER										
			P22	P21	P20	P19	P18	P17	P16	P15	P14	P13	P12	P11	6	5	4	3	2	1	P10	P9	P8	P7	P6	P5	P4	P3	P2	
1-6450540-4	D C B A		GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	GP



PART NUMBER	ROWS		POWER			SIGNAL					POWER				
			P6	P5	P4	6	5	4	3	2	1	P3	P2		P1
2-6450540-0	D C B A	 HD	 GP	 GP	 GP	AP	AP	AP	AP	AP	AP	 GP	 GP	 GP	 HD
						AP	AP	AP	AP	AP	AP				
						AP	AP	AP	AP	AP	AP				
						AP	AP	AP	AP	AP	AP				



THIS DRAWING IS A CONTROLLED DOCUMENT.

OWN R. GRZYBOWSKI 29APR05
CHK M. PERCHERKE 29APR05
APVD M. PERCHERKE

PRODUCT SPEC
108-1973
APPLICATION SPEC
114-13038

WEIGHT
-

CUSTOMER DRAWING

TE Connectivity


VERTICAL RECEPTACLE ASSEMBLY
WITH GUIDES
MULTI-BEAM XL

SIZE 100779
CAGE CODE
DRAWING NO
A100779
C=6450540

RESTRICTED TO
-

SCALE 2:1
SHEET 7 OF 19
REV K9


PART NUMBER	ROWS		POWER		SIGNAL					POWER						
			P7	P6	5	4	3	2	1	P5	P4	P3	P2	P1		
4-6450540-3	D C B A	 HD			AP	AP	AP	AP	AP	AP						 HD
5P + 20S + 2P																




THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R. GRZYBOWSKI 29APR05		 TE Connectivity		
DIMENSIONS: INCHES		CHW M. PERCHERKE 29APR05				
	TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME	VERTICAL RECEPTACLE ASSEMBLY WITH GUIDES MULTI-BEAM XL		
	1 P/LC ±		APVD M. PERCHERKE			
	1 P/LC ±		PRODUCT SPEC			
	2 P/LC ±.01		108-1973			
	3 P/LC ±.005		APPLICATION SPEC			
4 P/LC ±.0020		114-13038	SIZE	CAGE CODE	DRAWING NO.	RESTRICTED TO
ANGLES ±°		WEIGHT -	A	00779	©=6450540	-
MATERIAL	FINISH	CUSTOMER DRAWING	SCALE	2:1	SHEET 8 OF 19	REV K9

[illegible][illegible]4805 (3/11)


PART NUMBER	ROWS	POWER										
		P11	P10	P9	P8	P7	P6	P5	P3	P2	P1	
4-6450540-2	D C B A	GP	GP	GP	GP	GP	GP	GP	GP	GP	GP	
11HDP												

4805 (3/11)


PART NUMBER	ROWS	POWER											
		P12	P11	P10	P9	P8	P7	P6	P5	P3	P2		P1
4-6450540-5	D C B A	GS	GS	GS	GS	GS	GS	GS	GS	GS	GS	GS	HD
12HDP													






PART NUMBER	ROWS		POWER			SIGNAL		POWER			
			P6	P5	P4	2	1	P3	P2	P1	
4-6450540-7	D C B A										
3P + 8S + 3P											

4805 (3/11)

LOC		DIST		REVISIONS				
P	LYR	DESCRIPTION			DATE	OWN	APVD	
-	-	SEE SHEET 1			-	-	-	

PART NUMBER	ROWS		POWER		SIGNAL				POWER		
			P2	4	3	2	1	P1			
4-6450540-8	D C B A		GS	AP	AP	AP	AP	GS			
				AP	AP	AP	AP				
				AP	AP	AP	AP				
				AP	AP	AP	AP				
IP + 16S + 1P											

PART NUMBER	ROWS		POWER		SIGNAL				POWER		
			P4	P3	4	3	2	1	P2	P1	
5-6450540-1	D C B A				AP	AP	AP	AP			
					AP	AP	AP	AP			
					AP	AP	AP	AP			
					AP	AP	AP	AP			
2P + 16S + 2P											



PART NUMBER	ROWS		POWER				SIGNAL								POWER			
			P7	P6	P5	P4	8	7	6	5	4	3	2	1	P3	P2	P1	
1-6450540-1	D C B A						P	P	P	P	P	P	P	P				
							P	P	P	P	P	P	P	P				
							P	P	P	P	P	P	P	P				
							P	P	P	P	P	P	P	P				
3P + 32S + 4P																		

THIS DRAWING IS A CONTROLLED DOCUMENT.

OWN R. GRZYBOWSKI 29APR05
CHK M. PERCHERKE 29APR05
APVD M. PERCHERKE

PRODUCT SPEC 108-1973
APPLICATION SPEC 114-13038
WEIGHT -
CUSTOMER DRAWING

DIMENSIONS:
INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±.
1 PLC ±.01
2 PLC ±.01
3 PLC ±.005
4 PLC ±.0020
ANGLES ±2°
FINISH

NAME

VERTICAL RECEPTACLE ASSEMBLY WITH GUIDES MULTI-BEAM XL

SIZE A1
CAGE CODE 100779
DRAWING NO. 6450540


RESTRICTED TO -

SCALE 2:1
SHEET 12 OF 19
REV K9


TE Connectivity


LOC		DIST		REVISIONS				
ES	00	P	LYR	DESCRIPTION		DATE	DWN	APVD
		-		SEE SHEET 1		-	-	-


PART NUMBER	ROWS		POWER										SIGNAL						POWER										
			P20	P19	P18	P17	P16	P15	P14	P13	P12	P11	6	5	4	3	2	1	P10	P9	P8	P7	P6	P5	P4	P3	P2	P1	
5-6450540-0	D C B A																												
10P + 24S + 10P																													



PART NUMBER	ROWS		POWER		SIGNAL				POWER	
			P2	4	3	2	1	P1		
5-6450540-2	D C B A		GS	AP	AP	AP	AP	GS		
				AP	AP	AP	AP			
				AP	AP	AP	AP			
				AP	AP	AP	AP			
				AP	AP	AP	AP			
1P + 16S + 1P										





PART NUMBER	ROWS		POWER				SIGNAL						POWER				
			P8	P7	P6	P5	6	5	4	3	2	1	P4	P3	P2	P1	
5-6450540-3	D C B A		GS	GS	GS	GS	AP	AP	AP	AP	AP	AP	GS	GS	GS	GS	
							AP	AP	AP	AP	AP	AP					
							AP	AP	AP	AP	AP	AP					
							AP	AP	AP	AP	AP	AP					
4P + 24S + 4P																	HD



THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R. GRZYBOWSKI CHK M. PERCHERKE APVD M. PERCHERKE	29APR05 29APR05 -
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:	
		PRODUCT SPEC	
MATERIAL		APPLICATION SPEC	
		WEIGHT	
		CUSTOMER DRAWING	
		SCALE 2:1	
		SHEET 13 OF 19	
		REV K9	


PART NUMBER	ROWS		POWER			SIGNAL		POWER			
			P6	P5	P4	2	1	P3	P2	P1	
5-6450540-5	D C B A	HD	GS	GS	GS	AP	AP	GS	GS	GS	HD
3P + 8S + 3P											



THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN: GRZYBOWSKI 29APR05 CHK: M. PERCHERKE 29APR05		 TE Connectivity	
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED: DECIMALS: ±. FRACTIONS: ±. HOLE LOCATIONS: ±.01 HOLE DIAMETERS: ±.005 ANGLES: ±°		NAME:	
		PART: M. PERCHERKE PRODUCT SPEC: 108-1973 APPLICATION SPEC: 114-13038 WEIGHT: -		MATERIAL: FINISH: -	
CUSTOMER DRAWING		SIZE: CAGE CODE: DRAWING NO: A100779C6450540		RESTRICTED TO: -	
		SCALE: 2:1		SHEET: 14 OF 19	
				REV: K	

LOC		DIST		REVISIONS					
ES		00		P	LTR	DESCRIPTION			DATE
					-	SEE SHEET 1			-

PART NUMBER	ROWS		POWER				SIGNAL							POWER				
			P8	P7	P6	P5	6	5	4	3	2	1	P4	P3	P2	P1		
6-6450540-0	D C B A		GS	GS	GS	GS	AP	AP	AP	AP	AP	AP	GS	GS	GS	GS		
							AP	AP	AP	AP	AP	AP						
							AP	AP	AP	AP	AP	AP						
							AP	AP	AP	AP	AP	AP						
4P + 24S + 4P																		



THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN

R. GRZYBOWSKI

29APR05

CHK

M. PERCHERKE

29APR05

APVD

M. PERCHERKE

-

DIMENSIONS:

INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±"

1 PLC ±.01

2 PLC ±.01

3 PLC ±.005

4 PLC ±.0020

ANGLES ±2°

FINISH

MATERIAL

PRODUCT SPEC

108-1973

APPLICATION SPEC

114-13038

WEIGHT

-

CUSTOMER DRAWING

NAME

VERTICAL RECEPTACLE ASSEMBLY WITH GUIDES MULTI-BEAM XL

SIZE

A1

CAGE CODE

00779

DRAWING NO

6450540

RESTRICTED TO

-

SCALE

2:1

SHEET

15


OF

19


REV


K9


TE Connectivity


-NO SIGNAL CONTACTS4805 (3/11)


PART NUMBER	ROWS		POWER		SIGNAL					POWER																								
			P2	5	4	3	2	1	P1																									
6-6450540-2	D C B A	 	<table><tr><td rowspan="4">GP</td><td></td><td>AP</td><td>AP</td><td>AP</td><td></td><td rowspan="4">GP</td></tr><tr><td></td><td>AP</td><td>AP</td><td>AP</td><td></td></tr><tr><td></td><td>AP</td><td>AP</td><td>AP</td><td></td></tr><tr><td></td><td>AP</td><td>AP</td><td>AP</td><td></td></tr></table>									GP		AP	AP	AP		GP		AP	AP	AP			AP	AP	AP			AP	AP	AP		 
GP		AP	AP	AP		GP																												
		AP	AP	AP																														
		AP	AP	AP																														
		AP	AP	AP																														
IP + 20S + IP																																		



THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN GRZYBOWSKI 29APR05		 TE Connectivity	
DIMENSIONS:		CWH M. PERCHERKE 29APR05		NAME VERTICAL RECEPTACLE ASSEMBLY WITH GUIDES MULTI-BEAM XL	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD M. PERCHERKE -			
INCHES		PRODUCT SPEC			
		108-1973 APPLICATION SPEC 114-13038			
0 PLC ±. 1 PLC ±. 2 PLC ±.01 3 PLC ±.005 4 PLC ±.0020 <i>7</i> ANGLES		SIZE		RESTRICTED TO	
MATERIAL		WEIGHT -		A100779 ©6450540 -	
FINISH		CUSTOMER DRAWING		SCALE 2:1 SHEET 17 of 19 REV K9	

[illegible]4805 (3/11)

PART NUMBER	ROWS		POWER	S I G N A L						POWER	
			P2	5	4	3	2	1	P1		
6-6450540-6	D C B A		GS	AP	AP	AP	AP	AP	AP	GS	
IP + 20S + IP											

4805 (3/11)

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9