

3632 Multi-Conductor - Enhanced Category 6 Bonded-Pair Cable

For more Information
please call

1-800-Belden1

**General Description:**

CAT6+ (400MHz), 4-Bonded-Pairs, U/UTP-Unshielded, Riser-CMR, Premise Horizontal Cable, 23 AWG Solid Bare Copper Conductors, Polyolefin Insulation, X-spline, Ripcord, PVC jacket.

Usage (Overall)

Suitable Applications:

Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Audio, AES51, RS-422, Noisy Environments

Physical Characteristics (Overall)**Conductor**

AWG:

# Pairs	AWG	Stranding	Conductor Material
4	23	Solid	BC - Bare Copper

Total Number of Conductors:

8

Insulation

Insulation Material:

Insulation Material
Polyolefin

Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC	0.017

Outer Jacket Diameter:

Nom. Dia. (in.)
0.235

Outer Jacket Ripcord:

Yes

Overall Cable

Overall Cabling Separator Material:

Patented X-Spline Center Member

Overall Nominal Diameter:

0.235 in.

Pair

Pair Color Code Chart:

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

Mechanical Characteristics (Overall)

Storage Temperature Range: -30°C To +75°C

Installation Temperature Range: -5°C To + 50°

Operating Temperature Range: 0°C To +75°C

UL Temperature Rating: 75°C

Bulk Cable Weight: 27 lbs/1000 ft.

Max. Recommended Pulling Tension: 50 lbs.

Min. Bend Radius/Minor Axis: 0.500 in.

Min. Bend/Installation: 2 in.

3632 Multi-Conductor - Enhanced Category 6 Bonded-Pair Cable

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMR
EU Directive 2011/65/EU (ROHS II):	Yes
Other Standards:	ISO/IEC 11801 ed 2.1 (2008) Class E
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/03/2009
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Telecommunications Standards:	Category 6 - TIA 568.C.2
Other Specification:	UL Verified to Category 6

Applicable Patents:

Country

www.belden.com/p

Flame Test

UL Flame Test:	UL1666 Vertical Riser
C(UL) Flame Test:	FT4

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	No
Suitability - Aerial:	No
Suitability - Burial:	No
Sunlight Resistance:	No

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	3633

Electrical Characteristics (Overall)

Nom. Mutual Capacitance:

Capacitance (pF/ft)

15.5

Maximum Capacitance Unbalance (pF/100 m):	90
---	----

Nominal Velocity of Propagation:

VP (%)

70.000

Maximum Delay:

Freq. (MHz) Delay (ns/100 m)

100.000 537.600

Typical Delay Skew:

Delay Skew (ns/ft)

30.000

Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)

7.700

Max. Operating Voltage - UL:

Voltage

300 V RMS

Maximum DCR Unbalanced:

DCR Unbalance @ 20°C (%)

3632 Multi-Conductor - Enhanced Category 6 Bonded-Pair Cable

3.000

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min RL (dB)
0.772	1.800	81.0	81.0	79.2	79.2	
1	2.000	79.3	79.3	77.3	77.3	20.000
4	3.700	70.3	70.3	66.6	66.6	23.000
8	5.200	65.8	65.8	60.6	60.6	24.500
10	5.800	64.3	64.3	58.5	58.5	25.000
16	7.400	61.2	61.2	53.9	53.9	25.000
20	8.300	59.8	59.8	51.5	51.5	25.000
25	9.300	58.3	58.3	49.1	49.1	25.000
31.25	10.400	56.9	56.9	46.5	46.5	25.000
62.5	15.000	52.4	52.4	37.4	37.4	25.000
100	19.300	49.3	49.3	30.0	30.0	25.000
155	24.600	46.4	46.4	21.8	21.8	22.800
200	28.300	44.8	44.8	16.5	16.5	21.600
250	32.100	43.3	43.3	11.2	11.2	20.500
300	35.600	42.1	42.1	6.5	6.5	20.100
350	38.900	41.1	41.1	2.3	2.3	19.800
400	42.000	38.3	38.3	-3.7	-3.7	19.500
450	45.000	37.5	37.5			18.900
500	47.900	36.8	36.8			18.400
550	50.600	36.2	36.2			18.000
600	53.300	35.6	35.6			17.500
650	55.900	35.1	35.1			17.200

Premise Cable Electrical Table 2:

Freq. (MHz)	Input (Unfitted) Imp. (Ohms)	Fitted Impedance	Min. ACRF (dB)	Min. PSACRF (dB)
.772			75.0	73.0
1	100 ± 12	100 ± 12	72.8	70.8
4	100 ± 12	100 ± 10.4	60.8	58.8
8	100 ± 12	100 ± 8	54.7	52.7
10	100 ± 12	100 ± 7.3	52.8	50.8
16	100 ± 12	100 ± 5.7	48.7	46.7
20	100 ± 12	100 ± 5	46.8	44.8
25	100 ± 15	100 ± 5	44.8	42.8
31.25	100 ± 15	100 ± 5	42.9	40.9
62.5	100 ± 15	100 ± 5	36.9	34.9
100	100 ± 15	100 ± 5	32.8	30.8
155	100 ± 15	100 ± 5	28.9	26.9
200	100 ± 15	100 ± 5	26.8	24.8
250	100 ± 20	100 ± 5	24.8	22.8
300	100 ± 20	100 ± 5	23.3	21.3
350	100 ± 22	100 ± 5	21.9	19.9
400	100 ± 22	100 ± 5	20.8	18.8
450	100 ± 22	100 ± 5	19.7	17.7
500	100 ± 22	100 ± 5	18.8	16.8
550	100 ± 22	100 ± 5	18.0	16.0
600	100 ± 22	100 ± 5	17.2	15.2
650	100 ± 22	100 ± 5	16.5	14.5

Premise Cable Electrical Table 4:

Frequency (MHz)	Min. TCL (dB)	Min. ELCTL (dB)
0.772	42.000	39.200
1.000	42.000	37.000
4.000	42.000	25.000
8.000	42.000	18.900
10.000	42.000	17.000
16.000	40.000	12.900
20.000	39.000	11.000
25.000	38.000	9.000
31.250	37.100	
62.500	34.000	
100.000	32.000	
155.000	30.100	
200.000	29.000	

3632 Multi-Conductor - Enhanced Category 6 Bonded-Pair Cable

250.000	28.000	
---------	--------	--

Notes (Overall)

Notes: Jacket sequentially marked at 2 ft./1m intervals. Third party verified to ANSI/TIA-568-C.2 Category 6. Values above 400 MHz are for engineering information only.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
3632 003A1000	1,000 FT	30.000 LB	ORANGE	C	CAT6E 4PRB U/UTP CMR RIB
3632 004A1000	1,000 FT	30.000 LB	YELLOW	C	CAT6E 4PRB U/UTP CMR RIB
3632 004I1000	1,000 FT	28.000 LB	YELLOW	C	CAT6E 4PRB U/UTP CMR REEL
3632 005A1000	1,000 FT	30.000 LB	GREEN, DARK	C	CAT6E 4PRB U/UTP CMR RIB
3632 005I1000	1,000 FT	28.000 LB	GREEN, DARK	C	CAT6E 4PRB U/UTP CMR REEL
3632 006A1000	1,000 FT	30.000 LB	BLUE, LIGHT	C	CAT6E 4PRB U/UTP CMR RIB
3632 006U1000	1,000 FT	27.000 LB	BLUE, LIGHT		CAT6E 4PRB U/UTP CMR BOX
3632 006I1000	1,000 FT	28.000 LB	BLUE, LIGHT	C	CAT6E 4PRB U/UTP CMR REEL
3632 008A1000	1,000 FT	30.000 LB	GRAY	C	CAT6E 4PRB U/UTP CMR RIB
3632 008U1000	1,000 FT	27.000 LB	GRAY		CAT6E 4PRB U/UTP CMR BOX
3632 008I1000	1,000 FT	28.000 LB	GRAY	C	CAT6E 4PRB U/UTP CMR REEL
3632 009A1000	1,000 FT	30.000 LB	WHITE	C	CAT6E 4PRB U/UTP CMR RIB
3632 009U1000	1,000 FT	27.000 LB	WHITE		CAT6E 4PRB U/UTP CMR BOX
3632 009I1000	1,000 FT	28.000 LB	WHITE	C	CAT6E 4PRB U/UTP CMR REEL
3632 010A1000	1,000 FT	30.000 LB	BLACK	C	CAT6E 4PRB U/UTP CMR RIB
3632 010I1000	1,000 FT	28.000 LB	BLACK	C	CAT6E 4PRB U/UTP CMR REEL

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 12 Revision Date: 06-16-2014

© 2014 Belden, Inc
 All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9