



## Main

|                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product                   | Altivar 61                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Product or component type          | Variable speed drive                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Product specific application       | Pumping and ventilation machine                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Component name                     | ATV61                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Motor power kW                     | 250 kW 3 phasesat 500 V<br>315 kW 3 phasesat 690 V                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Motor power hp                     | 350 hp 3 phasesat 575 V                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| [Us] rated supply voltage          | 500...690 V (- 15...10 %)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Phase                              | 3 phases                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Line current                       | 311 Afor 600 V 3 phases 250 kW / 350 hp<br>317 Afor 690 V 3 phases 250 kW / 350 hp<br>342 Afor 500 V 3 phases 250 kW / 350 hp                                                                                                                                                                                                                                                                                                                                                                                                                             |
| EMC filter                         | Level 3 EMC filter                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Assembly style                     | With heat sink                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Prospective line Isc               | 35 kA 3 phases                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Maximum transient current          | 468 Afor 60 s 3 phases                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Nominal switching frequency        | 2.5 kHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Switching frequency                | 2.5...4.9 kHz adjustable<br>2.5...4.9 kHz with derating factor                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Asynchronous motor control profile | Voltage/frequency ratio, 2 points<br>Voltage/frequency ratio, 5 points<br>Flux vector control without sensor, standard<br>Voltage/frequency ratio - Energy Saving, quadratic U/f                                                                                                                                                                                                                                                                                                                                                                          |
| Synchronous motor control profile  | Vector control without sensor, standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Communication port protocol        | CANopen<br>Modbus                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Type of polarization               | No impedance Modbus                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Option card                        | APOGEE FLN communication card<br>BACnet communication card<br>CC-Link communication card<br>Controller inside programmable card<br>DeviceNet communication card<br>Ethernet/IP communication card<br>Fipio communication card<br>I/O extension card<br>Interbus-S communication card<br>LonWorks communication card<br>METASYS N2 communication card<br>Modbus Plus communication card<br>Modbus TCP communication card<br>Modbus/Uni-Telway communication card<br>Multi-pump card<br>Profibus DP communication card<br>Profibus DP V1 communication card |

## Complementary

|                           |                                                                                                         |
|---------------------------|---------------------------------------------------------------------------------------------------------|
| Product destination       | Asynchronous motors<br>Synchronous motors                                                               |
| Supply voltage limits     | 425...759 V                                                                                             |
| Supply frequency          | 50...60 Hz (- 5...5 %)                                                                                  |
| Network frequency         | 47.5...63 Hz                                                                                            |
| Continuous output current | 336 Aat 2.5 kHz, 575 V 3 phases<br>355 A at 2.5 kHz, 690 V 3 phases<br>390 A at 2.5 kHz, 500 V 3 phases |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                           |                                                                                                                                                                                                                                                                                                                                       |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Output frequency          | 0.1...500 Hz                                                                                                                                                                                                                                                                                                                          |
| Speed range               | 1...100 in open-loop mode, without speed feedback                                                                                                                                                                                                                                                                                     |
| Speed accuracy            | +/- 10 % of nominal slip 0.2 Tn to Tn torque variation without speed feedback                                                                                                                                                                                                                                                         |
| Torque accuracy           | +/- 15 % in open-loop mode, without speed feedback                                                                                                                                                                                                                                                                                    |
| Transient overtorque      | 130 % of nominal motor torque, +/- 10 %for 60 s                                                                                                                                                                                                                                                                                       |
| Braking torque            | 30 % without braking resistor<br>≤ 125 % with braking resistor                                                                                                                                                                                                                                                                        |
| Regulation loop           | Frequency PI regulator                                                                                                                                                                                                                                                                                                                |
| Motor slip compensation   | Adjustable<br>Automatic whatever the load<br>Can be suppressed<br>Not available in voltage/frequency ratio (2 or 5 points)                                                                                                                                                                                                            |
| Local signalling          | 1 LED red presence of drive voltage                                                                                                                                                                                                                                                                                                   |
| Output voltage            | ≤ power supply voltage                                                                                                                                                                                                                                                                                                                |
| Isolation                 | Between power and control terminals                                                                                                                                                                                                                                                                                                   |
| Type of cable             | With an IP21 or an IP31 kit: 3-strand IEC cableat 104 °F (40 °C), copper 70 °C PVC<br>Without mounting kit: 1-strand IEC cableat 113 °F (45 °C), copper 70 °C PVC<br>Without mounting kit: 1-strand IEC cableat 113 °F (45 °C), copper 90 °C XLPE/EPR<br>With UL Type 1 kit: 3-strand UL 508 cableat 104 °F (40 °C), copper 75 °C PVC |
| Electrical connection     | AI1-/AI1+, AI2, AO1, R1A, R1B, R1C, R2A, R2B, LI1...LI6, PWR terminal 2.5 mm <sup>2</sup> / AWG 14<br>L1/R, L2/S, L3/T, U/T1, V/T2, W/T3 terminal 4 x 185 mm <sup>2</sup> / 3 x 350 kcmil<br>PC/-, PA/+ terminal 4 x 185 mm <sup>2</sup> / 3 x 350 kcmil                                                                              |
| Tightening torque         | L1/R, L2/S, L3/T, U/T1, V/T2, W/T3 362.83 lbf.in (41 N.m) / 360 lb.in<br>PC/-, PA/+ 362.83 lbf.in (41 N.m) / 360 lb.in<br>AI1-/AI1+, AI2, AO1, R1A, R1B, R1C, R2A, R2B, LI1...LI6, PWR 5.31 lbf.in (0.6 N.m)                                                                                                                          |
| Supply                    | Internal supply for reference potentiometer (1 to 10 kOhm) 10.5 V DC +/- 5 %, ≤ 10 mAfor overload and short-circuit protection<br>Internal supply 24 V DC (21...27 V), ≤ 200 mAfor overload and short-circuit protection<br>External supply 24 V DC (19...30 V)                                                                       |
| Analogue input number     | 2                                                                                                                                                                                                                                                                                                                                     |
| Analogue input type       | AI1-/AI1+ bipolar differential voltage +/- 10 V DC, input voltage 24 V max, resolution 11 bits + sign<br>AI2 software-configurable current 0...20 mA, impedance 242 Ohm, resolution 11 bits<br>AI2 software-configurable voltage 0...10 V DC, input voltage 24 V max, impedance 30000 Ohm, resolution 11 bits                         |
| Sampling duration         | Analog input AI1-/AI1+ 2 ms, +/- 0.5 ms<br>Analog input AI2 2 ms, +/- 0.5 ms<br>Analog output AO1 2 ms, +/- 0.5 ms<br>Discrete input LI1...LI5 2 ms, +/- 0.5 ms<br>Discrete input LI6 (if configured as logic input) 2 ms, +/- 0.5 ms                                                                                                 |
| Accuracy                  | AI1-/AI1+ +/- 0.6 % for a temperature variation 60 °C<br>AI2 +/- 0.6 % for a temperature variation 60 °C<br>AO1 +/- 1 % for a temperature variation 60 °C                                                                                                                                                                             |
| Linearity error           | AI1-/AI1+ +/- 0.15 % of maximum value<br>AI2 +/- 0.15 % of maximum value<br>AO1 +/- 0.2 %                                                                                                                                                                                                                                             |
| Analogue output number    | 1                                                                                                                                                                                                                                                                                                                                     |
| Analogue output type      | AO1 software-configurable current, analogue output range 0...20 mA, impedance 500 Ohm, resolution 10 bits<br>AO1 software-configurable logic output 10 V, ≤ 20 mA<br>AO1 software-configurable voltage, analogue output range 0...10 V DC, impedance 470 Ohm, resolution 10 bits                                                      |
| Discrete output number    | 2                                                                                                                                                                                                                                                                                                                                     |
| Discrete output type      | (R1A, R1B, R1C) configurable relay logic NO/NC, electrical durability 100000 cycles<br>(R2A, R2B) configurable relay logic NO, electrical durability 100000 cycles                                                                                                                                                                    |
| Response time             | ≤ 100 ms in STO (Safe Torque Off)<br>R1A, R1B, R1C ≤ 7 ms, tolerance +/- 0.5 ms<br>R2A, R2B ≤ 7 ms, tolerance +/- 0.5 ms                                                                                                                                                                                                              |
| Minimum switching current | Configurable relay logic 3 mAat 24 V DC                                                                                                                                                                                                                                                                                               |
| Maximum switching current | R1, R2 on resistive load, 5 A at 30 V DC, cos phi = 1, 0 ms<br>R1, R2 on inductive load, 2 A at 30 V DC, cos phi = 0.4, 7 ms<br>R1, R2 on resistive load, 5 A at 250 V AC, cos phi = 1, 0 ms<br>R1, R2 on inductive load, 2 A at 250 V AC, cos phi = 0.4, 7 ms                                                                        |
| Discrete input number     | 7                                                                                                                                                                                                                                                                                                                                     |
| Discrete input type       | (LI1...LI5) programmable, 24 V DC, voltage limits ≤ 30 V, with level 1 PLC, impedance 3500 Ohm                                                                                                                                                                                                                                        |

|                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                     | (LI6) switch-configurable, 24 V DC, voltage limits ≤ 30 V, with level 1 PLC, impedance 3500 Ohm<br>(LI6) switch-configurable PTC probe, 0...6, impedance 1500 Ohm<br>(PWR) safety input, 24 V DC, voltage limits ≤ 30 V, impedance 1500 Ohm                                                                                                                                                                                                                                                                      |
| Discrete input logic                | LI1...LI5 positive logic (source), < 5 V (state 0), > 11 V (state 1)<br>LI1...LI5 negative logic (sink), > 16 V (state 0), < 10 V (state 1)<br>LI6 (if configured as logic input) negative logic (sink), > 16 V (state 0), < 10 V (state 1)<br>LI6 (if configured as logic input) positive logic (source), < 5 V (state 0), > 11 V (state 1)                                                                                                                                                                     |
| Acceleration and deceleration ramps | Automatic adaptation of ramp if braking capacity exceeded, by using resistor<br>Linear adjustable separately from 0.01 to 9000 s<br>S, U or customized                                                                                                                                                                                                                                                                                                                                                           |
| Braking to standstill               | By DC injection                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Protection type                     | Drive against exceeding limit speed<br>Drive against input phase loss<br>Drive break on the control circuit<br>Drive input phase breaks<br>Drive line supply overvoltage<br>Drive line supply undervoltage<br>Drive overcurrent between output phases and earth<br>Drive overheating protection<br>Drive overvoltages on the DC bus<br>Drive power removal<br>Drive short-circuit between motor phases<br>Drive thermal protection<br>Motor motor phase break<br>Motor power removal<br>Motor thermal protection |
| Insulation resistance               | > 1 mOhm at 500 V DC for 1 minute to earth                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Frequency resolution                | Analog input 0.024/50 Hz<br>Display unit 0.1 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Connector type                      | 1 RJ45 Modbus on front face<br>1 RJ45 Modbus on terminal<br>Male SUB-D 9 on RJ45 CANopen                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Physical interface                  | 2-wire RS 485 Modbus                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Transmission frame                  | RTU Modbus                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Transmission rate                   | 20 kbps, 50 kbps, 125 kbps, 250 kbps, 500 kbps, 1 Mbps CANopen<br>4800 bps, 9600 bps, 19200 bps, 38.4 Kbps Modbus on terminal<br>9600 bps, 19200 bps Modbus on front face                                                                                                                                                                                                                                                                                                                                        |
| Data format                         | 8 bits, 1 stop, even parity Modbus on front face<br>8 bits, odd even or no configurable parity Modbus on terminal                                                                                                                                                                                                                                                                                                                                                                                                |
| Number of addresses                 | 1...247 Modbus<br>1...127 CANopen                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Method of access                    | Slave CANopen                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Marking                             | CE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Operating position                  | Vertical +/- 10 degree                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Product weight                      | 399.04 lb(US) (181 kg)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Width                               | 23.43 in (595 mm)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Height                              | 46.85 in (1190 mm)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Depth                               | 14.84 in (377 mm)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

## Environment

|                               |                                                                                                                                                                                          |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| noise level                   | 77 dB conforming to 86/188/EEC                                                                                                                                                           |
| dielectric strength           | 3110 V DC between earth and power terminals<br>5345 V DC between control and power terminals                                                                                             |
| electromagnetic compatibility | Conforming to IEC 61000-4-2 level 3<br>Conforming to IEC 61000-4-11<br>Conforming to IEC 61000-4-6 level 3<br>Conforming to IEC 61000-4-3 level 3<br>Conforming to IEC 61000-4-4 level 4 |
| standards                     | EN 55011 class A group 2<br>EN 61800-3 environments 1 category C3<br>EN 61800-3 environments 2 category C3<br>EN/IEC 61800-3<br>EN/IEC 61800-5-1<br>IEC 60721-3-3 class 3C2<br>UL Type 1 |
| product certifications        | CSA<br>C-Tick                                                                                                                                                                            |

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                       | DNV<br>GOST<br>NOM 117<br>UL                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| pollution degree                      | 3 conforming to EN/IEC 61800-5-1<br>3 conforming to UL 840                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| IP degree of protection               | IP00 conforming to EN/IEC 60529<br>IP00 conforming to EN/IEC 61800-5-1<br>IP30 on side parts conforming to EN/IEC 60529<br>IP30 on side parts conforming to EN/IEC 61800-5-1<br>IP30 on the front panel conforming to EN/IEC 60529<br>IP30 on the front panel conforming to EN/IEC 61800-5-1<br>IP41 on upper part conforming to EN/IEC 60529<br>IP41 on upper part conforming to EN/IEC 61800-5-1<br>IP54 on lower part conforming to EN/IEC 60529<br>IP54 on lower part conforming to EN/IEC 61800-5-1 |
| vibration resistance                  | 1.5 mm peak to peak (f = 3...10 Hz) conforming to EN/IEC 60068-2-6<br>0.6 gn (f = 10...200 Hz) conforming to EN/IEC 60068-2-6                                                                                                                                                                                                                                                                                                                                                                            |
| shock resistance                      | 4 gn 11 ms conforming to EN/IEC 60068-2-27                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| relative humidity                     | 5...95 % without condensation conforming to IEC 60068-2-3<br>5...95 % without dripping water conforming to IEC 60068-2-3                                                                                                                                                                                                                                                                                                                                                                                 |
| ambient air temperature for operation | 14...113 °F (-10...45 °C) without derating<br>113...140 °F (45...60 °C) with derating factor                                                                                                                                                                                                                                                                                                                                                                                                             |
| ambient air temperature for storage   | -13...158 °F (-25...70 °C)                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| operating altitude                    | <= 3280.84 ft (1000 m) without derating<br>3280.84...7414.7 ft (1000...2260 m) with current derating 1 % per 100 m                                                                                                                                                                                                                                                                                                                                                                                       |

### Offer Sustainability

|                                                                                                                                  |                                                                                                                                  |
|----------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Green Premium product                                                                                                            | Green Premium product                                                                                                            |
| Compliant - since 1601 - Schneider Electric declaration of conformity                                                            | Compliant - since 1601 - Schneider Electric declaration of conformity                                                            |
| Reference not containing SVHC above the threshold                                                                                | Reference not containing SVHC above the threshold                                                                                |
| Available                                                                                                                        | Available                                                                                                                        |
| Need no specific recycling operations                                                                                            | Need no specific recycling operations                                                                                            |
| WARNING: This product can expose you to chemicals including:                                                                     | WARNING: This product can expose you to chemicals including:                                                                     |
| Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. | Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                                    | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                                    |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9