



## 1/4" BALANCED PATCH CABLE

### TCH SERIES OVERVIEW

Designed to be a flexible, yet rugged component of professional live sound and studio systems, the TCH Series Balanced Patch Cable can handle the rigors of any audio environment.

The IO-T3MCH-R, right angle connectors feature an extremely durable nickel tin plated brass shell and includes a clamp that tightens onto the cable to provide strain relief while an additional rubber boot delivers extended support. The gold plated plug contacts, silver plated wire terminals, and XLPE insulation all ensure the best possible signal flow and extend the useful life of the cable.

It's durable and flexible PVC jacket protects the OFC conductors from whatever life throws at it. Add to the equation two shields, aluminum foil and braided tinned copper, and the conductors have double the protection from EMI resulting in a dependable addition to any professional audio engineer's toolbox.



Product specifications may change without prior notification

Io Audio Technologies® is a registered trademark of Knight Electronics, Inc.  
10557 Metric Dr. Dallas, TX 75243 | 214-340-0265 | 800-323-2439 | Fax: 214-340-5870 |  
[www.ioaudiotechnologies.com](http://www.ioaudiotechnologies.com)



## SPECIFICATIONS

### Product

Part Number: **IO-BP176XXX-T3MCH-2R**

Number of Conductors: **2 plus shield**

### Conductors

Details: **25/0.08mm BC OFC**

Size: **26 AWG**

### Electrical and Mechanical Characteristics

Conductor DC Resistance:  **$0.152 \pm 1\% \Omega/m$**

Shield DC Resistance:  **$0.035 \pm 1\% \Omega/m$**

Capacitance Between Conductors:  **$\leq 14.4 \text{ pF/ft}$**

Capacitance Between Conductors and Shield:  **$\leq 27.1 \text{ pF/ft}$**

Voltage Breakdown: **500 V**

Flex Life:  **$\geq 17,700$**

Tensile Strength:  **$\geq 199 \text{ N}$**

Applicable Temperature:  **$-20^\circ\text{C} \sim +60^\circ\text{C}$  ( $-4^\circ\text{F} \sim +140^\circ\text{F}$ )**

Peak Temperature:  **$-40^\circ\text{C} \sim +70^\circ\text{C}$  ( $-40^\circ\text{F} \sim +158^\circ\text{F}$ )**

### Insulation

Material: **XLPE**

Colors: **Blue and White**

### Shield

Details: **Braided**

Construction: **16\*5/0.10 TC OFC**


### Jacket

O.D.: **6.0mm**

Material: **PVC**

Color: **Black**

## DRAWING



## STANDARDS & CLASSIFICATIONS



Product specifications may change without prior notification

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9