


3M™ HIGH ROUTABILITY INTERNAL MINISAS CABLE ASSEMBLY, 8F36 SERIES



- NOTES
1. ROHS COMPLIANT. SEE REGULATORY INFORMATION APPENDIX IN "ROHS COMPLIANCE" SECTION AT WWW.3M.COM/INTERCONNECT. (E1 & C1 APPLY).
 2. PADDLECARD PLATING:
30μ" MIN. GOLD PLATING
50μ" MIN. NICKEL UNDERPLATING.
CABLE A & B : 78-9101-1588-6.
CABLE C & D : 78-9101-0933-5.
 3. MINISAS CABLE PLUG DIMENSIONS SHALL CONFORM WITH SFF-8086 AND SFF-8087 STANDARDS.
 4. CLOTH TAPE WRAPPED AROUND CABLE RIBBONS AT BACK OF EACH CONNECTOR. ALSO, UP TO TWO ADDITIONAL TAPE PIECES WILL BE WRAPPED AROUND THE TWO CABLE RIBBONS SPACED EQUIDISTANT FROM THE CONNECTOR ENDS AND EACH OTHER, DEPENDING ON ASS'Y LENGTH (L):
L ≤ 0.2M: NO ADDITIONAL TAPE
0.2M < L ≤ 0.6M: 1 TAPE WRAP
0.6M < L ≤ 1.0M: 2 TAPE WRAP
 5. PRODUCT SPECIFICATION: #PS-0082.
 6. TWO RIBBONS OF 3M RIBBON TWIN AXIAL CABLE.
 7. THIS CABLE CONSTRUCTION HAS A THIN ALUMINUM LAYER AT EACH EDGE USER SHOULD EVALUATE ITS USE IN THEIR APPLICATION AND, IF NECESSARY, INSULATING TAPE MAY BE APPLIED TO COVER THE ALUMINUM LAYER, AS USER DEEMS APPROPRIATE.
 8. LENGTH TOLERANCE:
±10MM FOR LENGTH ≤ 0.5 METERS
±15MM FOR LENGTH > 0.5 METERS.

8 F 36 - AA X X 05 - X.XX

LENGTH IN METERS

PINOUT (SEE PINOUTS ON SHEET 2)

CABLE USED

A 4-LANE WITH SIDEBANDS,	SN-PLATED SIGNAL,CABLE P/N SL8801/12-11DA5-00
B 4-LANE WITH SIDEBANDS,	AG-PLATED SIGNAL,CABLE P/N SL8801/12-10DA5-00
C 4-LANE NO SIDEBANDS,	SN-PLATED SIGNAL,CABLE P/N SL8802/08-21DN5-00
D 4-LANE NO SIDEBANDS,	AG-PLATED SIGNAL,CABLE P/N SL8802/08-20DN5-00

DESIGN REFERENCE		NEXT ASSEMBLY	
DISTRIBUTION CODES			
DIVISION	Interconnect Solutions	DIVISION CODE	ISD
DO NOT SCALE DRAWING	SCALE	TOLERANCES EXCEPT AS NOTED	
THIRD ANGLE PROJECTION		INCHES	
INTERPRET PER ASME Y14.5 - 1994		MILLIMETERS	
MAX SURFACE ROUGHNESS			
ALL SURFACES			
MARKED ONLY			
ANGLES			

REV	ECO	ISSUE DATE AND DESCRIPTION		DRFT	CHKD
RAO VITTAPALLI		DATE JUN 06,2012	WFS MING KHIANG	DATE JUN 06,2012	
CHKD MARK LETTANG		DATE JUN 06,2012	APPLV ALAN ANG	DATE JUN 06,2012	

3M		© 3M COPYRIGHT 2013	
3M Center St. Paul, MN 55144		This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.	

TITLE		CABLE ASSEMBLY INTERNAL 36P MINISAS RIBBON TWINAX	
CAGE NUMBER	SIZE	DRAWING NO.	REV.
	C	78-5100-2363-9	C
MODEL		DET. LISTS	YES NO
		SHT 1 OF 2	

3M™ HIGH ROUTABILITY INTERNAL MINISAS CABLE ASSEMBLY, 8F36 SERIES

PINOUT 1
BACKPLANE-TO-CONTROLLER

P1		P2	
A1	GND	B1	GND
A2	Rx 0+	B2	Tx 0+
A3	Rx 0-	B3	Tx 0-
A4	GND	B4	GND
A5	Rx 1+	B5	Tx 1+
A6	Rx 1-	B6	Tx 1-
A7	GND	B7	GND
A8	SIDEBAND	B8	SIDEBAND
A9	SIDEBAND	B9	SIDEBAND
A10	SIDEBAND	B10	SIDEBAND
A11	SIDEBAND	B11	SIDEBAND
A12	GND	B12	GND
A13	Rx 2+	B13	Tx 2+
A14	Rx 2-	B14	Tx 2-
A15	GND	B15	GND
A16	Rx 3+	B16	Tx 3+
A17	Rx 3-	B17	Tx 3-
A18	GND	B18	GND


NOTE:
1. A1, A4, A7, A12, A15, A18, B1, B4, B7, B12, B15 AND B18 ARE ALL REFERENCE GROUNDS AND ARE SHORTED TOGETHER THROUGH THE PADDLECARD GROUND PLANES.

PINOUT 3
BACKPLANE-TO-CONTROLLER (NO SIDEBANDS)

P1		P2	
A1	GND	B1	GND
A2	Rx 0+	B2	Tx 0+
A3	Rx 0-	B3	Tx 0-
A4	GND	B4	GND
A5	Rx 1+	B5	Tx 1+
A6	Rx 1-	B6	Tx 1-
A7	GND	B7	GND
A12	GND	B12	GND
A13	Rx 2+	B13	Tx 2+
A14	Rx 2-	B14	Tx 2-
A15	GND	B15	GND
A16	Rx 3+	B16	Tx 3+
A17	Rx 3-	B17	Tx 3-
A18	GND	B18	GND

P1		P2	
B1	GND	A1	GND
B2	Tx 0+	A2	Rx 0+
B3	Tx 0-	A3	Rx 0-
B4	GND	A4	GND
B5	Tx 1+	A5	Rx 1+
B6	Tx 1-	A6	Rx 1-
B7	GND	A7	GND
B12	GND	A12	GND
B13	Tx 2+	A13	Rx 2+
B14	Tx 2-	A14	Rx 2-
B15	GND	A15	GND
B16	Tx 3+	A16	Rx 3+
B17	Tx 3-	A17	Rx 3-
B18	GND	A18	GND

NOTE:
1. A1, A4, A7, A12, A15, A18, B1, B4, B7, B12, B15 AND B18 ARE ALL REFERENCE GROUNDS AND ARE SHORTED TOGETHER THROUGH THE PADDLECARD GROUND PLANES.
2. A8-A11 AND B8-B11 HAVE NO CONNECTIONS TO CABLE.



4	LABEL 30X40MM	1X
3	ACETATE TAPE	AS REQUIRED
2	CABLE RIBBON TWINAX , 150V ,80 C 30AWG AG/SN PLATED. REFER TO SHEET 1 FOR SELECTION.	AS PER LENGTH
1	36 PIN MINISAS CONNECTOR, PCB FR4, OVERMOULD -PBT 30% GF, LATCH -STAINLESS STEEL.	2X
ITEM	SPECIFICATION	QUANTITY

C	43801	OCT 12,2012 CHANGE TO SOLID DRAIN WIRE.	RAO	MARK
B	37070	OCT 25,2011 ADD LENGTH TOLERANCE	JNC	ML
A	30167	AUG 09,2010 RELEASED	ML	ML

DESIGN REFERENCE				NEXT ASSEMBLY				REV				ECO				ISSUE DATE AND DESCRIPTION				DRFT		CHKD											
DISTRIBUTION CODES																DRFT				RAO VITTAPALLI		DATE		JUN 06,2012		WFS		MING KHIANG		DATE		JUN 06,2012	
																CHKD				MARK LETTANG		DATE		JUN 06,2012		APPL		ALAN ANG		DATE		JUN 06,2012	
DIVISION								DIVISION CODE								3M 3M Center St. Paul, MN 55144 © 3M COPYRIGHT 2013 This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.																	
Interconnect Solutions								ISD																									
DO NOT SCALE DRAWING				SCALE				TOLERANCES EXCEPT AS NOTED				TITLE																					
								INCHES																									
				THIRD ANGLE PROJECTION				.0 ±				CABLE ASSEMBLY																					
								.00 ±																									
								.000 ±				INTERNAL 36P MINISAS																					
								.0000 ±																									
INTERPRET PER ASME Y14.5 - 1994								MILLIMETERS				RIBBON TWINAX																					
								.0 ±																									
MAX SURFACE ROUGHNESS								.00 ±				CAGE NUMBER																					
								.000 ±																									
✓ ☐ ALL SURFACES								.000 ±				SIZE																					
								.000 ±																									
✓ ☐ MARKED ONLY								ANGLES				DRAWING NO.																					
								ANGLES																									
MODEL								DET. LISTS								YES ☐ NO ☒								SHT 2 OF 2									

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9