

Multi-Turn Precision Potentiometer

Model 7200 Series



Features:

- 7/8" diameter
- 10-turn
- Wirewound



Model Styles Available

| | |
|------------|-------------------------------|
| 7216, 7221 | Bushing Mount, Sleeve Bearing |
| 7223 | Servo Mount, Ball Bearing |

Electrical

| | |
|---|---|
| Resistance Range, Ohms | 10 to 125K |
| Standard Resistance Tolerance | ±3% |
| Minimum Practical Resistance Tolerance | ±1% |
| Independent Linearity | ±0.25% |
| Minimum Practical Independent Linearity | ±0.25%, ≤ 20 Ohms ±0.15%, 21-49 Ohms ±0.10%, 50-99 Ohms ±0.075%, 100-999 Ohms ±0.05%, ≥ 1K Ohms |
| Power Rating, Watts | 2.0 at 70°C derating to 0 at 125°C |
| Dielectric Strength | 1,000V rms |
| Insulation Resistance, Minimum | 1,000 Megohms |
| Noise, Maximum | 100 Ohms |
| Actual Electrical Travel | 3600° + 10° - 0°, > 25 Ohms 3600° + 10° - 5°, ≤ 25 Ohms |
| Tap Tolerance | ±5°, ≤20 Ohms ±3°, 21-49 Ohms ±2°, ≥50 Ohms |
| End Voltage, Maximum (% of input voltage) | 0.5%, <100 Ohms 0.25%, ≥100 Ohms |

Specifications subject to change without notice.
Available in a Hybrid version – contact factory for details.

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

© TT electronics plc

TT Electronics | BI Technologies
413 Rood RD, Suite 7
Calexico, CA 92231
Ph: +1 714 447 2345
www.ttelectronics.com/bi-technologies

Multi-Turn Precision Potentiometer

Model 7200 Series



Environmental

| | |
|-----------------------------|--|
| Operating Temperature Range | Static: -65°C to +125°C Dynamic: -40°C to +125°C |
| Temperature Cycling | 5 cycles, -65°C to +125°C (5% ΔR) |
| Shock, 6ms Sawtooth | 50G's (0.1ms discontinuity max.) |
| Vibration | 15G's, 10 to 2,000 Hz (5% ΔR, 0.1ms discontinuity max.) |
| Moisture Resistance | Ten 24 hour cycles (3% ΔR) |
| High Temperature Exposure | 1,000 hours at 125°C (5% ΔR) |
| Rotational Load Life | 2 mil. shaft rev. + 900 hrs. at rated wattage at 70°C (5% ΔR)* |

* Model 7216 - Rotational Load Life = 1 mil. shaft rev.+900 hrs. at rated wattage at 70°C (5% ΔR)

Mechanical

| | | | |
|--|--------------------------|-------------|-------------|
| Total Mechanical Travel | 3600° + 10° - 0° | | |
| Number of Gangs, Maximum | 2 | | |
| Weight, Nominal (single Gang) | 1.25 oz. | | |
| Static Stop Strength | 128 oz.-in. | | |
| Backlash, Maximum | 1.5° | | |
| | 7216 | 7221 | 7223 |
| Panel Nut Tightening Torque, Maximum | 25 lb.-in. | 25 lb.-in. | N/A |
| Shaft End Play, Maximum | .0085" | .005" | .005" |
| Shaft Runout, T.I.R., Maximum | .001" | .001" | .001" |
| Pilot Diameter Runout, T.I.R., Maximum | .001" | .001" | .0015" |
| Lateral Runout, T.I.R., Maximum | .003" | .003" | .003" |
| Shaft Radial Play, Maximum | .003" | .003" | .002" |
| Start/Run Torque, Maximum (per Gang) | 0.6 oz.-in / 0.5 oz.-in. | | |

Special Features

| | |
|------------------------------|----|
| Center Tap | CT |
| Linearity Tape | LT |
| Rear Shaft Extension | RS |
| Flatted Shaft | FS |
| Slotted Shaft | SS |
| Shaft Lock (7216, 7221 only) | SL |
| Additional Gangs | 2G |

General Note
TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | BI Technologies
413 Rood RD, Suite 7
Calxico, CA 92231
Ph: +1 714 447 2345
www.ttelectronics.com/bi-technologies

Multi-Turn Precision Potentiometer

Model 7200 Series




STANDARD RESISTANCE VALUES, OHMS

| Total Resistance | Theoretical Resolution (% Nominal) | Tempco of Wire |
|------------------|------------------------------------|----------------|
| 10 | 0.083 | + 800 ppm/°C * |
| 25 | 0.055 | + 800 ppm/°C * |
| 50 | 0.048 | + 800 ppm/°C * |
| 100 | 0.040 | + 800 ppm/°C * |
| 200 | 0.033 | + 800 ppm/°C * |
| 500 | 0.031 | ± 20 ppm/°C |
| 1K | 0.028 | ± 20 ppm/°C |
| 2K | 0.025 | ± 20 ppm/°C |
| 5K | 0.020 | + 130 ppm/°C * |
| 10K | 0.018 | + 130 ppm/°C * |
| 20K | 0.016 | + 130 ppm/°C * |
| 50K | 0.012 | ± 20 ppm/°C |
| 100K | 0.011 | ± 20 ppm/°C |

* Lower tempco available as a special model.


Ordering Information



MATCHING TURNS COUNTING DIALS

7216: 2606, 2606S, 2607, 2607S, 2626, 2627, 2646, 2646S, 2647, 2647S, RB
 7221: RBJ, 2601, 2641

CIRCUIT DIAGRAM



NOTES

Metric equivalents, based on 1 inch = 25.4mm are rounded to the same number of significant figures as in the original English units and are provided for general information only.

Tolerances unless otherwise specified:
 Linear = ± .01 inches (.25mm)
 Angular = ± 2 degrees

General Note
 TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | BI Technologies
 413 Rood RD, Suite 7
 Calexico, CA 92231
 Ph: +1 714 447 2345
www.ttelectronics.com/bi-technologies

Multi-Turn Precision Potentiometer

Model 7200 Series



Outline Drawing

Model 7216 & 7221
Bushing Mount with Sleeve Bearing



METRIC CONVERSIONS

| | | | |
|-------|---------|-----------|-----------|
| 1 in. | 25.4 mm | 1 oz.-in. | 0,007 N-m |
| 1 oz. | 28.4 gm | 1 lb.-in. | 0,113 N-m |

General Note
TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | BI Technologies
413 Rood RD, Suite 7
Calexico, CA 92231
Ph: +1 714 447 2345
www.ttelectronics.com/bi-technologies

Multi-Turn Precision Potentiometer


Model 7200 Series



TT Electronics

Outline Drawing

Model 7223
Servo Mount with Ball Bearing



General Note
 TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

© TT electronics plc

TT Electronics | BI Technologies
 413 Rood RD, Suite 7
 Calexico, CA 92231
 Ph: +1 714 447 2345
www.ttelectronics.com/bi-technologies

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9