



Apr. 2015 Ver.2.0
TDK Corporation

Multilayer Diplexer

For UWB

DPX Series


2012 TYPE

P/N: **DPX209504DT-4183A1**


DPX209504DT-4183A1

■ SHAPES AND DIMENSIONS

[Top View]



[Bottom View]



Dimensions (mm)

L	W	T	a	b	c	d
2.00	1.25	0.60	0.20	0.30	0.35	0.65
+/-0.15	+/-0.15	+/-0.10	+/-0.20	+/-0.20	+/-0.20	+/-0.20

Terminal functions

(1)	GND
(2)	Common Port
(3)	GND
(4)	Low-Band Port
(5)	GND
(6)	High-Band Port

Note:

These samples are marked with trial sample identification.

In mass production, this sample marking will be changed to show in the TDK full specification.

■ TEMPERATURE RANGE

Operating temperature	Storage temperature
-40 to +85 °C	-40 to +85 °C

DPX209504DT-4183A1

■ ELECTRICAL CHARACTERISTICS

(Measurement)

Low-Band

Parameter	Frequency (MHz)	Target Spec		
		Min.	Typ.	Max.
Insertion Loss (dB)	3168 to 4752	-	0.31	0.60
Attenuation (dB)	6336 to 9504	18	20.0	-
VSWR	3168 to 4752	-	1.4	2.0

Ta = +25+/-5°C

High-Band

Parameter	Frequency (MHz)	Target Spec		
		Min.	Typ.	Max.
Insertion Loss (dB)	6336 to 9504	-	0.59	0.85
Attenuation (dB)	3168 to 4752	16	20	-
VSWR	6336 to 9504	-	1.8	2.2

Ta = +25+/-5°C

ESD

The Diplexer satisfies the electrical specification after the following tests.
 (When measured after two hours in normal conditions):

•HBM
 MIL-STD-883D
 EIAJ ED-4701-1 C-111
 Cd=100pF Rd=1.5kohm V=+/-1000V 1time


Apr. 2015 Ver.2.0
TDK Corporation

DPX209504DT-4183A1

FREQUENCY CHARACTERISTICS


(Measurement)

Low band-Port




Attenuation	
6336 MHz	20.23 dB
9504 MHz	29.63 dB

High band-Port




Attenuation	
3168 MHz	20.52 dB
4752 MHz	28.28 dB

Low band-Port




Insertion Loss	
3168 MHz	0.15 dB
4752 MHz	0.31 dB

High band-Port




Insertion Loss	
6336 MHz	0.61 dB
9504 MHz	0.50 dB

Common Port Return Loss




3168 MHz	23.62 dB
4752 MHz	22.95 dB
6336 MHz	14.15 dB
9504 MHz	11.49 dB

Isolation




3168 MHz	21.2 dB
4752 MHz	30.0 dB
6336 MHz	19.9 dB
9504 MHz	28.8 dB

Low band-Port Return Loss



3168 MHz	22.90 dB
4752 MHz	21.65 dB

High band-Port Return Loss




6336 MHz	13.71 dB
9504 MHz	11.55 dB

Apr. 2015 Ver.2.0
TDK Corporation

DPX209504DT-4183A1

RECOMMENDED LAND PATTERN



 No pattern area of internal layers


* Line width should be designed to match 50 ohm characteristic impedance depending on PCB material and thickness.

ENVIRONMENT INFORMATION

RoHS Statement
RoHS Compliance

DPX209504DT-4183A1**RECOMMENDED REFLOW PROFILE**

Pb free solder




Soaking			Working		Soldering		Peak
Temp.		Time	Temp.	Time	Temp.	Time	Temp.
T1	T2	t1	T3	t2	T4	t3	T5
150°C	180°C	60 to 120sec	230°C	more than 30sec	247 to 253°C	within 10sec	260°C Max.

Apr. 2015 Ver.2.0
TDK Corporation


DPX209504DT-4183A1

■ PACKAGING STYLE

Reel Dimensions



Carrier Tape



STANDARD PACKAGE QUANTITY (pieces/reel)
2,000

REMINDERS FOR USING THESE PRODUCTS

Before using these products, be sure to request the delivery specifications.

SAFETY REMINDERS

Please pay sufficient attention to the warnings for safe designing when using these products.

REMINDERS

The products listed on this specification sheet are intended for use in general electronic equipment (AV equipment, telecommunications equipment, home appliances, amusement equipment, computer equipment, personal equipment, office equipment, measurement equipment, industrial robots) under a normal operation and use condition.

The products are not designed or warranted to meet the requirements of the applications listed below, whose performance and/or quality require a more stringent level of safety or reliability, or whose failure, malfunction or trouble could cause serious damage to society, person or property. Please understand that we are not responsible for any damage or liability caused by use of the products in any of the applications below or for any other use exceeding the range or conditions set forth in this specification sheet.

1. Aerospace/Aviation equipment
2. Transportation equipment (cars, electric trains, ships, etc.)
3. Medical equipment
4. Power-generation control equipment
5. Atomic energy-related equipment
6. Seabed equipment
7. Transportation control equipment
8. Public information-processing equipment
9. Military equipment
10. Electric heating apparatus, burning equipment
11. Disaster prevention/crime prevention equipment
12. Safety equipment
13. Other applications that are not considered general-purpose applications

When using this product in general-purpose applications, you are kindly requested to take into consideration securing protection circuit/equipment or providing backup circuits, etc., to ensure higher safety.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9