



Micro Commercial Components™



Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

SMAJ5913B THRU SMAJ5956B

Features


- Lead Free Finish/Rohs Compliant (Note1) ("P" Suffix designates Compliant. See ordering information)
- Low Zener Impedance
- Low Regulation Factor
- V_z - tolerance: $\pm 5\%$
- For Surface Mount Applications
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Halogen free available upon request by adding suffix "-HF"

Maximum Ratings

- Junction Temperature: 150°C
- Storage Temperature: -65°C to +175°C
- 1.5 Watt DC Power Dissipation ($T_L \leq 75^\circ\text{C}$)
- Thermal Resistance Junction to Lead: 50°C/W
- Thermal Resistance Junction to Ambient: 83°C/W
- Forward Voltage @ 200mA: 1.5 Volts


1.5 Watt Zener Diode 3.3 to 200 Volts

DO-214AC (SMA)(LEAD FRAME)



| DIM | DIMENSIONS | | | | NOTE |
|-----|------------|------|------|------|------|
| | INCHES | | MM | | |
| A | .079 | .096 | 2.00 | 2.44 | |
| B | .050 | .064 | 1.27 | 1.63 | |
| C | .002 | .008 | .05 | .20 | |
| D | --- | .02 | --- | .51 | |
| E | .030 | .060 | .76 | 1.52 | |
| F | .065 | .091 | 1.65 | 2.32 | |
| G | .189 | .220 | 4.80 | 5.59 | |
| H | .157 | .181 | 4.00 | 4.60 | |
| J | .090 | .115 | 2.25 | 2.92 | |

SUGGESTED SOLDER PAD LAYOUT



Note: 1. High Temperature Solder Exemptions Applied, see EU Directive Annex 7.

SMAJ5913B THRU SMAJ5956B



Micro Commercial Components™

ELECTRICAL CHARACTERISTICS @25°C

| MCC PART NUMBER | ZENER VOLTAGE VZ (1) | TEST CURRENT IZT | MAXIMUM DYNAMIC IMPEDANCE ZZT @IZT | KNEE CURRENT IZK | KNEE IMPEDANCE ZZK | MAXIMUM REVERSE CURRENT IR | REVERSE VOLTAGE VR | DEVICE MARKING |
|-----------------|----------------------|------------------|------------------------------------|------------------|--------------------|----------------------------|--------------------|----------------|
| | VOLTS | mA | OHMS | mA | OHMS | µA | VOLTS | |
| SMAJ5913B | 3.3 | 113.6 | 10 | 1 | 500 | 100 | 1 | 13B |
| SMAJ5914B | 3.6 | 104.2 | 9 | 1 | 500 | 75 | 1 | 14B |
| SMAJ5915B | 3.9 | 96.1 | 7.5 | 1 | 500 | 25 | 1 | 15B |
| SMAJ5916B | 4.3 | 87.2 | 6 | 1 | 500 | 5.0 | 1 | 16B |
| SMAJ5917B | 4.7 | 79.8 | 5 | 1 | 500 | 5.0 | 1.5 | 17B |
| SMAJ5918B | 5.1 | 73.5 | 4 | 1 | 350 | 5.0 | 2 | 18B |
| SMAJ5919B | 5.6 | 66.9 | 2 | 1 | 250 | 5.0 | 3 | 19B |
| SMAJ5920B | 6.2 | 60.5 | 2 | 1 | 200 | 5.0 | 4 | 20B |
| SMAJ5921B | 6.8 | 55.1 | 2.5 | 1 | 200 | 5.0 | 5.2 | 21B |
| SMAJ5922B | 7.5 | 50 | 3 | 0.5 | 400 | 5.0 | 6 | 22B |
| SMAJ5923B | 8.2 | 45.7 | 3.5 | 0.5 | 400 | 5.0 | 6.5 | 23B |
| SMAJ5924B | 9.1 | 41.2 | 4 | 0.25 | 500 | 5.0 | 7 | 24B |
| SMAJ5925B | 10 | 37.5 | 4.5 | 0.25 | 500 | 5.0 | 8 | 25B |
| SMAJ5926B | 11 | 34.1 | 5.5 | 0.25 | 550 | 1.0 | 8.4 | 26B |
| SMAJ5927B | 12 | 31.2 | 6.5 | 0.25 | 550 | 1.0 | 9.1 | 27B |
| SMAJ5928B | 13 | 28.8 | 7 | 0.25 | 550 | 1.0 | 9.9 | 28B |
| SMAJ5929B | 15 | 25 | 9 | 0.25 | 600 | 1.0 | 11.4 | 29B |
| SMAJ5930B | 16 | 23.4 | 10 | 0.25 | 600 | 1.0 | 12.2 | 30B |
| SMAJ5931B | 18 | 20.8 | 12 | 0.25 | 650 | 1.0 | 13.7 | 31B |
| SMAJ5932B | 20 | 18.7 | 14 | 0.25 | 650 | 1.0 | 15.2 | 32B |
| SMAJ5933B | 22 | 17 | 17.5 | 0.25 | 650 | 1.0 | 16.7 | 33B |
| SMAJ5934B | 24 | 15.6 | 19 | 0.25 | 700 | 1.0 | 18.2 | 34B |
| SMAJ5935B | 27 | 13.9 | 23 | 0.25 | 700 | 1.0 | 20.6 | 35B |
| SMAJ5936B | 30 | 12.5 | 28 | 0.25 | 750 | 1.0 | 22.8 | 36B |
| SMAJ5937B | 33 | 11.4 | 33 | 0.25 | 800 | 1.0 | 25.1 | 37B |
| SMAJ5938B | 36 | 10.4 | 38 | 0.25 | 850 | 1.0 | 27.4 | 38B |
| SMAJ5939B | 39 | 9.6 | 45 | 0.25 | 900 | 1.0 | 29.7 | 39B |
| SMAJ5940B | 43 | 8.7 | 53 | 0.25 | 950 | 1.0 | 32.7 | 40B |
| SMAJ5941B | 47 | 8 | 67 | 0.25 | 1000 | 1.0 | 35.8 | 41B |
| SMAJ5942B | 51 | 7.3 | 70 | 0.25 | 1100 | 1.0 | 38.8 | 42B |
| SMAJ5943B | 56 | 6.7 | 86 | 0.25 | 1300 | 1.0 | 42.6 | 43B |
| SMAJ5944B | 62 | 6 | 100 | 0.25 | 1500 | 1.0 | 47.1 | 44B |
| SMAJ5945B | 68 | 5.5 | 120 | 0.25 | 1700 | 1.0 | 51.7 | 45B |
| SMAJ5946B | 75 | 5 | 140 | 0.25 | 2000 | 1.0 | 56 | 46B |
| SMAJ5947B | 82 | 4.6 | 160 | 0.25 | 2500 | 1.0 | 62.2 | 47B |
| SMAJ5948B | 91 | 4.1 | 200 | 0.25 | 3000 | 1.0 | 69.2 | 48B |
| SMAJ5949B | 100 | 3.7 | 250 | 0.25 | 3100 | 1.0 | 76 | 49B |
| SMAJ5950B | 110 | 3.4 | 300 | 0.25 | 4000 | 1.0 | 83.6 | 50B |
| SMAJ5951B | 120 | 3.1 | 380 | 0.25 | 4500 | 1.0 | 91.2 | 51B |
| SMAJ5952B | 130 | 2.9 | 450 | 0.25 | 5000 | 1.0 | 98.8 | 52B |
| SMAJ5953B | 150 | 2.5 | 600 | 0.25 | 6000 | 1.0 | 114 | 53B |
| SMAJ5954B | 160 | 2.3 | 700 | 0.25 | 6500 | 1.0 | 121.6 | 54B |
| SMAJ5955B | 180 | 2.1 | 900 | 0.25 | 7000 | 1.0 | 136.8 | 55B |
| SMAJ5956B | 200 | 1.9 | 1200 | 0.25 | 8000 | 1.0 | 152 | 56B |

1) Based on DC-measurement at thermal equilibrium while maintaining the lead temperature(T_L) at 30°C, 9.5mm(3/8) from the diode body.

Characteristics ($T_j=25^{\circ}\text{C}$ unless otherwise specified)

| Symbol | Parameter |
|----------|------------------------------------|
| V_Z | Reverse zener voltage @ I_{ZT} |
| I_{ZT} | Reverse current |
| Z_{ZT} | Maximum zener impedance @ I_{ZT} |
| I_{ZK} | Reverse current |
| Z_{ZK} | Maximum zener impedance @ I_{ZK} |
| I_R | Reverse leakage current @ V_R |
| V_R | Breakdown voltage |
| I_F | Forward current |
| V_F | Forward voltage @ I_F |




Figure 1. Zener voltage regulator




Figure 2. Steady state power derating




Figure 3. V_Z - 3.3 thru 10 volts




Figure 4. Zener voltage - 3.3 to 12 volts




Figure 5. Zener voltage - 14 to 43 volts




Figure 6. Effect of zener voltage




Figure 7. Capacitance curve




Figure 8. Typical pulse rating curve




Figure 9. Pulse waveform




Figure 10. Pulse waveform



Micro Commercial Components TM

Ordering Information :

| Device | Packing |
|----------------|-------------------------|
| Part Number-TP | Tape&Reel: 7.5Kpcs/Reel |

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9