

4813 Multi-Conductor - Enhanced Category 6 Nonbonded-Pair Cable



For more Information
please call

1-800-Belden1

**Description:**

23 AWG Solid Bare Copper Conductors, Dual FRPO/FEP Teflon® insulation, X-Spline Center Member, Rip Cord, Flamarrest® Jacket.

Usage (Overall)**Suitable Applications:**

Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG
ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video,
AES/EBU Digital Audio, AES51, RS-422, Noisy Environments

Physical Characteristics (Overall)**Conductor****AWG:**

# Pairs	AWG	Stranding	Conductor Material
4	23	Solid	BC - Bare Copper

Total Number of Conductors:

8

Insulation**Insulation Material:**

Insulation Material
FRPO/FEP - Flame Retardant Polyolefin/Fluorinated Ethylene Propylene

Outer Shield**Outer Shield Material:**

Outer Shield Material
Unshielded

Outer Jacket**Outer Jacket Material:**

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

Outer Jacket Diameter:

Nom. Dia. (in.)
0.255

Outer Jacket Ripcord:

Yes

Overall Cable**Overall Cabling Separator Material:**

Patented X-Spline Center Member

Pair**Pair Color Code Chart:**

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

Mechanical Characteristics (Overall)**Installation Temperature Range:**

+5°C To +50°C

Operating Temperature Range:

-20°C To +75°C

4813 Multi-Conductor - Enhanced Category 6 Nonbonded-Pair Cable

Bulk Cable Weight:	34 lbs/1000 ft.
Max. Recommended Pulling Tension:	45 lbs.
Min. Bend Radius/Minor Axis:	1.500 in.
Min. Bend/Installation:	2.500 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMP
NEC Articles:	800
CEC/C(UL) Specification:	CMP
Other Standards:	ISO/IEC 11801 ed 2.1 (2008) Class E
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2006
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Telecommunications Standards:	Category 6 - TIA 568.C.2
Other Specification:	UL Verified to Category 6

Applicable Patents:

Country	Patent
US	5563377
US	6074503
US	7663061
CANADA	2144694
US	7977575

Flame Test

UL Flame Test:	NFPA 262
CSA Flame Test:	FT6

Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	4812

Electrical Characteristics (Overall)

Nom. Mutual Capacitance:

Capacitance (pF/ft)
15.5

Maximum Capacitance Unbalance (pF/100 m):	330
---	-----

Nominal Velocity of Propagation:

VP (%)
70.000

Maximum Delay:

Delay (ns/100 m)
510.000

Max. Delay Skew:

Delay Skew (ns/100 m)

4813 Multi-Conductor - Enhanced Category 6 Nonbonded-Pair Cable

25.000

Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)

6.600

Max. Operating Voltage - UL:

Voltage

300 V RMS

Maximum DCR Unbalanced:

DCR Unbalance @ 20°C (%)

3

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min RL (dB)
0.772	1.700	82	80	80.3	78.3	
1	1.800	80.3	78.3	78.5	76.5	20.000
4	3.400	71.3	69.3	67.9	65.9	23.000
8	4.800	66.8	64.8	62	60	24.500
10	5.300	65.3	63.3	60	58	25.000
16	6.800	62.2	60.2	55.5	53.5	25.000
20	7.600	60.8	58.8	53.2	51.2	25.000
25	8.500	59.3	57.3	50.8	48.8	25.000
31.25	9.600	57.9	55.9	48.3	46.3	24.200
62.5	13.800	53.4	51.4	39.6	37.6	22.900
100	17.800	50.3	48.3	32.5	30.5	22.100
155	22.700	47.4	45.4	24.8	22.8	21.300
200	26.200	45.8	43.8	19.6	17.6	20.900
250	29.700	44.3	42.3	14.6	12.6	20.400
300	33.000	43.1	41.1	10.2	8.2	20.100
350	36.000	42.1	40.1	6.1	4.1	19.800
400	39.000	41.3	39.3	2.3	0.3	19.600
450	41.800	40.5	38.5	-1.3	-3.3	19.400
500	44.500	39.8	37.8	-4.6	-6.6	19.200
550	47.100	39.2	37.2	-7.9	-9.9	19.000
600	49.600	38.6	36.6	-11.0	-13.0	18.900

Premise Cable Electrical Table 2:

Freq. (MHz)	Input (Unfitted) Imp. (Ohms)	Fitted Impedance	Min. ACRF (dB)	Min. PSACRF (dB)
0.772		102 ± 15	77.0	74.0
1	100 ± 15	100 ± 15	74.8	71.8
4	100 ± 15	100 ± 15	62.8	59.8
8	100 ± 15	100 ± 15	56.7	53.7
10	100 ± 15	100 ± 15	54.8	51.8
16	100 ± 15	100 ± 15	50.7	47.7
20	100 ± 15	100 ± 15	48.8	45.8
25	100 ± 15	100 ± 15	46.8	43.8
31.25	100 ± 15	100 ± 15	44.9	41.9
62.5	100 ± 15	100 ± 15	38.9	35.9
100	100 ± 15	100 ± 15	34.8	31.8
155	100 ± 15	100 ± 15	31.0	28.0
200	100 ± 15	100 ± 15	28.8	25.8
250	100 ± 22	100 ± 15	26.8	23.8
300	100 ± 22	100 ± 15	25.3	22.3
350	100 ± 22	100 ± 15	23.9	20.9
400	100 ± 22	100 ± 15	22.8	19.8
450			21.7	18.7
500			20.8	17.8
550			20.0	17.0
600			19.2	16.2

4813 Multi-Conductor - Enhanced Category 6 Nonbonded-Pair Cable**Premise Cable Electrical Table 4:**

Frequency (MHz)	Min. TCL (dB)	Min. ELTCTL (dB)
0.772	40.000	37.200
1.000	40.000	35.000
4.000	40.000	23.000
8.000	40.000	16.900
10.000	40.000	15.000
16.000	38.000	10.900
20.000	37.000	9.000
25.000	36.000	7.000
31.250	35.100	
62.500	32.000	
100.000	30.000	
155.000	28.100	
200.000	27.000	
250.000	26.000	

Notes (Overall)

Notes: Belden IBDN. Jacket sequentially marked at 2 ft./1m intervals. Values above 400 MHz are for Engineering Information Only. Third party verified to ANSI/TIA-568-C.2, Category 6.

Reference (Overall)**Previous Part Number:**

24587785, 24587785+US, 25087885, 25087885+US, 24587185,
 24587185+US, 24587385, 24587385+US, 24587336, 24587336+US,
 24587315, 24587485, 24587485+US, 24587451+US, 24587985,
 24587985+US, 24587915, 24587915+US

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
4813 D15A1000	1,000 FT	30.000 LB	BLUE		CAT6E+ 4PR U/UTP CMP RIB
4813 D15I1000	1,000 FT	30.000 LB	BLUE		CAT6E+ 4PR U/UTP CMP REEL
4813 004I1000	1,000 FT	30.000 LB	YELLOW		CAT6E+ 4PR U/UTP CMP REEL
4813 005I1000	1,000 FT	30.000 LB	GREEN, DARK		CAT6E+ 4PR U/UTP CMP REEL
4813 008I1000	1,000 FT	30.000 LB	GRAY		CAT6E+ 4PR U/UTP CMP REEL
4813 009A1000	1,000 FT	30.000 LB	WHITE		CAT6E+ 4PR U/UTP CMP RIB
4813 009I1000	1,000 FT	30.000 LB	WHITE		CAT6E+ 4PR U/UTP CMP REEL
4813 0092500	2,500 FT	80.000 LB	WHITE		CAT6E+ 4PR U/UTP CMP REEL
4813 010I1000	1,000 FT	30.000 LB	BLACK		CAT6E+ 4PR U/UTP CMP REEL
4813 0103000	3,000 FT	99.000 LB	BLACK		CAT6E+ 4PR U/UTP CMP REEL

Revision Number: 8 Revision Date: 07-10-2012

© 2012 Belden, Inc
 All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9