

THIS ENTIRE DRAWING IS SUBJECT TO THE FOLLOWING LEGEND:

THOSE PORTIONS OF THIS TECHNICAL DATA INDICATED AS LIMITED RIGHTS DATA SHALL NOT, WITHOUT THE WRITTEN PERMISSION OF THE ABOVE CONTRACTOR, BE EITHER (a) USED, RELEASED OR DISCLOSED IN WHOLE OR IN PART OUTSIDE THE GOVERNMENT (b) USED IN WHOLE OR IN PART BY THE GOVERNMENT FOR MANUFACTURE OR, IN THE CASE OF COMPUTER SOFTWARE DOCUMENTATION, FOR PREPARING THE SAME OR SIMILAR COMPUTER SOFTWARE, OR (c) USED BY A PARTY OTHER THAN THE GOVERNMENT, EXCEPT FOR (1) EMERGENCY REPAIR OR OVERHAUL WORK ONLY, BY OR FOR THE GOVERNMENT, WHERE THE ITEM OR PROCESS CONCERNED IS NOT OTHERWISE REASONABLY AVAILABLE TO ENABLE TIMELY PERFORMANCE OF THE WORK, PROVIDED THAT THE RELEASE OR DISCLOSURE HEREOF OUTSIDE THE GOVERNMENT SHALL BE MADE SUBJECT TO A PROHIBITION AGAINST FURTHER USE, RELEASE OR DISCLOSURE; OR (2) RELEASE TO A FOREIGN GOVERNMENT, AS THE INTEREST OF THE UNITED STATES MAY REQUIRE, ONLY FOR INFORMATION OR EVALUATION WITHIN SUCH GOVERNMENT OR FOR EMERGENCY REPAIR OR OVERHAUL WORK BY OR FOR SUCH GOVERNMENT UNDER THE CONDITIONS OF (1) ABOVE. THIS LEGEND, TOGETHER WITH THE INDICATIONS OF THE PORTIONS OF THIS DATA WHICH ARE SUBJECT TO SUCH LIMITATIONS SHALL BE INCLUDED ON ANY REPRODUCTION HEREOF WHICH INCLUDES ANY PART OF THE PORTIONS SUBJECT TO SUCH LIMITATION.

HARTMAN® PROPRIETARY (DO NOT COPY)

HARTMAN®



REVISIONS

RELEASED

REV.

K

REV.	DESCRIPTION	DATE	APPROVED
F 24801	ADDED ITEM 5	93/06/10	WS
G 32568	FIND NO 5 QTY 2 WAS 3	97/04/07	RS
H 41370	NOTE 3 ADDED	00/01/14	RS
J 0218-04	ADDED LAMP TEST	04/04/01	CB
K 12-020166	ADDED NOTE 4; MAX WT WAS 6-1/4 OZ.	12/11/15	MM



NOTES:

- CONTACT RATING MUST BE DERATED IF CONTACTS ARE USED AS S.P.D.T.
- COIL TRANSIENT VOLTAGE LIMITED TO ± 42 VOLTS REFERENCED TO ZERO VOLTS.
- DIRECTION OF OPEN END OF HOOK IS OPTIONAL.
- ILLUSTRATIONS FOR REF. ONLY. PRODUCT MEETS FUNCTIONAL AND DIMENSIONAL REQUIREMENTS.

CONSTRUCTION
CONTACT CONFIGURATION
CONTACT RATING. RES.
IND.. NO
NC
MOTOR
LAMP
COIL VOLTAGE
PICKUP
DROPOUT
ALTITUDE
VIBRATION
SHOCK
TEMPERATURE
RATED DUTY
LIFE: ELECTRICAL
MECHANICAL
DESIGN OBJECTIVE: AMEND. 2 OF
MAX. WEIGHT

HERMETICALLY SEALED
1 NO. 1 NC (SEE NOTE)
25A.. 28 VDC
25A
25A
15A
16A
30 VDC MAX
18 VDC MAX 71°C
7 V TO 1 VDC
80,000 FT
MIL-E-5272. PROC. 1
15 G
-55° TO +71°C
CONTINUOUS
50,000 CYCLES
100,000 CYCLES
MIL-R-6106E, TYPE 1, CLASS A
6.5 OZ

5	2	39529-017	OVERLAY						
4	1	32389-001	WIRING DIAGRAM						
3	1	19336-070	RELAY ASS'Y PRIMARY				1616184-6		
2	1	17959-001	PLATE WARNING				1-1616178-1		
1	1	16225-003	PLATE-NAME						
FIND NO	QTY REQD	PART OR IDENTIFYING NO	NOMENCLATURE OR DESCRIPTION	DRAWING OR SPECIFICATION	FSC NO	TE PART NO	MATERIAL OR NOTE		

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON		
2 PL DEC.	3 PL DEC.	ANGLES
$\pm .060$	$\pm .010$	$\pm 1^\circ$
DASH NO.	NEXT ASSY	USED ON
APPLICATION		

DR BY	RCB	04/04/01
CHK BY	CB	04/04/01
ENGR	DAW	04/04/22
MFG	WW	04/04/22
SIZE	CODE IDENT	
A	74063	
SCALE 1:1	SHEET SHEET	

STE

Hartman Division 175 N. DIAMOND STREET MANSFIELD, OHIO 44902

RELAY-25A, 28 VDC, SPDT, N.O.
IN.C. DOUBLE BREAK

DWG NO. DH-14AT

REF TE PN 1616089-3

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9