

# High Temperature, Programmable SMD MEMS Oscillator

ASTMHT



ESD Sensitive



RoHS/RoHS II compliant



2.0 x 1.6 x 0.75mm; 2.5 x 2.0 x 0.75mm;  
3.2 x 2.5 x 0.75mm; 5.0 x 3.2 x 0.75mm;  
7.0 x 5.0 x 0.9mm

Moisture Sensitivity Level (MSL) – 1

## FEATURES:

- Industry standard package sizes: 2.0 x 1.6 x 0.75mm, 2.5 x 2.0 x 0.75mm, 3.2 x 2.5 x 0.75mm, 5 x 3.2 x 0.75mm, 7.0 x 5.0 x 0.9mm
- Output frequency between 1MHz and 137MHz
- Supply voltage options: 3.3V, 3.0V, 2.8V, 2.5V, 1.8V, 2.25V ~ 3.63V
- Low current consumption: 3.5mA typ. (@20MHz, 1.8V, no load); 4.9mA typ. (@125MHz, 1.8V, no load)
- Wide operating temperature range options: -40 ~ +105°C; -40 ~ +125°C; -55 ~ +125°C
- Frequency stability options: ±20ppm, ±25ppm, ±30ppm, ±50ppm
- Factory programmable drive strength for improved jitter, reduced EMI or higher capacitive output load

## APPLICATIONS:

- High temperature applications for Industrial, medical, non-automotive and avionics
- Harsh environment (vibration, shock-prone and humid)

## STANDARD SPECIFICATIONS:

All electrical specifications are specified with 15pF output load and for all Vdd(s) unless otherwise stated. The typical value of any parameter in the table is specified for the nominal value of the highest voltage option for that parameter and at 25°C temperature.

| Parameters                                      | Min                                      | Typ | Max        | Unit | Notes                                                                                                                                                                 |
|-------------------------------------------------|------------------------------------------|-----|------------|------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Output Frequency Range (F)                      | 1.000000                                 |     | 110.000000 | MHz  | Available with operation temp. range option "X", "A" and "Z"                                                                                                          |
|                                                 | 115.194001                               |     | 119.342000 |      | Available with operation temp. range option "X" and "A"                                                                                                               |
|                                                 | 119.342001                               |     | 137.000000 |      | Available with operation temp. range option "X", "A" and "Z"                                                                                                          |
| Standard Frequencies                            | See Section 1.1 for Standard Frequencies |     |            | MHz  |                                                                                                                                                                       |
| Frequency Stability (F <sub>stab</sub> )        | -20                                      |     | +20        | ppm  | Inclusive of initial tolerance at 25°C, 1 <sup>st</sup> year aging at 25°C, and variations over operating temperature, rated power supply voltage and load (15pF±10%) |
|                                                 | -25                                      |     | +25        |      |                                                                                                                                                                       |
|                                                 | -30                                      |     | +30        |      |                                                                                                                                                                       |
|                                                 | -50                                      |     | +50        |      |                                                                                                                                                                       |
| Operating Temperature Range (T <sub>use</sub> ) | -40                                      |     | +105       | °C   | Option "X"                                                                                                                                                            |
|                                                 | -40                                      |     | +125       |      | Option "A"                                                                                                                                                            |
|                                                 | -55                                      |     | +125       |      | Option "Z"                                                                                                                                                            |
| Supply Voltage (V <sub>dd</sub> )               | 1.62                                     | 1.8 | 1.98       | V    | Option "18"                                                                                                                                                           |
|                                                 | 2.25                                     | 2.5 | 2.75       |      | Option "25"                                                                                                                                                           |
|                                                 | 2.52                                     | 2.8 | 3.08       |      | Option "28"                                                                                                                                                           |
|                                                 | 2.7                                      | 3.0 | 3.3        |      | Option "30"                                                                                                                                                           |
|                                                 | 2.97                                     | 3.3 | 3.63       |      | Option "33"                                                                                                                                                           |
|                                                 | 2.25                                     |     | 3.63       |      | Option "Blank" (default)                                                                                                                                              |
| Current Consumption (I <sub>dd</sub> )          |                                          | 3.8 | 4.7        | mA   | No load, F=20MHz, V <sub>dd</sub> =2.8V, 3.0V, 3.3V                                                                                                                   |
|                                                 |                                          | 3.6 | 4.5        |      | No load, F=20MHz, V <sub>dd</sub> =2.5V                                                                                                                               |
|                                                 |                                          | 3.5 | 4.5        |      | No load, F=20MHz, V <sub>dd</sub> =1.8V                                                                                                                               |
|                                                 |                                          | 6.2 | 8          |      | No load, F=125MHz, V <sub>dd</sub> =2.8V, 3.0V, 3.3V                                                                                                                  |
|                                                 |                                          | 5.4 | 7          |      | No load, F=125MHz, V <sub>dd</sub> =2.5V                                                                                                                              |
|                                                 |                                          | 4.9 | 6          |      | No load, F=125MHz, V <sub>dd</sub> =1.8V                                                                                                                              |
| OE Disable Current (I <sub>OD</sub> )           |                                          |     | 4.5        | mA   | F=1MHz~110MHz, V <sub>dd</sub> =2.5V-3.3V, OE=Low, output is in High-Z state                                                                                          |
|                                                 |                                          |     | 4.3        |      | F=1MHz~110MHz, V <sub>dd</sub> =1.8V, OE=Low, output is in High-Z state                                                                                               |
|                                                 |                                          |     | 4.7        |      | F=115.194001MHz~110MHz, V <sub>dd</sub> =2.5V-3.3V, OE=Low, output is in High-Z state                                                                                 |
|                                                 |                                          |     | 4.5        |      | F=115.194001MHz~110MHz, V <sub>dd</sub> =1.8V, OE=Low, output is in High-Z state                                                                                      |

# High Temperature, Programmable SMD MEMS Oscillator

ASTMHT



RoHS/RoHS II compliant



2.0 x 1.6 x 0.75mm; 2.5 x 2.0 x 0.75mm;  
3.2 x 2.5 x 0.75mm; 5.0 x 3.2 x 0.75mm;  
7.0 x 5.0 x 0.9mm

(Continued)

| Parameters                              | Min           | Typ | Max           | Unit       | Notes                                                                                   |
|-----------------------------------------|---------------|-----|---------------|------------|-----------------------------------------------------------------------------------------|
| Standby Current ( $I_{std}$ )           |               | 2.6 | 8.5           | $\mu A$    | $\overline{ST}$ =Low, $V_{dd}$ =2.8V-3.3V, output is weakly pulled down                 |
|                                         |               | 1.4 | 5.5           |            | $\overline{ST}$ =Low, $V_{dd}$ =2.5V, output is weakly pulled down                      |
|                                         |               | 0.6 | 4.0           |            | $\overline{ST}$ =Low, $V_{dd}$ =1.8V, output is weakly pulled down                      |
| Output Type                             | LVCMOS        |     |               |            |                                                                                         |
| Duty Cycle                              | 45            |     | 55            | %          | All $V_{dd}$ options                                                                    |
| Rise/Fall Time ( $T_r/T_f$ )            |               | 1   | 2             | ns         | $V_{dd}$ =2.5V, 2.8V, 3.0V or 3.3V, 20%-80%                                             |
|                                         |               | 1.3 | 2.5           |            | $V_{dd}$ =1.8V, 20%-80%                                                                 |
|                                         |               | 1   | 3             |            | $V_{dd}$ =2.25V-3.63V, 20%-80%                                                          |
| Output High Voltage ( $V_{OH}$ )        | 90%* $V_{dd}$ |     |               | V          | $I_{OH}$ =-4mA ( $V_{dd}$ =3.0V or 3.3V)                                                |
|                                         |               |     |               |            | $I_{OH}$ =-3mA ( $V_{dd}$ =2.8V or 2.5V)                                                |
|                                         |               |     |               |            | $I_{OH}$ =-2mA ( $V_{dd}$ =1.8V)                                                        |
| Output Low Voltage ( $V_{OL}$ )         |               |     | 10%* $V_{dd}$ | V          | $I_{OL}$ =4mA ( $V_{dd}$ =3.0V or 3.3V)                                                 |
|                                         |               |     |               |            | $I_{OL}$ =3mA ( $V_{dd}$ =2.8V or 2.5V)                                                 |
|                                         |               |     |               |            | $I_{OL}$ =2mA ( $V_{dd}$ =1.8V)                                                         |
| Input High Voltage( $V_{IH}$ )          | 70%* $V_{dd}$ |     |               | V          | Pin 1                                                                                   |
| Input Low Voltage( $V_{IL}$ )           |               |     | 30%* $V_{dd}$ | V          | Pin 1                                                                                   |
| Input Pull-up Impedance ( $Z_{in}$ )    | 50            | 87  | 150           | k $\Omega$ | Pin 1, OE logic high or logic low, $\overline{ST}$ logic high                           |
|                                         | 2             |     |               | M $\Omega$ | Pin 1, $\overline{ST}$ logic low                                                        |
| Startup Time ( $T_{start}$ )            |               |     | 5             | ms         | Measured from the time $V_{dd}$ reaches 90% of its final value                          |
| Enable/Disable Time ( $T_{oe}$ )        |               |     | 130           | ns         | F=110MHz, 115.194001MHz, 119.342001MHz. For other frequencies, $T_{oe}$ =100ns+3*cycles |
| Resume Time ( $T_{resume}$ )            |               |     | 5             | ms         | Measured from the time $\overline{ST}$ pin crosses 50% threshold                        |
| RMS Period Jitter ( $T_{jitt}$ )        |               | 1.6 | 2.5           | ps         | F=75MHz, 125MHz, $V_{dd}$ =2.5V, 2.8V, 3.0V or 3.3V                                     |
|                                         |               | 1.9 | 3             |            | F=75MHz, 125MHz, $V_{dd}$ =1.8V                                                         |
| Peak-to-peak Period Jitter ( $T_{pk}$ ) |               | 12  | 20            | ps         | F=75MHz, 125MHz, $V_{dd}$ =2.5V, 2.8V, 3.0V or 3.3V                                     |
|                                         |               | 14  | 25            |            | F=75MHz, 125MHz, $V_{dd}$ =1.8V                                                         |
| RMS Phase Jitter (random) ( $T_{phj}$ ) |               | 0.5 | 0.8           | ps         | F=75MHz, 125MHz integration bandwidth=900kHz to 7.5MHz                                  |
|                                         |               | 1.3 | 2             |            | F=75MHz, 125MHz integration bandwidth=12kHz to 20MHz                                    |

# High Temperature, Programmable SMD MEMS Oscillator

ASTMHT



RoHS/RoHS II compliant



2.0 x 1.6 x 0.75mm; 2.5 x 2.0 x 0.75mm;  
3.2 x 2.5 x 0.75mm; 5.0 x 3.2 x 0.75mm;  
7.0 x 5.0 x 0.9mm

## Standard Frequency (MHz)

| Standard Frequency (MHz) |          |          |         |         |         |        |        |         |
|--------------------------|----------|----------|---------|---------|---------|--------|--------|---------|
| 7.3728                   | 8        | 8.192    | 9.8304  | 9.84375 | 11.0592 | 12     | 12.288 | 13      |
| 13.225625                | 13.52127 | 14.31818 | 14.7456 | 15      | 16      | 16.384 | 18.432 | 19.6608 |
| 20                       | 22.1184  | 24       | 24.56   | 24.576  | 25      | 26     | 27     | 29.4912 |
| 30                       | 32       | 33       | 36      | 40      | 48      |        |        |         |

## Absolute Maximum Ratings

Attempted operation outside the absolute maximum ratings may cause permanent damage to the part. Actual performance of the IC is only guaranteed within the operational specifications, not at absolute maximum ratings.

| Parameters                                                              | Min. | Max. | Unit |
|-------------------------------------------------------------------------|------|------|------|
| Storage Temperature                                                     | -65  | 150  | °C   |
| V <sub>DD</sub>                                                         | -0.5 | 4    | V    |
| Electrostatic Discharge (HBM)                                           |      | 2000 | V    |
| Soldering Temperature<br>(follow standard Pb free soldering guidelines) |      | 260  | °C   |
| Junction Temperature <sup>(1)</sup>                                     |      | 150  | °C   |

Note: 1. Exceeding this temperature for extended period of time may damage the device

## Thermal Consideration

| Package     | θJA, 4 Layer Board<br>(°C/W) | θJA, 2 Layer Board<br>(°C/W) | θJC, Bottom<br>(°C/W) |
|-------------|------------------------------|------------------------------|-----------------------|
| 7.0 x 5.0mm | 142                          | 273                          | 30                    |
| 5.0 x 3.2mm | 97                           | 199                          | 24                    |
| 3.2 x 2.5mm | 109                          | 212                          | 27                    |
| 2.5 x 2.0mm | 117                          | 222                          | 26                    |
| 2.0 x 1.6mm | 152                          | 252                          | 36                    |

## Maximum Operating Junction Temperature <sup>(2)</sup>

| Max. Operating Temperature (ambient) | Max. Operating Junction Temperature |
|--------------------------------------|-------------------------------------|
| 105°C                                | 115°C                               |
| 125°C                                | 135°C                               |

Note: 2. Datasheet specifications are not guaranteed if junction temperature exceeds the maximum operating junction temperature

# High Temperature, Programmable SMD MEMS Oscillator

ASTMHT



RoHS/RoHS II compliant



2.0 x 1.6 x 0.75mm; 2.5 x 2.0 x 0.75mm;  
3.2 x 2.5 x 0.75mm; 5.0 x 3.2 x 0.75mm;  
7.0 x 5.0 x 0.9mm

## PART IDENTIFICATION:

ASTMHT [ ] - [ ] - [ ] MHz - [ ] [ ] - [ ] [ ] - [ ]

| Package Size  |
|---------------|
| A: 2.0x1.6mm  |
| D: 2.5x2.0mm  |
| E: 3.2x2.5mm  |
| FL: 5.0x3.2mm |
| V: 7.0x5.0mm  |

| Output Frequency in MHz |
|-------------------------|
| e.g. 7.3728, 125.000    |

| Operating Temp.   |
|-------------------|
| X: -40°C ~ +105°C |
| A: -40°C ~ +125°C |
| Z: -55°C ~ +125°C |

| Pin 1 Function   |
|------------------|
| E: Output Enable |
| S: Standby       |
| N: No Connect    |

| Packaging                      |
|--------------------------------|
| Blank: Bulk                    |
| T: Tape & Reel (1kpcs / reel)  |
| T3: Tape & Reel (3kpcs / reel) |

| Supply Voltage     |
|--------------------|
| Blank: 2.25V~3.63V |
| 18: 1.8V±10%       |
| 25: 2.5V±10%       |
| 28: 2.8V±10%       |
| 30: 3.0V±10%       |
| 33: 3.3V±10%       |

| Freq. Stability |
|-----------------|
| J: ±20ppm       |
| R: ±25 ppm      |
| K: ±30ppm       |
| C: ±50 ppm      |

| Output Drive Strength* |
|------------------------|
| Blank: Default         |
| L**                    |
| A**                    |
| R                      |
| B                      |
| T                      |
| E                      |
| U                      |
| F                      |

\* See Table 1 to 5 for the Rise/Fall times at different drive strength and available options

\*\* Only available for F=1MHz~110MHz

| List of Supported Frequency Ranges (MHz) |            |              |            |
|------------------------------------------|------------|--------------|------------|
| -40°C~+105°C/-40°C~+125°C                |            | -55°C~+125°C |            |
| Min                                      | Max        | Min          | Max        |
| 1.000000                                 | 61.222999  | 1.000000     | 61.222999  |
| 61.974001                                | 69.795999  | 61.674001    | 69.239999  |
| 70.485001                                | 79.062999  | 70.827001    | 78.714999  |
| 79.162001                                | 81.427999  | 79.561001    | 80.159999  |
| 82.232001                                | 91.833999  | 80.174001    | 80.779999  |
| 92.155001                                | 94.248999  | 82.632001    | 91.833999  |
| 94.430001                                | 94.874999  | 95.474001    | 96.191999  |
| 94.994001                                | 97.713999  | 96.209001    | 96.935999  |
| 98.679001                                | 110.000000 | 99.158001    | 110.000000 |
| 115.194001                               | 117.810999 | 119.342001   | 120.238999 |
| 118.038001                               | 118.593999 | 120.262001   | 121.169999 |
| 118.743001                               | 122.141999 | 121.243001   | 121.600999 |
| 122.705001                               | 123.021999 | 123.948001   | 137.000000 |
| 123.348001                               | 137.000000 |              |            |



**Table 1:  $V_{dd}=1.8V$  Rise/Fall Times for Specific  $C_{LOAD}$**

**(a) Output Frequency: 1MHz – 110MHz**

| Drive Strength Options | Rise/Fall Time Typ. (ns) |       |       |       |       |
|------------------------|--------------------------|-------|-------|-------|-------|
|                        | $C_{LOAD}$               |       |       |       |       |
|                        | 5pF                      | 15pF  | 30pF  | 45pF  | 60pF  |
| L                      | 6.16                     | 11.61 | 22.00 | 31.27 | 39.91 |
| A                      | 3.19                     | 6.35  | 11.00 | 16.01 | 21.52 |
| R                      | 2.11                     | 4.31  | 7.65  | 10.77 | 14.47 |
| B                      | 1.65                     | 3.23  | 5.79  | 8.18  | 11.08 |
| T                      | 0.93                     | 1.91  | 3.32  | 4.66  | 6.48  |
| E                      | 0.78                     | 1.66  | 2.94  | 4.09  | 5.74  |
| U                      | 0.70                     | 1.48  | 2.64  | 3.68  | 5.09  |
| F or Blank (default)   | 0.65                     | 1.30  | 2.40  | 3.35  | 4.56  |

**(b) Output Frequency: 115.194001MHz – 137MHz**

| Drive Strength Options | Rise/Fall Time Typ. (ns) |      |
|------------------------|--------------------------|------|
|                        | $C_{LOAD}$               |      |
|                        | 5pF                      | 15pF |
| T                      | 0.93                     | N/A  |
| E                      | 0.78                     | N/A  |
| U                      | 0.70                     | 1.48 |
| F or Blank (default)   | 0.65                     | 1.30 |

**Table 2:  $V_{dd}=2.5V$  Rise/Fall Times for Specific  $C_{LOAD}$**

**(a) Output Frequency: 1MHz – 110MHz**

| Drive Strength Options | Rise/Fall Time Typ. (ns) |      |       |       |       |
|------------------------|--------------------------|------|-------|-------|-------|
|                        | $C_{LOAD}$               |      |       |       |       |
|                        | 5pF                      | 15pF | 30pF  | 45pF  | 60pF  |
| L                      | 4.13                     | 8.25 | 12.82 | 21.45 | 27.79 |
| A                      | 2.11                     | 4.27 | 7.64  | 11.20 | 14.49 |
| R                      | 1.45                     | 2.81 | 5.16  | 7.65  | 9.88  |
| B                      | 1.09                     | 2.20 | 3.88  | 5.86  | 7.57  |
| T                      | 0.62                     | 1.28 | 2.27  | 3.51  | 4.45  |
| E or Blank (default)   | 0.54                     | 1.00 | 2.01  | 3.10  | 4.01  |
| U                      | 0.43                     | 0.96 | 1.81  | 2.79  | 3.65  |
| F                      | 0.34                     | 0.88 | 1.64  | 2.54  | 3.32  |

**(b) Output Frequency: 115.194001MHz – 137MHz**

| Drive Strength Options | Rise/Fall Time Typ. (ns) |      |
|------------------------|--------------------------|------|
|                        | $C_{LOAD}$               |      |
|                        | 5pF                      | 15pF |
| R                      | 1.45                     | N/A  |
| B                      | 1.09                     | N/A  |
| T                      | 0.62                     | 1.28 |
| E or Blank (default)   | 0.54                     | 1.00 |
| U                      | 0.43                     | 0.96 |
| F                      | 0.34                     | 0.88 |

**Table 3:  $V_{dd}=2.8V$  Rise/Fall Times for Specific  $C_{LOAD}$**

**(a) Output Frequency: 1MHz – 110MHz**

| Drive Strength Options | Rise/Fall Time Typ. (ns) |      |       |       |       |
|------------------------|--------------------------|------|-------|-------|-------|
|                        | $C_{LOAD}$               |      |       |       |       |
|                        | 5pF                      | 15pF | 30pF  | 45pF  | 60pF  |
| L                      | 3.77                     | 7.54 | 12.28 | 19.57 | 25.27 |
| A                      | 1.94                     | 3.90 | 7.03  | 10.24 | 13.34 |
| R                      | 1.29                     | 2.57 | 4.72  | 7.01  | 9.06  |
| B                      | 0.97                     | 2.00 | 3.54  | 5.43  | 6.93  |
| T                      | 0.55                     | 1.12 | 2.08  | 3.22  | 4.08  |
| E or Blank (default)   | 0.44                     | 1.00 | 1.83  | 2.82  | 3.67  |
| U                      | 0.34                     | 0.88 | 1.64  | 2.52  | 3.30  |
| F                      | 0.29                     | 0.81 | 1.48  | 2.29  | 2.99  |

**(b) Output Frequency: 115.194001MHz – 137MHz**

| Drive Strength Options | Rise/Fall Time Typ. (ns) |      |      |
|------------------------|--------------------------|------|------|
|                        | $C_{LOAD}$               |      |      |
|                        | 5pF                      | 15pF | 30pF |
| R                      | 1.29                     | N/A  | N/A  |
| B                      | 0.97                     | N/A  | N/A  |
| T                      | 0.55                     | 1.12 | N/A  |
| E or Blank (default)   | 0.44                     | 1.00 | N/A  |
| U                      | 0.34                     | 0.88 | N/A  |
| F                      | 0.29                     | 0.81 | 1.48 |



## TYPICAL PERFORMANCE DATA

**Table 4:  $V_{dd}=3.0V$  Rise/Fall Times for Specific  $C_{LOAD}$**

(a) Output Frequency: 1MHz – 110MHz

| Drive Strength Options | Rise/Fall Time Typ. (ns) |      |       |       |       |
|------------------------|--------------------------|------|-------|-------|-------|
|                        | $C_{LOAD}$               |      |       |       |       |
|                        | 5pF                      | 15pF | 30pF  | 45pF  | 60pF  |
| L                      | 3.60                     | 7.21 | 11.97 | 18.74 | 24.30 |
| A                      | 1.84                     | 3.71 | 6.72  | 9.86  | 12.68 |
| R                      | 1.22                     | 2.46 | 4.54  | 6.76  | 8.62  |
| B                      | 0.89                     | 1.92 | 3.39  | 5.20  | 6.64  |
| T or Blank (default)   | 0.51                     | 1.00 | 1.97  | 3.07  | 3.90  |
| E                      | 0.38                     | 0.92 | 1.72  | 2.71  | 3.51  |
| U                      | 0.30                     | 0.83 | 1.55  | 2.40  | 3.13  |
| F                      | 0.27                     | 0.76 | 1.39  | 2.16  | 2.85  |

(b) Output Frequency: 115.194001MHz – 137MHz

| Drive Strength Options | Rise/Fall Time Typ. (ns) |      |      |
|------------------------|--------------------------|------|------|
|                        | $C_{LOAD}$               |      |      |
|                        | 5pF                      | 15pF | 30pF |
| R                      | 1.22                     | N/A  | N/A  |
| B                      | 0.89                     | N/A  | N/A  |
| T or Blank (default)   | 0.51                     | 1.00 | N/A  |
| E                      | 0.38                     | 0.92 | N/A  |
| U                      | 0.30                     | 0.83 | N/A  |
| F                      | 0.27                     | 0.76 | 1.39 |

**Table 5:  $V_{dd}=3.3V$  Rise/Fall Times for Specific  $C_{LOAD}$**

(a) Output Frequency: 1MHz – 110MHz

| Drive Strength Options | Rise/Fall Time Typ. (ns) |      |       |       |       |
|------------------------|--------------------------|------|-------|-------|-------|
|                        | $C_{LOAD}$               |      |       |       |       |
|                        | 5pF                      | 15pF | 30pF  | 45pF  | 60pF  |
| L                      | 3.39                     | 6.88 | 11.63 | 17.56 | 23.59 |
| A                      | 1.74                     | 3.50 | 6.38  | 8.98  | 12.19 |
| R                      | 1.16                     | 2.33 | 4.29  | 6.04  | 8.34  |
| B                      | 0.81                     | 1.82 | 3.22  | 4.52  | 6.33  |
| T or Blank (default)   | 0.46                     | 1.00 | 1.86  | 2.60  | 3.84  |
| E                      | 0.33                     | 0.87 | 1.64  | 2.30  | 3.35  |
| U                      | 0.28                     | 0.79 | 1.46  | 2.05  | 2.93  |
| F                      | 0.25                     | 0.72 | 1.31  | 1.83  | 2.61  |

(b) Output Frequency: 115.194001MHz – 137MHz

| Drive Strength Options | Rise/Fall Time Typ. (ns) |      |      |
|------------------------|--------------------------|------|------|
|                        | $C_{LOAD}$               |      |      |
|                        | 5pF                      | 15pF | 30pF |
| R                      | 1.16                     | N/A  | N/A  |
| B                      | 0.81                     | N/A  | N/A  |
| T or Blank (default)   | 0.46                     | 1.00 | N/A  |
| E                      | 0.33                     | 0.87 | N/A  |
| U                      | 0.28                     | 0.79 | 1.46 |
| F                      | 0.25                     | 0.72 | 1.31 |

## Calculating Maximum Frequency

Based on the rise and fall time data given in Table 1 through 5, the maximum frequency the oscillator can operate with a guaranteed full swing of the output voltage over temperature is calculated as follows:

$$Max. Frequency = \frac{1}{5 \times T_{r/f}}$$

Example:

Calculate  $F_{max}$  of a 1MHz ~ 110MHz device with the following condition:

- $V_{dd} = 1.8V$  (Table 1)
- Capacitive Load = 30pF
- Desired  $T_{r/f}$  Time: = 3ns (rise/fall time option code “E”)

The  $F_{max}$  is 66.66666MHz.

# High Temperature, Programmable SMD MEMS Oscillator

ASTMHT



RoHS/RoHS II compliant




2.0 x 1.6 x 0.75mm; 2.5 x 2.0 x 0.75mm;  
3.2 x 2.5 x 0.75mm; 5.0 x 3.2 x 0.75mm;  
7.0 x 5.0 x 0.9mm

## TYPICAL PERFORMANCE DATA


All plots are measured with 15pF load at room temperature, unless otherwise stated.

### I<sub>DD</sub> vs. Frequency



1MHz-110MHz Devices



115.194001MHz -137MHz Devices



### Frequency vs. Temperature



# High Temperature, Programmable SMD MEMS Oscillator

ASTMHT



RoHS/RoHS II compliant





2.0 x 1.6 x 0.75mm; 2.5 x 2.0 x 0.75mm;  
3.2 x 2.5 x 0.75mm; 5.0 x 3.2 x 0.75mm;  
7.0 x 5.0 x 0.9mm

## TYPICAL PERFORMANCE DATA

### RMS Period Jitter vs. Frequency

1MHz-110MHz Devices



115.194001MHz -137MHz Devices



### Duty Cycle vs. Frequency

1MHz-110MHz Devices

115.194001MHz -137MHz Devices



# High Temperature, Programmable SMD MEMS Oscillator

ASTMHT



RoHS/RoHS II compliant




2.0 x 1.6 x 0.75mm; 2.5 x 2.0 x 0.75mm;  
3.2 x 2.5 x 0.75mm; 5.0 x 3.2 x 0.75mm;  
7.0 x 5.0 x 0.9mm


## TYPICAL PERFORMANCE DATA

### 20% - 80% Rise Time vs. Temperature



1MHz-110MHz Devices



115.194001MHz -137MHz Devices



### 20% - 80% Fall Time vs. Temperature



# High Temperature, Programmable SMD MEMS Oscillator

ASTMHT



RoHS/RoHS II compliant




2.0 x 1.6 x 0.75mm; 2.5 x 2.0 x 0.75mm;  
3.2 x 2.5 x 0.75mm; 5.0 x 3.2 x 0.75mm;  
7.0 x 5.0 x 0.9mm


## TYPICAL PERFORMANCE DATA

### RMS Integrated Phase Jitter Random (12kHz to 20MHz) vs Frequency<sup>(3)</sup>

1MHz-110MHz Devices




115.194001MHz -137MHz Devices




### RMS Integrated Phase Jitter Random (900kHz to 7.5MHz) vs Frequency<sup>(3)</sup>

1MHz-110MHz Devices



115.194001MHz -137MHz Devices



Notes: 3. Phase noise plots are measured with Agilent E5052B signal source analyzer. Integration range is 12kHz to 5MHz for carrier frequencies up to 40MHz.

# High Temperature, Programmable SMD MEMS Oscillator

ASTMHT




RoHS/RoHS II compliant




2.0 x 1.6 x 0.75mm; 2.5 x 2.0 x 0.75mm;  
3.2 x 2.5 x 0.75mm; 5.0 x 3.2 x 0.75mm;  
7.0 x 5.0 x 0.9mm

## OUTLINE DIMENSION:


### 2.0 x 1.6mm Package (Option "A")




### Recommended Land Pattern




### 2.5 x 2.0mm Package (Option "D")




### Recommended Land Pattern



### 3.2 x 2.5mm Package (Option "E")



### Recommended Land Pattern





ASTMHT




RoHS/RoHS II compliant


2.0 x 1.6 x 0.75mm; 2.5 x 2.0 x 0.75mm;  
3.2 x 2.5 x 0.75mm; 5.0 x 3.2 x 0.75mm;  
7.0 x 5.0 x 0.9mm

OUTLINE DIMENSION:

5.0 x 3.2mm Package (Option “FL”)



7.0 x 5.0mm Package (Option “V”)



| Pin | Name                       |               | Functionality                                                                                                                                                       |
|-----|----------------------------|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1   | OE/ $\overline{\text{ST}}$ | Output Enable | H or Open <sup>(4)</sup> : specified frequency output<br>L: output is high impedance. Only output driver is disabled                                                |
|     |                            | Standby       | H or Open <sup>(4)</sup> : specified frequency output<br>L: output is low (weak pull down). Device goes to sleep mode. Supply current reduces to $I_{\text{std}}$ . |
|     |                            | No Connect    | Any voltage between 0 and $V_{\text{dd}}$ or Open <sup>(4)</sup> : specified frequency output. Pin 1 has no function.                                               |
| 2   | GND                        | Power         | Electrical ground <sup>(5)</sup>                                                                                                                                    |
| 3   | Out                        | Output        | Oscillator clock output                                                                                                                                             |
| 4   | $V_{\text{dd}}$            | Power         | Power supply voltage <sup>(5)</sup>                                                                                                                                 |

Notes: 4. In OE or  $\overline{\text{ST}}$  mode, a pull-up resistor of 10k $\Omega$  or less between OE/ $\overline{\text{ST}}$  pin and  $V_{\text{dd}}$  is recommended if pin 1 is not externally driven. If pin 1 needs to be left floating, use the NC option.  
5. A capacitor value of 0.1 $\mu\text{F}$  or higher between  $V_{\text{dd}}$  and GND is required.

Dimensions: mm

# High Temperature, Programmable SMD MEMS Oscillator

ASTMHT




RoHS/RoHS II compliant




2.0 x 1.6 x 0.75mm; 2.5 x 2.0 x 0.75mm;  
3.2 x 2.5 x 0.75mm; 5.0 x 3.2 x 0.75mm;  
7.0 x 5.0 x 0.9mm

## REFLOW PROFILE:



| Item                                     | Conditions       |
|------------------------------------------|------------------|
| $T_S$ MAX to $T_L$ (Ramp-up Rate)        | 3°C/second max   |
| Preheat                                  |                  |
| Temperature Minimum ( $T_S$ MIN)         | 150°C            |
| Temperature Typical ( $T_S$ TYP)         | 175°C            |
| Temperature Maximum ( $T_S$ MAX)         | 200°C            |
| Time ( $t_S$ )                           | 60 – 180 seconds |
| Ramp-up Rate ( $T_L$ to $T_P$ )          | 3°C/second max   |
| Time Maintained Above                    |                  |
| Temperature ( $T_L$ )                    | 217°C            |
| Time ( $t_L$ )                           | 60 – 150 seconds |
| Peak Temperature ( $T_P$ )               | 260°C max        |
| Target Peak Temperature ( $T_P$ Target)  | 255°C            |
| Time within 5°C of actual peak ( $t_P$ ) | 20 – 40 seconds  |
| Max. Number of Reflow Cycles             | 3                |
| Ramp-down Rate                           | 6°C/second max   |
| Time 25°C to Peak Temperature (t)        | 8 minutes max    |

## TAPE & REEL:



Unit: mm

| Device Size | D0           | D1 min. | E1       | E2 min. | F        | P0      | P1      | P2       |
|-------------|--------------|---------|----------|---------|----------|---------|---------|----------|
| 2016        | 1.55±0.05    | 0.9     | 1.75±0.1 | 6.05    | 3.5±0.05 | 4.0±0.1 | 4.0±0.1 | 2.0±0.05 |
| 2520        | 1.55±0.05    | 1.0     | 1.75±0.1 | 5.85    | 3.5±0.05 | 4.0±0.1 | 4.0±0.1 | 2.0±0.05 |
| 3225        | 1.5+0.1/-0.0 | 1.0     | 1.75±0.1 | 5.95    | 3.5±0.05 | 4.0±0.1 | 4.0±0.1 | 2.0±0.05 |
| 5032        | 1.5+0.1/-0.0 | 1.5     | 1.75±0.1 | 10.25   | 5.5±0.05 | 4.0±0.1 | 8.0±0.1 | 2.0±0.05 |
| 7050        | 1.5+0.1/-0.0 | 1.5     | 1.75±0.1 | 14.25   | 7.5±0.1  | 4.0±0.1 | 8.0±0.1 | 2.0±0.1  |

Unit: mm

| Device Size | T        | T1 max. | T2 max. | W max. | A0        | B0       | K0        |
|-------------|----------|---------|---------|--------|-----------|----------|-----------|
| 2016        | 0.3±0.05 | 0.1     | 1.55    | 8.3    | 1.9±0.05  | 2.3±0.05 | 1.00±0.10 |
| 2520        | 0.3±0.05 | 0.1     | 1.65    | 8.3    | 2.25±0.05 | 2.8±0.05 | 1.10±0.10 |
| 3225        | 0.2±0.05 | 0.1     | 1.6     | 8.2    | 2.7±0.10  | 3.4±0.10 | 1.15±0.10 |
| 5032        | 0.6      | 0.1     | 1.65    | 12.3   | 3.5±0.10  | 5.3±0.10 | 1.10±0.10 |
| 7050        | 0.6      | 0.1     | 1.80    | 16.3   | 5.4±0.10  | 7.4±0.10 | 1.3±0.10  |

# High Temperature, Programmable SMD MEMS Oscillator

ASTMHT




RoHS/RoHS II compliant



2.0 x 1.6 x 0.75mm; 2.5 x 2.0 x 0.75mm;  
3.2 x 2.5 x 0.75mm; 5.0 x 3.2 x 0.75mm;  
7.0 x 5.0 x 0.9mm

## TAPE & REEL:



Unit: mm

| Tape Size | A max. | B min. | C             | D min. | N       | W1          | W2 max. |
|-----------|--------|--------|---------------|--------|---------|-------------|---------|
| 8mm       | 180    | 1.5    | 13.0+0.6/-0.2 | 20.2   | 60±0.5  | 8.4+1.5/-0  | 14.4    |
| 12mm      | 180    | 1.5    | 13.0±0.2      | 20.2   | 60±0.5  | 12.4+2.0/-0 | 18.4    |
|           | 330    | 1.5    | 13.0±0.2      | 20.2   | 100±0.5 | 12.4+2.0/-0 | 18.4    |
| 16mm      | 180    | 1.5    | 13.0±0.2      | 20.2   | 60±0.5  | 16.4+2.0/-0 | 22.4    |
|           | 330    | 1.5    | 13.0±0.2      | 20.2   | 100±0.5 | 16.4+2.0/-0 | 22.4    |

| Device Size | “T” (1k/reel) |         | “T3” (3k/reel) |          |
|-------------|---------------|---------|----------------|----------|
| 2016        | 8mm Tape      | 7” Reel | 8mm Tape       | 7” Reel  |
| 2520        | 8mm Tape      | 7” Reel | 8mm Tape       | 7” Reel  |
| 3225        | 8mm Tape      | 7” Reel | 8mm Tape       | 7” Reel  |
| 5032        | 12mm Tape     | 7” Reel | 12mm Tape      | 13” Reel |
| 7050        | 16mm Tape     | 7” Reel | 16mm Tape      | 13” Reel |

**ATTENTION:** Abracon Corporation’s products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon’s products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.

ABRACON IS  
ISO9001:2008  
CERTIFIED



5101 Hidden Creek Lane Spicewood TX 78669  
Phone: 512-371-6159 | Fax: 512-351-8858  
For terms and conditions of sales please visit:  
[www.abracon.com](http://www.abracon.com)

Revised: 06.17.2016

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9