

## Precision, Micropower, Low-Dropout Voltage References

### General Description

The MAX6190–MAX6195/MAX6198 precision, micropower, low-dropout voltage references offer high initial accuracy and very low temperature coefficient through a proprietary curvature-correction circuit and laser-trimmed precision thin-film resistors.

These series-mode bandgap references draw a maximum of only 35 $\mu$ A quiescent supply current, making them ideal for battery-powered instruments. They offer a supply current that is virtually immune to input voltage variations. Load-regulation specifications are guaranteed for source and sink currents up to 500 $\mu$ A. These devices are internally compensated, making them ideal for applications that require fast settling, and are stable with capacitive loads up to 2.2nF.

### Selector Guide

| PART            | OUTPUT VOLTAGE (V) | INITIAL ACCURACY (mV) | TEMPERATURE COEFFICIENT (ppm/°C) |
|-----------------|--------------------|-----------------------|----------------------------------|
| <b>MAX6190A</b> | 1.250              | $\pm 2$               | $< 5$                            |
| MAX6190B        | 1.250              | $\pm 4$               | $< 10$                           |
| MAX6190C        | 1.250              | $\pm 6$               | $< 25$                           |
| <b>MAX6191A</b> | 2.048              | $\pm 2$               | $< 5$                            |
| MAX6191B        | 2.048              | $\pm 5$               | $< 10$                           |
| MAX6191C        | 2.048              | $\pm 10$              | $< 25$                           |
| <b>MAX6192A</b> | 2.500              | $\pm 2$               | $< 5$                            |
| MAX6192B        | 2.500              | $\pm 5$               | $< 10$                           |
| MAX6192C        | 2.500              | $\pm 10$              | $< 25$                           |
| <b>MAX6193A</b> | 3.000              | $\pm 2$               | $< 5$                            |
| MAX6193B        | 3.000              | $\pm 5$               | $< 10$                           |
| MAX6193C        | 3.000              | $\pm 10$              | $< 25$                           |
| <b>MAX6198A</b> | 4.096              | $\pm 2$               | $< 5$                            |
| MAX6198B        | 4.096              | $\pm 5$               | $< 10$                           |
| MAX6198C        | 4.096              | $\pm 10$              | $< 25$                           |
| <b>MAX6194A</b> | 4.500              | $\pm 2$               | $< 5$                            |
| MAX6194B        | 4.500              | $\pm 5$               | $< 10$                           |
| MAX6194C        | 4.500              | $\pm 10$              | $< 25$                           |
| <b>MAX6195A</b> | 5.000              | $\pm 2$               | $< 5$                            |
| MAX6195B        | 5.000              | $\pm 5$               | $< 10$                           |
| MAX6195C        | 5.000              | $\pm 10$              | $< 25$                           |

Typical Operating Circuit appears at end of data sheet.

### Features

- ◆  $\pm 2$ mV (max) Initial Accuracy
- ◆ 5ppm/°C (max) Temperature Coefficient
- ◆ 35 $\mu$ A (max) Supply Current
- ◆ 100mV Dropout at 500 $\mu$ A Load Current
- ◆ 0.12 $\mu$ V/ $\mu$ A Load Regulation
- ◆ 8 $\mu$ V/V Line Regulation

### Applications

Hand-Held Instruments  
Analog-to-Digital and Digital-to-Analog Converters  
Industrial Process Control  
Precision 3V/5V Systems  
Hard-Disk Drives


### Ordering Information

| PART                | TEMP RANGE     | PIN-PACKAGE |
|---------------------|----------------|-------------|
| <b>MAX6190AESA+</b> | -40°C to +85°C | 8 SO        |
| MAX6190BESA+        | -40°C to +85°C | 8 SO        |
| MAX6190CESA+        | -40°C to +85°C | 8 SO        |
| <b>MAX6191AESA+</b> | -40°C to +85°C | 8 SO        |
| MAX6191BESA+        | -40°C to +85°C | 8 SO        |
| MAX6191CESA+        | -40°C to +85°C | 8 SO        |
| <b>MAX6192AESA+</b> | -40°C to +85°C | 8 SO        |
| MAX6192BESA+        | -40°C to +85°C | 8 SO        |
| MAX6192CESA+        | -40°C to +85°C | 8 SO        |

Ordering Information continued at end of data sheet.

+Denotes a lead(Pb)-free /RoHS-compliant package.

### Pin Configuration



For pricing, delivery, and ordering information, please contact Maxim Direct at 1-888-629-4642, or visit Maxim's website at [www.maximintegrated.com](http://www.maximintegrated.com).

# MAX6190–MAX6195/MAX6198

## Precision, Micropower, Low-Dropout Voltage References

### ABSOLUTE MAXIMUM RATINGS

Voltages Referenced to GND

IN .....-0.3V to +13.5V

OUT .....-0.3V to ( $V_{IN} + 0.3V$ )

Output Short Circuit to GND or IN ( $V_{IN} < 6V$ ) .....Continuous

Output Short Circuit to GND or IN ( $V_{IN} \geq 6V$ ) .....60s

Continuous Power Dissipation ( $T_A = +70^\circ C$ )

8-Pin SO (derate 5.88mW/ $^\circ C$  above  $+70^\circ C$ ).....471mW

Operating Temperature Range .....-40 $^\circ C$  to +85 $^\circ C$

Junction Temperature.....+150 $^\circ C$

Storage Temperature Range .....-65 $^\circ C$  to +150 $^\circ C$

Lead Temperature (soldering, 10s) .....+300 $^\circ C$

Soldering Temperature (reflow) .....+260 $^\circ C$

*Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.*

### ELECTRICAL CHARACTERISTICS—MAX6190

( $V_{IN} = 5V$ ,  $I_{OUT} = 0nA$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $T_A = +25^\circ C$ .)

| PARAMETER                                       | SYMBOL                          | CONDITIONS                               | MIN      | TYP   | MAX   | UNITS           |
|-------------------------------------------------|---------------------------------|------------------------------------------|----------|-------|-------|-----------------|
| <b>OUTPUT</b>                                   |                                 |                                          |          |       |       |                 |
| Output Voltage                                  | $V_{OUT}$                       | $T_A = +25^\circ C$                      | MAX6190A | 1.248 | 1.250 | 1.252           |
|                                                 |                                 |                                          | MAX6190B | 1.246 | 1.250 | 1.254           |
|                                                 |                                 |                                          | MAX6190C | 1.244 | 1.250 | 1.256           |
| Output-Voltage Temperature Coefficient (Note 1) | $TCV_{OUT}$                     | MAX6190A                                 |          | 2     | 5     | ppm/ $^\circ C$ |
|                                                 |                                 | MAX6190B                                 |          | 4     | 10    |                 |
|                                                 |                                 | MAX6190C                                 |          | 8     | 25    |                 |
| Line Regulation                                 | $\Delta V_{OUT}/\Delta V_{IN}$  | $2.5V \leq V_{IN} \leq 12.6V$            |          | 8     | 80    | $\mu V/V$       |
| Load Regulation                                 | $\Delta V_{OUT}/\Delta I_{OUT}$ | Sourcing: $0 \leq I_{OUT} \leq 500\mu A$ |          | 0.12  | 0.5   | $\mu V/\mu A$   |
|                                                 |                                 | Sinking: $-500\mu A \leq I_{OUT} \leq 0$ |          | 0.15  | 0.6   |                 |
| Short-Circuit Current                           | $I_{SC}$                        | Short to GND                             |          | 4     |       | mA              |
|                                                 |                                 | Short to IN                              |          | 4     |       |                 |
| Temperature Hysteresis (Note 2)                 | $\Delta V_{OUT}/\text{cycle}$   |                                          |          | 75    |       | ppm             |
| Long-Term Stability                             | $\Delta V_{OUT}/\text{time}$    | 1000hrs at $+25^\circ C$                 |          | 50    |       | ppm/1000hrs     |
| <b>DYNAMIC</b>                                  |                                 |                                          |          |       |       |                 |
| Noise Voltage                                   | $e_{OUT}$                       | 0.1Hz to 10Hz                            |          | 25    |       | $\mu V_{P-P}$   |
|                                                 |                                 | 10Hz to 10kHz                            |          | 65    |       | $\mu V_{RMS}$   |
| Ripple Rejection                                | $V_{OUT}/V_{IN}$                | $V_{IN} = 5V \pm 100mV$ , $f = 120Hz$    |          | 86    |       | dB              |
| Turn-On Settling Time                           | $t_R$                           | To 0.1%, $C_{OUT} = 50pF$                |          | 30    |       | $\mu s$         |
| Capacitive-Load Stability Range                 | $C_{OUT}$                       | (Note 3)                                 | 0        |       | 2.2   | nF              |
| <b>INPUT</b>                                    |                                 |                                          |          |       |       |                 |
| Supply Voltage Range                            | $V_{IN}$                        | Guaranteed by line-regulation test       | 2.5      |       | 12.6  | V               |
| Quiescent Supply Current                        | $I_{IN}$                        |                                          |          | 27    | 35    | $\mu A$         |
| Change in Supply Current                        | $I_{IN}/V_{IN}$                 | $2.5V \leq V_{IN} \leq 12.6V$            |          | 0.8   | 2     | $\mu A/V$       |

# MAX6190–MAX6195/MAX6198

## Precision, Micropower, Low-Dropout Voltage References

### ELECTRICAL CHARACTERISTICS—MAX6191

( $V_{IN} = 5V$ ,  $I_{OUT} = 0nA$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $T_A = +25^{\circ}C$ .)

| PARAMETER                                       | SYMBOL                               | CONDITIONS                             |          | MIN   | TYP   | MAX   | UNITS             |
|-------------------------------------------------|--------------------------------------|----------------------------------------|----------|-------|-------|-------|-------------------|
| OUTPUT                                          |                                      |                                        |          |       |       |       |                   |
| Output Voltage                                  | V <sub>OUT</sub>                     | T <sub>A</sub> = +25°C                 | MAX6191A | 2.046 | 2.048 | 2.050 | V                 |
|                                                 |                                      |                                        | MAX6191B | 2.043 | 2.048 | 2.053 |                   |
|                                                 |                                      |                                        | MAX6191C | 2.038 | 2.048 | 2.058 |                   |
| Output-Voltage Temperature Coefficient (Note 1) | TCV <sub>OUT</sub>                   | MAX6191A                               |          | 2     |       | 5     | ppm/°C            |
|                                                 |                                      | MAX6191B                               |          | 4     |       | 10    |                   |
|                                                 |                                      | MAX6191C                               |          | 8     |       | 25    |                   |
| Line Regulation                                 | ΔV <sub>OUT</sub> /ΔV <sub>IN</sub>  | 2.5V ≤ V <sub>IN</sub> ≤ 12.6V         |          | 10    |       | 100   | μV/V              |
| Load Regulation                                 | ΔV <sub>OUT</sub> /ΔI <sub>OUT</sub> | Sourcing: 0 ≤ I <sub>OUT</sub> ≤ 500μA |          | 0.12  |       | 0.55  | μV/μA             |
|                                                 |                                      | Sinking: -500μA ≤ I <sub>OUT</sub> ≤ 0 |          | 0.18  |       | 0.70  |                   |
| Short-Circuit Current                           | I <sub>SC</sub>                      | Short to GND                           |          | 4     |       |       | mA                |
|                                                 |                                      | Short to IN                            |          | 4     |       |       |                   |
| Temperature Hysteresis (Note 2)                 | ΔV <sub>OUT</sub> /cycle             |                                        |          | 75    |       |       | ppm               |
| Long-Term Stability                             | ΔV <sub>OUT</sub> /time              | 1000hrs at +25°C                       |          | 50    |       |       | ppm/1000hrs       |
| DYNAMIC                                         |                                      |                                        |          |       |       |       |                   |
| Noise Voltage                                   | e <sub>OUT</sub>                     | 0.1Hz to 10Hz                          |          | 40    |       |       | μV <sub>P-P</sub> |
|                                                 |                                      | 10Hz to 10kHz                          |          | 105   |       |       | μV <sub>RMS</sub> |
| Ripple Rejection                                | V <sub>OUT</sub> /V <sub>IN</sub>    | V <sub>IN</sub> = 5V ±100mV, f = 120Hz |          | 84    |       |       | dB                |
| Turn-On Settling Time                           | t <sub>R</sub>                       | To 0.1%, C <sub>OUT</sub> = 50pF       |          | 30    |       |       | μs                |
| Capacitive-Load Stability Range                 | C <sub>OUT</sub>                     | (Note 3)                               |          | 0     |       | 2.2   | nF                |
| INPUT                                           |                                      |                                        |          |       |       |       |                   |
| Supply Voltage Range                            | V <sub>IN</sub>                      | Guaranteed by line-regulation test     |          | 2.5   |       | 12.6  | V                 |
| Quiescent Supply Current                        | I <sub>IN</sub>                      |                                        |          | 27    |       | 35    | μA                |
| Change in Supply Current                        | I <sub>IN</sub> /V <sub>IN</sub>     | 2.5V ≤ V <sub>IN</sub> ≤ 12.6V         |          | 0.8   |       | 2     | μA/V              |

# MAX6190–MAX6195/MAX6198

## Precision, Micropower, Low-Dropout Voltage References

### ELECTRICAL CHARACTERISTICS—MAX6192

( $V_{IN} = 5V$ ,  $I_{OUT} = 0nA$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $T_A = +25^{\circ}C$ .)

| PARAMETER                                       | SYMBOL                               | CONDITIONS                                          |          | MIN                    | TYP   | MAX   | UNITS             |
|-------------------------------------------------|--------------------------------------|-----------------------------------------------------|----------|------------------------|-------|-------|-------------------|
| OUTPUT                                          |                                      |                                                     |          |                        |       |       |                   |
| Output Voltage                                  | V <sub>OUT</sub>                     | T <sub>A</sub> = +25°C                              | MAX6192A | 2.498                  | 2.500 | 2.502 | V                 |
|                                                 |                                      |                                                     | MAX6192B | 2.495                  | 2.500 | 2.505 |                   |
|                                                 |                                      |                                                     | MAX6192C | 2.490                  | 2.500 | 2.510 |                   |
| Output-Voltage Temperature Coefficient (Note 1) | TCV <sub>OUT</sub>                   | MAX6192A                                            |          | 2                      |       | 5     | ppm/°C            |
|                                                 |                                      | MAX6192B                                            |          | 4                      |       | 10    |                   |
|                                                 |                                      | MAX6192C                                            |          | 8                      |       | 25    |                   |
| Line Regulation                                 | ΔV <sub>OUT</sub> /ΔV <sub>IN</sub>  | (V <sub>OUT</sub> + 0.2V) ≤ V <sub>IN</sub> ≤ 12.6V |          | 15                     |       | 140   | μV/V              |
| Load Regulation                                 | ΔV <sub>OUT</sub> /ΔI <sub>OUT</sub> | Sourcing: 0 ≤ I <sub>OUT</sub> ≤ 500μA              |          | 0.14                   |       | 0.60  | μV/μA             |
|                                                 |                                      | Sinking: -500μA ≤ I <sub>OUT</sub> ≤ 0              |          | 0.18                   |       | 0.80  |                   |
| Dropout Voltage (Note 4)                        | V <sub>IN</sub> - V <sub>OUT</sub>   | ΔV <sub>OUT</sub> ≤ 0.2%, I <sub>OUT</sub> = 500μA  |          | 100                    |       | 200   | mV                |
| Short-Circuit Current                           | I <sub>SC</sub>                      | Short to GND                                        |          | 4                      |       |       | mA                |
|                                                 |                                      | Short to I <sub>N</sub>                             |          | 4                      |       |       |                   |
| Temperature Hysteresis (Note 2)                 | ΔV <sub>OUT</sub> /cycle             |                                                     |          | 75                     |       |       | ppm               |
| Long-Term Stability                             | ΔV <sub>OUT</sub> /time              | 1000hrs at +25°C                                    |          | 50                     |       |       | ppm/1000hrs       |
| DYNAMIC                                         |                                      |                                                     |          |                        |       |       |                   |
| Noise Voltage                                   | e <sub>OUT</sub>                     | 0.1Hz to 10Hz                                       |          | 60                     |       |       | μV <sub>P-P</sub> |
|                                                 |                                      | 10Hz to 10kHz                                       |          | 125                    |       |       | μV <sub>RMS</sub> |
| Ripple Rejection                                | V <sub>OUT</sub> /V <sub>IN</sub>    | V <sub>IN</sub> = 5V ±100mV, f = 120Hz              |          | 82                     |       |       | dB                |
| Turn-On Settling Time                           | t <sub>R</sub>                       | To 0.1%, C <sub>OUT</sub> = 50pF                    |          | 85                     |       |       | μs                |
| Capacitive-Load Stability Range                 | C <sub>OUT</sub>                     | (Note 3)                                            |          | 0                      |       | 2.2   | nF                |
| INPUT                                           |                                      |                                                     |          |                        |       |       |                   |
| Supply Voltage Range                            | V <sub>IN</sub>                      | Guaranteed by line-regulation test                  |          | V <sub>OUT</sub> + 0.2 |       | 12.6  | V                 |
| Quiescent Supply Current                        | I <sub>IN</sub>                      |                                                     |          | 27                     |       | 35    | μA                |
| Change in Supply Current                        | I <sub>IN</sub> /V <sub>IN</sub>     | (V <sub>OUT</sub> + 0.2V) ≤ V <sub>IN</sub> ≤ 12.6V |          | 0.8                    |       | 2     | μA/V              |

# MAX6190–MAX6195/MAX6198

## Precision, Micropower, Low-Dropout Voltage References

### ELECTRICAL CHARACTERISTICS—MAX6193

( $V_{IN} = 5V$ ,  $I_{OUT} = 0nA$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $T_A = +25^{\circ}C$ .)

| PARAMETER                                       | SYMBOL                               | CONDITIONS                                          |                        | MIN   | TYP   | MAX               | UNITS |
|-------------------------------------------------|--------------------------------------|-----------------------------------------------------|------------------------|-------|-------|-------------------|-------|
| OUTPUT                                          |                                      |                                                     |                        |       |       |                   |       |
| Output Voltage                                  | V <sub>OUT</sub>                     | T <sub>A</sub> = +25°C                              | MAX6193A               | 2.998 | 3.000 | 3.002             | V     |
|                                                 |                                      |                                                     | MAX6193B               | 2.995 | 3.000 | 3.005             |       |
|                                                 |                                      |                                                     | MAX6193C               | 2.990 | 3.000 | 3.010             |       |
| Output-Voltage Temperature Coefficient (Note 1) | TCV <sub>OUT</sub>                   | MAX6193A                                            | 2                      |       | 5     | ppm/°C            |       |
|                                                 |                                      | MAX6193B                                            | 4                      |       | 10    |                   |       |
|                                                 |                                      | MAX6193C                                            | 8                      |       | 25    |                   |       |
| Line Regulation                                 | ΔV <sub>OUT</sub> /ΔV <sub>IN</sub>  | 2.5V ≤ V <sub>IN</sub> ≤ 12.6V                      | 20                     |       | 150   | μV/V              |       |
| Load Regulation                                 | ΔV <sub>OUT</sub> /ΔI <sub>OUT</sub> | Sourcing: 0 ≤ I <sub>OUT</sub> ≤ 500μA              | 0.14                   |       | 0.60  | μV/μA             |       |
|                                                 |                                      | Sinking: -500μA ≤ I <sub>OUT</sub> ≤ 0              | 0.18                   |       | 0.80  |                   |       |
| Dropout Voltage (Note 4)                        | V <sub>IN</sub> - V <sub>OUT</sub>   | I <sub>OUT</sub> = 500μA                            | 100                    |       | 200   | mV                |       |
| Short-Circuit Current                           | I <sub>SC</sub>                      | Short to GND                                        | 4                      |       |       | mA                |       |
|                                                 |                                      | Short to IN                                         | 4                      |       |       |                   |       |
| Temperature Hysteresis (Note 2)                 | ΔV <sub>OUT</sub> /cycle             |                                                     | 75                     |       |       | ppm               |       |
| Long-Term Stability                             | ΔV <sub>OUT</sub> /time              | 1000hrs at +25°C                                    | 50                     |       |       | ppm/1000hrs       |       |
| DYNAMIC                                         |                                      |                                                     |                        |       |       |                   |       |
| Noise Voltage                                   | e <sub>OUT</sub>                     | 0.1Hz to 10Hz                                       | 75                     |       |       | μV <sub>P-P</sub> |       |
|                                                 |                                      | 10Hz to 10kHz                                       | 150                    |       |       | μV <sub>RMS</sub> |       |
| Ripple Rejection                                | V <sub>OUT</sub> /V <sub>IN</sub>    | V <sub>IN</sub> = 5V ±100mV, f = 120Hz              | 80                     |       |       | dB                |       |
| Turn-On Settling Time                           | t <sub>R</sub>                       | To 0.1%, C <sub>OUT</sub> = 50pF                    | 100                    |       |       | μs                |       |
| Capacitive-Load Stability Range                 | C <sub>OUT</sub>                     | (Note 3)                                            | 0                      |       | 2.2   | nF                |       |
| INPUT                                           |                                      |                                                     |                        |       |       |                   |       |
| Supply Voltage Range                            | V <sub>IN</sub>                      | Guaranteed by line-regulation test                  | V <sub>OUT</sub> + 0.2 |       | 12.6  | V                 |       |
| Quiescent Supply Current                        | I <sub>IN</sub>                      |                                                     | 27                     |       | 35    | μA                |       |
| Change in Supply Current                        | I <sub>IN</sub> /V <sub>IN</sub>     | (V <sub>OUT</sub> + 0.2V) ≤ V <sub>IN</sub> ≤ 12.6V | 0.8                    |       | 2     | μA/V              |       |

# MAX6190–MAX6195/MAX6198

## Precision, Micropower, Low-Dropout Voltage References

### ELECTRICAL CHARACTERISTICS—MAX6194

( $V_{IN} = 5V$ ,  $I_{OUT} = 0nA$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $T_A = +25^{\circ}C$ .)

| PARAMETER                                       | SYMBOL                               | CONDITIONS                                          |          | MIN                    | TYP   | MAX   | UNITS             |
|-------------------------------------------------|--------------------------------------|-----------------------------------------------------|----------|------------------------|-------|-------|-------------------|
| INPUT                                           |                                      |                                                     |          |                        |       |       |                   |
| Output Voltage                                  | V <sub>OUT</sub>                     | T <sub>A</sub> = +25°C                              | MAX6194A | 4.498                  | 4.500 | 4.502 | V                 |
|                                                 |                                      |                                                     | MAX6194B | 4.495                  | 4.500 | 4.505 |                   |
|                                                 |                                      |                                                     | MAX6194C | 4.490                  | 4.500 | 4.510 |                   |
| Output-Voltage Temperature Coefficient (Note 1) | TCV <sub>OUT</sub>                   | MAX6194A                                            |          | 2                      |       | 5     | ppm/°C            |
|                                                 |                                      | MAX6194B                                            |          | 4                      |       | 10    |                   |
|                                                 |                                      | MAX6194C                                            |          | 8                      |       | 25    |                   |
| Line Regulation                                 | ΔV <sub>OUT</sub> /ΔV <sub>IN</sub>  | (V <sub>OUT</sub> + 0.2V) ≤ V <sub>IN</sub> ≤ 12.6V |          | 25                     |       | 160   | μV/V              |
| Load Regulation                                 | ΔV <sub>OUT</sub> /ΔI <sub>OUT</sub> | Sourcing: 0 ≤ I <sub>OUT</sub> ≤ 500μA              |          | 0.16                   |       | 0.80  | μV/μA             |
|                                                 |                                      | Sinking: -500μA ≤ I <sub>OUT</sub> ≤ 0              |          | 0.22                   |       | 1.00  |                   |
| Dropout Voltage (Note 4)                        | V <sub>IN</sub> - V <sub>OUT</sub>   | ΔV <sub>OUT</sub> ≤ 0.2%, I <sub>OUT</sub> = 500μA  |          | 100                    |       | 200   | mV                |
| Short-Circuit Current                           | I <sub>SC</sub>                      | Short to GND                                        |          | 4                      |       |       | mA                |
|                                                 |                                      | Short to I <sub>N</sub>                             |          | 4                      |       |       |                   |
| Temperature Hysteresis (Note 2)                 | ΔV <sub>OUT</sub> /cycle             |                                                     |          | 75                     |       |       | ppm               |
| Long-Term Stability                             | ΔV <sub>OUT</sub> /time              | 1000hrs at +25°C                                    |          | 50                     |       |       | ppm/1000hrs       |
| DYNAMIC                                         |                                      |                                                     |          |                        |       |       |                   |
| Noise Voltage                                   | e <sub>OUT</sub>                     | 0.1Hz to 10Hz                                       |          | 110                    |       |       | μV <sub>P-P</sub> |
|                                                 |                                      | 10Hz to 10kHz                                       |          | 215                    |       |       | μV <sub>RMS</sub> |
| Ripple Rejection                                | V <sub>OUT</sub> /V <sub>IN</sub>    | V <sub>IN</sub> = 5V ±100mV, f = 120Hz              |          | 76                     |       |       | dB                |
| Turn-On Settling Time                           | t <sub>R</sub>                       | To 0.1%, C <sub>OUT</sub> = 50pF                    |          | 180                    |       |       | μs                |
| Capacitive-Load Stability Range                 | C <sub>OUT</sub>                     | (Note 3)                                            |          | 0                      |       | 2.2   | nF                |
| OUTPUT                                          |                                      |                                                     |          |                        |       |       |                   |
| Supply Voltage Range                            | V <sub>IN</sub>                      | Guaranteed by line-regulation test                  |          | V <sub>OUT</sub> + 0.2 |       | 12.6  | V                 |
| Quiescent Supply Current                        | I <sub>IN</sub>                      |                                                     |          | 27                     |       | 35    | μA                |
| Change in Supply Current                        | I <sub>IN</sub> /V <sub>IN</sub>     | (V <sub>OUT</sub> + 0.2V) ≤ V <sub>IN</sub> ≤ 12.6V |          | 0.8                    |       | 2     | μA/V              |

# MAX6190–MAX6195/MAX6198

## Precision, Micropower, Low-Dropout Voltage References

### ELECTRICAL CHARACTERISTICS—MAX6195

( $V_{IN} = 5.5V$ ,  $I_{OUT} = 0nA$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $T_A = +25^{\circ}C$ .)

| PARAMETER                                       | SYMBOL                               | CONDITIONS                                          |          | MIN                    | TYP   | MAX   | UNITS             |
|-------------------------------------------------|--------------------------------------|-----------------------------------------------------|----------|------------------------|-------|-------|-------------------|
| INPUT                                           |                                      |                                                     |          |                        |       |       |                   |
| Output Voltage                                  | V <sub>OUT</sub>                     | T <sub>A</sub> = +25°C                              | MAX6195A | 4.998                  | 5.000 | 5.002 | V                 |
|                                                 |                                      |                                                     | MAX6195B | 4.995                  | 5.000 | 5.005 |                   |
|                                                 |                                      |                                                     | MAX6195C | 4.990                  | 5.000 | 5.010 |                   |
| Output-Voltage Temperature Coefficient (Note 1) | TCV <sub>OUT</sub>                   | MAX6195A                                            |          | 2                      |       | 5     | ppm/°C            |
|                                                 |                                      | MAX6195B                                            |          | 4                      |       | 10    |                   |
|                                                 |                                      | MAX6195C                                            |          | 8                      |       | 25    |                   |
| Line Regulation                                 | ΔV <sub>OUT</sub> /ΔV <sub>IN</sub>  | (V <sub>OUT</sub> + 0.2V) ≤ V <sub>IN</sub> ≤ 12.6V |          | 25                     |       | 160   | μV/V              |
| Load Regulation                                 | ΔV <sub>OUT</sub> /ΔI <sub>OUT</sub> | Sourcing: 0 ≤ I <sub>OUT</sub> ≤ 500μA              |          | 0.17                   |       | 0.85  | μV/μA             |
|                                                 |                                      | Sinking: -500μA ≤ I <sub>OUT</sub> ≤ 0              |          | 0.24                   |       | 1.10  |                   |
| Dropout Voltage (Note 4)                        | V <sub>IN</sub> - V <sub>OUT</sub>   | ΔV <sub>OUT</sub> ≤ 0.2%, I <sub>OUT</sub> = 500μA  |          | 100                    |       | 200   | mA                |
| Short-Circuit Current                           | I <sub>SC</sub>                      | Short to GND                                        |          | 4                      |       |       | mA                |
|                                                 |                                      | Short to I <sub>N</sub>                             |          | 4                      |       |       |                   |
| Temperature Hysteresis (Note 2)                 | ΔV <sub>OUT</sub> /cycle             |                                                     |          | 75                     |       |       | ppm               |
| Long-Term Stability                             | ΔV <sub>OUT</sub> /time              | 1000hrs at +25°C                                    |          | 50                     |       |       | ppm/1000hrs       |
| DYNAMIC                                         |                                      |                                                     |          |                        |       |       |                   |
| Noise Voltage                                   | e <sub>OUT</sub>                     | 0.1Hz to 10Hz                                       |          | 120                    |       |       | μV <sub>P-P</sub> |
|                                                 |                                      | 10Hz to 10kHz                                       |          | 240                    |       |       | μV <sub>RMS</sub> |
| Ripple Rejection                                | V <sub>OUT</sub> /V <sub>IN</sub>    | V <sub>IN</sub> = 5.5V ±100mV, f = 120Hz            |          | 72                     |       |       | dB                |
| Turn-On Settling Time                           | t <sub>R</sub>                       | To 0.1%, C <sub>OUT</sub> = 50pF                    |          | 220                    |       |       | μs                |
| Capacitive-Load Stability Range                 | C <sub>OUT</sub>                     | (Note 3)                                            |          | 0                      |       | 2.2   | nF                |
| OUTPUT                                          |                                      |                                                     |          |                        |       |       |                   |
| Supply Voltage Range                            | V <sub>IN</sub>                      | Guaranteed by line-regulation test                  |          | V <sub>OUT</sub> + 0.2 |       | 12.6  | V                 |
| Quiescent Supply Current                        | I <sub>IN</sub>                      |                                                     |          | 27                     |       | 35    | μA                |
| Change in Supply Current                        | I <sub>IN</sub> /V <sub>IN</sub>     | (V <sub>OUT</sub> + 0.2V) ≤ V <sub>IN</sub> ≤ 12.6V |          | 0.8                    |       | 2     | μA/V              |

# MAX6190–MAX6195/MAX6198

## Precision, Micropower, Low-Dropout Voltage References

### ELECTRICAL CHARACTERISTICS—MAX6198

( $V_{IN} = 5V$ ,  $I_{OUT} = 0nA$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $T_A = +25^{\circ}C$ .)

| PARAMETER                                       | SYMBOL                               | CONDITIONS                                          |          | MIN                    | TYP   | MAX   | UNITS             |
|-------------------------------------------------|--------------------------------------|-----------------------------------------------------|----------|------------------------|-------|-------|-------------------|
| OUTPUT                                          |                                      |                                                     |          |                        |       |       |                   |
| Output Voltage                                  | V <sub>OUT</sub>                     | T <sub>A</sub> = +25°C                              | MAX6198A | 4.094                  | 4.096 | 4.098 | V                 |
|                                                 |                                      |                                                     | MAX6198B | 4.091                  | 4.096 | 4.101 |                   |
|                                                 |                                      |                                                     | MAX6198C | 4.086                  | 4.096 | 4.106 |                   |
| Output-Voltage Temperature Coefficient (Note 1) | TCV <sub>OUT</sub>                   | MAX6198A                                            |          | 2                      |       | 5     | ppm/°C            |
|                                                 |                                      | MAX6198B                                            |          | 4                      |       | 10    |                   |
|                                                 |                                      | MAX6198C                                            |          | 8                      |       | 25    |                   |
| Line Regulation                                 | ΔV <sub>OUT</sub> /ΔV <sub>IN</sub>  | (V <sub>OUT</sub> + 0.2V) ≤ V <sub>IN</sub> ≤ 12.6V |          | 25                     |       | 160   | μV/V              |
| Load Regulation                                 | ΔV <sub>OUT</sub> /ΔI <sub>OUT</sub> | Sourcing: 0 ≤ I <sub>OUT</sub> ≤ 500μA              |          | 0.15                   |       | 0.70  | μV/μA             |
|                                                 |                                      | Sinking: -500μA ≤ I <sub>OUT</sub> ≤ 0              |          | 0.20                   |       | 0.90  |                   |
| Dropout Voltage (Note 4)                        | V <sub>IN</sub> - V <sub>OUT</sub>   | ΔV <sub>OUT</sub> ≤ 0.2%, I <sub>OUT</sub> = 500μA  |          | 100                    |       | 200   | mV                |
| Short-Circuit Current                           | I <sub>SC</sub>                      | Short to GND                                        |          | 4                      |       |       | mA                |
|                                                 |                                      | Short to I <sub>N</sub>                             |          | 4                      |       |       |                   |
| Temperature Hysteresis (Note 2)                 | ΔV <sub>OUT</sub> /cycle             |                                                     |          | 75                     |       |       | ppm               |
| Long-Term Stability                             | ΔV <sub>OUT</sub> /time              | 1000hrs at +25°C                                    |          | 50                     |       |       | ppm/1000hrs       |
| DYNAMIC                                         |                                      |                                                     |          |                        |       |       |                   |
| Noise Voltage                                   | e <sub>OUT</sub>                     | 0.1Hz to 10Hz                                       |          | 100                    |       |       | μV <sub>P-P</sub> |
|                                                 |                                      | 10Hz to 10kHz                                       |          | 200                    |       |       | μV <sub>RMS</sub> |
| Ripple Rejection                                | V <sub>OUT</sub> /V <sub>IN</sub>    | V <sub>IN</sub> = 5V ±100mV, f = 120Hz              |          | 77                     |       |       | dB                |
| Turn-On Settling Time                           | t <sub>R</sub>                       | To 0.1%, C <sub>OUT</sub> = 50pF                    |          | 160                    |       |       | μs                |
| Capacitive-Load Stability Range                 | C <sub>OUT</sub>                     | (Note 3)                                            |          | 0                      |       | 2.2   | nF                |
| INPUT                                           |                                      |                                                     |          |                        |       |       |                   |
| Supply Voltage Range                            | V <sub>IN</sub>                      | Guaranteed by line-regulation test                  |          | V <sub>OUT</sub> + 0.2 |       | 12.6  | V                 |
| Quiescent Supply Current                        | I <sub>IN</sub>                      |                                                     |          | 27                     |       | 35    | μA                |
| Change in Supply Current                        | I <sub>IN</sub> /V <sub>IN</sub>     | (V <sub>OUT</sub> + 0.2V) ≤ V <sub>IN</sub> ≤ 12.6V |          | 0.8                    |       | 2     | μA/V              |

**Note 1:** Temperature Coefficient is measured by the “box” method; i.e., the maximum  $\Delta V_{OUT}$  is divided by the maximum  $\Delta t$ .

**Note 2:** Thermal Hysteresis is defined as the change in  $+25^{\circ}C$  output voltage before and after cycling the device from  $T_{MIN}$  to  $T_{MAX}$ .

**Note 3:** Not production tested. Guaranteed by design.

**Note 4:** Dropout voltage is the minimum input voltage at which  $V_{OUT}$  changes  $\leq 0.2\%$  from  $V_{OUT}$  at  $V_{IN} = 5.0V$  ( $V_{IN} = 5.5V$  for MAX6195).


# MAX6190–MAX6195/MAX6198

## Precision, Micropower, Low-Dropout Voltage References


### Typical Operating Characteristics

( $V_{IN} = 5V$  for MAX6190/1/2/3/4/8,  $V_{IN} = 5.5V$  for MAX6195;  $I_{OUT} = 0nA$ ;  $T_A = +25^\circ C$ ; unless otherwise noted.) (Note 5)


**MAX6190  
OUTPUT VOLTAGE  
TEMPERATURE DRIFT**




**MAX6195  
OUTPUT VOLTAGE  
TEMPERATURE DRIFT**




**MAX6195  
LONG-TERM DRIFT**




**MAX6190  
LINE REGULATION**




**MAX6195  
LINE REGULATION**




**MAX6192/MAX6193  
DROPOUT VOLTAGE  
vs. SOURCE CURRENT**




**MAX6190  
LOAD REGULATION**



**MAX6195  
LOAD REGULATION**



**MAX6194/MAX6195/MAX6198  
DROPOUT VOLTAGE  
vs. SOURCE CURRENT**












# MAX6190–MAX6195/MAX6198

## Precision, Micropower, Low-Dropout Voltage References

### Typical Operating Characteristics (continued)

( $V_{IN} = 5V$  for MAX6190/1/2/3/4/8,  $V_{IN} = 5.5V$  for MAX6195;  $I_{OUT} = 0nA$ ;  $T_A = +25^\circ C$ ; unless otherwise noted.) (Note 5)




# MAX6190–MAX6195/MAX6198

## Precision, Micropower, Low-Dropout Voltage References


### Typical Operating Characteristics (continued)

( $V_{IN} = 5V$  for MAX6190/1/2/3/4/8,  $V_{IN} = 5.5V$  for MAX6195;  $I_{OUT} = 0nA$ ;  $T_A = +25^{\circ}C$ ; unless otherwise noted.) (Note 5)


**MAX6190**  
**LOAD-TRANSIENT RESPONSE**




**MAX6195**  
**LOAD-TRANSIENT RESPONSE**




**MAX6195**  
**TURN-ON TRANSIENT**




**MAX6190**  
**LOAD-TRANSIENT RESPONSE**




**MAX6195**  
**LOAD-TRANSIENT RESPONSE**



**MAX6190**  
**LINE-TRANSIENT RESPONSE**



**MAX6195**  
**LINE-TRANSIENT RESPONSE**



**Note 5:** Many of the *Typical Operating Characteristics* of the MAX6190 family are extremely similar. The extremes of these characteristics are found in the MAX6190 (1.2V output) and the MAX6195 (5.0V output) devices. The *Typical Operating Characteristics* of the remainder of the MAX6190 family typically lie between these two extremes and can be estimated based on their output voltage.

# MAX6190–MAX6195/MAX6198

## Precision, Micropower, Low-Dropout Voltage References

### Pin Description

| PIN           | NAME | FUNCTION                                 |
|---------------|------|------------------------------------------|
| 1, 3, 5, 7, 8 | N.C. | No Connection. Not internally connected. |
| 2             | IN   | Supply Voltage Input                     |
| 4             | GND  | Ground                                   |
| 6             | OUT  | Reference Voltage Output                 |

### Detailed Description

The MAX6190–MAX6195/MAX6198 precision bandgap references use a proprietary curvature-correction circuit and laser-trimmed thin-film resistors, resulting in a low temperature coefficient of  $<5\text{ppm}/^{\circ}\text{C}$  and initial accuracy of better than 0.1%. These devices can sink and source up to  $500\mu\text{A}$  with  $<200\text{mV}$  of dropout voltage, making them attractive for use in low-voltage applications.

### Applications Information

#### Output/Load Capacitance

Devices in this family do not require an output capacitance for frequency stability. They are stable for capacitive loads from 0 to  $2.2\text{nF}$ . However, in applications where the load or the supply can experience step changes, an output capacitor will reduce the amount of overshoot (or undershoot) and assist the circuit's transient response. Many applications do not need an external capacitor, and this family can offer a significant advantage in these applications when board space is critical.

#### Supply Current

The quiescent supply current of these series-mode references is a maximum of  $35\mu\text{A}$  and is virtually independent of the supply voltage, with only a  $0.8\mu\text{A/V}$  variation with supply voltage. Unlike series references, shunt-mode references operate with a series resistor connected to the power supply. The quiescent current of a shunt-mode reference is thus a function of the input

voltage. Additionally, shunt-mode references have to be biased at the maximum expected load current, even if the load current is not present all the time. In the series-mode MAX6190 family, the load current is drawn from the input voltage only when required, so supply current is not wasted and efficiency is maximized at all input voltages. This improved efficiency can help reduce power dissipation and extend battery life.

When the supply voltage is below the minimum specified input voltage (as during turn-on), the devices can draw up to  $200\mu\text{A}$  beyond the nominal supply current. The input voltage source must be capable of providing this current to ensure reliable turn-on.

#### Output Voltage Hysteresis

Output voltage hysteresis is the change in the output voltage at  $T_A = +25^{\circ}\text{C}$  before and after the device is cycled over its entire operating temperature range. Hysteresis is caused by differential package stress appearing across the bandgap core transistors. The typical temperature hysteresis value is  $75\text{ppm}$ .

#### Turn-On Time

These devices typically turn on and settle to within 0.1% of their final value in  $30\mu\text{s}$  to  $220\mu\text{s}$ , depending on the device. The turn-on time can increase up to  $1.5\text{ms}$  with the device operating at the minimum dropout voltage and the maximum load.

#### Positive and Negative Low-Power Voltage Reference

Figure 1 shows a typical method for developing a bipolar reference. The circuit uses a MAX681 voltage doubler/inverter charge-pump converter to power an ICL7652, thus creating a positive as well as a negative reference voltage.

# MAX6190–MAX6195/MAX6198

## Precision, Micropower, Low-Dropout Voltage References




Figure 1. Positive and Negative References from Single 3V or 5V Supply

### Ordering Information (continued)

| PART                 | TEMP RANGE     | PIN-PACKAGE |
|----------------------|----------------|-------------|
| <b>MAX6193</b> AESA+ | -40°C to +85°C | 8 SO        |
| MAX6193BESA+         | -40°C to +85°C | 8 SO        |
| MAX6193CESA+         | -40°C to +85°C | 8 SO        |
| <b>MAX6194</b> AESA+ | -40°C to +85°C | 8 SO        |
| MAX6194BESA+         | -40°C to +85°C | 8 SO        |
| MAX6194CESA+         | -40°C to +85°C | 8 SO        |
| <b>MAX6195</b> AESA+ | -40°C to +85°C | 8 SO        |
| MAX6195BESA+         | -40°C to +85°C | 8 SO        |
| MAX6195CESA+         | -40°C to +85°C | 8 SO        |
| <b>MAX6198</b> AESA+ | -40°C to +85°C | 8 SO        |
| MAX6198BESA+         | -40°C to +85°C | 8 SO        |
| MAX6198CESA+         | -40°C to +85°C | 8 SO        |
| MAX6198AESA/V+       | -40°C to +85°C | 8 SO        |


+Denotes a lead(Pb)-free /RoHS-compliant package.

/V denotes an automotive qualified part.

### Chip Information

PROCESS: BiCMOS

### Typical Operating Circuit



### Package Information

For the latest package outline information and land patterns (footprints), go to [www.maximintegrated.com/packages](http://www.maximintegrated.com/packages). Note that a "+", "#", or "-" in the package code indicates RoHS status only. Package drawings may show a different suffix character, but the drawing pertains to the package regardless of RoHS status.

| PACKAGE TYPE | PACKAGE CODE | OUTLINE NO.             | LAND PATTERN NO.        |
|--------------|--------------|-------------------------|-------------------------|
| 8 SO         | S8+2         | <a href="#">21-0041</a> | <a href="#">90-0096</a> |

# **MAX6190–MAX6195/MAX6198**

## **Precision, Micropower, Low-Dropout Voltage References**

---

### **Revision History**

| REVISION<br>NUMBER | REVISION<br>DATE | DESCRIPTION                                                                      | PAGES<br>CHANGED |
|--------------------|------------------|----------------------------------------------------------------------------------|------------------|
| 3                  | 4/10             | Added automotive grade part, added lead-free information, and made style changes | 1–14             |



Maxim Integrated cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim Integrated product. No circuit patent licenses are implied. Maxim Integrated reserves the right to change the circuitry and specifications without notice at any time. The parametric values (min and max limits) shown in the Electrical Characteristics table are guaranteed. Other parametric values quoted in this data sheet are provided for guidance.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9