

# Glass Encapsulated TransGuard® Automotive Series



## Multilayer Varistors for Automotive Applications



### GENERAL DESCRIPTION

The Glass Encapsulated TransGuard® Automotive Series are zinc oxide (ZnO) based ceramic semiconductor devices with non-linear, bi-directional voltage-current characteristics.

They have the advantage of offering bi-directional overvoltage protection as well as EMI/RFI attenuation in a single SMT package. The Automotive Series high current and high energy handling capability make them well suited for protection against automotive related transients.

These large case size parts extend TransGuard range into high energy applications. In addition the glass encapsulation provides enhanced resistance against harsh environment or process such as acidic environment, salts or chlorite flux.

### GENERAL CHARACTERISTICS

- Operating Temperature: -55°C to 125°C
- Case Size: 1206-2200
- Working Voltage: 16-65Vdc
- Energy: 07-12J
- Peak Current: 200-2000A

### FEATURES

- High Reliability
- High Energy Absorption (Load Dump)
- High Current Handling
- Bi-Directional protection
- EMI/RFI attenuation in off-state
- Multi-strike capability
- Sub 1nS response to ESD strike
- AEC Q200 Qualified

### APPLICATIONS

- Various Automotive Applications
- Internal Combustion Engine (ICE) Vehicles
- Hybrid Electric Vehicles (HEV)
- Plug-in Hybrid Electric Vehicles (PHEV)
- Commercial Vehicles
- Sensors
- LIN BUS
- ECU
- DC Motor
- Relays
- and more
- Applications where Glass Encapsulation is needed for Harsh Environment/Acid-Resistance

### HOW TO ORDER

|                           |   |                                     |   |   |   |  |  |  |
|---------------------------|---|-------------------------------------|---|---|---|--|--|--|
| <b>V</b><br>↓<br>Varistor | <b>G</b><br>↓<br>Glass Encapsulate Chip | <b>AS</b><br>↓<br>Automotive Series | <b>1812</b><br>↓<br>Chip Size<br>1206<br>1210<br>1812<br>2220 | <b>16</b><br>↓<br>Working Voltage<br>16 = 16Vdc<br>18 = 18Vdc<br>26 = 26Vdc<br>30 = 30Vdc<br>31 = 31Vdc<br>34 = 34Vdc<br>42 = 42Vdc<br>48 = 48Vdc<br>60 = 60Vdc<br>65 = 65Vdc | <b>P</b><br>↓<br>Energy Rating<br>F = 0.7J<br>H = 1.2J<br>J = 1.6J<br>S = 2.0J<br>P = 2.5-3.7J<br>U = 4.0-5.0J<br>Y = 6.5-12J | <b>400</b><br>↓<br>Clamping Voltage<br>390 = 40V<br>400 = 42V<br>440 = 44V<br>540 = 54V<br>560 = 60V<br>570 = 57V<br>650 = 65V<br>770 = 77V<br>900 = 90V<br>101 = 100V<br>121 = 120V<br>131 = 135V | <b>R</b><br>↓<br>Package<br>D = 7" reel<br>R = 7" reel<br>T = 13" reel | <b>P</b><br>↓<br>Termination<br>P = Ni/Sn plated |
|---------------------------|---|-------------------------------------|---|---|---|--|--|--|

### PHYSICAL DIMENSIONS: mm (inches)

| Size (EIA) | Length (L)                 | Width (W)                  | Max Thickness (T) | Land Length (t)           |
|------------|----------------------------|----------------------------|-------------------|---------------------------|
| 1206       | 3.20±0.20<br>(0.126±0.008) | 1.60±0.20<br>(0.063±0.008) | 1.70<br>(0.067)   | 0.94 max.<br>(0.037 max.) |
| 1210       | 3.20±0.20<br>(0.126±0.008) | 2.49±0.20<br>(0.098±0.008) | 1.70<br>(0.067)   | 0.14 max.<br>(0.045 max.) |
| 1812       | 4.50±0.30<br>(0.177±0.012) | 3.20±0.30<br>(0.126±0.012) | 2.00<br>(0.079)   | 1.00 max.<br>(0.040 max.) |
| 2220       | 5.70±0.40<br>(0.224±0.016) | 5.00±0.40<br>(0.197±0.016) | 2.50<br>(0.098)   | 1.00 max.<br>(0.040 max.) |

# Glass Encapsulated TransGuard® Automotive Series



## Multilayer Varistors for Automotive Applications

### ELECTRIAL CHARACTERISTICS

| AVX PN         | V <sub>W</sub> (DC) | V <sub>W</sub> (AC) | V <sub>B</sub> | V <sub>C</sub> | I <sub>Vc</sub> | I <sub>L</sub> | E <sub>T</sub> | E <sub>LD</sub> | I <sub>P</sub> | Cap   | Freq | V <sub>Jump</sub> | P <sub>Diss, MAX</sub> |
|----------------|---------------------|---------------------|----------------|----------------|-----------------|----------------|----------------|-----------------|----------------|-------|------|-------------------|------------------------|
| VGAS120616K390 | 16                  | 11                  | 24.5±10%       | 40             | 1               | 15             | 0.6            | 1.5             | 200            | 1100  | K    | 27.5              | 0.01                   |
| VGAS120616N390 | 16                  | 11                  | 24.5±10%       | 40             | 1               | 15             | 1.1            | 2               | 200            | 1300  | K    | 27.5              | 0.01                   |
| VGAS121016J400 | 16                  | 13                  | 25.5±10%       | 42             | 5               | 15             | 1.6            | 3               | 500            | 2300  | K    | 27.5              | 0.03                   |
| VGAS181216P390 | 16                  | 11                  | 24.5±10%       | 40             | 5               | 15             | 2.9            | 10              | 1000           | 7000  | K    | 27.5              | 0.07                   |
| VGAS181216P400 | 16                  | 11                  | 24.5±10%       | 42             | 5               | 10             | 2.9            | 10              | 1000           | 5000  | K    | 27.5              | 0.07                   |
| VGAS222016Y400 | 16                  | 11                  | 24.5±10%       | 42             | 10              | 10             | 7.2            | 25              | 1500           | 13000 | K    | 25.5              | 0.10                   |
| VGAS120618D400 | 18                  | 13                  | 25.5±10%       | 42             | 1               | 15             | 0.4            | 1.5             | 150            | 1200  | K    | 27.5              | 0.008                  |
| VGAS181218P440 | 18                  | 14                  | 27.5±10%       | 44             | 5               | 15             | 2.9            | 6               | 800            | 5000  | K    | 27.5              | 0.05                   |
| VGAS120626F540 | 26                  | 18                  | 33.0±10%       | 54             | 1               | 15             | 0.7            | 1.5             | 200            | 600   | K    | 27.5              | 0.008                  |
| VGAS121026H560 | 26                  | 18                  | 34.5±10%       | 60             | 5               | 15             | 1.2            | 3               | 300            | 1200  | K    | 27.5              | 0.018                  |
| VGAS181226P570 | 26                  | 23                  | 35.0±10%       | 57             | 5               | 15             | 3.0            | 8               | 600            | 3000  | K    | 30                | 0.015                  |
| VGAS222026Y570 | 26                  | 23                  | 35±10%         | 57             | 10              | 15             | 6.8            | 20              | 1100           | 7000  | K    | 30                | 0.03                   |
| VGAS121030H620 | 30                  | 21                  | 41.0±10%       | 67             | 5               | 15             | 1.2            | 3               | 280            | 1000  | K    | 30                | 0.018                  |
| VGAS181231P650 | 31                  | 25                  | 39.0±10%       | 65             | 5               | 15             | 3.7            | 8               | 800            | 2600  | K    | 30                | 0.06                   |
| VGAS121034S770 | 34                  | 30                  | 47.0±10%       | 77             | 2.5             | 15             | 2              | 3               | 400            | 1000  | K    | 48                | 0.04                   |
| VGAS181234U770 | 34                  | 30                  | 47.0±10%       | 77             | 5               | 15             | 5              | 6.1             | 800            | 1500  | K    | 48                | 0.08                   |
| VGAS222034Y770 | 34                  | 30                  | 47.0±10%       | 77             | 10              | 15             | 12             | 25              | 2000           | 6300  | K    | 48                | 0.24                   |
| VGAS181242U900 | 42                  | 35                  | 56.0±10%       | 90             | 5               | 15             | 4.0            | 6               | 500            | 1800  | K    | 48                | 0.015                  |
| VGAS121048H101 | 48                  | 34                  | 62.0±10%       | 100            | 5               | 15             | 1.2            | -               | 250            | 500   | K    | 48                | 0.022                  |
| VGAS121060J121 | 60                  | 42                  | 76.0±10%       | 120            | 5               | 15             | 1.5            | -               | 250            | 400   | K    | 48                | 0.03                   |
| VGAS121065P131 | 65                  | 50                  | 82.0±10%       | 135            | 2.5             | 15             | 2.7            | -               | 350            | 600   | K    | 48                | 0.05                   |

|                     |   |                   |   |
|---------------------|---|-------------------|---|
| V <sub>W</sub> (DC) | DC Working Voltage [V]                                    | E <sub>T</sub>    | Transient Energy Rating [J, 10x1000µS]  |
| V <sub>W</sub> (AC) | AC Working Voltage [V]                                    | E <sub>LD</sub>   | Load Dump Energy (x10) [J]  |
| V <sub>B</sub>      | Typical Breakdown Voltage [V @ 1mA <sub>Vc</sub> , 25°C]  | I <sub>P</sub>    | Peak Current Rating [A, 8x20µS]   |
| V <sub>C</sub>      | Clamping Voltage [V @ I <sub>Vc</sub> ]                   | Cap               | Typical capacitance [pF] @ frequency specified and 0.5V <sub>VMS</sub> , 25°C, M = 1MHz, K = 1kHz |
| I <sub>Vc</sub>     | Test Current for V <sub>C</sub> [A, 8x20µs]               | V <sub>Jump</sub> | Jump Start [V, 5 min]   |
| I <sub>L</sub>      | Maximum leakage current at the working voltage, 25°C [µA] | P <sub>Diss</sub> | Power Dissipation [W]   |

### AUTOMOTIVE SERIES – LOAD DUMP TEST

#### According to ISO DP7637 rev 2 Pulse 5

#### Automotive Load Dump Pulse (According to ISO 7637 Pulse 5)



When using the test method indicated below, the amount of Energy dissipated by the varistor must not exceed the Load Dump Energy value specified in the product table.

#### 12V SYSTEMS

|                       |      |    |    |
|-----------------------|------|----|----|
| <b>VGAS181216P400</b> | 0.5Ω | 1Ω | 4Ω |
| 100ms                 | 46   | 52 | 72 |
| 200ms                 | 37   | 41 | 59 |
| 400ms                 | 32   | 35 | 51 |
| <b>VGAS222016Y400</b> | 0.5Ω | 1Ω | 4Ω |
| 100ms                 | 53   | 60 | 77 |
| 200ms                 | 50   | 55 | 73 |
| 400ms                 | 47   | 50 | 66 |



## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9