

VOLTAGE-CONTROLLED CRYSTAL OSCILLATOR (VCXO)

OUTPUT : LV-PECL



Product Number (Please contact us)

VG-4513CB: X1G004151xxxxxx

VG-4513CA: X1G004141xxxxxx

VG-4513CB
VG-4513CA

- Frequency range : 100 MHz to 250 MHz
- Supply voltage : 3.3 V
- Absolute pull range : $\pm 30 \times 10^{-6}$ Min, $\pm 50 \times 10^{-6}$ Min, $\pm 100 \times 10^{-6}$ Min
- Function : Output Enable(OE)
Active High or Low
- Output : LV-PECL



VG-4513CB
(5.0 × 3.2 × 1.3 mm)



VG-4513CA
(7.0 × 5.0 × 1.6 mm)

Actual size

VG-4513CB

VG-4513CA

Specifications (characteristics)

Item	Symbol	Specifications	Conditions / Remarks
Output frequency range	f_o	100.000 MHz to 250.000 MHz	Please contact us about available frequencies.
Supply voltage	V_{cc}	3.3 V \pm 0.165 V	
Storage temperature range	T_{stg}	-55 °C to +125 °C	
Operating temperature range	T_{use}	-40 °C to +85 °C	
Current consumption	I_{cc}	65 mA Max.	
Frequency tolerance	f_{tol}	100 MHz $\leq f_o \leq$ 200 MHz : $\pm 50 \times 10^{-6}$ Max. 200 MHz $< f_o \leq$ 250 MHz : $\pm 70 \times 10^{-6}$ Max.	Includes initial tolerance, temperature change, V_{cc} change and 10years aging
Absolute pull range	APR	120 MHz $\leq f_o \leq$ 200 MHz $\pm 30 \times 10^{-6}$ Min. $\pm 50 \times 10^{-6}$ Min. $\pm 100 \times 10^{-6}$ Min. 100 MHz $\leq f_o <$ 120 MHz, 200 MHz $< f_o \leq$ 250 MHz $\pm 30 \times 10^{-6}$ Min. $\pm 50 \times 10^{-6}$ Min.	$V_c = 1.65$ V ± 1.65 V
Input resistance	R_{in}	100 k Ω Min.	DC level
Output load condition	L_{ECL}	50 Ω at V_{cc} -2.0V	
High output voltage	V_{OH}	V_{cc} -1.1 V Min.	
Low output voltage	V_{OL}	V_{cc} -1.5 V Max.	
Symmetry	SYM	40 % to 60 %	at V_{cc} -1.30 V, $V_c=1/2V_{cc}$
Rise/Fall times	t_r/t_f	0.5 ns Max.	at 20 % to 80 % output swing
High input voltage	V_{IH}	70% V_{cc} Min.	
Low input voltage	V_{IL}	30% V_{cc} Max.	
Oscillation start up time	t_{str}	10ms Max.	

Item	Offset frequency	122.88 MHz	153.6 MHz	245.76 MHz
Phase noise (Typical value) APR $\pm 50 \times 10^{-6}$ Min.	10 Hz	-75 dBc/Hz	-70 dBc/Hz	-64 dBc/Hz
	100 Hz	-105 dBc/Hz	-100 dBc/Hz	-94 dBc/Hz
	1 kHz	-129 dBc/Hz	-124 dBc/Hz	-118 dBc/Hz
	10 kHz	-147 dBc/Hz	-143 dBc/Hz	-138 dBc/Hz
	100 kHz	-151 dBc/Hz	-152 dBc/Hz	-149 dBc/Hz

Product Name **VG-4513 CA - 122.880000 - G F C T**

(Standard form) ① ② ③ ④⑤⑥⑦

①Model ②Package type ③Frequency(MHz) ④Operating temperature range ⑤Absolute pull range

⑥Supply voltage (C: 3.3V Typ.) ⑦OE function

④Operating temperature	
G	-40 to +85°C
J	-20 to +70°C
K	0 to +70°C


⑤Absolute pull range	
H*	$\pm 100 \times 10^{-6}$ Min.
G	$\pm 50 \times 10^{-6}$ Min.
F	$\pm 30 \times 10^{-6}$ Min.

⑦OE function	
T	Active High
L	Active Low

*Only 120 MHz $\leq f_o \leq$ 200 MHz are available.


External dimensions

(Unit : mm)



Footprint (Recommended)

(Unit : mm)



PROMOTION OF ENVIRONMENTAL MANAGEMENT SYSTEM CONFORMING TO INTERNATIONAL STANDARDS

At Seiko Epson, all environmental initiatives operate under the Plan-Do-Check-Action (PDCA) cycle designed to achieve continuous improvements. The environmental management system (EMS) operates under the ISO 14001 environmental management standard.

All of our major manufacturing and non-manufacturing sites, in Japan and overseas, completed the acquisition of ISO 14001 certification.

ISO 14000 is an international standard for environmental management that was established by the International Standards Organization in 1996 against the background of growing concern regarding global warming, destruction of the ozone layer, and global deforestation.

WORKING FOR HIGH QUALITY

In order provide high quality and reliable products and services than meet customer needs,

Seiko Epson made early efforts towards obtaining ISO9000 series certification and has acquired ISO9001 for all business establishments in Japan and abroad. We have also acquired ISO/TS 16949 certification that is requested strongly by major automotive manufacturers as standard.

ISO/TS16949 is the international standard that added the sector-specific supplemental requirements for automotive industry based on ISO9001.

► Explanation of the mark that are using it for the catalog

	► Pb free.
	► Complies with EU RoHS directive. *About the products without the Pb-free mark. Contains Pb in products exempted by EU RoHS directive. (Contains Pb in sealing glass, high melting temperature type solder or other.)
	► Designed for automotive applications such as Car Multimedia, Body Electronics, Remote Keyless Entry etc.
	► Designed for automotive applications related to driving safety (Engine Control Unit, Air Bag, ESC etc).

Notice

- This material is subject to change without notice.
- Any part of this material may not be reproduced or duplicated in any form or any means without the written permission of Seiko Epson.
- The information about applied data, circuitry, software, usage, etc. written in this material is intended for reference only. Seiko Epson does not assume any liability for the occurrence of customer damage or infringing on any patent or copyright of a third party. This material does not authorize the licensing for any patent or intellectual copyrights.
- When exporting the products or technology described in this material, you should comply with the applicable export control laws and regulations and follow the procedures required by such laws and regulations.
- You are requested not to use the products (and any technical information furnished, if any) for the development and/or manufacture of weapon of mass destruction or for other military purposes. You are also requested that you would not make the products available to any third party who may use the products for such prohibited purposes.
- These products are intended for general use in electronic equipment. When using them in specific applications that require extremely high reliability, such as the applications stated below, you must obtain permission from Seiko Epson in advance.
/ Space equipment (artificial satellites, rockets, etc.) / Transportation vehicles and related (automobiles, aircraft, trains, vessels, etc.) / Medical instruments to sustain life / Submarine transmitters / Power stations and related / Fire work equipment and security equipment / traffic control equipment / and others requiring equivalent reliability.
- All brands or product names mentioned herein are trademarks and/or registered trademarks of their respective.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Epson:

[VG-4513CA 122.8800M-GGCT3](#) [VG-4513CB 122.8800M-GGCT3](#) [VG-4513CB 250.0000M-GGCT](#) [VG-4513CA 156.2500M-GGCT3](#) [VG-4513CA 125.0000M-GGCT3](#) [VG-4513CB 125.0000M-GGCT3](#) [VG-4513CB 156.2500M-GGCT3](#) [VG-4513CA 120.0000M-GGCT3](#) [VG-4513CA 120.0000M-GGCTX](#) [VG-4513CA 130.0000M-GGCT](#) [VG-4513CA 200.0000M-GFCL](#) [VG-4513CA 250.0000M-GFCTX](#) [VG-4513CA 245.7600M-GGCT](#) [VG-4513CB 100.0000M-GGCT](#) [VG-4513CB 122.8800M-GGCT](#) [VG-4513CB 156.2500M-GGCT](#) [VG-4513CB 122.8800M-GGCTX](#) [VG-4513CB 204.8000M-GGCT](#) [VG-4513CA 122.8800M-GFCT3](#) [VG-4513CA 122.8800M-KFCT](#) [VG-4513CA 153.6000M-GFCT3](#) [VG-4513CA 204.8000M-GGCT3](#) [VG-4513CA 122.8800M-GGCT](#) [VG-4513CA 120.0000M-GGCL](#) [VG-4513CA 250.0000M-GFCT3](#) [VG-4513CA 204.8000M-GGCT](#) [VG-4513CB 153.6000M-GZCT](#)

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9