

EmETX-i2900

ETX

Intel® Atom™ N450/D510 ETX CPU Module



Features

- **Fanless Design**
- ETX 3.0 w/ SATA Connectors
- Soldered Onboard Intel® Atom™ N450/D510 Processor
- Single Channel 18-bit LVDS, and Analog RGB
- **Extended Operating Temp.: -20 ~ 70°C**

System

CPU	Soldered onboard Intel® Atom™ N450 1.6GHz / D510 1.66GHz processor
Memory	1 x 200-pin DDR2 SO-DIMM socket, supporting 667MHz SDRAM up to 2GB
Chipset	Intel® ICH8M
BIOS	AMI PnP Flash BIOS
Watchdog Timer	1~255 levels reset

I/O

I/O Chip	Winbond W83627HG
Serial Port	2 x COM ports
Parallel Port	SPP/EPP/ECP mode selectable
USB Port	4 x USB 2.0 ports
KB/MS	PS/2 interface for keyboard and mouse
Expansion Bus	PCI (4 x PCI masters) and ISA bus LPC (Low Pin Count) connector
Storage	1 x Ultra ATA port, supporting 2 IDE devices 2 x Serial ATA ports with 300MB/s HDD transfer rate
Ethernet Chipset	1 x Realtek 8103EL PCIe 10/100Base-T Ethernet controller
Audio Interface	Realtek ALC888 7.1 Channel HD Audio Codec, Mic-in/ Line-in/Line-out


Display

Graphics Chipset	Integrated Intel® Graphics Media Accelerator 3150 Analog RGB supports resolution up to: - 1400 x 1050 @60Hz (N450) - 2048 x 1536 @60Hz (D510)
Graphics Interface	Single channel 18-bit LVDS supports resolution up to: - 1280 x 800 or 1366 x 768 (N450) - 1366 x 768 (D510)


Mechanical & Environmental

Power Requirement	+5V, 5VSB
Power Consumption	2.21A@+5V with N450 CPU (Typical) 3.18A@+5V with D510 CPU (Typical)
Operating Temp.	-20 ~ 70°C (-4 ~ 158°F)
Operating Humidity	10 ~ 95% @ 70°C (non-condensing)
Dimension (L x W)	114 x 95 mm (4.5" x 3.7")

Dimensions



Block Diagram



Ordering Information

EmETX-i2900-N4	Intel® Atom™ N450 1.6GHz ETX CPU module
EmETX-i2900-D5	Intel® Atom™ D510 1.66GHz ETX CPU module

Optional Accessories

HS-0742-F3	Heat spreader (114x95x8 mm)
HS-0000-W4	Universal evaluation heatsink kit w/ thermal pad (dimension: 125x95x22mm, only used on a flat type heatspreader)

PBE-1000 R2.1 ETX® evaluation board in ATX form factor

Page 66

CBK-05-1000-00	Cable kit for PBE-1000 R2.1
	• 1 x FDD cable
	• 3 x COM port cables
	• 1 x TV-out cable
	• 1 x USB cable
	• 2 x IDE cables

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9