



TO-220



ITO-220




Pin Definition:

1. Gate
2. Drain
3. Source


Key Parameter Performance

Parameter	Value	Unit
V_{DS}	650	V
$R_{DS(on)}$ (max)	3.37	Ω
Q_g	13.46	nC

TO-251
(IPAK)



TO-252
(DPAK)



Application


- Power Supply.
- Lighting

Ordering Information

Part No.	Package	Packing
TSM4NB65CZ C0G	TO-220	50pcs / Tube
TSM4NB65CI C0G	ITO-220	50pcs / Tube
TSM4NB65CH C5G	TO-251	75pcs / Tube
TSM4NB65CP ROG	TO-252	2.5kpcs / 13" Reel

Note: "G" denotes for Halogen- and Antimony-free as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds

Block Diagram



N-Channel MOSFET

Absolute Maximum Ratings ($T_C = 25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Limit			Unit
		IPAK/DPAK	ITO-220	TO-220	
Drain-Source Voltage	V_{DS}	650			V
Gate-Source Voltage	V_{GS}	± 30			V
Continuous Drain Current ^(Note 1)	I_D	4			A
		2.4			A
Pulsed Drain Current ^(Note 2)	I_{DM}	16			A
Single Pulse Avalanche Energy ^(Note 3)	E_{AS}	31.2			mJ
Total Power Dissipation @ $T_C = 25^\circ\text{C}$	P_{TOT}	50	25	70	W
Operating Junction Temperature	T_J	-55 to +150			$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-55 to +150			$^\circ\text{C}$

Thermal Performance

Parameter	Symbol	Limit			Unit
		IPAK/DPAK	ITO-220	TO-220	
Thermal Resistance - Junction to Case	$R_{\theta JC}$	2.5	5	1.78	$^{\circ}\text{C/W}$
Thermal Resistance - Junction to Ambient	$R_{\theta JA}$	83	62.5	62.5	$^{\circ}\text{C/W}$

Electrical Specifications ($T_A=25^{\circ}\text{C}$ unless otherwise noted)


Parameter	Conditions	Symbol	Min	Typ	Max	Unit
Static ^(Note 4)						
Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = 250μA	BV _{DSS}	650	--	--	V
Drain-Source On-State Resistance	V _{GS} = 10V, I _D = 2A	R _{DS(ON)}	--	2.7	3.37	Ω
Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250μA	V _{GS(TH)}	2.5	3.6	4.5	V
Zero Gate Voltage Drain Current	V _{DS} = 650V, V _{GS} = 0V	I _{DSS}	--	--	1	μA
Gate Body Leakage	V _{GS} = ±30V, V _{DS} = 0V	I _{GSS}	--	--	±100	nA
Forward Transfer Conductance	V _{DS} = 40V, I _D = 2A	g _{fs}	--	2.6	--	S
Dynamic ^(Note 5)						
Total Gate Charge	V _{DS} = 480V, I _D = 4A, V _{GS} = 10V	Q _g	--	13.46	--	nC
Gate-Source Charge		Q _{gs}	--	2.98	--	
Gate-Drain Charge		Q _{gd}	--	6.66	--	
Input Capacitance	V _{DS} = 25V, V _{GS} = 0V, f = 1.0MHz	C _{iss}	--	549	--	pF
Output Capacitance		C _{oss}	--	75	--	
Reverse Transfer Capacitance		C _{rss}	--	18	--	
Switching ^(Note 6)						
Turn-On Delay Time	V _{GS} = 10V, I _D = 4A, V _{DD} = 300V, R _G = 25Ω	t _{d(on)}	--	11	--	ns
Turn-On Rise Time		t _r	--	20	--	
Turn-Off Delay Time		t _{d(off)}	--	30	--	
Turn-Off Fall Time		t _f	--	19	--	
Source-Drain Diode Ratings and Characteristic ^(Note 4)						
Source Current	Integral reverse diode in the MOSFET	I _S	--	--	4	A
Source Current (Pulse)		I _{SM}	--	--	16	A
Diode Forward Voltage	I _S = 4A, V _{GS} = 0V	V _{SD}	--	--	1.13	V

Notes:


1. Current limited by package
2. Pulse width limited by the maximum junction temperature
3. $L = 10\text{mH}, I_{AS} = 2.4\text{A}, V_{DD} = 50\text{V}, R_G = 25\Omega$, Starting $T_J = 25^{\circ}\text{C}$
4. Pulse test: $PW \leq 300\mu\text{s}$, duty cycle $\leq 2\%$
5. For DESIGN AID ONLY, not subject to production testing.
6. Switching time is essentially independent of operating temperature.

Electrical Characteristics Curves


Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current




Gate-Source Voltage vs. Gate Charge



On-Resistance vs. Junction Temperature




Source-Drain Diode Forward Current vs. Voltage




Electrical Characteristics Curves


Capacitance vs. Drain-Source Voltage




BV_{DSS} vs. Junction Temperature




Maximum Safe Operating Area (TO-220)



Maximum Safe Operating Area (ITO-220)




Maximum Safe Operating Area (DPAK/IPAK)




Electrical Characteristics Curves


Normalized Thermal Transient Impedance, Junction-to-Case (TO-220)




Normalized Thermal Transient Impedance, Junction-to-Case (ITO-220)



Normalized Thermal Transient Impedance, Junction-to-Case (DPAK/IPAK)




TO-220 Mechanical Drawing




Unit: Millimeters

Marking Diagram




Y = Year Code
M = Month Code for Halogen Free Product
O =Jan **P** =Feb **Q** =Mar **R** =Apr
S =May **T** =Jun **U** =Jul **V** =Aug
W =Sep **X** =Oct **Y** =Nov **Z** =Dec
L = Lot Code

ITO-220 Mechanical Drawing




Unit: Millimeters

Marking Diagram




- G** = Halogen Free
- Y** = Year Code
- WW** = Week Code (01~52)
- F** = Factory Code

TO-252 (DPAK) Mechanical Drawing




Unit: Millimeters

Marking Diagram




Y = Year Code
M = Month Code for Halogen Free Product
O =Jan P =Feb Q =Mar R =Apr
S =May T =Jun U =Jul V =Aug
W =Sep X =Oct Y =Nov Z =Dec
L = Lot Code

TO-251 (IPAK) Mechanical Drawing



Unit: Millimeters

Marking Diagram



Y = Year Code
M = Month Code for Halogen Free Product
O =Jan P =Feb Q =Mar R =Apr
S =May T =Jun U =Jul V =Aug
W =Sep X =Oct Y =Nov Z =Dec
L = Lot Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9