

Feed-through modular terminal block - UK3 N WH - 0719155

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)




Feed-through modular terminal block, Connection method: Screw connection, Cross section: 0.2 mm² - 4 mm², AWG 24 - 12, Width: 5.2 mm, Color: white, Mounting type: NS 32, NS 35/15, NS 35/7.5

Product description

Feed-through modular terminal block, Connection method: Screw connection, Cross section: 0.2 mm² - 4 mm², AWG 24 - 12, Width: 5.2 mm, Color: white, Mounting type: NS 32, NS 35/15, NS 35/7.5



Key commercial data

Packing unit	1
Minimum order quantity	50
GTIN	 4 017918 591502
Weight per piece (including packing)	0.0 GRM
Weight per Piece (excluding packing)	7.04 GRM
Country of origin	GERMANY

Technical data

General

Number of levels	1
Number of connections	2
Color	white
Insulating material	PA
Inflammability class according to UL 94	V0

Dimensions

Width	5.2 mm
Length	42.5 mm
Height NS 35/7.5	47 mm
Height NS 32	52 mm

Technical data

Maximum load current	32 A (with 4 mm ² conductor cross section)
Rated surge voltage	8 kV

Feed-through modular terminal block - UK3 N WH - 0719155

Technical data

Technical data

Pollution degree	3
Surge voltage category	III
Insulating material group	I
Connection in acc. with standard	IEC 60947-7-1
Nominal current I _N	24 A
Nominal voltage U _N	800 V
Open side panel	ja

Connection data

Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Conductor cross section stranded, with ferrule without plastic sleeve min.	0.25 mm ²
Conductor cross section stranded, with ferrule without plastic sleeve max.	2.5 mm ²
Conductor cross section stranded, with ferrule with plastic sleeve min.	0.25 mm ²
Conductor cross section stranded, with ferrule with plastic sleeve max.	1.5 mm ²
2 conductors with same cross section, solid min.	0.2 mm ²
2 conductors with same cross section, solid max.	1.5 mm ²
2 conductors with same cross section, stranded min.	0.2 mm ²
2 conductors with same cross section, stranded max.	1.5 mm ²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min.	0.5 mm ²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max.	1 mm ²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.	0.25 mm ²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.	1.5 mm ²
Cross section with insertion bridge, solid max.	4 mm ²
Cross section with insertion bridge, stranded max.	2.5 mm ²
Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Tightening torque, min	0.6 Nm
Tightening torque max	0.8 Nm

Feed-through modular terminal block - UK3 N WH - 0719155

Classifications

eClass

eClass 4.0	27141120
eClass 4.1	27141120
eClass 5.0	27141120
eClass 5.1	27141120
eClass 6.0	27141120

etim

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC000897

unspsc

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

Approvals

Certificates

Certification

UL Recognized / GOST / GL / DNV / GOST

Certification EX

IECEX / ATEX / FM approved / GL

Certification submitted

Approval details

UL Recognized	
	C
mm ² /AWG/kcmil	28-12
Nominal current I _N	20 A
Nominal voltage U _N	600 V

GOST

Feed-through modular terminal block - UK3 N WH - 0719155

Approvals

GL

DNV

GOST

Accessories

Accessories

Assembly

DIN rail - NS 35/ 7,5 UNPERF 2000MM - 0801681



DIN rail, material: Steel, unperforated, height 7.5 mm, width 35 mm, length: 2 m

DIN rail perforated - NS 35/ 7,5 PERF 2000MM - 0801733



DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 7.5 mm, width 35 mm, length: 2000 mm

DIN rail - NS 35/ 7,5 CU UNPERF 2000MM - 0801762



DIN rail, material: Copper, unperforated, height 7.5 mm, width 35 mm, length: 2 m

DIN rail - NS 32 AL UNPERF 2000MM - 1201028



G rail 32 mm (NS 32)

Feed-through modular terminal block - UK3 N WH - 0719155

Accessories

DIN rail - NS 35/15 UNPERF 2000MM - 1201714



DIN rail, material: Steel, unperforated, height 15 mm, width 35 mm, length: 2 m

DIN rail - NS 32 CU/35QMM UNPERF 2000MM - 1201358



G-profile DIN rail, material: Copper, unperforated, height 15 mm, width 32 mm, length 2 m

DIN rail - NS 32 CU/120QMM UNPERF 2000MM - 1201280



G-profile DIN rail, deep-drawn, material: Copper, unperforated, height 15 mm, width 32 mm, length 2 m

DIN rail - NS 32 UNPERF 2000MM - 1201015



G-profile DIN rail, material: Steel, unperforated, height 15 mm, width 32 mm, length 2 m

DIN rail - NS 32 PERF 2000MM - 1201002



G-profile DIN rail, material: Steel, perforated, height 15 mm, width 32 mm, length 2 m

DIN rail - NS 35/15 CU UNPERF 2000MM - 1201895



DIN rail, material: Copper, unperforated, 1.5 mm thick, height 15 mm, width 35 mm, length: 2 m

Feed-through modular terminal block - UK3 N WH - 0719155

Accessories

DIN rail - NS 35/15-2,3 UNPERF 2000MM - 1201798



DIN rail, material: Steel, unperforated, 2.3 mm thick, height 15 mm, width 35 mm, length: 2 m

DIN rail, unperforated - NS 35/15 AL UNPERF 2000MM - 1201756



DIN rail, deep drawn, high profile, unperforated, 1.5 mm thick, material: aluminum, height 15 mm, width 35 mm, length 2000

DIN rail perforated - NS 35/15 PERF 2000MM - 1201730



DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 15 mm, width 35 mm, length: 2000 m

End clamp - CLIPFIX 35 - 3022218



Snap-on end bracket, for 35 mm NS 35/7.5 or NS 35/15 DIN rail, can be fitted with Zack strip ZB 8 and ZB 8/27, terminal strip

End clamp - E/UK - 1201442



End clamp, for assembly on NS 32 or NS 35/7.5 DIN rail

Feed-through modular terminal block - UK3 N WH - 0719155

Accessories

End cover - D-UK 4/10 - 3003020

End cover, Length: 42.5 mm, Width: 1.8 mm, Height: 35.9 mm, Color: gray



End cover - D-UK 4/10 BU - 3003101

End cover, Length: 42.5 mm, Width: 1.8 mm, Height: 47 mm, Color: blue



Screw - ZSR - 2303608

Distance piece, metal, for branches of FB-150, with screw and thrust washer



Fixed bridge - FB-150 METER - 0201595

Cross connection rail, for fixed bridging of identical inputs and outputs, made of Cu, nickel-plated, 1 m long



Cover - EA 5-WS - 1024085

Single covers, for covering one terminal block, with black symbol (lightning flash) snap fit, color: transparent/yellow



Cover - EA 5 - 1024014

Single covers, color: transparent



Feed-through modular terminal block - UK3 N WH - 0719155

Accessories

Separating plate - TS-K - 1302215

Separating plate, Length: 22 mm, Height: 22 mm, Color: gray



Partition plate - ATP-UK - 3003224

Partition plate, Length: 56 mm, Width: 1.5 mm, Height: 45.7 mm, Color: gray



Bridges

Fixed bridge - FBR 80-5-EX - 3000942

Fixed bridge, Number of positions: 80, Color: silver



Fixed bridge - FBRI 20-5 N - 3000515

Fixed bridge, Number of positions: 20, Color: silver



Fixed bridge - FBRI 16-5 N - 3000476

Fixed bridge, Number of positions: 16, Color: silver



Feed-through modular terminal block - UK3 N WH - 0719155

Accessories

Fixed bridge - FBRI 12-5 N - 3000434

Fixed bridge, Number of positions: 12, Color: silver



Fixed bridge - FBRI 2-5 N - 3000227

Fixed bridge, Number of positions: 2, Color: silver



Fixed bridge - FBRI 10-5 N - 2770642

Fixed bridge, Number of positions: 10, Color: silver



Fixed bridge - FBR 10-5-EX - 2303226

Fixed bridge, Number of positions: 10, Color: silver



Fixed bridge - FBRI 40-5 N - 3006823

Fixed bridge, Number of positions: 40, Color: silver



Insertion bridge - EBL 3- 5 - 2303158

Insertion bridge, Number of positions: 3, Color: gray



Feed-through modular terminal block - UK3 N WH - 0719155

Accessories

Insertion bridge - EBL 2- 5 - 2303145

Insertion bridge, Number of positions: 2, Color: gray



Insertion bridge - EBL 10- 5 - 2303132

Insertion bridge, Number of positions: 10, Color: gray



Switching jumper - USBR 2-7 - 2303239

Switching jumper, Number of positions: 2, Color: silver



Switching jumper - USBRJ 2-7 - 2305538

Switching jumper, Color: silver



Marking

Zack marker strip - ZB 5:SO/CMS - 1050295

Zack marker strip, white, For terminal block width: 5 mm



Feed-through modular terminal block - UK3 N WH - 0719155

Accessories

Warning label - WS 3- 5 - 0805357

Warning plate, with 2 plastic screws, across 3 terminal blocks, pitch 5 mm



Warning label - WS 4- 5 - 0805344

Warning plate, with 2 plastic screws, across 4 terminal blocks, pitch 5 mm



Warning label - WS 5- 5 - 0805331

Warning plate, with 2 plastic screws, across 5 terminal blocks, pitch 5 mm



Marker cards - SBS 5:UNBEDRUCKT - 1007219

Marker cards, Card, white, Unlabeled, Can be labeled with: Plotter, Mounting type: Snap into tall marker groove, Snap into fl



Plug/Adapter

Female test connector - PSBJ 3/13/4 - 0201304

Female test connector, Color: silver



Feed-through modular terminal block - UK3 N WH - 0719155

Accessories

Female test connector - PSB 3/10/4 - 0601292

Female test connector, Color: silver



Short-circuit connector - KSS 5 - 2303543

Short-circuit connector, Number of positions: 2, Color: black



Test plugs - PS-UK 3-5/Z-5 - 3001459

Test plug

Test plugs - PS-UK 2,5 B/Z-5 - 3001226

Test plugs, Color: red



Test plugs - PS-UK 2,5 B/E - 3001132

Test plugs, Color: red



Reducing plug - RPS - 0201647

Reducing plug, Color: gray



Feed-through modular terminal block - UK3 N WH - 0719155

Accessories

Test plugs - MPS-MT - 0201744

Test plugs



© Phoenix Contact 2012 - all rights reserved
<http://www.phoenixcontact.com>

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9