


ALUMINUM ELECTROLYTIC CAPACITORS

nichicon

CX Chip Type, High Reliability
Low temperature ESR specification
series



- Chip type, high temperature range, for +135°C use.
- Added ESR specification after the test at -40°C.
- Applicable to automatic mounting machine fed with carrier tape.
- Compliant to the RoHS directive (2011/65/EU).

CX




Specifications


Item	Performance Characteristics							
Category Temperature Range	-40 to +135°C							
Rated Voltage Range	10 to 50V							
Rated Capacitance Range	47 to 3300μF							
Capacitance Tolerance	±20% at 120Hz, 20°C							
Leakage Current	After 2 minutes' application of rated voltage, leakage current is not more than 0.01CV or 3(μA), whichever is greater.							
Tangent of loss angle (tan δ)	Rated voltage (V)	10	16	25	35	50	Measurement frequency : 120Hz at 20°C	
	tan δ (MAX.)	0.30	0.23	0.18	0.16	0.16		
Stability at Low Temperature	Rated voltage (V)		10	16	25	35	50	Measurement frequency : 120Hz
	Impedance ratio ZT / Z20 (MAX.)	Z-40°C / Z+20°C	12	8	6	4	4	
	Endurance	The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 2000 hours at 135°C.				Capacitance Change		Within ± 30% of the initial capacitance value
					tan δ		300% or less than the initial specified value	
					Leakage current		Less than or equal to the initial specified value	
Shelf Life	After storing the capacitors under no load at 135°C for 1000 hours and then performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they shall meet the specified values for the endurance characteristics listed above.							
Resistance to soldering heat	The capacitors shall be kept on the hot plate for 30 seconds, which is maintained at 250°C. The capacitors shall meet the characteristic requirements listed at right when they are removed from the plate and restored to 20°C.				Capacitance Change		Within ±10% of the initial capacitance value	
					tan δ		Less than or equal to the initial specified value	
					Leakage current		Less than or equal to the initial specified value	
Marking	Black print on the case top.							

Radial Lead Type


(φ6.3)【Vibration Resistance】




(φ8 to φ10)【Standard】




(φ12.5 to φ18)【Standard】




Type numbering system (Example : 35V 47μF)



(φ8 to φ10)【Vibration Resistance】



(φ12.5 to φ18)【Vibration Resistance】



Standard

φD×L	8×10	10×10	12.5×13.5	16×16.5, 21.5	18×16.5, 21.5
A	2.9	3.2	4.8	5.4	6.4
B	8.3	10.3	13.6	17.1	19.1
C	8.3	10.3	13.6	17.1	19.1
E	3.1	4.5	4	6.3	6.3
L	10	10	13.5	16.5, 21.5	16.5, 21.5
H	0.8 to 1.1	0.8 to 1.1	1.0 to 1.4	1.0 to 1.4	1.0 to 1.4

Vibration Resistance

φD×L	6.3×10	8×10	10×10	12.5×13.5	16×16.5, 21.5	18×16.5, 21.5
A	2.4	2.9	3.2	4.8	5.4	6.4
B	6.6	8.3	10.3	13.6	17.1	19.1
C	6.6	8.3	10.3	13.6	17.1	19.1
E	2.2	3.1	4.5	4	6.3	6.3
L	10	10	10	13.5	16.5, 21.5	16.5, 21.5
H	0.5 to 0.8	1.1 to 1.5	1.1 to 1.5	1.0 to 1.4	1.0 to 1.4	1.0 to 1.4

⬜ Aid electrode

●Dimension table in next page.

Rated Voltage

V	10	16	25	35	50
Code	A	C	E	V	H

CAT.8100D



■ Dimensions

Cap.(μF)	V Code	10					16					25					35					50				
		1A					1C					1E					1V					1H				
47	470																●6.3×10	0.25	4	15	197	8×10	0.25	3.5	15	270
																	8×10	0.20	3	12	270					
68	680																8×10	0.20	3	12	270					
100	101						●6.3×10	0.25	4	15	197	8×10	0.20	3	12	270	●6.3×10	0.25	4	15	197	10×10	0.2	2.5	12	500
							8×10	0.20	3	12	270						8×10	0.20	3	12	270					
220	221	8×10	0.20	3	12	270	8×10	0.20	3	12	270	10×10	0.15	2	10	500	10×10	0.15	2	10	500					
330	331	●8×10	0.20	3	12	270	10×10	0.15	2	10	500	10×10	0.15	2	10	500										
		10×10	0.15	2	10	500																				
390	391																					12.5×13.5	0.09	1.3	6.5	750
470	471	10×10	0.15	2	10	500	10×10	0.15	2	10	500						12.5×13.5	0.07	1.0	5.0	750	16×16.5	0.07	0.70	3.5	1000
560	561																12.5×13.5	0.07	1.0	5.0	750	16×16.5	0.07	0.70	3.5	1000
680	681																12.5×13.5	0.07	1.0	5.0	750	18×16.5	0.07	0.70	3.5	1200
820	821											12.5×13.5	0.07	1.0	5.0	750	16×16.5	0.05	0.50	2.5	1200	18×16.5	0.07	0.70	3.5	1200
1000	102											12.5×13.5	0.07	1.0	5.0	750	16×16.5	0.05	0.50	2.5	1200	16×21.5	0.05	0.40	2.0	1600
1200	122											16×16.5	0.05	0.50	2.5	1200	18×16.5	0.05	0.50	2.5	1400	18×21.5	0.04	0.32	1.6	1900
1500	152											16×16.5	0.05	0.50	2.5	1200	●16×21.5	0.04	0.32	1.6	1900					
								18×16.5	0.05	0.50	2.5						1400									
1800	182											16×16.5	0.05	0.50	2.5	1200	18×21.5	0.035	0.28	1.4	2200					
2200	222											18×16.5	0.05	0.50	2.5	1400	18×21.5	0.035	0.28	1.4	2200	Case size φD×L (mm)	Initial 20℃	Initial -40℃	After endurance test 1000hours -40℃	Rated ripple
2700	272										16×21.5	0.04	0.32	1.6	1900											
3300	332										18×21.5	0.035	0.28	1.4	2200											
		ESR																								

MAX. ESR (Ω) at 20°C / -40°C 100kHz, Rated ripple current(mArms) at 135°C 100kHz

●In this case, [6] will be put at 12th digit of type numbering system.

● Frequency coefficient of rated ripple current

Frequency	50Hz	120Hz	300Hz	1kHz	10kHz or more
Coefficient	0.35	0.50	0.64	0.83	1.00

- Taping specifications are given in page 23.
- Recommended land size, soldering by reflow are given in page 18, 19.
- Please refer to page 3 for the minimum order quantity.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9