

89907 Coax - Coaxial Cable - Thinnet 10Base2 Ethernet

For more Information
please call

1-800-Belden1

**Description:**

20 AWG stranded (19x32) .037" tinned copper conductor, foam FEP insulation, Duobond® II (100% coverage) plus a tinned copper braid shield (93% coverage), fluorocopolymer jacket.

Usage (Overall)

Suitable Applications: Thin Ethernet

Physical Characteristics (Overall)**Conductor**

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	20	19x32	TC - Tinned Copper	0.9398

Insulation

Insulation Material:

Insulation Material	Dia. (mm)
FFEP - Foam Fluorinated Ethylene Propylene	2.413

Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Bonded Duofoil®	Tape	Bonded Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	TC - Tinned Copper	93

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVDF - Fluorocopolymer

Overall Cabling

Overall Nominal Diameter: 4.064 mm

Mechanical Characteristics (Overall)

Operating Temperature Range:	-20°C To +150°C
UL Temperature Rating:	150°C
Bulk Cable Weight:	37.205 Kg/Km
Max. Recommended Pulling Tension:	200.169 N
Min. Bend Radius (Install)/Minor Axis:	45.720 mm

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	CMP, CL2P
CEC/C(UL) Specification:	CMP
IEEE Specification:	IEEE802.3 10Base2
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes

89907 Coax - Coaxial Cable - Thinnet 10Base2 Ethernet

EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Customer Part Number Reference Specification:	DEC Part No. 17-01246-00
RG Type:	58A/U

Flame Test

UL Flame Test:	NFPA 262
CSA Flame Test:	FT6

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes

Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	9907

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)	Tolerance (Ohms)
50	+/- 2

Nom. Inductance:

Inductance (µH/m)
0.208344

Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)
83.3374

Nominal Velocity of Propagation:

VP (%)
80

Nominal Delay:

Delay (ns/m)
4.16687

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
28.8728

Maximum Loop Resistance:

Resistance (Ohm/km)
50.0024

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
19.0298

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
1	1.41083
10	4.2653
50	9.54771
100	13.7146

METRIC MEASUREMENT VERSION

89907 Coax - Coaxial Cable - Thinnet 10Base2 Ethernet

200	20.0141
400	30.1852
700	42.3249
900	49.215
1000	52.496

Max. Power Rating:

Freq. (MHz)	Rating (W)
1	6450
2	4500
10	1850
20	1400
50	890
100	640
200	470
400	360
700	290
900	270
1000	260

Max. Operating Voltage - UL:

Voltage
300 V RMS

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
89907 E4X1000	305 MT	9.979 KG	GRAY, LIGHT DEC	C	#20 FPFA BRD SLF COAX
89907 E4X2500	762 MT	27.216 KG	GRAY, LIGHT DEC	C Z	#20 FPFA BRD SLF COAX
89907 E4X500	152 MT	4.990 KG	GRAY, LIGHT DEC	C	#20 FPFA BRD SLF COAX

Notes:

C = CRATE REEL PUT-UP.

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND(+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 1 Revision Date: 09-23-2008

© 2011 Belden, Inc
 All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9