

TCJ Series



Tantalum Solid Electrolytic Chip Capacitors with Conductive Polymer Electrode



FEATURES

- Conductive polymer electrode reduces ignition failure mode
- Lower ESR
- 3x reflow 260°C compatible
- CV range: 0.47-470µF / 2.5-125V
- 17 case sizes available

APPLICATIONS

- Smart phone, Tablets, Notebook, LCD TV, Power supplies



Elektra Award 2010



LEAD-FREE
LEAD-FREE COMPATIBLE
COMPONENT



RoHS
COMPLIANT



CASE DIMENSIONS: millimeters (inches)

| Code | EIA Code | EIA Metric | L±0.20 (0.008) | W+0.20 (0.008) -0.10 (0.004) | H+0.20 (0.008) -0.10 (0.004) | W1±0.20 (0.008) | A+0.30 (0.012) -0.20 (0.008) | S Min. |
|------|----------|------------|----------------|------------------------------|------------------------------|-------------------------|------------------------------|--------------|
| A | 1206 | 3216-18 | 3.20 (0.126) | 1.60 (0.063) | 1.60 (0.063) | 1.20 (0.047) | 0.80 (0.031) | 1.10 (0.043) |
| B | 1210 | 3528-21 | 3.50 (0.138) | 2.80 (0.110) | 1.90 (0.075) | 2.20 (0.087) | 0.80 (0.031) | 1.40 (0.055) |
| C | 2312 | 6032-28 | 6.00 (0.236) | 3.20 (0.126) | 2.60 (0.102) | 2.20 (0.087) | 1.30 (0.051) | 2.90 (0.114) |
| D | 2917 | 7343-31 | 7.30 (0.287) | 4.30 (0.169) | 2.90 (0.114) | 2.40 (0.094) | 1.30 (0.051) | 4.40 (0.173) |
| E | 2917 | 7343-43 | 7.30 (0.287) | 4.30 (0.169) | 4.10 (0.162) | 2.40 (0.094) | 1.30 (0.051) | 4.40 (0.173) |
| G | 1206 | 3216-15 | 3.20 (0.126) | 1.60 (0.063) | 1.50 (0.059) max | 1.20 (0.047) | 0.80 (0.031) | 1.10 (0.043) |
| H | 1210 | 3528-15 | 3.50 (0.138) | 2.80 (0.110) | 1.50 (0.059) max | 2.20 (0.087) | 0.80 (0.031) | 1.40 (0.055) |
| K | 1206 | 3216-10 | 3.20 (0.126) | 1.60 (0.063) | 1.00 (0.039) max | 1.20 (0.047) | 0.80 (0.031) | 1.10 (0.043) |
| N | 0805 | 2012-10 | 2.05 (0.081) | 1.30 (0.051) | 1.00 (0.039) max | 1.00 (0.039) | 0.50 (0.020) | 0.85 (0.033) |
| P | 0805 | 2012-15 | 2.05 (0.081) | 1.35 (0.050) | 1.50 (0.059) max | 1.00±0.10 (0.039±0.004) | 0.50 (0.020) | 0.85 (0.033) |
| R | 0805 | 2012-12 | 2.05 (0.081) | 1.30 (0.051) | 1.20 (0.047) max | 1.00±0.10 (0.039±0.004) | 0.50 (0.020) | 0.85 (0.033) |
| S | 1206 | 3216-12 | 3.20 (0.126) | 1.60 (0.063) | 1.20 (0.047) max | 1.20 (0.047) | 0.80 (0.031) | 1.10 (0.043) |
| T | 1210 | 3528-12 | 3.50 (0.138) | 2.80 (0.110) | 1.20 (0.047) max | 2.20 (0.087) | 0.80 (0.031) | 1.40 (0.055) |
| V | 2924 | 7361-38 | 7.30 (0.287) | 6.10 (0.240) | 3.55 (0.140) | 3.10 (0.120) | 1.30 (0.051) | 4.40 (0.173) |
| W | 2312 | 6032-15 | 6.00 (0.236) | 3.20 (0.126) | 1.50 (0.059) max | 2.20 (0.087) | 1.30 (0.051) | 2.90 (0.114) |
| X | 2917 | 7343-15 | 7.30 (0.287) | 4.30 (0.169) | 1.50 (0.059) max | 2.40 (0.094) | 1.30 (0.051) | 4.40 (0.173) |
| Y | 2917 | 7343-20 | 7.30 (0.287) | 4.30 (0.169) | 2.00 (0.079) max | 2.40 (0.094) | 1.30 (0.051) | 4.40 (0.173) |


W1 dimension applies to the termination width for A dimensional area only.

MARKING

A, B, C, D, E, G, H, K, S, T, V, W, X, Y CASE



N, P, R CASE



HOW TO ORDER

| TCJ | A | 226 | M | 004 | R | 0300 |
|------|-----------------|--|-----------|--|---|-----------|
| Type | Case Size | Capacitance Code | Tolerance | Rated DC Voltage | Packaging | ESR in mΩ |
| | See table above | pF code: 1st two digits represent significant figures, 3rd digit represents multiplier (number of zeros to follow) | M = ±20% | 002 = 2.5Vdc 004 = 4Vdc 006 = 6.3Vdc 010 = 10Vdc 016 = 16Vdc 020 = 20Vdc 025 = 25Vdc 035 = 35Vdc 050 = 50Vdc 063 = 63Vdc 075 = 75Vdc 100 = 100Vdc 125 = 125Vdc | R = Pure Tin 7" Reel S = Pure Tin 13" Reel | |

TECHNICAL SPECIFICATIONS (Common for all TCJ series)

| | |
|-------------------------------|--|
| Technical Data: | All technical data relate to an ambient temperature of +25°C |
| Capacitance Tolerance: | ±20% |
| Leakage Current DCL: | 0.1CV |
| Reliability: | 1% per 1000 hours at 85°C, V _R with 0.1Ω/V series impedance, 60% confidence level |
| Resistance to soldering heat: | 3x260°C peak for max. 10s reflow |



Tantalum Solid Electrolytic Chip Capacitors with Conductive Polymer Electrode

CAPACITANCE AND RATED VOLTAGE RANGE (LETTER DENOTES CASE SIZE)

| Cap | | Rated Voltage DC (V _R) to 85°C | | | | | | | | | | | | |
|------|------|--|---|--|----------------------------------|--------------------------------|----------------------------|--|--|---------------------|----------------------|---------|----------|----------|
| µF | Code | 2.5V (e) | 4V (G) | 6.3V (J) | 10V (A) | 16V (C) | 20V (D) | 25V (E) | 35V (V) | 50V (T) | 63V (J) | 75V (P) | 100V (A) | 125V (B) |
| 0.47 | 474 | | | | | | | | | | | | | B(400) |
| 0.68 | 684 | | | | | | | | | B(400) | B(300) | | | |
| 1.0 | 105 | | | | | | | P(500) | | B(300) | B(300) C(300) | | | |
| 1.5 | 155 | | | | | | | | B(200) | B(300) C(300) | C(300) | | | |
| 2.2 | 225 | | | | | | | | B(200) | C(300) | C(200) | | | |
| 3.3 | 335 | | | | | | | | B(200) | C(200) | C(200) | | | D(250) |
| 4.7 | 475 | | | | K(500) R(500) | | | B(100,150) | B(200) C(200) | C(200) | C(200) D(120) | D(150) | D(250) | |
| 6.8 | 685 | | | | | A(200) | | B(90,150) T(100,150) | C(200) | C(200) D(120) | D(120) E(100,150) | D(120) | | |
| 10 | 106 | | | A(300) N(250,500) R(500) | A(300) | A(200) B(200) T(150,200) | | B(90,100,150) | B(200) C(200) Y(70) | D(120) E(70,100) | E(100,150) | U* | U* | |
| 15 | 156 | | A(300) | A(300) | A(200) | B(150) | | B(100,150) Y(90) | B(200), C(200) D(70,100) Y(70,100) | E(70,100) | | | | |
| 22 | 226 | | A(300) | A(300), K(400) N(500), R(500) S(400), T(150) | B(300) T(70,150) | B(150) | B(90,150) Y(70) | B(100,150), C(100) D(60,100) Y(70) | D(70,100) Y* | | | | | |
| 33 | 336 | | A(300) | A(200) B(70,200) T(150) | B(70,200) C(100) T(70,150) | Y(45,60,70) | Y(70) | D(60,100) X(70,100) Y(60,70,100) | D(70,100) E(55,70) | | | | | |
| 47 | 476 | | A(200) T(80) | A(70,100,200), B(70) K(150,200,400) P(500), R(500) T(55,69,70,80,120) | B(70) C(100) | X(45,70) Y(45,70) | D(55) X(55,70) Y(70) | D(60,100) E(50) | E(55) | | | | | |
| 68 | 686 | A(250) | A(250) B(70) T(80) | B(55,70) C(100) T(200), W(70) | D(45,55) Y(45,55) | D(50) Y(50) | D(55) E(45) | D(70) E(50) | | | | | | |
| 100 | 107 | A(200), B(70) | A(200) B(40,70) G(300) T(150) | A(100,150) B(45,55,69,70) T(70,200) | D(45,55,80) Y(25,45,55) | D(50), E(40) Y(50) | D(55) E(45) | D(55,70) E(80) | | | | | | |
| 150 | 157 | B(70) | B(70), Y(25,45) | B(25,35,45,55,69,70) D(15,25,40) H(70,200), W(40,70) Y(15,25,40) | D(25,40,45,55) Y(25,40,45,55) | D(40,50) E(40) Y(40,50) | | | | | | | | |
| 220 | 227 | B(35,45,70) | B(35,45,55,60,70) D(15,25,40) Y(15,25,40) | B(70,200) D(25,35,40,50) Y(15,25,35,40,50) | D(15,18,25,40,50) Y(25,40,50) | | | | | | | | | |
| 330 | 337 | B(35,45,70) Y(25,40) | D(25,40,50) Y(25,40,50) | D(25,40,50) Y(25,40,50) | | E* | | | | | | | | |
| 470 | 477 | D(15,25,40,50) Y(15,25,40,50) | D(15,25,40,50) Y(15,25,40,50) | X(55,100) | | | | | | | | | | |
| 3300 | 208 | | | U* | | | | | | | | | | |

Available Ratings, (ESR ratings in mOhms in brackets)

Engineering samples - please contact manufacturer

*Codes under development – subject to change

Note: Voltage ratings are minimum values. AVX reserves the right to supply higher ratings in the same case size, to the same reliability standards.

TCJ Series



Tantalum Solid Electrolytic Chip Capacitors with Conductive Polymer Electrode

RATINGS & PART NUMBER REFERENCE

| AVX Part No. | Case Size | Cap (µF) | Rated Voltage (V) | Rated Temp. (°C) | Category Voltage (V) | Category Temp. (°C) | DCL (µA) Max. | DF % Max. | ESR Max. (mΩ) @ 100kHz | MSL | 100kHz RMS Current (mA) | | | | Product Category |
|------------------------|-----------|----------|-------------------|------------------|----------------------|---------------------|---------------|-----------|------------------------|-----|-------------------------|------|-------|-------|------------------|
| | | | | | | | | | | | 25°C | 85°C | 105°C | 125°C | |
| 2.5 Volt @ 85°C | | | | | | | | | | | | | | | |
| TCJA686M002#0250 | A | 68 | 2.5 | 85 | 2 | 105 | 17 | 6 | 250 | 3 | 600 | 400 | 300 | - | 105°C |
| TCJA107M002#0200 | A | 100 | 2.5 | 85 | 2 | 105 | 25 | 6 | 200 | 3 | 700 | 500 | 300 | - | 105°C |
| TCJB107M002#0070 | B | 100 | 2.5 | 85 | 1.7 | 125 | 25 | 6 | 70 | 3 | 1300 | 900 | 600 | 300 | 125°C |
| TCJB157M002#0070 | B | 150 | 2.5 | 85 | 2 | 105 | 37.5 | 6 | 70 | 3 | 1300 | 900 | 600 | - | 105°C |
| TCJB227M002#0035 | B | 220 | 2.5 | 85 | 2 | 105 | 55 | 8 | 35 | 3 | 1900 | 1300 | 900 | - | 105°C |
| TCJB227M002#0045 | B | 220 | 2.5 | 85 | 2 | 105 | 55 | 8 | 45 | 3 | 1700 | 1200 | 800 | - | 105°C |
| TCJB227M002#0070 | B | 220 | 2.5 | 85 | 2 | 105 | 55 | 8 | 70 | 3 | 1300 | 900 | 600 | - | 105°C |
| TCJB337M002#0035 | B | 330 | 2.5 | 85 | 2 | 105 | 82.5 | 8 | 35 | 3 | 1900 | 1300 | 900 | - | 105°C |
| TCJB337M002#0045 | B | 330 | 2.5 | 85 | 2 | 105 | 82.5 | 8 | 45 | 3 | 1700 | 1200 | 800 | - | 105°C |
| TCJB337M002#0070 | B | 330 | 2.5 | 85 | 2 | 105 | 82.5 | 8 | 70 | 3 | 1300 | 900 | 600 | - | 105°C |
| TCJY337M002#0025 | Y | 330 | 2.5 | 85 | 2 | 105 | 82.5 | 6 | 25 | 3 | 2700 | 1900 | 1200 | - | 105°C |
| TCJY337M002#0040 | Y | 330 | 2.5 | 85 | 2 | 105 | 82.5 | 6 | 40 | 3 | 2200 | 1500 | 1000 | - | 105°C |
| TCJD477M002#0015 | D | 470 | 2.5 | 105 | 2.5 | 105 | 117.5 | 6 | 15 | 3 | 3900 | 2700 | 1800 | - | 105°C |
| TCJD477M002#0025 | D | 470 | 2.5 | 85 | 2 | 105 | 117.5 | 6 | 25 | 3 | 3000 | 2100 | 1400 | - | 105°C |
| TCJD477M002#0040 | D | 470 | 2.5 | 85 | 2 | 105 | 117.5 | 6 | 40 | 3 | 2400 | 1700 | 1100 | - | 105°C |
| TCJD477M002#0050 | D | 470 | 2.5 | 85 | 2 | 105 | 117.5 | 6 | 50 | 3 | 2100 | 1500 | 900 | - | 105°C |
| TCJY477M002#0015 | Y | 470 | 2.5 | 85 | 2.5 | 85 | 117.5 | 6 | 15 | 3 | 3500 | 2500 | - | - | 85°C |
| TCJY477M002#0025 | Y | 470 | 2.5 | 85 | 2 | 105 | 117.5 | 6 | 25 | 3 | 2700 | 1900 | 1200 | - | 105°C |
| TCJY477M002#0040 | Y | 470 | 2.5 | 85 | 2 | 105 | 117.5 | 6 | 40 | 3 | 2200 | 1500 | 1000 | - | 105°C |
| TCJY477M002#0050 | Y | 470 | 2.5 | 85 | 2 | 105 | 117.5 | 6 | 50 | 3 | 1900 | 1300 | 900 | - | 105°C |
| 4 Volt @ 85°C | | | | | | | | | | | | | | | |
| TCJA156M004#0300 | A | 15 | 4 | 85 | 2.7 | 125 | 6 | 6 | 300 | 3 | 600 | 400 | 300 | 200 | 125°C |
| TCJA226M004#0300 | A | 22 | 4 | 85 | 2.7 | 125 | 8.8 | 6 | 300 | 3 | 600 | 400 | 300 | 200 | 125°C |
| TCJA336M004#0300 | A | 33 | 4 | 85 | 2.7 | 125 | 13.2 | 6 | 300 | 3 | 600 | 400 | 300 | 200 | 125°C |
| TCJA476M004#0200 | A | 47 | 4 | 85 | 3.2 | 105 | 18.8 | 6 | 200 | 3 | 700 | 500 | 300 | - | 105°C |
| TCJT476M004#0080 | T | 47 | 4 | 85 | 3.2 | 105 | 18.8 | 8 | 80 | 3 | 1100 | 800 | 500 | - | 105°C |
| TCJA686M004#0250 | A | 68 | 4 | 85 | 3.2 | 105 | 27.2 | 6 | 250 | 3 | 600 | 400 | 300 | - | 105°C |
| TCJB686M004#0070 | B | 68 | 4 | 85 | 2.7 | 125 | 27.2 | 6 | 70 | 3 | 1300 | 900 | 600 | 300 | 125°C |
| TCJT686M004#0080 | T | 68 | 4 | 85 | 3.2 | 105 | 27.2 | 8 | 80 | 3 | 1100 | 800 | 500 | - | 105°C |
| TCJA107M004#0200 | A | 100 | 4 | 85 | 3.2 | 105 | 40 | 6 | 200 | 3 | 700 | 500 | 300 | - | 105°C |
| TCJB107M004#0040 | B | 100 | 4 | 85 | 3.2 | 105 | 40 | 8 | 40 | 3 | 1800 | 1300 | 800 | - | 105°C |
| TCJB107M004#0070 | B | 100 | 4 | 85 | 2.7 | 125 | 40 | 8 | 70 | 3 | 1300 | 900 | 600 | 300 | 125°C |
| TCJG107M004#0300 | G | 100 | 4 | 85 | 3.2 | 105 | 40 | 10 | 300 | 3 | 600 | 400 | 300 | - | 105°C |
| TCJT107M004#0150 | T | 100 | 4 | 85 | 3.2 | 105 | 40 | 8 | 150 | 3 | 800 | 600 | 400 | - | 105°C |
| TCJB157M004#0070 | B | 150 | 4 | 85 | 3.2 | 105 | 60 | 6 | 70 | 3 | 1300 | 900 | 600 | - | 105°C |
| TCJY157M004#0025 | Y | 150 | 4 | 85 | 3.2 | 105 | 60 | 6 | 25 | 3 | 2700 | 1900 | 1200 | - | 105°C |
| TCJY157M004#0045 | Y | 150 | 4 | 85 | 3.2 | 105 | 60 | 6 | 45 | 3 | 2000 | 1400 | 900 | - | 105°C |
| TCJB227M004#0035 | B | 220 | 4 | 85 | 3.2 | 105 | 88 | 10 | 35 | 3 | 1900 | 1300 | 900 | - | 105°C |
| TCJB227M004#0045 | B | 220 | 4 | 85 | 3.2 | 105 | 88 | 10 | 45 | 3 | 1700 | 1200 | 800 | - | 105°C |
| TCJB227M004#0055 | B | 220 | 4 | 85 | 3.2 | 105 | 88 | 10 | 55 | 3 | 1500 | 1100 | 700 | - | 105°C |
| TCJB227M004#0060 | B | 220 | 4 | 85 | 3.2 | 105 | 88 | 10 | 60 | 3 | 1400 | 1000 | 600 | - | 105°C |
| TCJB227M004#0070 | B | 220 | 4 | 85 | 3.2 | 105 | 88 | 10 | 70 | 3 | 1300 | 900 | 600 | - | 105°C |
| TCJD227M004#0015 | D | 220 | 4 | 105 | 4 | 105 | 88 | 6 | 15 | 3 | 3900 | 2700 | 1800 | - | 105°C |
| TCJD227M004#0025 | D | 220 | 4 | 105 | 4 | 105 | 88 | 6 | 25 | 3 | 3000 | 2100 | 1400 | - | 105°C |
| TCJD227M004#0040 | D | 220 | 4 | 105 | 4 | 105 | 88 | 6 | 40 | 3 | 2400 | 1700 | 1100 | - | 105°C |
| TCJY227M004#0015 | Y | 220 | 4 | 85 | 4 | 85 | 88 | 6 | 15 | 3 | 3500 | 2500 | - | - | 85°C |
| TCJY227M004#0025 | Y | 220 | 4 | 85 | 3.2 | 105 | 88 | 6 | 25 | 3 | 2700 | 1900 | 1200 | - | 105°C |
| TCJY227M004#0040 | Y | 220 | 4 | 85 | 3.2 | 105 | 88 | 6 | 40 | 3 | 2200 | 1500 | 1000 | - | 105°C |
| TCJD337M004#0025 | D | 330 | 4 | 85 | 3.2 | 105 | 132 | 6 | 25 | 3 | 3000 | 2100 | 1400 | - | 105°C |
| TCJD337M004#0040 | D | 330 | 4 | 85 | 3.2 | 105 | 132 | 6 | 40 | 3 | 2400 | 1700 | 1100 | - | 105°C |
| TCJD337M004#0050 | D | 330 | 4 | 85 | 3.2 | 105 | 132 | 6 | 50 | 3 | 2100 | 1500 | 900 | - | 105°C |
| TCJY337M004#0025 | Y | 330 | 4 | 85 | 3.2 | 105 | 132 | 6 | 25 | 3 | 2700 | 1900 | 1200 | - | 105°C |
| TCJY337M004#0040 | Y | 330 | 4 | 85 | 3.2 | 105 | 132 | 6 | 40 | 3 | 2200 | 1500 | 1000 | - | 105°C |
| TCJY337M004#0050 | Y | 330 | 4 | 85 | 3.2 | 105 | 132 | 6 | 50 | 3 | 1900 | 1300 | 900 | - | 105°C |
| TCJD477M004#0015 | D | 470 | 4 | 105 | 4 | 105 | 188 | 6 | 15 | 3 | 3900 | 2700 | 1800 | - | 105°C |
| TCJD477M004#0025 | D | 470 | 4 | 85 | 3.2 | 105 | 188 | 6 | 25 | 3 | 3000 | 2100 | 1400 | - | 105°C |
| TCJD477M004#0040 | D | 470 | 4 | 105 | 4 | 105 | 188 | 6 | 40 | 3 | 2400 | 1700 | 1100 | - | 105°C |
| TCJD477M004#0050 | D | 470 | 4 | 105 | 4 | 105 | 188 | 6 | 50 | 3 | 2100 | 1500 | 900 | - | 105°C |
| TCJY477M004#0015 | Y | 470 | 4 | 85 | 4 | 85 | 188 | 6 | 15 | 3 | 3500 | 2500 | - | - | 85°C |
| TCJY477M004#0025 | Y | 470 | 4 | 85 | 3.2 | 105 | 188 | 6 | 25 | 3 | 2700 | 1900 | 1200 | - | 105°C |
| TCJY477M004#0040 | Y | 470 | 4 | 85 | 3.2 | 105 | 188 | 6 | 40 | 3 | 2200 | 1500 | 1000 | - | 105°C |
| TCJY477M004#0050 | Y | 470 | 4 | 85 | 3.2 | 105 | 188 | 6 | 50 | 3 | 1900 | 1300 | 900 | - | 105°C |
| 6.3 Volt @ 85°C | | | | | | | | | | | | | | | |
| TCJA106M006#0300 | A | 10 | 6.3 | 85 | 4 | 125 | 6 | 6 | 300 | 3 | 600 | 400 | 300 | 200 | 125°C |
| TCJN106M006#0250 | N | 10 | 6.3 | 85 | 5 | 105 | 6 | 6 | 250 | 3 | 600 | 400 | 300 | - | 105°C |
| TCJN106M006#0500 | N | 10 | 6.3 | 85 | 5 | 105 | 6 | 6 | 500 | 3 | 400 | 300 | 200 | - | 105°C |
| TCJR106M006#0500 | R | 10 | 6.3 | 85 | 5 | 105 | 6 | 6 | 500 | 3 | 400 | 300 | 200 | - | 105°C |
| TCJA156M006#0300 | A | 15 | 6.3 | 85 | 4 | 125 | 9 | 6 | 300 | 3 | 600 | 400 | 300 | 200 | 125°C |
| TCJA226M006#0300 | A | 22 | 6.3 | 85 | 4 | 125 | 13.2 | 6 | 300 | 3 | 600 | 400 | 300 | 200 | 125°C |
| TCJK226M006#0400 | K | 22 | 6.3 | 85 | 5 | 105 | 13.2 | 8 | 400 | 3 | 500 | 400 | 200 | - | 105°C |
| TCJN226M006#0500 | N | 22 | 6.3 | 85 | 5 | 105 | 13.2 | 10 | 500 | 3 | 400 | 300 | 200 | - | 105°C |
| TCJR226M006#0500 | R | 22 | 6.3 | 85 | 5 | 105 | 13.2 | 10 | 500 | 3 | 400 | 300 | 200 | - | 105°C |



TCJ Series



Tantalum Solid Electrolytic Chip Capacitors with Conductive Polymer Electrode

RATINGS & PART NUMBER REFERENCE

| AVX Part No. | Case Size | Cap (µF) | Rated Voltage (V) | Rated Temp. (°C) | Category Voltage (V) | Category Temp. (°C) | DCL (µA) Max. | DF % Max. | ESR Max. (mΩ) @ 100kHz | MSL | 100kHz RMS Current (mA) | | | | Product Category |
|-----------------------|-----------|----------|-------------------|------------------|----------------------|---------------------|---------------|-----------|------------------------|-----|-------------------------|------|-------|-------|------------------|
| | | | | | | | | | | | 25°C | 85°C | 105°C | 125°C | |
| TCJW686M006#0070 | W | 68 | 6.3 | 85 | 4 | 125 | 40.8 | 8 | 70 | 3 | 1400 | 1000 | 600 | 400 | 125°C |
| TCJS226M006#0400 | S | 22 | 6.3 | 85 | 5 | 105 | 13.2 | 8 | 400 | 3 | 500 | 400 | 200 | - | 105°C |
| TCJT226M006#0150 | T | 22 | 6.3 | 85 | 5 | 105 | 13.2 | 6 | 150 | 3 | 800 | 600 | 400 | - | 105°C |
| TCJA336M006#0200 | A | 33 | 6.3 | 85 | 5 | 105 | 19.8 | 6 | 200 | 3 | 700 | 500 | 300 | - | 105°C |
| TCJB336M006#0070 | B | 33 | 6.3 | 85 | 4 | 125 | 19.8 | 6 | 70 | 3 | 1300 | 900 | 600 | 300 | 125°C |
| TCJB336M006#0200 | B | 33 | 6.3 | 85 | 4 | 125 | 19.8 | 6 | 200 | 3 | 800 | 600 | 400 | 200 | 125°C |
| TCJT336M006#0150 | T | 33 | 6.3 | 85 | 5 | 105 | 19.8 | 8 | 150 | 3 | 800 | 600 | 400 | - | 105°C |
| TCJA476M006#0070 | A | 47 | 6.3 | 85 | 5 | 105 | 28.2 | 6 | 70 | 3 | 1200 | 800 | 500 | - | 105°C |
| TCJA476M006#0100 | A | 47 | 6.3 | 85 | 5 | 105 | 28.2 | 6 | 100 | 3 | 1000 | 700 | 500 | - | 105°C |
| TCJA476M006#0200 | A | 47 | 6.3 | 85 | 5 | 105 | 28.2 | 6 | 200 | 3 | 700 | 500 | 300 | - | 105°C |
| TCJB476M006#0070 | B | 47 | 6.3 | 85 | 4 | 125 | 28.2 | 6 | 70 | 3 | 1300 | 900 | 600 | 300 | 125°C |
| TCJK476M006#0150 | K | 47 | 6.3 | 85 | 5 | 105 | 28.2 | 6 | 150 | 3 | 800 | 600 | 400 | - | 105°C |
| TCJK476M006#0200 | K | 47 | 6.3 | 85 | 5 | 105 | 28.2 | 6 | 200 | 3 | 700 | 500 | 300 | - | 105°C |
| TCJA476M006#0400 | K | 47 | 6.3 | 85 | 5 | 105 | 28.2 | 6 | 400 | 3 | 500 | 400 | 200 | - | 105°C |
| TCJP476M006#0500 | P | 47 | 6.3 | 85 | 5 | 105 | 28.2 | 10 | 500 | 3 | 400 | 300 | 200 | - | 105°C |
| TCJR476M006#0500 | R | 47 | 6.3 | 85 | 5 | 105 | 28.2 | 10 | 500 | 3 | 400 | 300 | 200 | - | 105°C |
| TCJT476M006#0055 | T | 47 | 6.3 | 85 | 5 | 105 | 28.2 | 8 | 55 | 3 | 1300 | 900 | 600 | - | 105°C |
| TCJT476M006#0070 | T | 47 | 6.3 | 85 | 5 | 105 | 28.2 | 8 | 70 | 3 | 1200 | 800 | 500 | - | 105°C |
| TCJT476M006#0069 | T | 47 | 6.3 | 85 | 5 | 105 | 20 | 8 | 69 | 3 | 1200 | 800 | 500 | - | 105°C |
| TCJT476M006#0080 | T | 47 | 6.3 | 85 | 5 | 105 | 28.2 | 8 | 80 | 3 | 1100 | 800 | 500 | - | 105°C |
| TCJT476M006#0120 | T | 47 | 6.3 | 85 | 5 | 105 | 28.2 | 8 | 120 | 3 | 900 | 600 | 400 | - | 105°C |
| TCJB686M006#0055 | B | 68 | 6.3 | 85 | 4 | 125 | 40.8 | 8 | 55 | 3 | 1500 | 1100 | 700 | 400 | 125°C |
| TCJB686M006#0070 | B | 68 | 6.3 | 85 | 4 | 125 | 40.8 | 8 | 70 | 3 | 1300 | 900 | 600 | 300 | 125°C |
| TCJC686M006#0100 | C | 68 | 6.3 | 85 | 4 | 125 | 40.8 | 6 | 100 | 3 | 1300 | 900 | 600 | 300 | 125°C |
| TCJT686M006#0200 | T | 68 | 6.3 | 85 | 5 | 105 | 40.8 | 8 | 200 | 3 | 700 | 500 | 300 | - | 105°C |
| TCJA107M006#0100 | A | 100 | 6.3 | 85 | 6.3 | 85 | 60 | 10 | 100 | 3 | 1000 | 700 | - | - | 85°C |
| TCJA107M006#0150 | A | 100 | 6.3 | 85 | 6.3 | 85 | 60 | 10 | 150 | 3 | 800 | 600 | - | - | 85°C |
| TCJB107M006#0045 | B | 100 | 6.3 | 85 | 5 | 105 | 60 | 10 | 45 | 3 | 1700 | 1200 | 800 | - | 105°C |
| TCJB107M006#0055 | B | 100 | 6.3 | 85 | 5 | 105 | 60 | 10 | 55 | 3 | 1500 | 1100 | 700 | - | 105°C |
| TCJB107M006#0069 | B | 100 | 6.3 | 85 | 5 | 105 | 60 | 10 | 69 | 3 | 1300 | 900 | 600 | - | 105°C |
| TCJB107M006#0070 | B | 100 | 6.3 | 85 | 5 | 105 | 60 | 10 | 70 | 3 | 1300 | 900 | 600 | - | 105°C |
| TCJT107M006#0070 | T | 100 | 6.3 | 85 | 5 | 105 | 60 | 10 | 70 | 3 | 1200 | 800 | 500 | - | 105°C |
| TCJT107M006#0200 | T | 100 | 6.3 | 85 | 5 | 105 | 60 | 10 | 200 | 3 | 700 | 500 | 300 | - | 105°C |
| TCJB157M006#0035 | B | 150 | 6.3 | 85 | 5 | 105 | 90 | 10 | 35 | 3 | 1900 | 1300 | 900 | - | 105°C |
| TCJB157M006#0045 | B | 150 | 6.3 | 85 | 5 | 105 | 90 | 10 | 45 | 3 | 1700 | 1200 | 800 | - | 105°C |
| TCJB157M006#0055 | B | 150 | 6.3 | 85 | 5 | 105 | 90 | 10 | 55 | 3 | 1500 | 1100 | 700 | - | 105°C |
| TCJB157M006#0069 | B | 150 | 6.3 | 85 | 5 | 105 | 90 | 10 | 69 | 3 | 1300 | 900 | 600 | - | 105°C |
| TCJB157M006#0070 | B | 150 | 6.3 | 85 | 5 | 105 | 90 | 10 | 70 | 3 | 1300 | 900 | 600 | - | 105°C |
| TCJD157M006#0015 | D | 150 | 6.3 | 105 | 6.3 | 105 | 90 | 6 | 15 | 3 | 3900 | 2700 | 1800 | - | 105°C |
| TCJD157M006#0025 | D | 150 | 6.3 | 105 | 6.3 | 105 | 90 | 6 | 25 | 3 | 3000 | 2100 | 1400 | - | 105°C |
| TCJD157M006#0040 | D | 150 | 6.3 | 105 | 6.3 | 105 | 90 | 6 | 40 | 3 | 2400 | 1700 | 1100 | - | 105°C |
| TCJH157M006#0200 | H | 150 | 6.3 | 85 | 5 | 105 | 90 | 6 | 200 | 3 | 700 | 500 | 300 | - | 105°C |
| TCJW157M006#0040 | W | 150 | 6.3 | 85 | 5 | 105 | 90 | 6 | 40 | 3 | 1800 | 1300 | 800 | - | 105°C |
| TCJW157M006#0070 | W | 150 | 6.3 | 85 | 5 | 105 | 90 | 6 | 70 | 3 | 1400 | 1000 | 600 | - | 105°C |
| TCJY157M006#0015 | Y | 150 | 6.3 | 105 | 6.3 | 105 | 90 | 6 | 15 | 3 | 3500 | 2500 | 1600 | - | 105°C |
| TCJY157M006#0025 | Y | 150 | 6.3 | 85 | 5 | 105 | 90 | 6 | 25 | 3 | 2700 | 1900 | 1200 | - | 105°C |
| TCJY157M006#0040 | Y | 150 | 6.3 | 85 | 5 | 105 | 90 | 6 | 40 | 3 | 2200 | 1500 | 1000 | - | 105°C |
| TCJB227M006#0070 | B | 220 | 6.3 | 85 | 5 | 105 | 132 | 10 | 70 | 3 | 1300 | 900 | 600 | - | 105°C |
| TCJB227M006#0200 | B | 220 | 6.3 | 85 | 5 | 105 | 132 | 10 | 200 | 3 | 800 | 600 | 400 | - | 105°C |
| TCJD227M006#0025 | D | 220 | 6.3 | 85 | 5 | 105 | 132 | 6 | 25 | 3 | 3000 | 2100 | 1400 | - | 105°C |
| TCJD227M006#0035 | D | 220 | 6.3 | 85 | 5 | 105 | 132 | 6 | 35 | 3 | 2500 | 1800 | 1100 | - | 105°C |
| TCJD227M006#0040 | D | 220 | 6.3 | 85 | 5 | 105 | 132 | 6 | 40 | 3 | 2400 | 1700 | 1100 | - | 105°C |
| TCJD227M006#0050 | D | 220 | 6.3 | 85 | 5 | 105 | 132 | 6 | 50 | 3 | 2100 | 1500 | 900 | - | 105°C |
| TCJY227M006#0025 | Y | 220 | 6.3 | 85 | 5 | 105 | 132 | 6 | 25 | 3 | 2700 | 1900 | 1200 | - | 105°C |
| TCJY227M006#0035 | Y | 220 | 6.3 | 85 | 5 | 105 | 132 | 6 | 35 | 3 | 2300 | 1600 | 1000 | - | 105°C |
| TCJY227M006#0040 | Y | 220 | 6.3 | 85 | 5 | 105 | 132 | 6 | 40 | 3 | 2200 | 1500 | 1000 | - | 105°C |
| TCJY227M006#0050 | Y | 220 | 6.3 | 85 | 5 | 105 | 132 | 6 | 50 | 3 | 1900 | 1300 | 900 | - | 105°C |
| TCJD337M006#0025 | D | 330 | 6.3 | 85 | 5 | 105 | 198 | 6 | 25 | 3 | 3000 | 2100 | 1400 | - | 105°C |
| TCJD337M006#0040 | D | 330 | 6.3 | 105 | 6.3 | 105 | 198 | 6 | 40 | 3 | 2400 | 1700 | 1100 | - | 105°C |
| TCJD337M006#0050 | D | 330 | 6.3 | 105 | 6.3 | 105 | 198 | 6 | 50 | 3 | 2100 | 1500 | 900 | - | 105°C |
| TCJY337M006#0025 | Y | 330 | 6.3 | 85 | 5 | 105 | 198 | 12 | 25 | 3 | 2700 | 1900 | 1200 | - | 105°C |
| TCJY337M006#0040 | Y | 330 | 6.3 | 85 | 5 | 105 | 198 | 12 | 40 | 3 | 2200 | 1500 | 1000 | - | 105°C |
| TCJY337M006#0050 | Y | 330 | 6.3 | 85 | 5 | 105 | 198 | 12 | 50 | 3 | 1900 | 1300 | 900 | - | 105°C |
| TCJX477M006#0055 | X | 470 | 6.3 | 85 | 5 | 105 | 282 | 6 | 55 | 3 | 1800 | 1300 | 800 | - | 105°C |
| TCJX477M006#0100 | X | 470 | 6.3 | 85 | 5 | 105 | 282 | 6 | 100 | 3 | 1300 | 900 | 600 | - | 105°C |
| 10 Volt @ 85°C | | | | | | | | | | | | | | | |
| TCJK475M010#0500 | K | 4.7 | 10 | 85 | 8 | 105 | 4.7 | 6 | 500 | 3 | 400 | 300 | 200 | - | 105°C |
| TCJR475M010#0500 | R | 4.7 | 10 | 85 | 8 | 105 | 4.7 | 6 | 500 | 3 | 400 | 300 | 200 | - | 105°C |
| TCJA106M010#0300 | A | 10 | 10 | 85 | 7 | 125 | 10 | 6 | 300 | 3 | 600 | 400 | 300 | 200 | 125°C |
| TCJA156M010#0200 | A | 15 | 10 | 85 | 7 | 125 | 15 | 6 | 200 | 3 | 700 | 500 | 300 | 200 | 125°C |
| TCJB226M010#0300 | B | 22 | 10 | 85 | 7 | 125 | 22 | 6 | 300 | 3 | 600 | 400 | 300 | 200 | 125°C |
| TCJT226M010#0070 | T | 22 | 10 | 85 | 8 | 105 | 22 | 6 | 70 | 3 | 1200 | 800 | 500 | - | 105°C |
| TCJT226M010#0150 | T | 22 | 10 | 85 | 8 | 105 | 22 | 6 | 150 | 3 | 800 | 600 | 400 | - | 105°C |
| TCJB336M010#0070 | B | 33 | 10 | 85 | 7 | 125 | 33 | 6 | 70 | 3 | 1300 | 900 | 600 | 300 | 125°C |
| TCJB336M010#0200 | B | 33 | 10 | 85 | 7 | 125 | 33 | 6 | 200 | 3 | 800 | 600 | 400 | 200 | 125°C |



TCJ Series



Tantalum Solid Electrolytic Chip Capacitors with Conductive Polymer Electrode

RATINGS & PART NUMBER REFERENCE

| AVX Part No. | Case Size | Cap (µF) | Rated Voltage (V) | Rated Temp. (°C) | Category Voltage (V) | Category Temp. (°C) | DCL (µA) Max. | DF % Max. | ESR Max. (mΩ) @ 100kHz | MSL | 100kHz RMS Current (mA) | | | | Product Category |
|-----------------------|-----------|----------|-------------------|------------------|----------------------|---------------------|---------------|-----------|------------------------|-----|-------------------------|------|-------|-------|------------------|
| | | | | | | | | | | | 25°C | 85°C | 105°C | 125°C | |
| TCJC336M010#0100 | C | 33 | 10 | 85 | 7 | 125 | 33 | 6 | 100 | 3 | 1300 | 900 | 600 | 300 | 125°C |
| TCJT336M010#0070 | T | 33 | 10 | 85 | 8 | 105 | 33 | 6 | 70 | 3 | 1200 | 800 | 500 | - | 105°C |
| TCJT336M010#0150 | T | 33 | 10 | 85 | 8 | 105 | 33 | 6 | 150 | 3 | 800 | 600 | 400 | - | 105°C |
| TCJB476M010#0070 | B | 47 | 10 | 85 | 8 | 105 | 47 | 6 | 70 | 3 | 1300 | 900 | 600 | - | 105°C |
| TCJC476M010#0100 | C | 47 | 10 | 85 | 7 | 125 | 47 | 6 | 100 | 3 | 1300 | 900 | 600 | 300 | 125°C |
| TCJD686M010#0045 | D | 68 | 10 | 85 | 8 | 105 | 68 | 6 | 45 | 3 | 2200 | 1500 | 1000 | - | 105°C |
| TCJD686M010#0055 | D | 68 | 10 | 85 | 8 | 105 | 68 | 6 | 55 | 3 | 2000 | 1400 | 900 | - | 105°C |
| TCJY686M010#0045 | Y | 68 | 10 | 85 | 8 | 105 | 68 | 6 | 45 | 3 | 2000 | 1400 | 900 | - | 105°C |
| TCJY686M010#0055 | Y | 68 | 10 | 85 | 8 | 105 | 68 | 6 | 55 | 3 | 1800 | 1300 | 800 | - | 105°C |
| TCJD107M010#0045 | D | 100 | 10 | 85 | 8 | 105 | 100 | 6 | 45 | 3 | 2200 | 1500 | 1000 | - | 105°C |
| TCJD107M010#0055 | D | 100 | 10 | 85 | 8 | 105 | 100 | 6 | 55 | 3 | 2000 | 1400 | 900 | - | 105°C |
| TCJD107M010#0080 | D | 100 | 10 | 85 | 8 | 105 | 100 | 6 | 80 | 3 | 1700 | 1200 | 800 | - | 105°C |
| TCJY107M010#0025 | Y | 100 | 10 | 85 | 8 | 105 | 100 | 6 | 25 | 3 | 2700 | 1900 | 1200 | - | 105°C |
| TCJY107M010#0045 | Y | 100 | 10 | 85 | 8 | 105 | 100 | 6 | 45 | 3 | 2000 | 1400 | 900 | - | 105°C |
| TCJY107M010#0055 | Y | 100 | 10 | 85 | 8 | 105 | 100 | 6 | 55 | 3 | 1800 | 1300 | 800 | - | 105°C |
| TCJD157M010#0025 | D | 150 | 10 | 85 | 8 | 105 | 150 | 6 | 25 | 3 | 3000 | 2100 | 1400 | - | 105°C |
| TCJD157M010#0040 | D | 150 | 10 | 85 | 8 | 105 | 150 | 6 | 40 | 3 | 2400 | 1700 | 1100 | - | 105°C |
| TCJD157M010#0045 | D | 150 | 10 | 85 | 8 | 105 | 150 | 6 | 45 | 3 | 2200 | 1500 | 1000 | - | 105°C |
| TCJD157M010#0055 | D | 150 | 10 | 85 | 8 | 105 | 150 | 6 | 55 | 3 | 2000 | 1400 | 900 | - | 105°C |
| TCJY157M010#0025 | Y | 150 | 10 | 85 | 8 | 105 | 150 | 6 | 25 | 3 | 2700 | 1900 | 1200 | - | 105°C |
| TCJY157M010#0040 | Y | 150 | 10 | 85 | 8 | 105 | 150 | 6 | 40 | 3 | 2200 | 1500 | 1000 | - | 105°C |
| TCJY157M010#0045 | Y | 150 | 10 | 85 | 8 | 105 | 150 | 6 | 45 | 3 | 2000 | 1400 | 900 | - | 105°C |
| TCJY157M010#0055 | Y | 150 | 10 | 85 | 8 | 105 | 150 | 6 | 55 | 3 | 1800 | 1300 | 800 | - | 105°C |
| TCJD227M010#0025 | D | 220 | 10 | 85 | 8 | 105 | 220 | 6 | 25 | 3 | 3000 | 2100 | 1400 | - | 105°C |
| TCJD227M010#0040 | D | 220 | 10 | 85 | 8 | 105 | 220 | 6 | 40 | 3 | 2400 | 1700 | 1100 | - | 105°C |
| TCJD227M010#0050 | D | 220 | 10 | 85 | 8 | 105 | 220 | 6 | 50 | 3 | 2100 | 1500 | 900 | - | 105°C |
| TCJY227M010#0025 | Y | 220 | 10 | 85 | 8 | 105 | 220 | 6 | 25 | 3 | 2700 | 1900 | 1200 | - | 105°C |
| TCJY227M010#0040 | Y | 220 | 10 | 85 | 8 | 105 | 220 | 6 | 40 | 3 | 2200 | 1500 | 1000 | - | 105°C |
| TCJY227M010#0050 | Y | 220 | 10 | 85 | 8 | 105 | 220 | 6 | 50 | 3 | 1900 | 1300 | 900 | - | 105°C |
| 16 Volt @ 85°C | | | | | | | | | | | | | | | |
| TCJA685M016#0200 | A | 6.8 | 16 | 85 | 10 | 125 | 10.9 | 6 | 200 | 3 | 700 | 500 | 300 | 200 | 125°C |
| TCJA106M016#0200 | A | 10 | 16 | 85 | 10 | 125 | 16 | 6 | 200 | 3 | 700 | 500 | 300 | 200 | 125°C |
| TCJB106M016#0200 | B | 10 | 16 | 85 | 10 | 125 | 16 | 6 | 200 | 3 | 800 | 600 | 400 | 200 | 125°C |
| TCJT106M016#0150 | T | 10 | 16 | 85 | 10 | 125 | 16 | 6 | 150 | 3 | 800 | 600 | 400 | 200 | 125°C |
| TCJT106M016#0200 | T | 10 | 16 | 85 | 10 | 125 | 16 | 6 | 200 | 3 | 700 | 500 | 300 | 200 | 125°C |
| TCJB156M016#0150 | B | 15 | 16 | 85 | 10 | 125 | 24 | 6 | 150 | 3 | 900 | 600 | 400 | 200 | 125°C |
| TCJB226M016#0150 | B | 22 | 16 | 85 | 10 | 125 | 35.2 | 6 | 150 | 3 | 900 | 600 | 400 | 200 | 125°C |
| TCJY336M016#0045 | Y | 33 | 16 | 105 | 16 | 105 | 52.8 | 6 | 45 | 3 | 2000 | 1400 | 900 | - | 105°C |
| TCJY336M016#0060 | Y | 33 | 16 | 105 | 16 | 105 | 52.8 | 6 | 60 | 3 | 1800 | 1300 | 800 | - | 105°C |
| TCJY336M016#0070 | Y | 33 | 16 | 105 | 16 | 105 | 52.8 | 6 | 70 | 3 | 1600 | 1100 | 700 | - | 105°C |
| TCJX476M016#0045 | X | 47 | 16 | 105 | 16 | 105 | 75.2 | 6 | 45 | 3 | 2000 | 1400 | 900 | - | 105°C |
| TCJX476M016#0070 | X | 47 | 16 | 105 | 16 | 105 | 75.2 | 6 | 70 | 3 | 1600 | 1100 | 700 | - | 105°C |
| TCJY476M016#0045 | Y | 47 | 16 | 105 | 16 | 105 | 75.2 | 6 | 45 | 3 | 2000 | 1400 | 900 | - | 105°C |
| TCJY476M016#0070 | Y | 47 | 16 | 105 | 16 | 105 | 75.2 | 6 | 70 | 3 | 1600 | 1100 | 700 | - | 105°C |
| TCJD686M016#0050 | D | 68 | 16 | 105 | 16 | 105 | 108.8 | 6 | 50 | 3 | 2100 | 1500 | 900 | - | 105°C |
| TCJY686M016#0050 | Y | 68 | 16 | 105 | 16 | 105 | 108.8 | 6 | 50 | 3 | 1900 | 1300 | 900 | - | 105°C |
| TCJD107M016#0050 | D | 100 | 16 | 105 | 16 | 105 | 160 | 6 | 50 | 3 | 2100 | 1500 | 900 | - | 105°C |
| TCJE107M016#0040 | E | 100 | 16 | 105 | 16 | 105 | 160 | 6 | 40 | 3 | 2500 | 1800 | 1100 | - | 105°C |
| TCJY107M016#0050 | Y | 100 | 16 | 105 | 16 | 105 | 160 | 6 | 50 | 3 | 1900 | 1300 | 900 | - | 105°C |
| TCJD157M016#0040 | D | 150 | 16 | 85 | 16 | 85 | 240 | 6 | 40 | 3 | 2400 | 1700 | - | - | 85°C |
| TCJD157M016#0050 | D | 150 | 16 | 85 | 16 | 85 | 240 | 6 | 50 | 3 | 2100 | 1500 | - | - | 85°C |
| TCJE157M016#0040 | E | 150 | 16 | 105 | 16 | 105 | 240 | 6 | 40 | 3 | 2500 | 1800 | 1100 | - | 105°C |
| TCJY157M016#0040 | Y | 150 | 16 | 85 | 16 | 85 | 240 | 6 | 40 | 3 | 2200 | 1500 | - | - | 85°C |
| TCJY157M016#0050 | Y | 150 | 16 | 85 | 16 | 85 | 240 | 6 | 50 | 3 | 1900 | 1300 | - | - | 85°C |
| 20 Volt @ 85°C | | | | | | | | | | | | | | | |
| TCJB226M020#0090 | B | 22 | 20 | 85 | 16 | 105 | 44 | 6 | 90 | 3 | 1200 | 800 | 500 | - | 105°C |
| TCJB226M020#0150 | B | 22 | 20 | 85 | 16 | 105 | 44 | 6 | 150 | 3 | 900 | 600 | 400 | - | 105°C |
| TCJY226M020#0070 | Y | 22 | 20 | 105 | 20 | 105 | 44 | 6 | 70 | 3 | 1600 | 1100 | 700 | - | 105°C |
| TCJY336M020#0070 | Y | 33 | 20 | 105 | 20 | 105 | 66 | 6 | 70 | 3 | 1600 | 1100 | 700 | - | 105°C |
| TCJD476M020#0055 | D | 47 | 20 | 105 | 20 | 105 | 94 | 6 | 55 | 3 | 2000 | 1400 | 900 | - | 105°C |
| TCJX476M020#0055 | X | 47 | 20 | 85 | 16 | 105 | 94 | 6 | 55 | 3 | 1800 | 1300 | 800 | - | 105°C |
| TCJX476M020#0070 | X | 47 | 20 | 85 | 16 | 105 | 94 | 6 | 70 | 3 | 1600 | 1100 | 700 | - | 105°C |
| TCJY476M020#0070 | Y | 47 | 20 | 105 | 20 | 105 | 94 | 6 | 70 | 3 | 1600 | 1100 | 700 | - | 105°C |
| TCJD686M020#0055 | D | 68 | 20 | 85 | 16 | 105 | 136 | 6 | 55 | 3 | 2000 | 1400 | 900 | - | 105°C |
| TCJE686M020#0045 | E | 68 | 20 | 105 | 20 | 105 | 136 | 6 | 45 | 3 | 2400 | 1700 | 1100 | - | 105°C |
| TCJD107M020#0055 | D | 100 | 20 | 85 | 16 | 105 | 200 | 6 | 55 | 3 | 2000 | 1400 | 900 | - | 105°C |
| TCJE107M020#0045 | E | 100 | 20 | 85 | 16 | 105 | 200 | 6 | 45 | 3 | 2400 | 1700 | 1100 | - | 105°C |
| 25 Volt @ 85°C | | | | | | | | | | | | | | | |
| TCJP105M025#0500 | P | 1.0 | 25 | 105 | 25 | 105 | 2.5 | 6 | 500 | 3 | 400 | 300 | 200 | - | 105°C |
| TCJB475M025#0100 | B | 4.7 | 25 | 85 | 20 | 105 | 11.8 | 6 | 100 | 3 | 1100 | 800 | 500 | - | 105°C |
| TCJB475M025#0150 | B | 4.7 | 25 | 85 | 20 | 105 | 11.8 | 6 | 150 | 3 | 900 | 600 | 400 | - | 105°C |
| TCJB685M025#0090 | B | 6.8 | 25 | 105 | 25 | 105 | 17 | 6 | 90 | 3 | 1200 | 800 | 500 | - | 105°C |
| TCJB685M025#0150 | B | 6.8 | 25 | 85 | 20 | 105 | 17 | 6 | 150 | 3 | 900 | 600 | 400 | - | 105°C |
| TCJT685M025#0100 | T | 6.8 | 25 | 85 | 20 | 105 | 17 | 6 | 100 | 3 | 1000 | 700 | 500 | - | 105°C |
| TCJT685M025#0150 | T | 6.8 | 25 | 85 | 20 | 105 | 17 | 6 | 150 | 3 | 800 | 600 | 400 | - | 105°C |



TCJ Series



Tantalum Solid Electrolytic Chip Capacitors with Conductive Polymer Electrode

RATINGS & PART NUMBER REFERENCE

| AVX Part No. | Case Size | Cap (µF) | Rated Voltage (V) | Rated Temp. (°C) | Category Voltage (V) | Category Temp. (°C) | DCL (µA) Max. | DF % Max. | ESR Max. (mΩ) @ 100kHz | MSL | 100kHz RMS Current (mA) | | | | Product Category |
|------------------------|-----------|----------|-------------------|------------------|----------------------|---------------------|---------------|-----------|------------------------|-----|-------------------------|------|-------|-------|------------------|
| | | | | | | | | | | | 25°C | 85°C | 105°C | 125°C | |
| TCJE685M063#0100 | E | 6.8 | 63 | 85 | 50 | 105 | 42.8 | 6 | 100 | 3 | 1600 | 1100 | 700 | - | 105°C |
| TCJE685M063#0150 | E | 6.8 | 63 | 85 | 50 | 105 | 42.8 | 6 | 150 | 3 | 1300 | 900 | 600 | - | 105°C |
| TCJE106M063#0100 | E | 10 | 63 | 85 | 50 | 105 | 63 | 6 | 100 | 3 | 1600 | 1100 | 700 | - | 105°C |
| TCJE106M063#0150 | E | 10 | 63 | 85 | 50 | 105 | 63 | 6 | 150 | 3 | 1300 | 900 | 600 | - | 105°C |
| 75 Volt @ 85°C | | | | | | | | | | | | | | | |
| TCJD475M075#0150 | D | 4.7 | 75 | 85 | 60 | 105 | 35.3 | 6 | 150 | 3 | 1200 | 800 | 500 | - | 105°C |
| TCJD685M075#0120 | D | 6.8 | 75 | 85 | 60 | 105 | 51 | 6 | 120 | 3 | 1400 | 1000 | 600 | - | 105°C |
| 100 Volt @ 85°C | | | | | | | | | | | | | | | |
| TCJD475M100#0250 | D | 4.7 | 100 | 85 | 80 | 105 | 47 | 8 | 250 | 3 | 900 | 600 | 400 | - | 105°C |
| 125 Volt @ 85°C | | | | | | | | | | | | | | | |
| TCJD335M125#0250 | D | 3.3 | 125 | 85 | 100 | 105 | 41.2 | 8 | 250 | 3 | 900 | 600 | 400 | - | 105°C |

Moisture Sensitivity Level (MSL) is defined according to J-STD-020.

All technical data relates to an ambient temperature of +25°C. Capacitance and DF are measured at 120Hz, 0.5RMS with DC bias of 2.2 volts. DCL is measured at rated voltage after 5 minutes.

ESR allowed to move up to 1.25 times catalog limit post mounting.

For typical weight and composition see page 214.

NOTE: AVX reserves the right to supply a higher voltage rating or tighter tolerance part in the same case size, to the same reliability standards.

PRODUCT CATEGORY 125°C

| TEST | 125°C series (Temperature range -55°C to +125°C) | | | | | | | | | |
|------------------------------|--|---------------|---------------|--------------------|----------------------------------|-----------|-------|-----------|------------|-------|
| | Condition | | | Characteristics | | | | | | |
| Endurance | Determine after application of rated voltage for 2000 +48/-0 hours at 85±2°C and then leaving 1-2 hours at room temperature. Also determine of 125°C temperature, category voltage for 2000 +48/-0 hours and then leaving 1-2 hours at room temperature. Power supply impedance to be ≤0.1Ω/V. | | | Visual examination | no visible damage | | | | | |
| | | | | DCL | 1.25 x initial limit | | | | | |
| | | | | ΔC/C | within +20/-30% of initial value | | | | | |
| | | | | DF | 1.5 x initial limit | | | | | |
| | | | | ESR | 2 x initial limit | | | | | |
| Storage Life | 125°C, 0V, 2000h | | | Visual examination | no visible damage | | | | | |
| | | | | DCL | 2 x initial limit | | | | | |
| | | | | ΔC/C | within ±20% of initial value | | | | | |
| | | | | DF | 1.5 x initial limit | | | | | |
| | | | | ESR | 2 x initial limit | | | | | |
| Humidity | Determine after storage without applied voltage at 65±2°C and 95±2% relative humidity for 500 hours and then recovery 1-2 hours at room temperature. | | | Visual examination | no visible damage | | | | | |
| | | | | DCL | 3 x initial limit | | | | | |
| | | | | ΔC/C | within +30/-20% of initial value | | | | | |
| | | | | DF | 1.5 x initial limit | | | | | |
| | | | | ESR | 2 x initial limit | | | | | |
| Temperature Stability | Step | Temperature°C | Duration(min) | | +20°C | -55°C | +20°C | +85°C | +125°C | +20°C |
| | 1 | +20±2 | 15 | | | | | | | |
| | 2 | -55+0/-3 | 15 | DCL | IL* | n/a | IL* | 10 x IL* | 12.5 x IL* | IL* |
| | 3 | +20±2 | 15 | ΔC/C | n/a | +0/-20% | ±5% | +20/-0% | +30/-0% | ±5% |
| | 4 | +85+3/-0 | 15 | DF | IL* | 1.5 x IL* | IL* | 1.5 x IL* | 2 x IL* | IL* |
| | 5 | +125+3/-0 | 15 | | | | | | | |
| | 6 | +20±2 | 15 | | | | | | | |
| Surge Voltage | Test temperature: 125°C+3/0°C Test voltage: Category voltage at 125°C Surge voltage: 1.3 x category voltage at 125°C Series protection resistance 1000±100Ω Discharge resistance: 1000Ω Number of cycles: 1000x Cycle duration: 6 min; 30 sec charge, 5 min 30 sec discharge | | | Visual examination | no visible damage | | | | | |
| | | | | DCL | initial limit | | | | | |
| | | | | ΔC/C | within +20/-30% of initial value | | | | | |
| | | | | DF | 1.25 x initial limit | | | | | |

*Initial Limit

Tantalum Solid Electrolytic Chip Capacitors with Conductive Polymer Electrode

PRODUCT CATEGORY 105°C

| TEST | 105°C series (Temperature range -55°C to +105°C) | | | | | | | |
|-----------------------|--|---------------|---------------|----------------------------|----------------------------------|--|--|--|
| | Condition | | | Characteristics | | | | |
| Endurance | Determine after application of rated voltage for 2000 +48/-0 hours at 85±2°C and then leaving 1-2 hours at room temperature. Also determine after application of 105°C temperature, category voltage for 2000 +48/-0 hours and then leaving 1-2 hours at room temperature. Power supply impedance to be ≤0.1Ω/V. | | | Visual examination | no visible damage | | | |
| | | | | DCL | 1.25 x initial limit | | | |
| | | | | ΔC/C | within +20/-30% of initial value | | | |
| | | | | DF | 1.5 x initial limit | | | |
| | | | | ESR | 2 x initial limit | | | |
| Storage Life | 105°C, 0V, 2000h | | | Visual examination | no visible damage | | | |
| | | | | DCL (V _R ≤ 75V) | 1.25 x initial limit | | | |
| | | | | DCL (V _R > 75V) | 2 x initial limit | | | |
| | | | | ΔC/C | within ±20% of initial value | | | |
| | | | | DF | 1.5 x initial limit | | | |
| | | | | ESR | 2 x initial limit | | | |
| Humidity | Determine after storage without applied voltage at 65±2°C and 95±2% relative humidity for 500 hours and then recovery 1-2 hours at room temperature. | | | Visual examination | no visible damage | | | |
| | | | | DCL | 3 x initial limit | | | |
| | | | | ΔC/C | within +30/-20% of initial value | | | |
| | | | | DF | 1.5 x initial limit | | | |
| | | | | ESR | 2 x initial limit | | | |
| Temperature Stability | Step | Temperature°C | Duration(min) | | | | | |
| | 1 | +20±2 | 15 | | | | | |
| | 2 | -55+0/-3 | 15 | | | | | |
| | 3 | +20±2 | 15 | | | | | |
| | 4 | +85+3/-0 | 15 | | | | | |
| | 5 | +105+3/-0 | 15 | | | | | |
| | 6 | +20±2 | 15 | | | | | |
| Surge Voltage | Test temperature: 105°C+3/0°C Test voltage: Category voltage at 105°C Surge voltage: 1.3 x category voltage at 105°C Series protection resistance 1000±100Ω Discharge resistance: 1000Ω Number of cycles: 1000x Cycle duration: 6 min; 30 sec charge, 5 min 30 sec discharge | | | Visual examination | no visible damage | | | |
| | | | | DCL | initial limit | | | |
| | | | | ΔC/C | within +20/-30% of initial value | | | |
| | | | | DF | 1.25 x initial limit | | | |

*Initial Limit

PRODUCT CATEGORY 85°C

| TEST | 85°C series (Temperature range -55°C to +85°C) | | | | | | | |
|-----------------------|--|---------------|---------------|--------------------|--|--|--|--------------------|
| | Condition | | | Characteristics | | | | |
| Endurance | Determine after application of rated voltage for 2000 +48/-0 hours at 85±2°C and then leaving 1-2 hours at room temperature. Power supply impedance to be ≤0.1Ω/V. | | | Visual examination | no visible damage | | | |
| | | | | DCL | 1.25 x initial limit | | | |
| | | | | ΔC/C | within +20/-30% of initial value | | | |
| | | | | DF | 1.5 x initial limit | | | |
| | | | | ESR | 2 x initial limit | | | |
| Storage Life | 85°C, 0V, 2000h | | | Visual examination | no visible damage | | | |
| | | | | DCL | 1.25 x initial limit | | | |
| | | | | ΔC/C | within ±20% of initial value | | | |
| | | | | DF | 1.5 x initial limit | | | |
| | | | | ESR | 2 x initial limit | | | |
| | | | | Humidity | Determine after storage without applied voltage at 65±2°C and 95±2% relative humidity for 500 hours and then recovery 1-2 hours at room temperature. | | | Visual examination |
| DCL | 5 x initial limit | | | | | | | |
| ΔC/C | within +40/-20% of initial value | | | | | | | |
| DF | 1.5 x initial limit | | | | | | | |
| ESR | 2 x initial limit | | | | | | | |
| Temperature Stability | Step | Temperature°C | Duration(min) | | | | | |
| | 1 | +20±2 | 15 | | | | | |
| | 2 | -55+0/-3 | 15 | | | | | |
| | 3 | +20±2 | 15 | | | | | |
| | 4 | +85+3/-0 | 15 | | | | | |
| | 5 | +20±2 | 15 | | | | | |
| Surge Voltage | Test temperature: 85+3/0°C Test voltage: Rated voltage Surge voltage: 1.3 x rated voltage Series protection resistance 1000±100Ω. Discharge resistance: 1000Ω Number of cycles: 1000x Cycle duration: 6 min; 30 sec charge, 5 min 30 sec discharge | | | Visual examination | no visible damage | | | |
| | | | | DCL | initial limit | | | |
| | | | | ΔC/C | within +20/-30% of initial value | | | |
| | | | | DF | 1.25 x initial limit | | | |

*Initial Limit

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9