





Bidirectional Asymmetrical (BiAs) Single Line ESD Protection Diode in LLP1006-2L



FEATURES

- Ultra compact LLP1006-2L
- Low package height = 0.4 mm
- 1-line ESD protection
- Working range -6 V up to +10 V or -10 V up to +6 V
- Low leakage current < 0.1 μ A
- Low load capacitance typical $C_D = 5.4$ pF at 0 V
- ESD immunity acc. IEC 61000-4-2 ± 18 kV contact discharge ± 18 kV air discharge
- Tin plated exposed side wall of leadframe; soldering can be checked by standard vision inspection; (AOI = Automated Outgoing Inspection); no X-ray necessary
- e3 - Sn
- PATENT(S): www.vishay.com/patents
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



MARKING (example only)



Bar = pin 1 marking
 Y = type code (see table below)
 X = date code

DESIGN SUPPORT TOOLS click logo to get started



| ORDERING INFORMATION | | | |
|----------------------|--------------------|---|------------------------|
| DEVICE NAME | ORDERING CODE | TAPED UNITS PER REEL (8 mm TAPE ON 7" REEL) | MINIMUM ORDER QUANTITY |
| VCUT0610AHD1 | VCUT0610AHD1-G3-08 | 10 000 | 100 000 |

| PACKAGE DATA | | | | | | |
|--------------|--------------|-----------|---------|--------------------------------------|-----------------------------------|--------------------------|
| DEVICE NAME | PACKAGE NAME | TYPE CODE | WEIGHT | MOLDING COMPOUND FLAMMABILITY RATING | MOISTURE SENSITIVITY LEVEL | SOLDERING CONDITIONS |
| VCUT0610AHD1 | LLP1006-2L | 6 | 0.72 mg | UL 94 V-0 | MSL level 1 (according J-STD-020) | 260 °C/10 s at terminals |


| ABSOLUTE MAXIMUM RATINGS VCUT0610AHD1 | | | | |
|---------------------------------------|---|-----------|-------------|------|
| PARAMETER | TEST CONDITIONS | SYMBOL | VALUE | UNIT |
| Peak pulse current | Pin 1 to pin 2 acc. IEC 61000-4-5, 8/20 μ s/single shot; $T_{amb} = 25$ °C | I_{PPM} | 3.2 | A |
| | Pin 2 to pin 1 acc. IEC 61000-4-5, 8/20 μ s/single shot; $T_{amb} = 25$ °C | | 2.3 | A |
| Peak pulse power | Pin 1 to pin 2 acc. IEC 61000-4-5, 8/20 μ s/single shot; $T_{amb} = 25$ °C | P_{PP} | 54 | W |
| | Pin 2 to pin 1 acc. IEC 61000-4-5, 8/20 μ s/single shot; $T_{amb} = 25$ °C | | 64 | W |
| ESD immunity | Contact discharge acc. IEC 61000-4-2; 10 pulses; $T_{amb} = 25$ °C | V_{ESD} | ± 18 | kV |
| | Air discharge acc. IEC 61000-4-2; 10 pulses | | ± 18 | kV |
| Operating temperature | Junction temperature | T_J | -40 to +125 | °C |
| Storage temperature | | T_{STG} | -55 to +125 | °C |

PATENT(S): www.vishay.com/patents

This Vishay product is protected by one or more United States and international patents.

CUT THE SPIKES WITH VCUT0610AHD1

The VCUT0610AHD1 is a bidirectional but asymmetrical (BiAs) ESD protection device which clamps positive and negative overvoltage transients to ground. Connected between the signal or data line and the ground the VCUT0610AHD1 offers a high isolation (low leakage current, small capacitance) within the specified working range of -6 V to +10 V or -10 V and +6 V. Due to the short leads and small package size of the tiny LLP1006-2L package the line inductance is very low, so that fast transients like an ESD strike can be clamped with minimal over- or undershoots.



| ELECTRICAL CHARACTERISTICS VCUT0610AHD1 (T _{amb} = 25 C°, unless otherwise specified) | | | | | | |
|---|---|----------------------|------|------|------|-------|
| Measured from pin 2 to pin 1 | | | | | | |
| PARAMETER | TEST CONDITIONS/REMARKS | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| Protection paths | Number of lines which can be protected | N _{channel} | - | - | 1 | lines |
| Reverse stand-off voltage | Max. reverse working voltage | V _{RWM} | - | - | 10 | V |
| Reverse voltage | At I _R = 0.1 μA | V _R | 10 | - | - | V |
| Reverse current | At V = 10 V | I _R | - | - | 0.1 | μA |
| Reverse breakdown voltage | At I = 1 mA | V _{BR} | 12 | - | - | V |
| Reverse clamping voltage | At I _{PP} = 1 A; t _p = 8/20 μs | V _C | - | 19 | 23 | V |
| | At I _{PP} = I _{PPM} = 2.3 A; t _p = 8/20 μs | | - | 24 | 28 | V |
| Capacitance | At V = 0 V; f = 1 MHz | C _D | - | 5.4 | 6.5 | pF |
| | At V = 3.3 V; f = 1 MHz | | - | 3.4 | - | pF |

| ELECTRICAL CHARACTERISTICS VCUT0610AHD1 (T _{amb} = 25 C°, unless otherwise specified) | | | | | | |
|---|---|----------------------|------|------|------|-------|
| Measured from pin 1 to pin 2 | | | | | | |
| PARAMETER | TEST CONDITIONS/REMARKS | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| Protection paths | Number of lines which can be protected | N _{channel} | - | - | 1 | lines |
| Reverse stand-off voltage | Max. reverse working voltage | V _{RWM} | - | - | 6 | V |
| Reverse voltage | At I _R = 0.1 μA | V _R | 6 | - | - | V |
| Reverse current | At V = 6 V | I _R | - | - | 0.1 | μA |
| Reverse breakdown voltage | At I = 1 mA | V _{BR} | 6.5 | - | - | V |
| Reverse clamping voltage | At I _{PP} = 1 A; t _p = 8/20 μs | V _C | - | 10.3 | 12 | V |
| | At I _{PP} = I _{PPM} = 3.2 A; t _p = 8/20 μs | | - | 13.8 | 17 | V |
| Capacitance | At V = 0 V; f = 1 MHz | C _D | - | 5.4 | 6.5 | pF |
| | At V = 3.3 V; f = 1 MHz | | - | 4 | - | pF |

TYPICAL CHARACTERISTICS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)




Fig. 1 - ESD Discharge Current Wave Form acc. IEC 61000-4-2 (330 Ω /150 pF)




Fig. 4 - Typical Forward and Reverse Voltage vs. Reverse Current




Fig. 2 - 8/20 μs Peak Pulse Current Wave Form acc. IEC 61000-4-5




Fig. 5 - Typical Clamping Voltage vs. Peak Pulse Current




Fig. 3 - Typical Capacitance vs. Reverse Voltage






Fig. 6 - Typical Peak Clamping Voltage vs. Peak Pulse Current



PACKAGE DIMENSIONS in millimeters (inches): **LLP1006-2L**




Foot print recommendation:



Pad Design Patented:
(©US 9.018.537 B2)

Document no.: S8-V-3906.04-005 (4)
Rev. 7 - Date: 11.May 2016
20812



S8-V-3906.04-017 (4)
02.05.2017
22965



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9