





#### **DUAL P-CHANNEL ENHANCEMENT MODE MOSFET**

### **Product Summary**

V <sub>(BR)DSS</sub>	R <sub>DS(on) max</sub>	<b>Ι</b> <sub>D</sub> Τ <sub>A</sub> = +25°C
-50V	10Ω @ V <sub>GS</sub> = -5V	-130mA

### **Description**

This MOSFET has been designed to minimize the on-state resistance  $(R_{DS(on)})$  and yet maintain superior switching performance, making it ideal for high efficiency power management applications.

## **Applications**

- · General Purpose Interfacing Switch
- · Power Management Functions
- Analog Switch

**SOT363** 




Top View

#### **Features and Benefits**

- Low On-Resistance
- Low Gate Threshold Voltage
- Low Input Capacitance
- Fast Switching Speed
- Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)
- Halogen and Antimony Free. "Green" Device (Note 3)
- Qualified to AEC-Q101 Standards for High Reliability

#### **Mechanical Data**

- Case: SOT363
- Case Material: Molded Plastic. "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Matte Tin Finish annealed over Alloy 42 leadframe (Lead Free Plating). Solderable per MIL-STD-202, Method 208
- Terminal Connections: See Diagram
- Weight: 0.006 grams (approximate)



Top View Internal Schematic


## **Ordering Information** (Note 4)

Part Number	Compliance	Case	Packaging
BSS84DW-7-F	Standard	SOT363	3,000/Tape & Reel
BSS84DWQ-13	Automotive	SOT363	10,000/Tape & Reel
BSS84DWQ-7	Automotive	SOT363	3,000/Tape & Reel

Notes:

- 1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant.
- 2. See http://www.diodes.com/quality/lead\_free.html for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
- 3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
- 4. For packaging details, go to our website at http"//www.diodes.com/products/packages.html

#### **Marking Information**



K84 = Product Type Marking Code

YM = Date Code Marking

Y = Year (ex: N = 2002)

M = Month (ex: 9 = September)

#### Date Code Key

Year	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012
Code	J	K	L	М	N	Р	R	S	Т	U	V	W	Х	Υ	Z
Month	Jan	Fe	b I	Mar	Apr	May	Ju	n	Jul	Aug	Sep	Oc	t I	Nov	Dec
Code	1	2		3	4	5	6		7	8	9	0		N	D



## Maximum Ratings (@T<sub>A</sub> = +25°C, unless otherwise specified.)

Characteristic	Symbol	Value	Units	
Drain-Source Voltage		$V_{DSS}$	-50	V
Drain-Gate Voltage (Note 5)		$V_{DGR}$	-50	V
Gate-Source Voltage	Continuous	$V_{GSS}$	±20	V
Drain Current (Note 6)	Continuous	I <sub>D</sub>	-130	mA

## Thermal Characteristics (@T<sub>A</sub> = +25°C, unless otherwise specified.)

Characteristic	Symbol	Value	Units
Total Power Dissipation (Note 6)	$P_{D}$	300	mW
Thermal Resistance, Junction to Ambient	$R_{ heta JA}$	417	°C/W
Operating and Storage Temperature Range	T <sub>J</sub> , T <sub>STG</sub>	-55 to +150	°C


## Electrical Characteristics (@T<sub>A</sub> = +25°C, unless otherwise specified.)


Characteristic	Symbol	Min	Тур	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 7)						
Drain-Source Breakdown Voltage	BV <sub>DSS</sub>	-50	-75	_	<b>V</b>	$V_{GS} = 0V, I_D = -250\mu A$
		_	-	-1	μΑ	$V_{DS} = -50V, V_{GS} = 0V, T_{J} = +25^{\circ}C$
Zero Gate Voltage Drain Current	Inco	_	_	-2	μΑ	$V_{DS} = -50V$ , $V_{GS} = 0V$ , $T_{J} = +125$ °C
Zero Gate Voltage Drain Guirent	I <sub>DSS</sub>	_		-100	nA	$V_{DS} = -25V$ , $V_{GS} = 0V$ , $T_{J} = +25$ °C
Gate-Body Leakage	I <sub>GSS</sub>			±10	nA	$V_{GS} = \pm 20V, V_{DS} = 0V$
ON CHARACTERISTICS (Note 7)				a.		
Gate Threshold Voltage	V <sub>GS(th)</sub>	-0.8	-1.6	-2.0	>	$V_{DS} = V_{GS}$ , $I_D = -1mA$
Static Drain-Source On-Resistance	R <sub>DS (ON)</sub>		6	10	Ω	$V_{GS} = -5V$ , $I_D = -0.100A$
Forward Transconductance	<b>g</b> FS	0.05		_	S	$V_{DS} = -25V, I_D = -0.1A$
DYNAMIC CHARACTERISTICS						
Input Capacitance	C <sub>iss</sub>	_		45	pF	
Output Capacitance	Coss	_		25	pF	$V_{DS} = -25V$ , $V_{GS} = 0V$ , $f = 1.0MHz$
Reverse Transfer Capacitance	C <sub>rss</sub>	_	_	12	pF	
SWITCHING CHARACTERISTICS						
Turn-On Delay Time	t <sub>D(ON)</sub>		10	_	ns	$V_{DD} = -30V, I_D = -0.27A,$
Turn-Off Delay Time	t <sub>D(OFF)</sub>	_	18	_	ns	$R_{GEN} = 50\Omega$ , $V_{GS} = -10V$


Notes:


<sup>5.</sup>  $R_{GS} \le 20K\Omega$ . 6. Device mounted on FR-4 PCB, 1 inch x 0.85 inch x 0.062 inch; pad layout as shown on Diodes Inc. suggested pad layout document AP02001, which can be found on our website at http://www.diodes.com.
7. Short duration pulse test used to minimize self-heating effect.















Fig. 6 On-Resistance vs. Drain-Current



## **Package Outline Dimensions**


Please see AP02002 at http://www.diodes.com/datasheets/ap02002.pdf for latest version.



	SOT363							
Dim	Min	Max	Тур					
Α	0.10	0.30	0.25					
В	1.15	1.35	1.30					
С	2.00	2.20	2.10					
D		0.65 Ty	р					
F	0.40	0.425						
Н	1.80	2.20	2.15					
J	0	0.10	0.05					
K	0.90	1.00	1.00					
L	0.25	0.40	0.30					
M	0.10	0.22	0.11					
α	0°	8°	-					
All	Dimen	sions i	n mm					

## **Suggested Pad Layout**

Please see AP02001 at http://www.diodes.com/datasheets/ap02001.pdf for the latest version.



Dimensions	Value (in mm)
Z	2.5
G	1.3
Х	0.42
Y	0.6
C1	1.9
C2	0.65



#### **IMPORTANT NOTICE**

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

#### LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

- A. Life support devices or systems are devices or systems which:
  - 1. are intended to implant into the body, or
  - 2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.
- B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2013, Diodes Incorporated

www.diodes.com

## **ПОСТАВКА** ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

многоканальный

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

# Данный компонент на территории Российской Федерации Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

## http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г. Москва, ул. Щербаковская д. 3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru moschip.ru\_6 moschip.ru 4 moschip.ru 9