



Certifications & Ratings

- RoHS compliant
- NEMA 4X (Watertight only)
- IP66 (Watertight only)

Application

The 609 Series LED Panel Mount Indicators are designed for a variety of applications such as:


- Main power indication
- Remote power indication
- Status indication
- Maintenance and warning indication
- Instrumentation

... and many more!


Dimensions

inches [mm]

Protruding



Recessed



Mechanical Information

Mounting Hole Size:	0.374" (9.5mm)
Max Panel Thickness:	0.374" (9.5mm); with Gasket: 0.318" (8.0mm)
Mounting Torque:	0.362 lbs/ft (5 kg/cm)

Specifications

Voltage Options:	6, 12 & 24 V DC (no resistor required)
Operating Temp:	-30 °C to +85 °C (-22 °F to +185 °F)
Storage Temp:	-40 °C to +85 °C (-40 °F to +185 °F)
Electrical Connection:	Solder terminals
Housing:	Brass—Chrome or Black Plated
Terminals:	Copper—Nickel Plated
Lock washer:	Iron—Nickel Plated
Nut:	Brass—Nickel Plated

Ordering Information 609 Series

Part Number Guide										RoHS Compliant		
6	0	9	-	X	X	X	2	-	X	X	0	F
LED Position				Plating				Voltage				
Protruding		1			1 Chrome		2		6VDC			
Recessed		2			2 Black		3		12VDC			
Color								4		24VDC		
Red		1			1		Standard					
Green		2			3		Watertight					
Yellow		3										

Protruding LED

Part Number	Part Number	Color	Voltage (V DC)	Current (mA)	Intensity Typ. (mcd)	Plating
Standard	Watertight					
609-1112-120F	609-1112-320F	● Red	6	15	60	Chrome
609-1212-120F	609-1212-320F	● Green			110	
609-1312-120F	609-1312-320F	● Yellow			90	
609-1112-130F	609-1112-330F	● Red	12		60	
609-1212-130F	609-1212-330F	● Green			110	
609-1312-130F	609-1312-330F	● Yellow			90	
609-1112-140F	609-1112-340F	● Red	24		60	
609-1212-140F	609-1212-340F	● Green			110	
609-1312-140F	609-1312-340F	● Yellow			90	
609-1122-120F	609-1122-320F	● Red	6		60	Black
609-1222-120F	609-1222-320F	● Green			110	
609-1322-120F	609-1322-320F	● Yellow			90	
609-1122-130F	609-1122-330F	● Red	12		60	
609-1222-130F	609-1222-330F	● Green			110	
609-1322-130F	609-1322-330F	● Yellow			90	
609-1122-140F	609-1122-340F	● Red	24		60	
609-1222-140F	609-1222-340F	● Green			110	
609-1322-140F	609-1322-340F	● Yellow			90	

Recessed LED

Part Number	Part Number	Color	Voltage (V DC)	Current (mA)	Intensity Typ. (mcd)	Plating	
Standard	Watertight						
609-2112-120F	609-2112-320F	Red	6	15	60	Chrome	
609-2212-120F	609-2212-320F	Green			110		
609-2312-120F	609-2312-320F	Yellow			90		
609-2112-130F	609-2112-330F	Red	12		60		
609-2212-130F	609-2212-330F	Green			110		
609-2312-130F	609-2312-330F	Yellow			90		
609-2112-140F	609-2112-340F	Red	24		60		
609-2212-140F	609-2212-340F	Green			110		
609-2312-140F	609-2312-340F	Yellow			90		
609-2122-120F	609-2122-320F	Red	6		60		
609-2222-120F	609-2222-320F	Green			110		
609-2322-120F	609-2322-320F	Yellow			90		
609-2122-130F	609-2122-330F	Red	12		60		Black
609-2222-130F	609-2222-330F	Green			110		
609-2322-130F	609-2322-330F	Yellow			90		
609-2122-140F	609-2122-340F	Red	24		60		
609-2222-140F	609-2222-340F	Green			110		
609-2322-140F	609-2322-340F	Yellow			90		

Dialight reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: www.dialightsignalsandcomponents.com

Warranty Statement: Except for the warranty expressly provided for [herein/above/below], Dialight disclaims any and all other warranties, express or implied, including, without limitation, any warranties of merchantability, fitness for a particular purpose, title, and noninfringement.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9