




DESIGNED FOR USE WITH RG-188/U	
CABLE ENTRY DIAMETER MINIMUM	
CLAMP NUT	.113
COLLAR	.065
DIELECTRIC	.066
CONTACT	.023

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₀	RELEASED		
01 ₁	SEE ECN 80-0084	G.B. 2/18/80	
01 ₂	REDRAWN AND UPDATE PER ECN 88-0678	EFH 8/27/91	<i>OK</i> 8/30/91

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) <u>50</u>	Interface Dimensions MIL-STD-348A, Fig. <u>310.2</u>	Temperature Rating <u>-65°C TO +125°C</u>
Frequency Range (GHz) <u>DC to MAX</u>	Recommended Mating	Vibration MIL-STD-202, Method
Operating Frequency of Applicable Cable Per MIL-C-17	Torque <u>N/A</u>	204, Condition <u>D</u>
Volt Rating (VRMS MAX)	Mating Characteristics:	Shock MIL-STD-202, Method 213,
@ Sea Level <u>250</u>	Insertion (MAX Lbs) <u>3.0</u>	Condition <u>I</u>
VSWR <u>1.15 + .01 f GHz</u>	Withdrawal (MIN Oz) <u>1.0</u>	Thermal Shock MIL-STD-202,
Insertion Loss (dB MAX) <u>.06 √fGHz</u>	Force to Engage and	Method 107, Condition <u>B</u>
RF Leakage (dB MIN) <u>-[90-f{GHz}]</u>	Disengage (In-Lbs MAX) <u>2.0</u>	Moisture Resistance MIL-STD-202,
Corona, 70,000 Ft (VRMS MIN) <u>190</u>	Center Contact Captivation	Method 106, Except Vibration
Dielectric Withstanding Voltage	Axial (Lbs) <u>6.0</u>	Shall Be Omitted
(VRMS MIN) @ Sea Level <u>750</u>	Radial (In-Oz) <u>N/A</u>	Corrosion - MIL-STD-202, Method
Contact Resistance (Milliohms MAX)	Cable Retention	101, Condition B, 5% salt spray
Center Contact <u>2.0</u>	Axial Force (Lbs) <u>20</u>	
Outer Contact <u>2.0</u>	Torque (In-Oz) <u>N/A</u>	
Cable to Housing <u>5.0</u>	Weight (Grams) <u>4.1</u>	
RF High Potential @ Sea Level		
(VRMS MIN @ 5 MHz) <u>500</u>		
IR.(Megohms MIN) <u>10,000</u>		

HOUSING CLAMP NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER ASTM-A380
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
COLLAR	BRASS PER QQ-B-626 COMP. 360, HALF HARD	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
COMPONENT	MATERIAL	FINISH
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± 1°		
DRAWN BY J.B.L. DATE 5/13/75 CHECKED BY B.M.F. 5/13/75 APPD BY C.B.D. 5/13/75		
These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.		
USE ASS'Y PROCEDURE 408-04906 NO. AP. (20-075)		
AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599		
TITLE OSM STRAIGHT CABLE JACK CLAMP ATTACHMENT		
SIZE B	CODE IDENT NO. 26805	2002-7188-02
SCALE 5:1	REV 01 ₂	
SHEET 1 OF 1		

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9