



For more Information
please call

1-800-Belden1



General Description:

18 AWG solid bare copper-covered steel conductor, foam polyethylene insulation, Duobond IV® quad shield (100% coverage), PVC inner jacket, aluminum interlocked armor, PVC sunlight-resistant outer jacket.

Usage (Overall)

Suitable Applications: ControlNet™, Modbus II, Industrial Coax

Physical Characteristics (Overall)

Conductor

AWG:

| # Coax | AWG | Stranding | Conductor Material | Dia. (mm) |
|--------|-----|-----------|----------------------------------|-----------|
| 1 | 18 | Solid | BCCS - Bare Copper Covered Steel | 1.016 |

Total Number of Conductors: 1

Insulation

Insulation Material:

| Insulation Material | Dia. (mm) |
|-------------------------|-----------|
| FPE - Foam Polyethylene | 4.572 |

Inner Jacket

Inner Jacket Material:

| Inner Jacket Material | Nom. Dia. (mm) |
|--------------------------|----------------|
| PVC - Polyvinyl Chloride | 7.569 |

Outer Shield

Outer Shield Material:

| Layer # | Outer Shield Trade Name | Type | Outer Shield Material | Coverage (%) |
|---------|-------------------------|-------|---|--------------|
| 1 | Bonded Duofoil® | Tape | Bonded Aluminum Foil-Polyester Tape-Aluminum Foil | 100 |
| 2 | | Braid | AL - Aluminum | 60 |
| 3 | Duofoil® | Tape | Aluminum Foil-Polyester Tape-Aluminum Foil | 100 |
| 4 | | Braid | AL - Aluminum | 40 |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material | Nom. Wall Thickness (mm) |
|--------------------------|--------------------------|
| PVC - Polyvinyl Chloride | 1.143 |

Armor

Armor Type: Interlocking

Armor Material: Aluminum

Diameter over Armor: .501

Overall Cable

Overall Nominal Diameter: 15.011 mm

Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +75°C

Bulk Cable Weight: 211.324 Kg/Km

123092A Coax - ControlNet™ Quad Shielded Coax

| | |
|-----------------------------------|------------|
| Max. Recommended Pulling Tension: | 889.640 N |
| Min. Bend Radius/Minor Axis: | 180.340 mm |

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|---------------------------------------|------------|
| NEC/(UL) Specification: | CL2, CM |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 10/01/2005 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |
| RG Type: | 6/U |

Flame Test

| | |
|-----------------|---------------------------------|
| UL Flame Test: | UL1685 Vertical Tray Flame Test |
| CSA Flame Test: | FT4 |

Suitability

| | |
|------------------------|-----|
| Suitability - Indoor: | Yes |
| Suitability - Outdoor: | Yes |
| Sunlight Resistance: | Yes |

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

| |
|-----------------|
| Impedance (Ohm) |
| 75 |

Nom. Inductance:

| |
|-------------------|
| Inductance (µH/m) |
| 0.318257 |

Nom. Capacitance Conductor to Shield:

| |
|--------------------|
| Capacitance (pF/m) |
| 53.1522 |

Nominal Velocity of Propagation:

| |
|--------|
| VP (%) |
| 82 |

Nominal Delay:

| |
|--------------|
| Delay (ns/m) |
| 4.19968 |

Nom. Conductor DC Resistance:

| |
|---------------------|
| DCR @ 20°C (Ohm/km) |
| 91.868 |

Nominal Outer Shield DC Resistance:

| |
|---------------------|
| DCR @ 20°C (Ohm/km) |
| 11.8116 |

Nom. Attenuation:

| |
|-----------------------------------|
| Freq. (MHz) Attenuation (dB/100m) |
|-----------------------------------|

METRIC MEASUREMENT VERSION

123092A Coax - ControlNet™ Quad Shielded Coax

| | |
|-----|---------|
| 1 | 1.14835 |
| 2 | 1.24678 |
| 5 | 1.47645 |
| 10 | 1.93579 |
| 20 | 2.82166 |
| 50 | 4.49497 |
| 100 | 6.46357 |
| 200 | 9.25242 |
| 300 | 11.4179 |
| 400 | 13.2552 |

Max. Operating Voltage - UL:

| |
|----------------|
| Voltage |
| 300 V RMS |

Minimum Structural Return Loss:

| Description | Freq. (MHz) | Start Freq. (MHz) | Stop Freq. (MHz) | Min. SRL (dB) |
|-------------|-------------|-------------------|------------------|---------------|
| | | 5 | 50 | 23 |

Notes (Overall)

Notes: ControlNet is a ControlNet International trademark.

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|-----------------|----------|-------------|--------------|-------|----------------------|
| 123092A J221000 | 305 MT | 68.039 KG | BLUE, STRONG | | 3092A ALUM ARMOR PVC |
| 123092A J225000 | 1,524 MT | 360.608 KG | BLUE, STRONG | | 3092A ALUM ARMOR PVC |
| 123092A 0101000 | 305 MT | 68.039 KG | BLACK | | 3092A ALUM ARMOR PVC |
| 123092A 0102000 | 610 MT | 140.614 KG | BLACK | | 3092A ALUM ARMOR PVC |

Revision Number: 3 Revision Date: 08-16-2012

© 2013 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9