

4

3

2

1


THIS DRAWING IS UNPUBLISHED.	RELEASED FOR PUBLICATION
© COPYRIGHT	ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS				
		P	LTR	DESCRIPTION	DATE	APVD
			H1	27MAR14	27MAR14	RS LZ

REPLACED BY OCEAN STYLE APPLICATOR PART
NUMBER 2150054-2

FOR REPLACEMENT PARTS FOR APPLICATOR 1891273
REFER TO ADDITIONAL PAGE(S). SPARE PARTS KIT (IF LISTED)
WILL REMAIN AVAILABLE.

THE REPLACEMENT OCEAN STYLE APPLICATOR HAS THE
SAME TERMINATOR/PRESS INTERFACE AS APPLICATOR
1891273

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R.SHEN	 TE Connectivity			
DIMENSIONS:		CHK LJ.ZHANG				
		APVD U.GUO	NAME END FEED HDJ APPLICATOR			
		PRODUCT SPEC	SIZE A3			
		APPLICATION SPEC				
MATERIAL		WEIGHT	CAGE CODE	DRAWING NO C- 1891273	RESTRICTED TO	
		CUSTOMER ACCESSIBLE PRODUCTION DRAWING		SCALE	SHEET 1 OF 2	REV H1

DRAWING MADE IN THIRD ANGLE PROJECTION

1891273 1891273

PART NUMBER	REV	TERMINATOR	FEED TYPE	DESCRIPTION
1891273-1	E	LEADMAKER	MECH POST FEED	STD C/H DIAL
1891273-2	E	BENCH	MECH PRE FEED	STD C/H DIAL
1-1891273-1	D	LEADMAKER	MECH POST FEED	FINE ADJ C/H DIAL
1-1891273-2	E	BENCH	MECH PRE FEED	FINE ADJ C/H DIAL
2-1891273-1	H	LEADMAKER	AIR POST FEED	STD C/H DIAL
2-1891273-2	H	BENCH	AIR PRE FEED	STD C/H DIAL
3-1891273-1	H	LEADMAKER	AIR POST FEED	FINE ADJ C/H DIAL
3-1891273-2	H	BENCH	AIR PRE FEED	FINE ADJ C/H DIAL

SUPERCEDED BY 1339815-1
SUPERCEDED BY 1339815-1
SUPERCEDED BY 1529169-1
SUPERCEDED BY 1529169-1

CRIMP DATA AMP TERMINAL AMP CRIMP SPECS

TERMINAL NAME: 187 SERIES POSITIVE LOCK (MARK-II) REC.

CRIMP	SIZE	TYPE	RANGE
WIRE	3.05	F	0.7-2.08 mm ²
INSUL	5.9	O	2.1-3.6 mm

WIRE STRIP LENGTH 4.50-5.48 mm
APPL INSTRUCTION 408-8323

TERMINAL 4 - FEED
APPL SPEC 114-5041 - 22.1

TERMINALS APPLIED

170326	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-

WIRE SIZE mm ² AWG	CRIMP HEIGHT *	REF SETTING
14 AWG	1.57 ±0.05	A
16 AWG	1.40 ±0.05	B
18 AWG	1.24 ±0.05	C
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-

RECOMMENDED SPARE PARTS.

- GREASE RAM, CAM, CAM FOLLOWER AND FEED ROD LIGHTLY.
- LUBRICATE DAILY PER THE APPLICATOR INSTRUCTION SHEET SUPPLIED WITH THE APPLICATOR.

THIS APPLICATOR HAS BEEN DESIGNED TO APPLY WIRES WITH THIN WALL (FLR) INSULATION. THE INSULATION CRIMP & APPLICABLE CRIMP RANGE MAY NOT CONFORM TO THE PARAMETERS LISTED IN THE APPLICATION SPECIFICATION.

REPLACE WITH THIS PART FOR 1891273-2, 1-1891273-1/-2.

REPLACE WITH THIS PART FOR 2-1891273-1/-2, 3-1891273-1/-2.

REPLACE WITH THIS PART FOR 2-1891273-1/-2, 3-1891273-1/-2.

ADD THIS PART IN ITEM NO 50 FOR 2-1891273-1/-2, 3-1891273-1/-2.

VIEW B ROTATED 180°

POST FEED 40 mm STROKE		POST FEED 30 mm STROKE		PRE FEED 40 mm STROKE		PRE FEED 30 mm STROKE	
LOC ES							
		DIST					

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9