



Product: [73603WS](#)

MachFlex™, 3 C #16 Str BC, PVC Ins, OA TC Brd, PVC Jkt, PVC Jkt, AWM 2587 CLASS K

Request Sample

Product Description

MachFlex™ for Moderate Flex, 3 Conductor 16AWG (26x30) Bare Copper, PVC Insulation, Overall Tinned Copper Braid(85%) Shield, PVC Inner Jacket, PVC Outer Jacket, AWM 2587 CLASS K

Technical Specifications

Physical Characteristics (Overall)

Conductor

| Element   | AWG | Stranding | Material         | No. of Conductors |
|-----------|-----|-----------|------------------|-------------------|
| Conductor | 16  | 26x30     | BC - Bare Copper | 2                 |
| Ground    | 16  | 26x30     | BC - Bare Copper | 1                 |

Conductor Count: 3

Insulation

| Element   | Material                 | Nominal Diameter | Nominal Wall Thickness |
|-----------|--------------------------|------------------|------------------------|
| Conductor | PVC - Polyvinyl Chloride | 0.104 in         | 0.022 in               |
| Ground    | PVC - Polyvinyl Chloride |                  |                        |

Color Chart

| Color              |
|--------------------|
| Black and Numbered |

Inner Jacket Material

| Material                 | Nominal Diameter | Nominal Wall Thickness |
|--------------------------|------------------|------------------------|
| PVC - Polyvinyl Chloride | .290 in          | .030 in                |

Outer Shield Material

| Type  | Material           | Coverage [%] |
|-------|--------------------|--------------|
| Braid | Tinned Copper (TC) | 85%          |

Outer Jacket Material

| Material                 | Nominal Diameter | Nominal Wall Thickness |
|--------------------------|------------------|------------------------|
| PVC - Polyvinyl Chloride | 0.388 in         | 0.035 in               |

Electrical Characteristics

Conductor DCR

| Nominal Conductor DCR | Nominal Outer Shield DCR |
|-----------------------|--------------------------|
| 4.1 Ohm/1000ft        | 2.28 Ohm/1000ft          |

Capacitance

| Nom. Capacitance Conductor to Conductor |
|-----------------------------------------|
| 51 pF/ft                                |

Inductance

| Nominal Inductance |
|--------------------|
|--------------------|

|            |
|------------|
| .180 μH/ft |
|------------|

Voltage

| UL Voltage Rating |
|-------------------|
| 600 V             |

Temperature Range

|                       |                                                |
|-----------------------|------------------------------------------------|
| UL Temp Rating:       | 90°C                                           |
| Operating Temp Range: | -40°C To 90°C (Static), -5°C To 90°C (Flexing) |

Mechanical Characteristics

|                                       |                  |
|---------------------------------------|------------------|
| Oil Resistance:                       | Yes              |
| Flex Cycle Rating:                    | 1 Million Cycles |
| Bulk Cable Weight:                    | 194 lbs/1000ft   |
| Max. Pull Tension:                    | 70 lbs           |
| Min Bend Radius (Continuous Flexing): | 3.1 in           |
| Min Bend Radius/Minor Axis:           | 3.1 in           |

Standards

|                          |                                |
|--------------------------|--------------------------------|
| UL AWM Style Compliance: | AWM 2587                       |
| CSA AWM Compliance:      | AWM I/II A/B                   |
| Other Compliance:        | VDE 0472, Section 803 Oil Test |

Applicable Environmental and Other Programs

|                                    |                               |
|------------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV):     | Yes                           |
| EU Directive 2003/11/EC (BFR):     | Yes                           |
| EU Directive 2011/65/EU (ROHS II): | Yes                           |
| EU Directive 2012/19/EU (WEEE):    | Yes                           |
| EU Directive 2015/863/EU:          | Yes                           |
| EU Directive Compliance:           | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                        | Yes                           |

Flammability, LS0H, Toxicity Testing

|                    |           |
|--------------------|-----------|
| CSA Flammability:  | FT1       |
| UL voltage rating: | 600 V RMS |

Part Number

Variants

| Item #          | Color | Putup Type | UPC          |
|-----------------|-------|------------|--------------|
| 73603WS 008100  | Gray  | Reel       | 612825409731 |
| 73603WS 0081000 | Gray  | Reel       | 612825409748 |
| 73603WS 008500  | Gray  | Reel       | 612825409755 |

History

|                      |                                                 |
|----------------------|-------------------------------------------------|
| Update and Revision: | Revision Number: 0.56 Revision Date: 04-28-2020 |
|----------------------|-------------------------------------------------|

© 2020 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9