



# Military COTS 28V<sub>IN</sub> Filter

**M-FIAM7B**

Example Model Number **M-FIAM7BM21**

Actual size:  
2.28 x 2.2 x 0.5in  
[57,9 x 55,9 x 12,7mm]

## Input Attenuator Module

### Features & Benefits

- EMI filtering-MIL-STD-461E <sup>[b]</sup>
- Transient protection:  
MIL-STD-1275A/B/D,  
MIL-STD-704A-F and  
DO-160E
- Environments: MIL-STD-810,  
MIL-STD-202
- Environmental stress screening
- Low-profile mounting options
- Output power up to 400W
- Mini-sized package
- Inrush current limiting

### Product Highlights

The M-FIAM7B is a DC front-end module that provides EMI filtering and transient protection. The M-FIAM7B enables designers using Vicor 28V DC-DC VI Chip and VI Brick® modules to meet conducted emission/ conducted susceptibility per MIL-STD-461E; and input transients per MIL-STD-1275A/B/D, MIL-STD-704A-F and DO-160E. The M-FIAM7B accepts an input voltage of 14 – 50V<sub>DC</sub> and delivers output power up to 400W.

M-FIAM7B is housed in an industry-standard “half-brick” module measuring 2.28 x 2.2 x 0.5in and depending upon model selected, may be mounted onboard or inboard for height-critical applications.

### Compatible Products

- 28V Input DC-DC VI Chip® or VI Brick modules

**Note:** This product is not compatible with Maxi, Mini, Micro DC-DC converters.

### Absolute Maximum Rating

| Parameter                 | Rating    | Unit            | Notes               |
|---------------------------|-----------|-----------------|---------------------|
| +IN to -IN                | 50        | V <sub>DC</sub> | Continuous          |
| Mounting torque           | 5 [0.57]  | in-lbs [N·m]    | 6 each, #4-40 or M3 |
| Pin soldering temperature | 500 [260] | °F [°C]         | <5sec; wave solder  |
|                           | 750 [390] | °F [°C]         | <7sec; hand solder  |


### Thermal Resistance and Capacity

| Parameter                    | Min | Typ  | Max | Unit    |
|------------------------------|-----|------|-----|---------|
| Baseplate to sink            |     |      |     |         |
| flat, greased surface        |     | 0.16 |     | °C/Watt |
| with thermal pad (P/N 20264) |     | 0.1  |     | °C/Watt |
| Baseplate to ambient         |     |      |     |         |
| Free convection              |     | 7.9  |     | °C/Watt |
| 1000LFM                      |     | 2.2  |     | °C/Watt |

### MTBF per MIL-HDBK-217F (M-FIAM7BM21)

| Temperature | Environment                      | MTBF  | Unit     |
|-------------|----------------------------------|-------|----------|
| 25°C        | Ground Benign: G.B.              | 4,041 | 1,000Hrs |
| 50°C        | Naval Sheltered: N.S.            | 727   | 1,000Hrs |
| 65°C        | Airborne Inhabited Cargo: A.I.C. | 570   | 1,000Hrs |

### Part Numbering



<sup>[a]</sup> Compatible with SurfMate and InMate socketing system

<sup>[b]</sup> EMI performance is subject to a wide variety of external influences such as PCB construction, circuit layout etc. As such, external components in addition to those listed herein may be required in specific instances to gain full compliance to the standards specified.

<sup>[c]</sup> Not intended for socket or Surfmate mounting

**Note:** Product images may not highlight current product markings.

## Specifications

Typical at  $T_{BP} = 25^{\circ}\text{C}$ , nominal line and 75% load, unless otherwise specified.

### Input Specifications

| Parameter          | Min | Typ | Max   | Unit             | Notes                                                                                                 |
|--------------------|-----|-----|-------|------------------|-------------------------------------------------------------------------------------------------------|
| Input voltage      | 14  | 28  | 50    | $V_{DC}$         | Continuous                                                                                            |
| Inrush limiting    |     |     | 0.007 | A/ $\mu\text{F}$ | See Figure 4                                                                                          |
| Transient immunity |     |     | 100   | $V_{DC}$         | 50ms per MIL-STD-1275A/B/D, continuous operation (see Figure 3)                                       |
|                    |     |     | 250   | $V_{DC}$         | 70 $\mu\text{s}$ per MIL-STD-1275B, continuous operation                                              |
|                    |     |     | 70    | $V_{DC}$         | 20ms per MIL-STD-704A, continuous operation                                                           |
|                    |     |     | 80    | $V_{DC}$         | 100ms per DO-160E, Section 16, Power Input, Category Z<br>50ms per MIL-STD-704A, continuous operation |

### Output Specifications

| Parameter             | Min | Typ | Max  | Unit          | Notes                                                |
|-----------------------|-----|-----|------|---------------|------------------------------------------------------|
| Output current        |     |     | 25   | A             | Over continuous input and temp. range                |
| Output power          |     |     | 400  | W             | Transient compliance over temp. range (see Figure 7) |
| Efficiency            | 96  | 98  |      | %             | @ 25A, 100°C baseplate                               |
| Internal voltage drop |     | 0.5 | 0.7  | V             |                                                      |
| External capacitance  | 330 |     | 3300 | $\mu\text{F}$ | See Figure 8<br>63V                                  |

### Control Pin Specifications

| Parameter      | Min | Typ   | Max  | Unit     | Notes                                   |
|----------------|-----|-------|------|----------|-----------------------------------------|
| ON/OFF control |     |       |      |          |                                         |
| Enable (ON)    | 0.0 |       | 1.0  | $V_{DC}$ | Referenced to $-V_{OUT}$                |
| Disable (OFF)  | 4.0 |       | 5.50 | $V_{DC}$ | 100k $\Omega$ internal pull-up resistor |
| EMI GRD        |     | earth |      |          | Not electrically connected to baseplate |

### Safety Specifications

| Parameter            | Min   | Typ | Max | Unit      | Notes                |
|----------------------|-------|-----|-----|-----------|----------------------|
| Dielectric withstand | 1,500 |     |     | $V_{RMS}$ | Input/Output to Base |
|                      | 2,121 |     |     | $V_{DC}$  | Input/Output to Base |

### EMI

| Standard                  | Test Procedure                        | Notes                                      |
|---------------------------|---------------------------------------|--------------------------------------------|
| MIL-STD-461E              |                                       |                                            |
| Conducted emissions:      | CE101, CE102                          |                                            |
| Conducted susceptibility: | CS101 (see note), CS114, CS115, CS116 | With suggested Reverse Polarity Protection |

EMI performance is subject to a wide variety of external influences such as PCB construction, circuit layout etc. As such, external components in addition to those listed herein may be required in specific instances to gain full compliance to the standards specified.

### General Specifications

| Parameter | Min | Typ | Max      | Unit           | Notes |
|-----------|-----|-----|----------|----------------|-------|
| Weight    |     |     | 3.3 [94] | Ounces [grams] |       |
| Warranty  |     |     | 2        | Years          |       |

## Specifications (Cont.)

Typical at  $T_{BP} = 25^{\circ}\text{C}$ , nominal line and 75% load, unless otherwise specified.

### Environmental Qualification

#### Altitude

MIL-STD-810F, Method 500.4, Procedure I & II, 40,000ft. and 70,000ft. Operational.

#### Explosive Atmosphere

MIL-STD-810F, Method 511.4, Procedure I, Operational.

#### Vibration

MIL-STD-810F, Method 514.5, Procedure I, Category 14, Sine and Random vibration per Table 514.5C for Helicopter AH-6J Main Rotor with overall level of 5.6Grms for 4 hours per axis. MIL-STD-810F, Method 514.5C, General Minimum Integrity Curve per Figure 514.5C-17 with overall level of 7.7Grms for 1 hour per axis.

#### Shock

MIL-STD-810F, Method 516.5, Procedure I, Functional Shock, 40g. MIL-S-901D, Lightweight Hammer Shock, 3 impacts/axis, 1,3,5ft. MIL-STD-202F, Method 213B, 60g, 9ms half sine. MIL-STD-202F, Method 213B, 75g, 11ms Saw Tooth Shock.

#### Acceleration

MIL-STD-810F, Method 513.5, Procedure II, table 513.5-II, Operational, 2-7g, 6 directions.

#### Humidity

MIL-STD-810F, Method 507.4.

#### Solder Test

MIL-STD-202G, Method 208H, 8 hour aging.

### Environmental Stress Screening

| Parameter                           | H-Grade                                            | M-Grade                                            |
|-------------------------------------|----------------------------------------------------|----------------------------------------------------|
| Operating temperature               | -40 to +100°C                                      | -55 to +100°C                                      |
| Storage temperature                 | -55 to +125°C                                      | -65 to +125°C                                      |
| Temperature cycling*                | 12 cycles<br>-65 to +100°C                         | 12 cycles<br>-65 to +100°C                         |
| Ambient test @ 25°C                 | Yes                                                | Yes                                                |
| Power cycling burn-in               | 12 hours, 29 cycles                                | 24 hours, 58 cycles                                |
| Functional and parametric ATE tests | -40 and +100°C                                     | -55 and +100°C                                     |
| Hi-Pot test                         | Yes                                                | Yes                                                |
| Visual inspection                   | Yes                                                | Yes                                                |
| Test data                           | <a href="http://vicorpower.com">vicorpower.com</a> | <a href="http://vicorpower.com">vicorpower.com</a> |

\*Temperature cycled with power off, 17°C per minute rate of change.




**Figure 1** —  $T$  = time period before overvoltage protection.  
 $V_{IN}$  = input voltage (switching up from 28V<sub>DC</sub>)




**Figure 2** — MIL-STD-461F, CE102; M-FIAM7B and three MIL-COTS PRMs and three MIL-COTS VTMs, 350W




**Figure 3** — Transient immunity; M-FIAM7B output response to an input transient




**Figure 4** — Inrush limiting; inrush current with 3300 $\mu$ F external capacitance




**Figure 5** — Insertion loss curve




Figure 6 — M-FIAM7B EMI compliance only




Figure 7 — M-FIAM7B EMI and MIL-STD-1275D transient compliance




Figure 8 — Basic connection diagram with suggested transient, surge protection and reverse-polarity protection (R.P.P)

## Storage

Vicor products, when not installed in customer units, should be stored in ESD safe packaging in accordance with ANSI/ESD S20.20, "Protection of Electrical and Electronic Parts, Assemblies and Equipment" and should be maintained in a temperature controlled factory/warehouse environment not exposed to outside elements controlled between the temperature ranges of 15°C and 38°C. Humidity shall not be condensing, no minimum humidity when stored in an ESD compliant package.

## Mechanical Drawings




Figure 9 — Mechanical diagram




Figure 10 — PCB mounting specifications

**Vicor's comprehensive line of power solutions includes high density AC-DC and DC-DC modules and accessory components, fully configurable AC-DC and DC-DC power supplies, and complete custom power systems.**

Information furnished by Vicor is believed to be accurate and reliable. However, no responsibility is assumed by Vicor for its use. Vicor makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication. Vicor reserves the right to make changes to any products, specifications, and product descriptions at any time without notice. Information published by Vicor has been checked and is believed to be accurate at the time it was printed; however, Vicor assumes no responsibility for inaccuracies. Testing and other quality controls are used to the extent Vicor deems necessary to support Vicor's product warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

**Specifications are subject to change without notice.**

Visit [http://www.vicorpower.com/mil-cots\\_dc-dc/mil-cots\\_m-fiam\\_filter\\_input\\_attenuator\\_module](http://www.vicorpower.com/mil-cots_dc-dc/mil-cots_m-fiam_filter_input_attenuator_module) for the latest product information.

**Vicor's Standard Terms and Conditions and Product Warranty**

All sales are subject to Vicor's Standard Terms and Conditions of Sale, and Product Warranty which are available on Vicor's webpage (<http://www.vicorpower.com/termsconditionswarranty>) or upon request.

**Life Support Policy**

VICOR'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS PRIOR WRITTEN APPROVAL OF THE CHIEF EXECUTIVE OFFICER AND GENERAL COUNSEL OF VICOR CORPORATION. As used herein, life support devices or systems are devices which (a) are intended for surgical implant into the body, or (b) support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in a significant injury to the user. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system or to affect its safety or effectiveness. Per Vicor Terms and Conditions of Sale, the user of Vicor products and components in life support applications assumes all risks of such use and indemnifies Vicor against all liability and damages.

**Intellectual Property Notice**

Vicor and its subsidiaries own Intellectual Property (including issued U.S. and Foreign Patents and pending patent applications) relating to the products described in this data sheet. No license, whether express, implied, or arising by estoppel or otherwise, to any intellectual property rights is granted by this document. Interested parties should contact Vicor's Intellectual Property Department.

Contact Us: <http://www.vicorpower.com/contact-us>

**Vicor Corporation**  
25 Frontage Road  
Andover, MA, USA 01810  
Tel: 800-735-6200  
Fax: 978-475-6715  
[www.vicorpower.com](http://www.vicorpower.com)

**email**

Customer Service: [custserv@vicorpower.com](mailto:custserv@vicorpower.com)  
Technical Support: [apps@vicorpower.com](mailto:apps@vicorpower.com)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Vicor:](#)

[M-FIAM7BHG1](#) [M-FIAM7BH22](#) [M-FIAM7BH11](#) [M-FIAM7BH12](#) [M-FIAM7BH21](#) [M-FIAM7BH23](#) [M-FIAM7BHF1](#) [M-FIAM7BM22](#) [M-FIAM7BMG1](#) [M-FIAM7BMG3](#) [M-FIAM7BMN1](#) [M-FIAM7BMN3](#) [M-FIAM7BMS1](#) [M-FIAM7BMS3](#) [M-FIAM7BHN2](#) [M-FIAM7BHN3](#) [M-FIAM7BHS1](#) [M-FIAM7BM11](#) [M-FIAM7BM21](#) [M-FIAM7BM23](#)

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9