

Anderson Power Products' family of Euro Battery Connectors (EBC) exceeds all the requirements of DIN 43589-1 and EN 1175-1. The connector design incorporates an innovative, cost effective contact carrier for ease of assembly.

The connectors have a Degree of Protection of IP23 per IEC 60529. The acid resistance and temperature range of the PBT-PC housing exceeds the requirements of EN 1175-1. Contacts are pure copper with silver plate for maximum conductivity.

All materials meet RoHS requirements and are selected to ensure years of reliable service under adverse battery environments.

Features

- **Sturdy advanced polymer housings**

PBT-PC alloy housings provides superior resistance to acids and temperature extremes

- **DIN 43589-1 voltage keying**

Dry-cell, wet-cell & universal keying plugs
coded for 24 / 36 / 48 / 72 / 80 & 96 volts DC

- **Mating compatibility with connectors of other manufacturers**

APP "E" series connectors offer dimensional compatibility for air tube and auxiliary contacts over and above the DIN 43589-1 compatibility of housings and main contacts



- **Silver plated pure copper contacts**

For lowest voltage drop and superior performance

SPECIFICATIONS

Electrical			Mechanical	
Current Rating (Amperes) *			Life	
UL	220		a. No Load (mating cycles)	>5000
EN1175-1:1998	190		b. Under Load (Hot Plug 5 mating cycles @96V)	400A
CSA	160			
Voltage Rating			Average Mating / Unmating Force (lbf)	12
UL / CSA	600		(N)	53
EN1175-1:1998	150		Degree of Protection	IP23
Wire Range			Acid Resistance	1.38g / cm ³
- Power Contacts - AWG (mm ²)	#6 to 1/0 (16 / 50)		Contact Retention - minimum (lbf)	100
- Auxiliary Contacts - AWG (mm ²)	#12 to #10 (4 / 6)		(N)	445
Dielectric Withstanding Voltage (AC)	2,200		Air Tube Rating	2 bar
Average Contact Resistance (micro-ohms)	55			
Operating Temperature (°C)	-25° to 105°			
(°F)	-13° to 221°			
			Materials	
			Housing	PBT/PC blend, glass filled
			Contacts	Copper alloy, silver plate
			Hardware	Steel, zinc chromate plate

* Current derating curves must be observed as current capacity will vary dependent on wire cross section and ambient temperature. Maximum current carrying capacity is measured at 40°C / 104°F using the maximum wire cross section permissible, crimped to contacts using APP recommended tooling.

ORDERING INFORMATION

Connector Part Number Selection

Series	Gender	Main Contact	Handle	Coding Key	Auxiliary Contacts & Air Tubes	Packaging	
E16 **	5	25	-	1	0	2	9
5	Socket						9 Individual
00	None - Order Separately				0	None	8 Bulk
16	16 mm² / #6 AWG				1	(2) Lower Auxiliary Contacts	
25	25 mm² / #4 AWG				2	(2) Upper Auxiliary Contacts	
35	35 mm² / #2 AWG				4	(2) Lower Auxiliary Contacts &	
50	50 mm² / #1/0 AWG			0	Grey, Wet Cell	(2) Upper Auxiliary Contacts	
0	No			2	Green, Dry Cel	5	Air Tube
1	Black			3	Yellow, Universal	6	Air Tube & (2) Upper Auxiliary Contacts

Accessories

Part Number	Description
E160-21	Twin air tube
E16-89	Handle kit - low profile
E32-89	Handle kit - high profile
A320LP-MK	Latch plate for mating side
A320HL-MK	Handle with latch & hardware

**** A supplemental auxiliary holder will ship with each pair of contacts**

HEADQUARTERS: Anderson Power Products®, 13 Pratts Junction Road, Sterling, MA 01564-2305 USA T:978-422-3600 F:978-422-3700

EUROPE: Anderson Power Products® Ltd., Unit 3, Europa Court, Europa Boulevard, Westbrook, Warrington, Cheshire, WA5 7TN United Kingdom T: +44 (0) 1925 428390 F: +44 (0) 1925 428399

ASIA / PACIFIC: IDEAL Anderson Asia Pacific Ltd., Unit 922-928 Topsail Plaza, 11 On Sum Street, Shatin N.T., Hong Kong T: +(852) 2636 0836 F: +(852) 2635 9036

CHINA: IDEAL Anderson Technologies (Shenzhen) Ltd., Block A8 Tantou Western Industrial Park, Songgang Baoan District, Shenzhen, PR. China 518105 T: (+86) 755 2768 2118 F: (+86) 755 2768 2218
TAIWAN: IDEAL Anderson Asia Pacific Ltd., Taiwan Branch, 4F-2, No.116, Dadun 20th St., Situn District, Taichung City 407, Taiwan (R.O.C.) T: (+886) 4 2310 6451 F: (+886) 4 2310 6460

www.andersonpower.com

ORDERING INFORMATION

Tooling

Part


Number	Description
1387G3	Hydraulic tool for power contacts
E160-36	Extraction tool

Note: For tooling die information, see tooling chart on website.

DIMENSIONS


Pin Contact

Part Number	- Wire - mm ² AWG	- ØA - mm in.	- ØB - mm in.
160-1116	16 #6	8.4 0.33	6.0 0.24
160-1125	25 #4	11.0 0.43	8.0 0.31
160-1135	35 #2	12.5 0.49	9.0 0.35
160-1150	50 #1/0	14.5 0.57	11.0 0.43




Upper Auxiliary Contact

E160-33 upper auxiliary contact for 4 mm² (#12 AWG)




Lower Auxiliary Contact


160-13 lower auxiliary contact for 6 mm² (#10 AWG)




Handle / Lever Assembly / Latch




Housing Front View





Housing Side View



Housing Top View



TEMPERATURE CHARTS



Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9