







Copyright FCI.

PRODUCT NUMBER SEE SHEET 2




spec ref				dr	Rainbow Zhan	2015/01/07	projection		MM		size	A3	scale	3:2
tolerance std ASME Y14.5	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	Rainbow Zhan	2015/01/15					ecn no		-	
				chr	-	-								
				appr							Pei-Ming Zheng	2015/01/15	product family	
surface ✓	linear	0.X	±0.50		title 5ACP VT PF RECEPTACLE				dwg no	10106123-5000001		rev	A	
		0.XX	±0.25											
		0.XXX	±0.10											
ASME Y14.5	angular	0°	±2°	www.fci.com	cat. no.			Product - Customer Drw			sheet 1 of 3			



Copyright FCI.

PRODUCT NO.	ROWS		HIGH POWER					
		E1	P5	P4	P3	P2	P1	E2
10106123-5000001LF	D C B A							


CODE	DESCRIPTION
HG	STD HIGH POWER CONTACT (3.43)



dr	Rainbow Zhan	2015/01/07	projection 	MM 	size	A3	scale	3:2		
eng	Rainbow Zhan	2015/01/15			ecn no	-				
chr	-	-								
appr	Pei-Ming Zheng	2015/01/15	product family		PowerBlade+		rel level		Released	
			title			5ACP			rev	
			VT PF RECEPTACLE			dwg no				10106123-5000001
www.fci.com			cat. no.		Product - Customer Drw				sheet 2 of 3	
										A

NOTES:

- 1) "FCI", PART NUMBER AND DATE CODE TO BE MARKED ON THIS SURFACE.
THE MARK CAN BE OMITTED IF THERE IS NOT ENOUGH SPACE ON THIS SURFACE.
- 2) MATERIALS:
 - HOUSING - GLASS FILLED WITH HIGH TEMP THERMOPLASTIC, UL94V-0.
 - SIGNAL CONTACT - COPPER ALLOY.
 - POWER CONTACT - HIGH CONDUCTIVITY COPPER ALLOY.
- 3) PLATING SPECIFICATION REFER TO FCI 10116351
- 4) DENOTES CONNECTOR KEEP OUT ZONE.
- 5) DATUM AND BASIC DIMENIONS WERE ESTABLISHED BY CUSTOMER.
- 6) ALL HOLE DIAMETERS ARE FINISHED HOLE SIZES.
- 7) 1.15 ± 0.025MM DRILLED HOLE PLATED WITH 0.00762MM MIN Sn
OVER 0.0254-0.0762MM Cu PLATING TO ACHIEVE A 1.02 ± 0.07MM HOLE.
- 8) PRODUCT SPECIFICATION REFER TO FCI GS-12-658.
APPLICATION SPECIFICATION REFER TO FCI GS-20-141.
PRODUCT PACKAGED IN TRAYS, REFER TO FCI GS-14-1502.
- 9) THE VOID CORING IN BETWEEN POWER MODULES, SIGNAL
MODULES AND END MODULES ARE OPTIONAL AND THE SHAPE
MAY BE DIFFERENT FOR OPTIMIZE THE MOLDING PROCESS. THE
VOID CORING WILL NOT EFFECT TO PRODUCT FUNCTION.

dr	Rainbow Zhan	2015/01/07	projection 	MM 	size	A3	scale	1:1	
eng	Rainbow Zhan	2015/01/15							
chr	-	-				ecn no	-		
appr	Pei-Ming Zheng	2015/01/15	product family		PowerBlade+	rel level	Released		
	title	5ACP			dwg no	10106123-5000001		rev	
		VT PF RECEPTACLE						A	
	www.fci.com	cat. no.				Product - Customer Drw			sheet 3 of 3



Copyright FCI.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9