

INDICATES THE PRODUCT IS RoHS
COMPATIBLE, SEE NOTE 5

TOTAL NB OF POSITIONS

- 1 - MATERIAL :
HOUSING MAT'L : GLASS FILLED
THERMOPLASTIC. UL94V-0 COLOR: GREY
PIN MATERIAL : PHOSPHOR BRONZE
- 2 - PLATING SPECIFICATIONS :
0.76 μ m GOLD/GXT(PdNi WITH GOLD FLASH)
ON CONTACT AREA
2 μ m MIN MATTE TIN ON TAILS
1.27 μ m NICKEL TIN UNDERLAYER

4 - 40N MIN LATCH RETENTION FORCE
AT FIRST EXTRACTION

a - PLATING:

- "LF" MEANS THE PRODUCT IS LEAD-FREE, 2μm MINIMUM MATTE TIN OVER 1.27μm MINIMUM NICKEL UNDERPLATE.

- THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C ±5°C SOLDER BATH TEMPERATURE FOR 5 SECONDS IN A WAVE SOLDER APPLICATION WITH A 1.6mm MIN THICK CIRCUIT BOARD.

– MEETS PACKAGING SPECS AS PER GS-14-920

1.8

5.84

$\phi 1.02 \pm 0.08$

2.54 ± 0.08

$\phi 2.8$ MIN

2.54 ± 0.08

NON-ACCUM TYP

RECOMMENDED HOLE PATTERN

Technical drawing of a mechanical component, likely a pump or motor housing, showing dimensions in millimeters. The drawing includes a top view and a side view. Key dimensions are:

- Overall length: 39.62
- Overall width: 8.6
- Top view dimensions:
 - Distance from left edge to first hole: 2.54
 - Distance between holes: 17.78
 - Distance from last hole to right edge: 1.52
 - Distance from left edge to center of first hole: 2.54
 - Distance from center of last hole to right edge: 1.52
- Side view dimensions:
 - Overall height: 6.3
 - Distance from left edge to center of first hole: 3.81
 - Distance from center of last hole to right edge: 1.27
 - Distance from left edge to center of last hole: 25.85
 - Distance from center of last hole to right edge: 1.27
 - Distance from left edge to center of first hole: 3.81
 - Distance from center of last hole to right edge: 1.27

Technical drawing of the front view of a mechanical part. The drawing shows a complex profile with a central vertical section. Key dimensions are indicated: a horizontal dimension of 6 MAX at the top, a vertical dimension of 10.8 on the left side, and a vertical dimension of 24 MAX on the right side. The part features a central circular feature, a rectangular slot, and a small circular feature at the bottom center. A dashed line indicates a hidden internal feature.

FOR LATCH DETAILS
SEE DRAWING 10129768

Technical drawing of a mechanical part, likely a bracket or base plate, showing dimensions and features. The drawing includes a central vertical slot, two circular holes, and a rectangular feature on the right. Dimensions are given in millimeters. Key dimensions include: overall width 29.46, overall height 17.4, central slot width 4.3, distance from left edge to center of slot 11.73, distance from center of slot to right edge 17.73, distance from left edge to center of left hole 11.73, distance from center of left hole to center of right hole 17.73, distance from center of right hole to right edge 11.73, distance from left edge to center of left hole 11.73, distance from center of left hole to center of right hole 17.73, distance from center of right hole to right edge 11.73, distance from left edge to center of left hole 11.73, distance from center of left hole to center of right hole 17.73, distance from center of right hole to right edge 11.73. Features include: 0.62 SQUARE, LATCH, and a hole with diameter $\varnothing 2.6^{+0}_{-0.1}$.

Technical drawing of a mechanical part with dimensions:

- Top horizontal dimension: 2.54
- Right vertical dimension: $5.8^{+0.55}_0$
- Right vertical dimension (bottom): 2.54
- Bottom horizontal dimension (left): 2.9
- Bottom horizontal dimension (middle): 1.5
- Bottom horizontal dimension (right): 1.8

[illegible]

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9