



## N-channel 600 V, 0.094 $\Omega$ typ., 25 A, MDmesh™ DM6 Power MOSFET in a PowerFLAT™ 8x8 HV package



PowerFLAT™ 8x8 HV



### Product status link

[STL45N60DM6](#)

### Product summary

|            |                   |
|------------|-------------------|
| Order code | STL45N60DM6       |
| Marking    | 45N60DM6          |
| Package    | PowerFLAT™ 8x8 HV |
| Packing    | Tape and reel     |

### Features

| Order code  | V <sub>DS</sub> | R <sub>DS(on)</sub> max. | I <sub>D</sub> |
|-------------|-----------------|--------------------------|----------------|
| STL45N60DM6 | 600 V           | 0.110 $\Omega$           | 25 A           |

- Fast-recovery body diode
- Lower R<sub>DS(on)</sub> per area vs previous generation
- Low gate charge, input capacitance and resistance
- 100% avalanche tested
- Extremely high dv/dt ruggedness
- Zener-protected

### Applications

- Switching applications

### Description

This high-voltage N-channel Power MOSFET is part of the MDmesh™ DM6 fast-recovery diode series. Compared with the previous MDmesh fast generation, DM6 combines very low recovery charge (Q<sub>rr</sub>), recovery time (t<sub>rr</sub>) and excellent improvement in R<sub>DS(on)</sub> per area with one of the most effective switching behaviors available in the market for the most demanding high-efficiency bridge topologies and ZVS phase-shift converters.

## 1 Electrical ratings

**Table 1. Absolute maximum ratings**

| Symbol         | Parameter                                                         | Value      | Unit               |
|----------------|-------------------------------------------------------------------|------------|--------------------|
| $V_{GS}$       | Gate-source voltage                                               | $\pm 25$   | V                  |
| $I_D$          | Drain current (continuous) at $T_C = 25\text{ }^{\circ}\text{C}$  | 25         | A                  |
|                | Drain current (continuous) at $T_C = 100\text{ }^{\circ}\text{C}$ | 16         | A                  |
| $I_{DM}^{(1)}$ | Drain current (pulsed)                                            | 95         | A                  |
| $P_{TOT}$      | Total power dissipation at $T_C = 25\text{ }^{\circ}\text{C}$     | 160        | W                  |
| $dv/dt^{(2)}$  | Peak diode recovery voltage slope                                 | 50         | V/ns               |
| $dv/dt^{(3)}$  | MOSFET $dv/dt$ ruggedness                                         | 100        | V/ns               |
| $T_{stg}$      | Storage temperature range                                         | -55 to 150 | $^{\circ}\text{C}$ |
| $T_J$          | Operating junction temperature range                              |            |                    |

1. Pulse width is limited by safe operating area.
2.  $I_{SD} \leq 25\text{ A}$ ,  $di/dt \leq 900\text{ A}/\mu\text{s}$ ,  $V_{DS(peak)} < V_{(BR)DSS}$ ,  $V_{DD} = 400\text{ V}$
3.  $V_{DS} \leq 480\text{ V}$

**Table 2. Thermal data**

| Symbol              | Parameter                        | Value | Unit                        |
|---------------------|----------------------------------|-------|-----------------------------|
| $R_{thj-case}$      | Thermal resistance junction-case | 0.78  | $^{\circ}\text{C}/\text{W}$ |
| $R_{thj-pcb}^{(1)}$ | Thermal resistance junction-pcb  | 45    | $^{\circ}\text{C}/\text{W}$ |

1. When mounted on FR-4 board of 1 inch<sup>2</sup>, 2oz Cu.

**Table 3. Avalanche characteristics**

| Symbol   | Parameter                                                                                                              | Value | Unit |
|----------|------------------------------------------------------------------------------------------------------------------------|-------|------|
| $I_{AR}$ | Avalanche current, repetitive or not repetitive (pulse width limited by $T_{jmax}$ )                                   | 6     | A    |
| $E_{AS}$ | Single pulse avalanche energy (starting $T_J = 25\text{ }^{\circ}\text{C}$ , $I_D = I_{AR}$ , $V_{DD} = 50\text{ V}$ ) | 630   | mJ   |

## 2 Electrical characteristics

$T_C = 25\text{ }^{\circ}\text{C}$  unless otherwise specified

**Table 4. On/off states**

| Symbol        | Parameter                         | Test conditions                                                                                | Min. | Typ.  | Max.    | Unit          |
|---------------|-----------------------------------|------------------------------------------------------------------------------------------------|------|-------|---------|---------------|
| $V_{(BR)DSS}$ | Drain-source breakdown voltage    | $V_{GS} = 0\text{ V}$ , $I_D = 1\text{ mA}$                                                    | 600  |       |         | V             |
| $I_{DSS}$     | Zero gate voltage drain current   | $V_{GS} = 0\text{ V}$ , $V_{DS} = 600\text{ V}$                                                |      |       | 1       | $\mu\text{A}$ |
|               |                                   | $V_{GS} = 0\text{ V}$ , $V_{DS} = 600\text{ V}$ ,<br>$T_C = 125\text{ }^{\circ}\text{C}^{(1)}$ |      |       | 100     | $\mu\text{A}$ |
| $I_{GSS}$     | Gate-body leakage current         | $V_{DS} = 0\text{ V}$ , $V_{GS} = \pm 25\text{ V}$                                             |      |       | $\pm 5$ | $\mu\text{A}$ |
| $V_{GS(th)}$  | Gate threshold voltage            | $V_{DS} = V_{GS}$ , $I_D = 250\text{ }\mu\text{A}$                                             | 3.25 | 4     | 4.75    | V             |
| $R_{DS(on)}$  | Static drain-source on-resistance | $V_{GS} = 10\text{ V}$ , $I_D = 12.5\text{ A}$                                                 |      | 0.094 | 0.110   | $\Omega$      |

1. Defined by design, not subject to production test.

**Table 5. Dynamic**

| Symbol                     | Parameter                     | Test conditions                                                                                                                    | Min. | Typ. | Max. | Unit     |
|----------------------------|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------|------|------|------|----------|
| $C_{iss}$                  | Input capacitance             | $V_{DS} = 100\text{ V}$ , $f = 1\text{ MHz}$ ,<br>$V_{GS} = 0\text{ V}$                                                            | -    | 1920 | -    | pF       |
| $C_{oss}$                  | Output capacitance            |                                                                                                                                    | -    | 120  | -    | pF       |
| $C_{rss}$                  | Reverse transfer capacitance  |                                                                                                                                    | -    | 2    | -    | pF       |
| $C_{oss\text{ eq.}}^{(1)}$ | Equivalent output capacitance | $V_{DS} = 0\text{ to }480\text{ V}$ , $V_{GS} = 0\text{ V}$                                                                        | -    | 310  | -    | pF       |
| $R_G$                      | Intrinsic gate resistance     | $f = 1\text{ MHz}$ , $I_D = 0\text{ A}$                                                                                            | -    | 1.5  | -    | $\Omega$ |
| $Q_g$                      | Total gate charge             | $V_{DD} = 480\text{ V}$ , $I_D = 30\text{ A}$ ,<br>$V_{GS} = 0\text{ to }10\text{ V}$<br>(see Figure 14. Gate charge test circuit) | -    | 44   | -    | nC       |
| $Q_{gs}$                   | Gate-source charge            |                                                                                                                                    | -    | 10   | -    | nC       |
| $Q_{gd}$                   | Gate-drain charge             |                                                                                                                                    | -    | 25   | -    | nC       |

1.  $C_{oss\text{ eq.}}$  is defined as a constant equivalent capacitance giving the same charging time as  $C_{oss}$  when  $V_{DS}$  increases from 0 to 80%  $V_{DSS}$ .

**Table 6. Switching times**

| Symbol       | Parameter           | Test conditions                                                                                                                                                                                                  | Min. | Typ. | Max. | Unit |
|--------------|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------|------|------|
| $t_{d(on)}$  | Turn-on delay time  | $V_{DD} = 300\text{ V}$ , $I_D = 15\text{ A}$ ,<br>$R_G = 4.7\text{ }\Omega$ , $V_{GS} = 10\text{ V}$<br>(see Figure 13. Switching times test circuit for resistive load and Figure 18. Switching time waveform) | -    | 15   | -    | ns   |
| $t_r$        | Rise time           |                                                                                                                                                                                                                  | -    | 5.3  | -    | ns   |
| $t_{d(off)}$ | Turn-off delay time |                                                                                                                                                                                                                  | -    | 50   | -    | ns   |
| $t_f$        | Fall time           |                                                                                                                                                                                                                  | -    | 7.3  | -    | ns   |

**Table 7. Source drain diode**


| Symbol          | Parameter                     | Test conditions                                                                                                                                                                                                     | Min. | Typ. | Max. | Unit          |
|-----------------|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------|------|---------------|
| $I_{SD}$        | Source-drain current          |                                                                                                                                                                                                                     | -    |      | 25   | A             |
| $I_{SDM}^{(1)}$ | Source-drain current (pulsed) |                                                                                                                                                                                                                     | -    |      | 95   | A             |
| $V_{SD}^{(2)}$  | Forward on voltage            | $V_{GS} = 0\text{ V}$ , $I_{SD} = 25\text{ A}$                                                                                                                                                                      | -    |      | 1.5  | V             |
| $t_{rr}$        | Reverse recovery time         | $I_{SD} = 30\text{ A}$ , $di/dt = 100\text{ A}/\mu\text{s}$ ,<br>$V_{DD} = 100\text{ V}$<br>(see Figure 15. Test circuit for inductive load switching and diode recovery times)                                     | -    | 105  |      | ns            |
| $Q_{rr}$        | Reverse recovery charge       |                                                                                                                                                                                                                     | -    | 0.48 |      | $\mu\text{C}$ |
| $I_{RRM}$       | Reverse recovery current      |                                                                                                                                                                                                                     | -    | 9.3  |      | A             |
| $t_{rr}$        | Reverse recovery time         | $I_{SD} = 30\text{ A}$ , $di/dt = 100\text{ A}/\mu\text{s}$ ,<br>$V_{DD} = 100\text{ V}$ , $T_j = 150\text{ }^\circ\text{C}$<br>(see Figure 15. Test circuit for inductive load switching and diode recovery times) | -    | 210  |      | ns            |
| $Q_{rr}$        | Reverse recovery charge       |                                                                                                                                                                                                                     | -    | 1.95 |      | $\mu\text{C}$ |
| $I_{RRM}$       | Reverse recovery current      |                                                                                                                                                                                                                     | -    | 18.6 |      | A             |

1. Pulse width is limited by safe operating area.


2. Pulsed: pulse duration = 300  $\mu\text{s}$ , duty cycle 1.5 %.

## 2.1 Electrical characteristics (curves)


**Figure 1. Safe operating area**




**Figure 2. Thermal impedance**




**Figure 3. Output characteristics**




**Figure 4. Transfer characteristics**




**Figure 5. Gate charge vs gate-source voltage**




**Figure 6. Static drain-source on-resistance**




**Figure 7. Capacitance variations**




**Figure 8. Normalized gate threshold voltage vs temperature**




**Figure 9. Normalized on-resistance vs temperature**




**Figure 10. Normalized  $V_{(BR)DSS}$  vs temperature**




**Figure 11. Source-drain diode forward characteristics**




**Figure 12. Output capacitance stored energy**




### 3 Test circuits

**Figure 13. Switching times test circuit for resistive load**



AM15855v1

**Figure 14. Gate charge test circuit**



AM01469v2

**Figure 15. Test circuit for inductive load switching and diode recovery times**



AM15857v1

**Figure 16. Unclamped inductive load test circuit**


AM15858v1

**Figure 17. Unclamped inductive waveform**


AM01472v1

**Figure 18. Switching time waveform**


AM01473v1

---


## 4 Package information

---

In order to meet environmental requirements, ST offers these devices in different grades of **ECOPACK®** packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK® is an ST trademark.

## 4.1 PowerFLAT™ 8x8 HV package information


Figure 19. PowerFLAT™ 8x8 HV package outline



8222871\_Rev\_4

**Table 8. PowerFLAT™ 8x8 HV mechanical data**

| Ref. | Dimensions (in mm) |      |      |
|------|--------------------|------|------|
|      | Min.               | Typ. | Max. |
| A    | 0.75               | 0.85 | 0.95 |
| A1   | 0.00               |      | 0.05 |
| A3   | 0.10               | 0.20 | 0.30 |
| b    | 0.90               | 1.00 | 1.10 |
| D    | 7.90               | 8.00 | 8.10 |
| E    | 7.90               | 8.00 | 8.10 |
| D2   | 7.10               | 7.20 | 7.30 |
| E1   | 2.65               | 2.75 | 2.85 |
| E2   | 4.25               | 4.35 | 4.45 |
| e    | 2.00 BSC           |      |      |
| L    | 0.40               | 0.50 | 0.60 |


**Figure 20. PowerFLAT™ 8x8 HV footprint**


8222871\_REV\_4\_footprint

**Note:** All dimensions are in millimeters.

## 4.2 PowerFLAT™ 8x8 HV packing information


**Figure 21. PowerFLAT™ 8x8 HV tape**




8229819\_Tape\_revA

*Note: All dimensions are in millimeters.*

**Figure 22. PowerFLAT™ 8x8 HV package orientation in carrier tape**



**Figure 23. PowerFLAT™ 8x8 HV reel**



8229819\_Reel\_revA

**Note:** All dimensions are in millimeters.

## Revision history

**Table 9. Document revision history**

| Date        | Revision | Changes                                                                                                                                                                                                                                                                                                                                                                       |
|-------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 27-May-2016 | 1        | First release.                                                                                                                                                                                                                                                                                                                                                                |
| 02-Aug-2017 | 2        | Modified title and features in cover page.<br>Updated <i>Section 1: "Electrical ratings" and Section 2: "Electrical characteristics"</i> .<br>Added <i>Section 2.1: "Electrical characteristics (curves)"</i> .<br>Minor text changes                                                                                                                                         |
| 03-Jul-2018 | 3        | Removed maturity status indication from cover page.<br>Updated features on cover page.<br>Minor text changes                                                                                                                                                                                                                                                                  |
| 28-Jan-2019 | 4        | Updated <a href="#">Table 1. Absolute maximum ratings</a> , <a href="#">Table 4. On/off states</a> and <a href="#">Table 7. Source drain diode</a> .<br>Updated <a href="#">Figure 1. Safe operating area</a> , <a href="#">Figure 6. Static drain-source on-resistance</a> and <a href="#">Figure 11. Source-drain diode forward characteristics</a> .<br>Minor text changes |

## Contents

|            |                                             |           |
|------------|---------------------------------------------|-----------|
| <b>1</b>   | <b>Electrical ratings .....</b>             | <b>2</b>  |
| <b>2</b>   | <b>Electrical characteristics.....</b>      | <b>3</b>  |
| <b>2.1</b> | Electrical characteristics (curves) .....   | 5         |
| <b>3</b>   | <b>Test circuits .....</b>                  | <b>7</b>  |
| <b>4</b>   | <b>Package information.....</b>             | <b>8</b>  |
| <b>4.1</b> | PowerFLAT™ 8x8 HV package information.....  | 8         |
| <b>4.2</b> | PowerFLAT™ 8x8 HV packing information ..... | 10        |
|            | <b>Revision history .....</b>               | <b>13</b> |

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2019 STMicroelectronics – All rights reserved

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9