

VIPerPlus

Truly innovative AC-DC conversion



April 2009

Advanced solutions for switch-mode power supplies

ST's VIPerPlus series of high-voltage converters combine the innovative avalanche-rugged SuperMESH™ power MOSFET with state-of-the-art PWM circuitry. The result is truly innovative AC-DC conversion that is efficient, simpler, quicker and - with component count halved - less expensive.

In addition to benefits such as optimized current-mode control and comprehensive built-in protection circuits, the VIPerPlus family represents the easiest solution to comply with the Blue Angel and Energy Star eco norms, with extremely low total power consumption from the mains when the system is in standby mode.

Key benefits

- Ultra-low power-supply consumption: 30 mW standby at 265 V_{AC}
- Easily meets all energy efficiency regulations
- Avalanche-rugged 800 V power section for high robustness and reduced clamp cost
- Jittering feature reduces EMI filter cost and helps meet the EN550022 class B specifications
- High efficiency using quasi-resonant version
- No auxiliary winding costs for very low-power SMPS
- Embedded advanced protection features for high PSU reliability
- Easily compliant with the 2002/95/EC European directive
- Extended pin creepage distance for safe operation in humid environments

Description	Power section: 800 V avalanche rugged						
	R _{DS(on)} : 24 ohm			R _{DS(on)} : 7 ohm			
	I _{DLIM} *: 400 mA			I _{DLIM} *: 700 mA			I _{DLIM} *: 800 mA
	VIPER15	VIPER16	VIPER17	VIPER25	VIPER26	VIPER27	VIPER28
Fixed-frequency PWM current-mode controller			✓			✓	✓
Quasi-resonant PWM current-mode controller	✓			✓			
Fixed-frequency PWM current-mode controller with embedded error amplifier		✓			✓		
Limiting drain current with adjustable set point	✓	✓	✓	✓	✓	✓	✓
Fixed-frequency 60 kHz (L type) or 115 kHz (H type) with jittering		✓	✓		✓	✓	✓
Advanced standby management	✓	✓	✓	✓	✓	✓	✓
Automatic autorestart after fault	✓	✓	✓	✓	✓	✓	✓
Advanced overload and short circuit management	✓	✓	✓	✓	✓	✓	✓
Accurate overvoltage protection	✓		✓	✓		✓	✓
Open-loop failure detection		✓			✓		
Feed forward compensation	✓			✓			
On-board soft start up	✓	✓	✓	✓	✓	✓	✓
Hysteretic thermal shutdown	✓	✓	✓	✓	✓	✓	✓
Brown-out protection	✓		✓	✓		✓	
Extra power timer for peak power management							✓
Eliminates bias winding supply		✓					
Packages	DIP7 (N type) S016N (D type)			DIP7 (N type) S016N (D type)			
Maximum output power with 230 V _{AC} ±10%	up to 10 W			up to 20 W			
Maximum output power with 85 to 265 V _{AC}	up to 6 W			up to 12 W			

Topologies and applications

ViPerPlus converters are suitable for a wide range of applications and switch-mode power supply topologies.

ViPerPlus selection (by SMPS topology)	Power section: 800 V avalanche-rugged						
	$R_{DS(on)}: 24 \text{ ohm}$			$R_{DS(on)}: 24 \text{ ohm}$			
	$I_{DLIM}: 400 \text{ mA}$			$I_{DLIM}: 700 \text{ mA}$			$I_{DLIM}: 800 \text{ mA}$
	VIPER15	VIPER16	VIPER17	VIPER25	VIPER26	VIPER27	VIPER28
Buck converter		✓			✓		
Buck-boost converter		✓			✓		
Flyback isolated converter	✓	✓	✓	✓	✓	✓	✓
Flyback primary regulation converter	✓	✓ ☺	✓	✓	✓ ☺	✓	✓
Flyback non-isolated converter	✓	✓ ☺	✓	✓	✓ ☺	✓	✓

☺ = high-performance topology

Home appliances: washing machines, dishwashers, dryers, ovens, fridges



ViPerPlus function

■ Power supplies for microcontrollers and displays

Non-isolated PSU

Viper16

Viper26

Isolated PSU

Viper15

Viper17

ViperV25

Viper27

Main benefits

- Robustness: 800 V avalanche-rugged power section plus embedded failure protection functions
- Cost saving: Easy design for positive and negative voltages with minimized total component count
- Flexibility: Same PCB for PSU from 1 W to 12 W
- Energy saving: 30 mW PSU standby and high efficiency

Smaller home appliances: coffee makers, food processors, microwave ovens



ViPerPlus function

■ Replacement of capacitive power supplies

Non-isolated PSU

Viper16

Viper26

Main benefits

- Energy saving: 30 mW PSU standby and high efficiency
- Cost saving: Minimized design for positive or negative voltage without transformer and self supplied.
- In case of fly-back converter, eliminates the auxiliary winding.
- EMI: Easily meets the EN550022 class B specification
- Robustness: 800 V avalanche-rugged power section plus embedded failure protection functions

Consumer electronics: LCD TVs, DVD players/recorders and set-top boxes, home theater



VIPerPlus function
■ Auxiliary power supplies

Non-isolated PSU

Viper16

Viper26

Isolated PSU

Viper15

Viper17

Viper25

Viper27

Viper28

Main benefits

- Energy saving: 30 mW PSU standby and high efficiency
- Robustness: 800 V avalanche-rugged power section plus embedded failure protection functions, brown-out function or peak power management
- Cost saving: Simple design with minimized total component count
- EMI: Easily meets the EN550022 class B specification
- Flexibility: Same PCB for PSU from 1 W to 12 W

LED driver: architectural lighting, interior decorating lighting, emergency lights



VIPerPlus function
■ Power supplies

Non-isolated PSU

Viper16

Viper26

Isolated PSU

Viper15

Viper17

Viper25

Viper27

Viper28

Main benefits

- Energy saving: 30 mW PSU standby and high efficiency
- Robustness: 800 V avalanche-rugged power section plus embedded failure protection functions
- Cost saving: Simple design with minimized total component count and high reliability
- Flexibility: Same PCB for PSU from 1 W to 12 W

Computer: desktop PC, server



VIPerPlus function
■ Auxiliary power supplies

Non-isolated PSU

Viper26

Isolated PSU

Viper25

Viper27

Viper28

Main benefits

- Energy saving: 30 mW PSU standby and high efficiency
- Robustness: 800 V avalanche-rugged power section plus embedded failure protection functions and peak power management
- Cost saving: Simple design with minimized total component count
- EMI: Easily meets the EN550022 class B specification
- Flexibility: Same PCB for PSU from 1 W to 12 W

Adapters, chargers for: mobile/smart phones, cordless appliances, shavers, toys, digital cameras, MP3/ portable audio



VIPerPlus function
■ Power supply

Non-isolated PSU

Viper16

Viper26

Isolated PSU

Viper15

Viper17

Viper25

Viper27

Main benefits

- Energy: 30 mW standby and high efficiency compliant with all relevant standards
- Robustness: 800 V avalanche-rugged power section plus embedded failure protection functions and peak power management
- Cost saving: Simple design with minimized total component count
- Flexibility: Same PCB for PSU from 1 W to 12 W

Product table

Part number	Package	Packaging	$R_{DS(on)}^{max}$ (ohm)	I_{DLIM} (mA)	Breakdown voltage (V)	VDD range (V)	Switching mode	F_{sw} (kHz)
VIPER15LN	DIP-7	Tube	24	400	800	8.5 to 23	Quasi-resonant	variable (limited to 150 kHz)
VIPER15HN	DIP-7	Tube	24	400	800	8.5 to 23	Quasi-resonant	variable (limited to 225 kHz)
VIPER15LD	SO16N	Tube	24	400	800	8.5 to 23	Quasi-resonant	variable (limited to 150 kHz)
VIPER15HD	SO16N	Tube	24	400	800	8.5 to 23	Quasi-resonant	variable (limited to 225 kHz)
VIPER15LDTR	SO16N	Tape and reel	24	400	800	8.5 to 23	Quasi-resonant	variable (limited to 150 kHz)
VIPER15HDTR	SO16N	Tape and reel	24	400	800	8.5 to 23	Quasi-resonant	variable (limited to 225 kHz)
VIPER16LN	DIP-7	Tube	24	400	800	8.5 to 23 ⁽¹⁾	Fixed-frequency	60
VIPER16HN	DIP-7	Tube	24	400	800	8.5 to 23 ⁽¹⁾	Fixed-frequency	115
VIPER16LD	SO16N	Tube	24	400	800	8.5 to 23 ⁽¹⁾	Fixed-frequency	60
VIPER16HD	SO16N	Tube	24	400	800	8.5 to 23 ⁽¹⁾	Fixed-frequency	115
VIPER16LDTR	SO16N	Tape and reel	24	400	800	8.5 to 23 ⁽¹⁾	Fixed-frequency	60
VIPER16HDTR	SO16N	Tape and reel	24	400	800	8.5 to 23 ⁽¹⁾	Fixed-frequency	115
VIPER17LN	DIP-7	Tube	24	400	800	8.5 to 23	Fixed-frequency	60
VIPER17HN	DIP-7	Tube	24	400	800	8.5 to 23	Fixed-frequency	115
VIPER17LD	SO16N	Tube	24	400	800	8.5 to 23	Fixed-frequency	60
VIPER17HD	SO16N	Tube	24	400	800	8.5 to 23	Fixed-frequency	115
VIPER17LDTR	SO16N	Tape and reel	24	400	800	8.5 to 23	Fixed-frequency	60
VIPER17HDTR	SO16N	Tape and reel	24	400	800	8.5 to 23	Fixed-frequency	115
VIPER25LN	DIP-7	Tube	7	700	800	8.5 to 23	Quasi-resonant	variable (limited to 150 kHz)
VIPER25HN	DIP-7	Tube	7	700	800	8.5 to 23	Quasi-resonant	variable (limited to 225 kHz)
VIPER25LD	SO16N	Tube	7	700	800	8.5 to 23	Quasi-resonant	variable (limited to 150 kHz)
VIPER25HD	SO16N	Tube	7	700	800	8.5 to 23	Quasi-resonant	variable (limited to 225 kHz)
VIPER25LDTR	SO16N	Tape and reel	7	700	800	8.5 to 23	Quasi-resonant	variable (limited to 150 kHz)
VIPER25HDTR	SO16N	Tape and reel	7	700	800	8.5 to 23	Quasi-resonant	variable (limited to 225 kHz)
VIPER26LN	DIP-7	Tube	7	700	800	8.5 to 23	Fixed-frequency	60
VIPER26HN	DIP-7	Tube	7	700	800	8.5 to 23	Fixed-frequency	115
VIPER26LD	SO16N	Tube	7	700	800	8.5 to 23	Fixed-frequency	60
VIPER26HD	SO16N	Tube	7	700	800	8.5 to 23	Fixed-frequency	115
VIPER26LDTR	SO16N	Tape and reel	7	700	800	8.5 to 23	Fixed-frequency	60
VIPER26HDTR	SO16N	Tape and reel	7	700	800	8.5 to 23	Fixed-frequency	115
VIPER27LN	DIP-7	Tube	7	700	800	8.5 to 23	Fixed-frequency	60
VIPER27HN	DIP-7	Tube	7	700	800	8.5 to 23	Fixed-frequency	115
VIPER27LD	SO16N	Tube	7	700	800	8.5 to 23	Fixed-frequency	60
VIPER27HD	SO16N	Tube	7	700	800	8.5 to 23	Fixed-frequency	115
VIPER27LDTR	SO16N	Tape and reel	7	700	800	8.5 to 23	Fixed-frequency	60
VIPER27HDTR	SO16N	Tape and reel	7	700	800	8.5 to 23	Fixed-frequency	115
VIPER28LN	DIP-7	Tube	7	800	800	8.5 to 23	Fixed-frequency	60
VIPER28HN	DIP-7	Tube	7	800	800	8.5 to 23	Fixed-frequency	115
VIPER28LD	SO16N	Tube	7	800	800	8.5 to 23	Fixed-frequency	60
VIPER28HD	SO16N	Tube	7	800	800	8.5 to 23	Fixed-frequency	115
VIPER28LDTR	SO16N	Tape and reel	7	800	800	8.5 to 23	Fixed-frequency	60
VIPER28HDTR	SO16N	Tape and reel	7	800	800	8.5 to 23	Fixed-frequency	115

(1) eliminates the bias winding supply

Design support

Part number	Package	F _{sw} (kHz)	Evaluation board order code	Description	Application note	Input voltage (Vac)	Output voltage (V)	Output current (A)
VIPER16HN	DIP-7	115	EVLVIP16H-4WFN	Non isolated fly-back PSU	*	85 to 265	16	0.25
VIPER16HN	DIP-7	115	EVLVIP16H-4WFL	Isolated flyback PSU	*	85 to 265	16	0.25
VIPER16LN	DIP-7	60	EVLVIP16L-4WFN	Non isolated fly-back PSU	*	85 to 265	16	0.25
VIPER16LN	DIP-7	60	EVLVIP16L-4WFL	Isolated flyback PSU	*	85 to 265	16	0.25
VIPER16LN	DIP-7	60	STEVAL-ISA010V1	Non-isolated buck converter	AN2872	85 to 500	12/5	0.15
VIPER17HN	DIP-7	115	EVLVIP17-5WCHG	Battery charger (isolated flyback)	AN2840	85 to 265	5	1
VIPER17HN	DIP-7	115	STEVAL-ILL017V1	LED driver (non-isolated flyback)	AN2811	220 ±10%	7	0.5
VIPER17HN	DIP-7	115	STEVAL-ISA062V1	Isolated flyback PSU	AN2934	85 to 265	5/12	0.5/0.25
VIPER17HN	DIP-7	115	STEVAL-ISA060V1	Isolated flyback PSU	AN2753	85 to 265	12	0.5
VIPER17LN	DIP-7	60	EVALVIPER17L-6W	Isolated flyback PSU	AN2803	85 to 265	12	0.5
VIPER17LN	DIP-7	60	STEVAL-ISA058V1	Isolated flyback PSU (standby 30 mW)	AN2864	85 to 265	5	1
VIPER28HN	DIP-7	115	EVLVIPER28H-10W	Isolated flyback PSU	*	85 to 265	5	2.4
VIPER28LN	DIP-7	60	EVLVIPER28L-10W	Isolated flyback PSU	*	85 to 265	5	2.4

* coming soon

DIP7 and S016N packages



© STMicroelectronics - April 2009 - Printed in Italy - All rights reserved

The STMicroelectronics corporate logo is a registered trademark of the STMicroelectronics group of companies. VIPER is a trademark of STMicroelectronics
All other names are the property of their respective owners.

For more information on ST products and solutions,
visit www.st.com

Order code: BRVIPERP0309



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[STMicroelectronics:](#)

[EVLVIP16H-4WFL](#) [EVLVIP16L-4WFL](#)

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9