CUSTOMER'S NAME

Mouser Electronics

ALPHA REFERENCE NO.
SP15080160

SPECIFICATION

PART NO.	ALPHA MODEL NAME
1.	MF01-N-221-A01

MODEL NAME
MODEL NO.

APPROVAL

PREPARED BY	REVIEWED BY	APPROVED BY

台灣艾華電子工業股份有限公司

33045 桃園市桃園區中正路 1221 號 9 樓

TAIWAN ALPHA ELECTRONIC CO., LTD.


9F, No. 1221, Chung Cheng Rd.,Taoyuan Dist., Taoyuan City ,330 Taiwan

Tel: 886-3-3577799 Fax: 886-3-3577700

EMAIL: sales@taiwanalpha.com.tw

URL: http//www.taiwanalpha.com

THIRD ANGLE PROJECTION



No.	DATE	DESCRIPTION	MODEL NAME	TOL.UNILESS OTHERWISE STATED	DIMENSION	SCALE	DRAWN BY	CHECKED BY	APPROVED BY	DRAWING No.
△				less than 0~4 ±0.1 above 4~14 ±0.2 above 14~63 ±0.2 above 63~250 ±0.3 above 250~600 ±0.4	mm	1:1	李 2015.06.09 宏祥	蔡 2015.06.09 信村	劉 2015.06.09 韋良	MF01-N-221-A01
△										
△										

TAIWAN ALPHA ELECTRONIC CO., LTD.

規格書

SPECIFICATION

Model name:MF01-N-221-A01

檢驗項目 Inspection Item	規格 SPEC.	備註 Notes
起始按壓力 Actuation Force	30g	
按壓力靈敏度範圍 Force Sensitivity Range	30~1000g(0.3~9.8N)	
再現性 Force Repeatability (Single Part)	±5%	
再現性 Force Repeatability (Part To Part)	±20%	
解析度 Force Resolution	Continuous(Analog)	
有效區域 Active Area	14.7 mm diameter	
未按壓阻值 Stand-Off Resistance(Unloaded)	>20MΩ	
反應時間 Response Time	<1ms	
操作溫度 Operation Temp.	-20℃ to +70℃	
使用壽命 Life Cycle	1 million	Without Failure
厚度 Thickness	0.43±0.05mm	

Taiwan Alpha Electronic Co., LTD.





Date：2015/8/17 Ver.：B

本資料為台灣艾華電子工業股份有限公司之機密與專有財產，非經書面許可，不得對外透露或使用本文件，亦不得複印、複製或轉變成任何其他形式使用。
The Information is confidential property of Taiwan Alpha Electronic Co., LTD. Unauthorized distribution, reproduced or disclosed part without prior written permission of Taiwan Alpha Electronic Co., LTD. is strictly prohibited.

Membrane sensor usage tips

Please follow the below stipulate to avoid error conditions such as false triggering, false readings, pre-loading, or gouging and cracking of the sensor.

1. The side of adhesive should be used on the firm, flat and smooth surfaces, can't not be used on the curved surfaces. Also, be careful of trapped air bubbles or dirt particles when laminating the membrane sensor to surface, it cause the sensor to appear loaded in the absence of an external load. Recommended to clean the surface before adhesive.
2. Do not kink, bending or scratches the tail of membrane sensors. The traces should not be bent more than 90° as the silver conductive leads could break. Also, be careful if bending the tail near the active area. This can cause stress on the active area and may result in pre-loading and false readings.
3. Do not block the vent. This vent assures pressure equilibrium with the environment, as well as allowing even loading and unloading of the device. Blocking this vent could cause sensors to respond to any actuation in a non-repeatable manner.
4. Please use an overlay, such as a polycarbonate film or an elastomer, to prevent gouging of the membrane sensors from sharp objects.
5. Do be careful of kinks or dents in active areas. They can cause false triggering of the sensors.
6. Do not apply excessive shear force. This can cause delamination of the layers.
7. Do not exceed 1mA of current per square centimeter of applied force (actuator area). This can irreversibly damage the device.
8. The sensors are not designed for use under water. The sensors are not compatible with direct liquid contact. Sensors are ideally suited to placement behind a waterproof enclosure.
9. With flexible substrates, the solder joint will not hold and the substrate can easily melt and distort if solder directly to the exposed silver traces. Choose standard connection, such as FFC connector, solder tabs, female contacts, or female contact with housing connectors.

FFC Connector	Solder Tabs(pin)	Female contacts	Female contact with housing
			

Taiwan Alpha Electronic Co., LTD.

Date：2015/8/31 Ver.：A

本資料為台灣艾華電子工業股份有限公司之機密與專有財產，非經書面許可，不得對外透露或使用本文件，亦不得複印、複製或轉變成任何其他形式使用。
The Information is confidential property of Taiwan Alpha Electronic Co., LTD. Unauthorized distribution, reproduced or disclosed part without prior written permission of Taiwan Alpha Electronic Co., LTD. is strictly prohibited.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Alpha (Taiwan):
MF01-N-221-A01

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9