

# MC74HC367A

## Hex 3-State Noninverting Buffer with Separate 2-Bit and 4-Bit Sections

### High-Performance Silicon-Gate CMOS

The MC74HC367A is identical in pinout to the LS367. The device inputs are compatible with standard CMOS outputs; with pullup resistors, they are compatible with LSTTL outputs.

This device is arranged into 2-bit and 4-bit sections, each having its own active-low Output Enable. When either of the enables is high, the affected buffer outputs are placed into high-impedance states. The HC367A has noninverting outputs.

#### Features

- Output Drive Capability: 15 LSTTL Loads
- Outputs Directly Interface to CMOS, NMOS, and TTL
- Operating Voltage Range: 2 to 6 V
- Low Input Current: 1  $\mu$ A
- High Noise Immunity Characteristic of CMOS Devices
- These are Pb-Free Devices





Figure 1. Logic Diagram



ON Semiconductor®

<http://onsemi.com>



A = Assembly Location  
WL, L = Wafer Lot  
YY, Y = Year  
WW, W = Work Week  
G or ■ = Pb-Free Package  
(Note: Microdot may be in either location)

#### PIN ASSIGNMENT

|                    |   |    |                    |
|--------------------|---|----|--------------------|
| OUTPUT<br>ENABLE 1 | 1 | 16 | V <sub>CC</sub>    |
| A0                 | 2 | 15 | OUTPUT<br>ENABLE 2 |
| Y0                 | 3 | 14 | A5                 |
| A1                 | 4 | 13 | Y5                 |
| Y1                 | 5 | 12 | A4                 |
| A2                 | 6 | 11 | Y4                 |
| Y2                 | 7 | 10 | A3                 |
| GND                | 8 | 9  | Y3                 |

#### FUNCTION TABLE

| Inputs                |   | Output |
|-----------------------|---|--------|
| Enable 1,<br>Enable 2 | A | Y      |
| L                     | L | L      |
| L                     | H | H      |
| H                     | X | Z      |

X = don't care

Z = high impedance

#### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 5 of this data sheet.

# MC74HC367A

## MAXIMUM RATINGS

| Symbol    | Parameter                                                        | Value                  | Unit |
|-----------|------------------------------------------------------------------|------------------------|------|
| $V_{CC}$  | DC Supply Voltage (Referenced to GND)                            | -0.5 to +7.0           | V    |
| $V_{in}$  | DC Input Voltage (Referenced to GND)                             | -0.5 to $V_{CC} + 0.5$ | V    |
| $V_{out}$ | DC Output Voltage (Referenced to GND)                            | -0.5 to $V_{CC} + 0.5$ | V    |
| $I_{in}$  | DC Input Current, per Pin                                        | $\pm 20$               | mA   |
| $I_{out}$ | DC Output Current, per Pin                                       | $\pm 25$               | mA   |
| $I_{CC}$  | DC Supply Current, $V_{CC}$ and GND Pins                         | $\pm 50$               | mA   |
| $P_D$     | Power Dissipation in Still Air,<br>SOIC Package<br>TSSOP Package | 500<br>450             | mW   |
| $T_{stg}$ | Storage Temperature                                              | -65 to + 150           | °C   |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

This device contains protection circuitry to guard against damage due to high static voltages or electric fields. However, precautions must be taken to avoid applications of any voltage higher than maximum rated voltages to this high-impedance circuit. For proper operation,  $V_{in}$  and  $V_{out}$  should be constrained to the range  $GND \leq (V_{in} \text{ or } V_{out}) \leq V_{CC}$ . Unused inputs must always be tied to an appropriate logic voltage level (e.g., either GND or  $V_{CC}$ ). Unused outputs must be left open.

## RECOMMENDED OPERATING CONDITIONS

| Symbol                             | Parameter                                            | Min                     | Max             | Unit |    |
|------------------------------------|------------------------------------------------------|-------------------------|-----------------|------|----|
| V <sub>CC</sub>                    | DC Supply Voltage (Referenced to GND)                | 2.0                     | 6.0             | V    |    |
| V <sub>in</sub> , V <sub>out</sub> | DC Input Voltage, Output Voltage (Referenced to GND) | 0                       | V <sub>CC</sub> | V    |    |
| T <sub>A</sub>                     | Operating Temperature, All Package Types             | −55                     | +125            | °C   |    |
| t <sub>r</sub> , t <sub>f</sub>    | Input Rise and Fall Time<br>(Figure 2)               | V <sub>CC</sub> = 2.0 V | 0               | 1000 | ns |
|                                    |                                                      | V <sub>CC</sub> = 3.0 V | 0               | 600  |    |
|                                    |                                                      | V <sub>CC</sub> = 4.5 V | 0               | 500  |    |
|                                    |                                                      | V <sub>CC</sub> = 6.0 V | 0               | 400  |    |

# MC74HC367A

## DC ELECTRICAL CHARACTERISTICS (Voltages Referenced to GND)

| Symbol          | Parameter                                      | Test Conditions                                                                                                                     | V <sub>CC</sub><br>V | Guaranteed Limit |        |         | Unit |
|-----------------|------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|----------------------|------------------|--------|---------|------|
|                 |                                                |                                                                                                                                     |                      | - 55 to<br>25°C  | ≤ 85°C | ≤ 125°C |      |
| V <sub>IH</sub> | Minimum High-Level Input Voltage               | V <sub>out</sub> = V <sub>CC</sub> - 0.1 V<br> I <sub>out</sub>   ≤ 20 μA                                                           | 2.0                  | 1.5              | 1.5    | 1.5     | V    |
|                 |                                                |                                                                                                                                     | 3.0                  | 2.1              | 2.1    | 2.1     |      |
|                 |                                                |                                                                                                                                     | 4.5                  | 3.15             | 3.15   | 3.15    |      |
|                 |                                                |                                                                                                                                     | 6.0                  | 4.2              | 4.2    | 4.2     |      |
| V <sub>IL</sub> | Maximum Low-Level Input Voltage                | V <sub>out</sub> = 0.1 V<br> I <sub>out</sub>   ≤ 20 μA                                                                             | 2.0                  | 0.50             | 0.50   | 0.50    | V    |
|                 |                                                |                                                                                                                                     | 3.0                  | 0.90             | 0.90   | 0.90    |      |
|                 |                                                |                                                                                                                                     | 4.5                  | 1.35             | 1.35   | 1.35    |      |
|                 |                                                |                                                                                                                                     | 6.0                  | 1.80             | 1.80   | 1.80    |      |
| V <sub>OH</sub> | Minimum High-Level Output Voltage              | V <sub>in</sub> = V <sub>IH</sub><br> I <sub>out</sub>   ≤ 20 μA                                                                    | 2.0                  | 1.9              | 1.9    | 1.9     | V    |
|                 |                                                |                                                                                                                                     | 4.5                  | 4.4              | 4.4    | 4.4     |      |
|                 |                                                |                                                                                                                                     | 6.0                  | 5.9              | 5.9    | 5.9     |      |
|                 |                                                | V <sub>in</sub> = V <sub>IH</sub><br> I <sub>out</sub>   ≤ 3.6 mA<br> I <sub>out</sub>   ≤ 6.0 mA<br> I <sub>out</sub>   ≤ 7.8 mA   | 3.0                  | 2.48             | 2.34   | 2.20    |      |
|                 |                                                |                                                                                                                                     | 4.5                  | 3.98             | 3.84   | 3.70    |      |
|                 |                                                |                                                                                                                                     | 6.0                  | 5.48             | 5.34   | 5.20    |      |
| V <sub>OL</sub> | Maximum Low-Level Output Voltage               | V <sub>in</sub> = V <sub>IL</sub><br> I <sub>out</sub>   ≤ 20 μA                                                                    | 2.0                  | 0.1              | 0.1    | 0.1     | V    |
|                 |                                                |                                                                                                                                     | 4.5                  | 0.1              | 0.1    | 0.1     |      |
|                 |                                                |                                                                                                                                     | 6.0                  | 0.1              | 0.1    | 0.1     |      |
|                 |                                                | V <sub>in</sub> = V <sub>IL</sub><br> I <sub>out</sub>   ≤ 3.6 mA<br> I <sub>out</sub>   ≤ 6.0 mA<br> I <sub>out</sub>   ≤ 7.8 mA   | 3.0                  | 0.26             | 0.33   | 0.40    |      |
|                 |                                                |                                                                                                                                     | 4.5                  | 0.26             | 0.33   | 0.40    |      |
|                 |                                                |                                                                                                                                     | 6.0                  | 0.26             | 0.33   | 0.40    |      |
| I <sub>in</sub> | Maximum Input Leakage Current                  | V <sub>in</sub> = V <sub>CC</sub> or GND                                                                                            | 6.0                  | ± 0.1            | ± 1.0  | ± 1.0   | μA   |
| I <sub>OZ</sub> | Maximum Three-State Leakage Current            | Output in High-Impedance State<br>V <sub>in</sub> = V <sub>IL</sub> or V <sub>IH</sub><br>V <sub>out</sub> = V <sub>CC</sub> or GND | 6.0                  | ± 0.5            | ± 5.0  | ± 10    | μA   |
| I <sub>CC</sub> | Maximum Quiescent Supply Current (per Package) | V <sub>in</sub> = V <sub>CC</sub> or GND<br>I <sub>out</sub> = 0 μA                                                                 | 6.0                  | 4                | 40     | 160     | μA   |

# MC74HC367A

## AC ELECTRICAL CHARACTERISTICS ( $C_L = 50$ pF, Input $t_r = t_f = 6$ ns)

| Symbol                   | Parameter                                                                  | $V_{CC}$<br>V            | Guaranteed Limit      |                        |                        | Unit |
|--------------------------|----------------------------------------------------------------------------|--------------------------|-----------------------|------------------------|------------------------|------|
|                          |                                                                            |                          | - 55 to<br>25°C       | ≤ 85°C                 | ≤ 125°C                |      |
| $t_{PLH}$ ,<br>$t_{PHL}$ | Maximum Propagation Delay, Input A to Output Y<br>(Figures 2 and 4)        | 2.0<br>3.0<br>4.5<br>6.0 | 120<br>60<br>24<br>20 | 150<br>75<br>30<br>26  | 180<br>90<br>36<br>31  | ns   |
| $t_{PLZ}$ ,<br>$t_{PHZ}$ | Maximum Propagation Delay, Output Enable to Output Y<br>(Figures 3 and 5)  | 2.0<br>3.0<br>4.5<br>6.0 | 175<br>90<br>35<br>30 | 220<br>110<br>44<br>37 | 265<br>135<br>53<br>45 | ns   |
| $t_{PZL}$ ,<br>$t_{PZH}$ | Maximum Propagation Delay, Output Enable to Output Y<br>(Figures 3 and 5)  | 2.0<br>3.0<br>4.5<br>6.0 | 190<br>95<br>38<br>32 | 240<br>120<br>48<br>21 | 285<br>150<br>57<br>48 | ns   |
| $t_{TLH}$ ,<br>$t_{THL}$ | Maximum Output Transition Time, Any Output<br>(Figures 2 and 4)            | 2.0<br>3.0<br>4.5<br>6.0 | 60<br>22<br>12<br>10  | 75<br>28<br>15<br>13   | 90<br>34<br>18<br>15   | ns   |
| $C_{in}$                 | Maximum Input Capacitance                                                  | –                        | 10                    | 10                     | 10                     | pF   |
| $C_{out}$                | Maximum Three-State Output Capacitance<br>(Output in High-Impedance State) | –                        | 15                    | 15                     | 15                     | pF   |

| C <sub>PD</sub> | Power Dissipation Capacitance (Per Buffer) | Typical @ 25°C, V <sub>CC</sub> = 5.0 V | pF |
|-----------------|--------------------------------------------|-----------------------------------------|----|
|                 |                                            | 60                                      |    |

## SWITCHING WAVEFORMS




Figure 2.




Figure 3.

## TEST CIRCUITS




\*This package is inherently Pb-Free.

# MC74HC367A

## PACKAGE DIMENSIONS

SOIC-16  
CASE 751B-05  
ISSUE K




### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.

| DIM | MILLIMETERS |       | INCHES    |       |
|-----|-------------|-------|-----------|-------|
|     | MIN         | MAX   | MIN       | MAX   |
| A   | 9.80        | 10.00 | 0.386     | 0.393 |
| B   | 3.80        | 4.00  | 0.150     | 0.157 |
| C   | 1.35        | 1.75  | 0.054     | 0.068 |
| D   | 0.35        | 0.49  | 0.014     | 0.019 |
| F   | 0.40        | 1.25  | 0.016     | 0.049 |
| G   | 1.27 BSC    |       | 0.050 BSC |       |
| J   | 0.19        | 0.25  | 0.008     | 0.009 |
| K   | 0.10        | 0.25  | 0.004     | 0.009 |
| M   | 0°          | 7°    | 0°        | 7°    |
| P   | 5.80        | 6.20  | 0.229     | 0.244 |
| R   | 0.25        | 0.50  | 0.010     | 0.019 |

### SOLDERING FOOTPRINT\*




DIMENSIONS: MILLIMETERS

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

# MC74HC367A

## PACKAGE DIMENSIONS


TSSOP-16  
DT SUFFIX  
CASE 948F-01  
ISSUE B



### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH OR GATE BURRS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 (0.010) PER SIDE.
5. DIMENSION K DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE K DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
7. DIMENSION A AND B ARE TO BE DETERMINED AT DATUM PLANE -W-

| DIM | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
|     | MIN         | MAX  | MIN       | MAX   |
| A   | 4.90        | 5.10 | 0.193     | 0.200 |
| B   | 4.30        | 4.50 | 0.169     | 0.177 |
| C   | ---         | 1.20 | ---       | 0.047 |
| D   | 0.05        | 0.15 | 0.002     | 0.006 |
| F   | 0.50        | 0.75 | 0.020     | 0.030 |
| G   | 0.65 BSC    |      | 0.026 BSC |       |
| H   | 0.18        | 0.28 | 0.007     | 0.011 |
| J   | 0.09        | 0.20 | 0.004     | 0.008 |
| J1  | 0.09        | 0.16 | 0.004     | 0.006 |
| K   | 0.19        | 0.30 | 0.007     | 0.012 |
| K1  | 0.19        | 0.25 | 0.007     | 0.010 |
| L   | 6.40 BSC    |      | 0.252 BSC |       |
| M   | 0°          | 8°   | 0°        | 8°    |



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

**ON Semiconductor** and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910

**Japan Customer Focus Center**  
Phone: 81-3-5773-3850

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative



## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9