

## Schottky Barrier Rectifier

### FEATURES

- Low forward voltage drop
- Low power loss, high efficiency
- Guardring for overvoltage protection
- High surge current capability
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21 definition



**TS-1**



### MECHANICAL DATA

**Case:** TS-1

Molding compound, UL flammability classification rating 94V-0

Base P/N with suffix "G" on packing code - halogen-free

Base P/N with prefix "H" on packing code - AEC-Q101 qualified

**Terminal:** Matte tin plated leads, solderable per JESD22-B102

Meet JESD 201 class 1A whisker test,

with prefix "H" on packing code meet JESD 201 class 2 whisker test

**Weight:** 0.2g (approximately)

| MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T <sub>A</sub> =25°C unless otherwise noted)                   |                    |              |           |           |              |           |           |            |            |      |
|----------------------------------------------------------------------------------------------------------------|--------------------|--------------|-----------|-----------|--------------|-----------|-----------|------------|------------|------|
| PARAMETER                                                                                                      | SYMBOL             | SRT<br>12    | SRT<br>13 | SRT<br>14 | SRT<br>15    | SRT<br>16 | SRT<br>19 | SRT<br>110 | SRT<br>115 | UNIT |
| Maximum repetitive peak reverse voltage                                                                        | V <sub>RRM</sub>   | 20           | 30        | 40        | 50           | 60        | 90        | 100        | 150        | V    |
| Maximum RMS voltage                                                                                            | V <sub>RMS</sub>   | 14           | 21        | 28        | 35           | 42        | 63        | 70         | 105        | V    |
| Maximum DC blocking voltage                                                                                    | V <sub>DC</sub>    | 20           | 30        | 40        | 50           | 60        | 90        | 100        | 150        | V    |
| Maximum average forward rectified current                                                                      | I <sub>F(AV)</sub> | 1            |           |           |              |           |           |            |            | A    |
| Peak forward surge current, 8.3 ms single half sine-wave superimposed on rated load                            | I <sub>FSM</sub>   | 25           |           |           |              |           |           |            |            | A    |
| Maximum instantaneous forward voltage (Note 1)<br>@ 1 A                                                        | V <sub>F</sub>     | 0.55         |           |           | 0.70         |           | 0.80      |            | 0.90       | V    |
| Maximum reverse current @ rated VR    T <sub>J</sub> =25 °C<br>T <sub>J</sub> =100°C<br>T <sub>J</sub> =125 °C | I <sub>R</sub>     | 0.5          |           |           |              |           | 0.1       |            |            | mA   |
|                                                                                                                |                    | 10           |           |           | 5            |           | -         |            |            |      |
|                                                                                                                |                    | -            |           |           | -            |           | 2         |            |            |      |
| Typical junction capacitance (Note 2)                                                                          | C <sub>j</sub>     | 110          |           |           | 80           |           | 28        |            |            | pF   |
| Typical thermal resistance                                                                                     | R <sub>θJA</sub>   | 50           |           |           |              |           |           |            |            | °C/W |
| Operating junction temperature range                                                                           | T <sub>J</sub>     | - 55 to +125 |           |           | - 55 to +150 |           |           |            |            | °C   |
| Storage temperature range                                                                                      | T <sub>STG</sub>   | - 55 to +150 |           |           |              |           |           |            |            | °C   |

Note 1: Pulse test with PW=300 μs, 1% duty cycle

Note 2: Measured at 1.0 MHz and Applied V<sub>R</sub>=4.0 Volts

| ORDERING INFORMATION |                    |              |                     |         |                                |
|----------------------|--------------------|--------------|---------------------|---------|--------------------------------|
| PART NO.             | AEC-Q101 QUALIFIED | PACKING CODE | GREEN COMPOUND CODE | PACKAGE | PACKING                        |
| SRT1xx<br>(Note 1)   | Prefix "H"         | A0           | Suffix "G"          | TS-1    | 3,000 / Ammo box (52mm taping) |
|                      |                    | A1           |                     | TS-1    | 3,000 / Ammo box (26mm taping) |
|                      |                    | R0           |                     | TS-1    | 5,000 / 13" Paper reel         |
|                      |                    | B0           |                     | TS-1    | 1,000 / Bulk packing           |

Note 1: "xx" defines voltage from 20V (SRT12) to 150V (SRT115)

| EXAMPLE       |          |                    |              |                     |                    |
|---------------|----------|--------------------|--------------|---------------------|--------------------|
| PREFERRED P/N | PART NO. | AEC-Q101 QUALIFIED | PACKING CODE | GREEN COMPOUND CODE | DESCRIPTION        |
| SRT16 A0      | SRT16    |                    | A0           |                     |                    |
| SRT16 A0G     | SRT16    |                    | A0           | G                   | Green compound     |
| SRT16HA0      | SRT16    | H                  | A0           |                     | AEC-Q101 qualified |

RATINGS AND CHARACTERISTICS CURVES

(TA=25°C unless otherwise noted)

FIG. 1- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG. 2- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 3- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4- TYPICAL REVERSE CHARACTERISTICS




FIG. 5- TYPICAL JUNCTION CAPACITANCE






FIG. 6- TYPICAL TRANSIENT THERMAL CHARACTERISTICS




PACKAGE OUTLINE DIMENSIONS



| DIM. | Unit (mm) |      | Unit (inch) |       |
|------|-----------|------|-------------|-------|
|      | Min       | Max  | Min         | Max   |
| A    | 2.00      | 2.70 | 0.079       | 0.106 |
| B    | 0.53      | 0.64 | 0.021       | 0.025 |
| C    | 25.40     | -    | 1.000       | -     |
| D    | 3.00      | 3.30 | 0.118       | 0.130 |
| E    | 25.40     | -    | 1.000       | -     |

MARKING DIAGRAM



P/N = Specific Device Code  
 G = Green Compound  
 YW = Date Code  
 F = Factory Code

### Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9