

10135292 - 10X LF

LEAD-FREE DESIGNATION
ONLY WITH APPLICABLE
PLATING CODES

SEE NOTE 2

MODULE
DESCRIPTION

LETTER DESIGNATION REPRESENTED IN DASH NUMBER

BASE
MODULE

LEFT
POLARIZING
GUIDANCE
MODULE
(SEE SHEET 3)

N

J
(NO KEY)

A

B

C

D











E

F

G

H

NO KEY
NO GUIDE PIN



RIGHT
POLARIZING
GUIDANCE
MODULE
(SEE SHEET 2)

Z

Y
(NO KEY)

P

Q

R

S











T

U

V


W


NO KEY
NO GUIDE PIN



PRELIMINARY

spec ref	---	dr	Tao Zhan	2015/05/26	projection	MM	size	A2	scale	8:1
tolerance std	ASME Y14.5M	eng	Jackie Chen	2016/03/15	chr	-	ecn no	-		
		appr	-	-	product family	AirMax VS2	rel level	Preliminary		
surface	-	linear	0.X	±.3	Amphenol FCi	title	AIRMAX VS2 R.A. RECEPTACLE ASS'Y, 4 PAIR, 120 POS, 10 IMLA, 20MM, W/GUIDE/KEY	dwg no	10135292	rev
			0.XX	±.15						
			0.XXX	±.050						
		angular	0°	±°		cat. no.	-	Product - Customer Drw	sheet 1 of 4	






spec ref		---		dr	Tao Zhan	2015/09/26	projection		MM	size	A2	scale	8:1	
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED				eng				Jackie Chen	2016/03/15	ecn no	rel level	Preliminary
ASME Y14.5M		chr	-	-	appr	-				product family	AIRMAX VS2			
surface	- 	linear	0.X	±.3	Amphenol FCI	title	AIRMAX VS2 R.A. RECEPTACLE			dwg no	10135292		rev	1
			0.XX	±.15										
			0.XXX	±.050										
		angular	0°	±°		cat. no.	-	Product - Customer Drw			sheet 3 of 4			

PRODUCT NUMBER	PRESS-FIT TAIL PLATING TYPE
10135292-10ALF	TIN OVER NICKEL (LEAD FREE)
10135292-10PLF	TIN OVER NICKEL (LEAD FREE)


- 1 - CONNECTOR MATERIALS:
HOUSING: HIGH TEMP THERMOPLASTIC, NATURAL, UL94-V0
IMLA PLASTIC: HIGH TEMP THERMOPLASTIC, BLACK, UL94-V0
CONTACT: COPPER ALLOY
ORGANIZER: HIGH TEMP THERMOPLASTIC, WHITE, UL94-V0
- 2 - CONTACT PLATING:
SEPARABLE INTERFACE:
PERFORMANCE-BASED PLATING, QUALIFIED TO MEET THE
REQUIREMENTS OF FCI PRODUCT SPECIFICATION GS-12-0956
INCLUDING TELCORDIA GR-1217-CORE (NOVEMBER 1995)
CENTRAL OFFICE TEST SEQUENCE

PRESS-FIT TAILS: SEE TABLE


- 3 - PRODUCT SPECIFICATION: GS-12-0956
- 4 - APPLICATION SPECIFICATION: GS-20-0305.
- 5 - PRODUCT MARKING, (PART NUMBER & LOT CODE), ON THIS SURFACE.
- 6 - THE MINIMUM CENTERLINE SPACING BETWEEN ADJACENT
MODULES IS 28.0 MM.
- 7 - CONNECTOR OUTLINE MAY BE SCREEN PRINTED ONTO CUSTOMER PCB TO
BE USED AS A GUIDE FOR MANUAL CONNECTOR PLACEMENT.
- 8 - REFER TO CUSTOMER DRAWING 10104444 FOR INFORMATION
ON PCB HOLE DIAMETERS AND PLATING OPTIONS
- 9 - LEAD FREE PRODUCT MEETS THE EUROPEAN UNION DIRECTIVES &
OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008
- 10 - PACKAGING MEETS GS-14-920 LEAD FREE LABELING
SPECIFICATION.
- 11 - GROUND CONTACTS (C,F, AND I IN ODD COLUMNS AND A, D, AND G,
EVEN COLUMNS) REQUIRE (Ø0.500) FINISHED HOLES. SIGNAL LOCATIONS
REQUIRE (Ø0.400) FINISHED HOLES.
- 12 - THESE OUTER VIAS (M) ARE OPTIONAL. WHILE NO CONNECTOR EONS ARE
PRESSED INTO THESE HOLES WE RECCOMEND (Ø0.500) FINISHED HOLES
AT THESE LOCATIONS TO PROVIDE GROUND SYMMETRY THROUGH THE PCB.
- 13 - A  SYMBOL WILL BE NEXT TO ANY DIMENSION, VIEW, OR NOTE, WHICH
HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION
- 14 - CUSTOMER CAN FIX THE CONNECTOR WITH THREAD FORMING SCREW THROUGH
THIS PTH. THE SCREW IS #2-32, THE VALID LENGTH OF SCREW IS 4.5MM PLUS THE
THICKNESS OF PCB.



10135292-10ALF



10135292-10PLF



DETAIL A
SCALE 20:1

spec ref	---	dr	Tao Zhan	2015/09/26	projection	MM	size	A2	scale	6:1
tolerance std	ASME Y14.5M	eng	Jackie Chen	2016/03/15	chr	-	ecn no	-	rel level	Preliminary
surface	-	appr	-	-	product family	AirMax VS2	cat. no.	-	Product - Customer Drw	sheet 4 of 4
linear	0.X ±.3	angular	0° ±°	0.XX ±.15	0.XXX ±.050	Amphenol FCI	title	AIRMAX VS2 R.A. RECEPTACLE	dwg no	10135292
angular	0° ±°	0° ±°	0° ±°	0° ±°	0° ±°	Amphenol FCI	ASS'Y, 4 PAIR, 120 POS, 10 IMLA, 20MM, W/GUIDE/KEY	rev	1	

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9